

# Product data sheet

Specifications



## APC NetShelter Rack PDU Advanced, Switched Metered Outlet, 3Phase, 11kW 400V 16A or 11.5kW 415V 20A, 48 Outlets, IEC309

APDU10250SM

### Overview

Lead time Usually in Stock

### Main

Color Black

Product or Component Type PDU

PDU Type Switched metered outlet

Cord length 5.9 ft (1.8 m)

### Complementary

Input Voltage 415 V 3 phase  
400 V 3 phase

Height 58.7 in (149.0 cm)

Width 2.2 in (5.6 cm)

Output Voltage 240 V

Depth 3.0 in (7.5 cm)

Net Weight 17.0 lb(US) (7.7 kg)

Mounting Location Side

Mounting preference No preference

Input Plug Type IEC 60309 20 A 3P+N+PE

Mounting Mode Rack-mounted

Rack units 0U

Mounting position Vertical

Communication Port Protocol 1000BASE-T  
10/100BASE-T

Line Rated Current 16 A

Acceptable Input Voltage 200...240 V  
346...415 V

Input current limits 20 A

Load Capacity 11500 VA

Input Frequency 50/60 Hz

Outlet type and quantity 24 C13/C15/C19/C21 C13/C15

### Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Product Certifications</b>	TAA compliance UKCA
<b>Standards</b>	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1
<b>IP Degree of Protection</b>	IP44
<b>Ambient Air Temperature for Operation</b>	23...140 °F (-5...60 °C)
<b>Relative Humidity</b>	5...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	-13...149 °F (-25...65 °C)
<b>Storage Relative Humidity</b>	5...95 %
<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

<b>GTIN</b>	731304439707
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	67.7 in (172 cm)
<b>Package 1 Width</b>	4.6 in (11.6 cm)
<b>Package 1 Length</b>	8.2 in (20.8 cm)
<b>Package 1 Weight</b>	21.4 lb(US) (9.7 kg)

## Contractual warranty

<b>Warranty</b>	3 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant  
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)  
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)