

Supercharged 24" All in One PC



- | | | | |
|-----------------------------|---|------------------------|--|
| Display | <ul style="list-style-type: none"> • 23.6-inch medical grade 16:9 LED (1920x1080) | I/O Ports | <ul style="list-style-type: none"> • 2 x USB 3.0 ports • 4 x USB 2.0 ports • 1 x RS232 upto 3 COM ports • DVI monitor out port • 1 x HDMI output (1080p) • Mic, Line-in, Line-out |
| CPU Support | <ul style="list-style-type: none"> • 2nd and 3rd generation Intel Core i3, i5 & i7 processors | Power Supply | <ul style="list-style-type: none"> • 120W 100 ~ 240V AC, 50-60Hz. • Supports Output range: DC12V/19V. 6.3 |
| Chipset | <ul style="list-style-type: none"> • Intel® H61 | Touch Screen | <ul style="list-style-type: none"> • Projected Capacitive Multi-Touch |
| Memory | <ul style="list-style-type: none"> • 2 x DDR3 204-pin SO-DIMM sockets, populated up to 8GB Max. Supports PC3-10600 1333MHz SO-DIMM | Wireless | <ul style="list-style-type: none"> • Intel Centrino 802.11 a/b/g/n + Bluetooth 4.0 |
| HDD Support | <ul style="list-style-type: none"> • Integrated Serial ATA controller facilitates high-speed transfers up to 3Gbps for each of the four ports | Webcam | <ul style="list-style-type: none"> • 3 megapixel camera |
| Video & Graphics | <ul style="list-style-type: none"> • Nvidia GT630 M Dedicated 1GB DDR3 or Intel® integrated H61 Chipset, with Intel® HD Graphics (Intel® GMA HD) | Wall Mount | <ul style="list-style-type: none"> • Supports both 75mm & 100mm VESA mounting holes |
| Networking | <ul style="list-style-type: none"> • 2 x Gigabit (GbE) Fast Ethernet (Realtek RTL 8111E) | Expansion Slots | <ul style="list-style-type: none"> • Two Mini PCI-e (1xFull-size and 1xHalf-size) |
| Audio | <ul style="list-style-type: none"> • Realtek ALC892 High Definition Audio enables premium Dolby Digital 5.1 surround sound, 10 channels of enhanced sound quality, and delivers advanced features such as multiple audio streams and "jack re-tasking" | Bios | <ul style="list-style-type: none"> • AMI Flash BIOS supports ACPI, API, DMI, Plug & Play, and security password. Supports booting from HDD, PXE, LAN, CD-ROM, and ANY USB device. Has BIOS System POST and BIOS setup password protection |
| | | Desktop Stand | <ul style="list-style-type: none"> • System Base enables left/right rotation up to 60°. Tilt from -5 to 60° |

- | | | | |
|--------------------------|--|-----------------------|---|
| Weight | • Unit: 22.9lbs with base, 17lbs without base, Power Adapter: 2.2lbs | O/S | • Window 8, Windows 7, Linux |
| Environment | • Ambient Temperature: 0°C ~ 40°C (operating) | Dimensions | • 23.5" long, 14.8" tall, 2.08" deep (not including base) |
| Relative Humidity | • 10% ~ 90% (non-condensing) | Colors | • Black |
| | | Certifications | • UL60950 electrical safety, FCC class B, CE, Energy Star 5.2, RoHs, WEEE |



Corporate Headquarters
Cybernet Manufacturing
5 Holland,
Irvine, CA 92618
Toll free: 888-834-4577
Local: 949-600-8000
Fax: 949-600-8013
www.cybernetman.com
sales@cybernetman.com
support@cybernetman.com

Cybernet Europe
Network House, Hawkins Road
Colchester, Essex CO2 8LA
United Kingdom
UK Phone: 0845-539-1200
UK Fax: 0845-539-1201
www.cyberneteuropa.com
sales@cyberneteuropa.com
support@cyberneteuropa.com

Cybernet Taiwan Company, LTD.
4F., No.25, Lane 140, Xingai Rd
Neihu District, Taipei City 11494
Taiwan (R.O.C.)
Phone: (02) 2790-4776
Fax: (02) 2793-3172
www.cybernet.com.tw
sales@cybernet.com.tw
support@cybernet.com.tw