

MPN: MO-TL-SM321A

SFP BX-D, 1.25Gb/s, 20Km Compatible with TP-Link TL-SM321A

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- ****100% TP-Link Compatible****



Specifikationer

Features	Brand compatibility	TP-Link
	Certification	MSA
	Compatible products	TP-Link TL-SM321A
	Easy to install	Yes
	Form factor	SFP
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	Operating relative humidity (H-H)	10 - 80 %
	Operating temperature (T-T)	0 - 70 ° C
	Storage relative humidity (H-H)	10 - 85 %
	Storage temperature (T-T)	-40 - 85 ° C
Package dimensions	Depth (package,cm)	10 cm
	Gross Weight (Package, kg)	0,04 kg
	Height (package,cm)	2 cm
	Width (package,cm)	6 cm
Packaging data	Number of products included	1 styck
Performance	Cabling technology	1000BASE-BX10-D
	Fiber cable diameters supported (core/cladding)	9/125 um
	Fiber optic connector	LC
	Maximum data transfer rate	1000 Mbit/s
	Maximum transfer distance	20000 m
	SFP transceiver standard	BX-D
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Yes

Product dimensions	Net Weight (Product, kg)	0,03 kg
	Product Depth	5,6 cm
	Product Height	0,85 cm
	Product Width	1,25 cm
Vendor information	Brand Name	Lanview
	Warranty	5 År

Andra bilder

