

USB to RJ45 Gigabit Ethernet Network Adapter (M/F) - USB 3.1 Gen 1, 2.5 Gbps Ethernet, Black

MODEL NUMBER: U336-06N-2P5-B



Connects the USB-A port on your laptop or PC to a wired Ethernet network at very fast 2.5 Gbps speeds with no network card needed.

Features

USB 3.1 to Gigabit Ethernet Adapter Connects You to a Wired 2.5G Network

This USB network adapter instantly connects your PC or laptop to a wired Gigabit network through a USB-A port. No internal Ethernet card is required. Ideal for settings in which no Wi-Fi is available or when a wired connection offers faster speeds, this USB 3.1 Gen 1 adapter lets you enjoy true 2.5 Gbps Ethernet speeds for uploading and downloading large files and streaming audio/video without buffering.

Plug-and-Play Operation Gets You Online Immediately

This bus-powered network adapter requires no external power source. Just connect the built-in USB 3.1 Gen 1 plug to your computer, and use a Cat5e/6 cable (sold separately) to connect the RJ45 end to a network. LEDs indicate when you're connected to a network and when data is being transferred. The compact unit fits easily into a pocket, purse, backpack or laptop bag for instant file transfers where needed. It's compatible with Windows, Mac, Chrome, Android and Linux.

Highlights

- Connects your laptop to a wired 2.5 Gbps network where Wi-Fi is weak or unavailable
- More convenient, less expensive than installing or upgrading an internal Ethernet card
- Widely compatible with Windows, Mac, Chrome, Android and Linux operating systems
- LED indicates successful connection to wired network and transfer of data
- Plug-and-play operation with no external power needed for easy, immediate installation

Applications

- Connect to a wired 2.5GBase-T Ethernet network in an office, trade show booth, lecture hall, classroom, hotel lobby or auditorium
- Extend the life of a legacy laptop or notebook computer with a failed internal Ethernet card
- Play network gaming consoles in areas without Wi-Fi capability

System Requirements

- PC, laptop or other compatible device with USB-A port (USB 3.1 required to achieve USB 3.1 speeds)
- Windows (10), Mac OS X (10.13 and above), Chrome OS (Linux driver required), Android 8.0 and



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

above, Linux Kernel 4.1 and
above

Package Includes

- U336-06N-2P5-B USB to
Gigabit Ethernet Network
Adapter (M/F), 2.5G, Black

Specifications

OVERVIEW	
UPC Code	037332249104
INPUT	
Bus Powered	Yes
PHYSICAL	
Color	Black
Unit Dimensions (hwd / in.)	0.98 x 1.57 x 3.35
Unit Dimensions (hwd / mm)	25 x 40 x 85
Unit Packaging Type	Polybag
ENVIRONMENTAL	
Operating Temperature Range	32 to 104°F (0 to 40°C)
Storage Temperature Range	-4 to 158°F (-20 to 70°C)
Relative Humidity	0 ~ 90% RH
COMMUNICATIONS	
Network Speed	2.5 Gbps
IEEE Standards Supported	802.1p; 802.1q; 802.3; 802.3ab; 802.3az; 802.3bz; 802.3u; 802.3x
CONNECTIONS	
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	RJ45 (FEMALE)
FEATURES & SPECIFICATIONS	
USB Specification	USB 3.1 Gen 1 (up to 5 Gbps)



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Full Duplex Support	Yes
Remote Wakeup Support	Yes
Technology	Cat5/5e; Cat6; Cat6a; USB; USB 3.1 (Gen 1)
SPECIAL FEATURES	
Data Transfer Rate	2.5 Gbps (2.5GBASE-T)
CERTIFICATIONS	
Certifications	CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>