



SLK-101-M

BACKLIT MOBILE INDUSTRIAL KEYBOARD

iKey's SlimKey™ SLK-101-M keyboard provides full-size versatility in a rugged, compact design. It features red LED backlit keys for use in areas with minimal lighting. Engineered for NEMA 4X protection from dust, water and corrosive liquids, the SlimKey™ SLK-101-M is ideal for use in industrial, medical and material handling applications. Its large numeric pads allow for easy data entry, while its robust polycarbonate cases have built-in mounting holes for convenient vehicle use. Features: 10-Key Numeric Pad 12 Function Keys Built-In Mounting Holes Integrated Backlighting MS Windows™ Function Keys USB and PS/2 configurations available

Product Code SLK-101-M

| | |
|-------------------|--|
| CERTIFICATIONS | NEMA 4X UL60950, FCC Part 15 Class B |
| SHOCK | 3x11 ms pulses of 50g on each of 3 axis |
| CABLE | LENGTH: 10' straight (3 m) |
| KEY SWITCH | MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with mechanical snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours |
| POWER | PS/2: 210mA@5V (from Keyboard port) USB: 210mA@5V (from CPU port) |
| FLAMMABILITY | PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB |
| COMPATABILITY | PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS |
| TEMPERATURE RANGE | STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F) |
| WEIGHT | 2 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg) |
| WARRANTY | 1 Year Limited Warranty |
| HUMIDITY | 100% Humidity Resistant |
| DIMENSIONS | 14.74" x 5.69" x 1.61" (w-h-d) 374.4mm x 144.5mm x 40.9mm |