



## Specifications

Type of Camera	Type of Camera			
Туре	Compact digital still camera with built-in flash, 10x Optical, 4x Digital and 40x Combined Zoom with Optical Image Stabilizer			
Image Capture Device				
Туре	20.0 Megapixel, 1/2.3-inch CCD			
Total Pixels	Approx. 20.5 Megapixels			
Effective Pixels	Approx. 20.0 Megapixels* * Image processing may cause a decrease in the number of pixels.			
Lens				
Focal Length	4.3 (W) – 43.0 (T) mm (35mm film equivalent: 24–240mm)			
Optical Zoom	10x			
Digital Zoom	4x			
Focusing Range	Normal: 2.0 in. (5.0cm) – infinity (W), 3.3 ft. (1.0m) – infinity (T) Auto: 0.4 in. (1.0cm) – infinity (W), 3.3 ft. (1.0m) – infinity (T) Macro: 0.4 in. – 1.6 ft. (1–50cm) (W) Infinity: 9.8 ft. (3.0m) – infinity (W), 9.8 ft. (3.0m) – infinity (T)			
Autofocus System	TTL Autofocus			
Viewfinder & Monito	Viewfinder & Monitor			
Viewfinder	Not available			
LCD Monitor	2.7-inch TFT Color LCD with wide viewing angle (4:3)			
LCD Pixels	Approx. 230,000 dots			
LCD Coverage	Approx. 100%			
Aperture & Shutter				
Maximum Aperture	f/3.0 (W), f/6.9 (T)			
Shutter Speed	1–1/2000 sec. 15–1 sec. (in Long Shutter Mode)			
Exposure Control				
ISO Sensitivity	Auto, ISO 100–1600			
Light Metering Method	Evaluative, Center Weighted Average, Spot			
Exposure Compensation	Still Images: ±2 stops in 1/3-stop increments			
White Balance				
White Balance Control	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom			
Flash				
Built-in Flash	Auto, On, Slow Synchro, Off			
Flash Range	1.6–13.0 ft. (W), 3.3–6.6 ft. (T) 50.0cm – 4.0m (W), 1.0–2.0m (T)			

Shooting Specifications					
Shooting Modes	P, Auto, Portrait, Face Self-Timer, Low Light, Fish-eye Effect, Miniature Effect, Toy Camera Effect, Monochrome, Super Vivid, Poster Effect, Fireworks, Long Shutter				
Self Timer	Off/2 sec./10 sec./Custom				
Wireless Control	Built-in Wi-Fi*^and NFC^^				
	Normal Continuous Shooting in Auto/P modes: Approx. 0.8 shots/sec. Normal Continuous Shooting Low Light mode: Approx. 2.2 shots/sec.				
Continuous Shooting	<ul> <li>Under lighting conditions where flash does not fire automatically.</li> <li>Excluding RAW and RAW+JPEG.</li> <li>Until memory card becomes full.</li> </ul>				
Image Storage	Image Storage				
Storage Media	SD/SDHC/SDXC Memory Cards				
File Format	Design rule for Camera File system (DCF) compliant; DPOF (Version 1.1) compatible				
Image Compression	Fine				
JPEG Compression Mode	Still Image: Exif. 2.3 (JPEG) Video: MP4 (Image: MPEG-4 AVC/H.264; Audio: MPEG-4 AAC-LC (Monaural))				
Number of Recording Pixels	Still Images: Large: 5152 x 3864 Medium 1 (M1): 3648 x 2736 Medium 2 (M2): 2048 x 1536 Medium: 2560 x 1920 Small: 640 x 480 Wide: 5152 x 2896  Videos: HD 1280 x 720: 25.00 fps 640 x 480: 29.97 fps				

## Approx. Number of Shots Recordable to 16 GB Memory Card

Large	F	3017
Medium 1 (M1)	F	5925
Medium 2 (M2)	F	16755
Medium	F	10798
Small	F	80988
Wide	F	4015

Note: F=Fine

## Total Movie Time Recordable to Memory Card

- The values in the table are based on Canon measurement conditions and may change depending on the subject, memory card and camera settings.
- After Low-level formatting.

Shooting Mode	Pixels	Frame Rate/ Video System	Recording Time per 16 GB Memory Card (Approx.)	Single Clip Recording Time (Approx.)*1	Movie Size (KB/sec.)	Video Recording Bit Rate
When Movie button is pressed in Auto	HD (1280 x 720)	25.00 fps	2 hr. 35 min. 37 sec.	29 min. 59 sec.	1624	Approx. 15 Mbps
	VGA (640 x 480)	29.97 fps	8 hr. 25 min. 48 sec.	1 hr.	450	Approx. 3 Mbps

<sup>\*</sup>I Using an SD Speed Class 10 / UHS-I compatible memory card

<sup>•</sup> Recording stops automatically once the file size reaches 4 GB or the memory card becomes full.

<sup>•</sup> Recording may stop unexpectedly if a memory card with a low Speed Class is used.

Playback Specifications					
Playback Modes File	Protect, Favorites, Erase, Slideshow, Rotate, i-Contrast, Resize, Red-Eye Correction, Photobook Set-up, Auto Rotate, Resume, Transition Effect				
Interfaces					
Video Out	NTSC/PAL				
Audio Out	Monaural				
Other	Hi-Speed USB (Mini-B); direct connection to Canon SELPHY, PIXMA Photo Printers & PictBridge compatible printers				
Power Supply	Power Supply				
Power Source	Battery Pack NB-11L				
Shooting Capacity	Approx. 190 shots Approx. 245 shots in ECO Mode				
	Video Recording Time: Approx. 50 min.				
Playback Time	Approx. 4 hr.				
Physical Specification	Physical Specifications				
Operating Temperature	32-104°F/0-40°C				
Operating Humidity	10-90%				
Dimensions (W x H x D)	3.75 x 2.24 x 0.93 in. / 95.3 x 56.8 x 23.6mm				
Weight	4.87 oz. / 138g (CIPA standard) 4.34 oz. / 123g (Body only)				

<sup>^</sup> Compatible with iOS versions 7.1/8.4/9.0, Android smartphone and tablet versions 4.0/4.1/4.2/4.3/4.4/5.0/5.1. Data charges may apply with the download of the free Canon Camera Connect app. This app helps enable you to upload images to social media services. Please note that image files may contain personally identifiable information that may implicate privacy laws. Canon disclaims and has no responsibility for your use of such images. Canon does not obtain, collect or use such images or any information included in such images through this app.

 $<sup>\</sup>label{lem:compatible} $$ ^\triangle Compatible with Android smartphone and tablet versions 4.0/4.1/4.2/4.3/4.4/5.0/5.1. $$$