

HP Engage 2D G2 Barcode Scanner



Model

HP Engage 2D G2 Barcode Scanner (Black)
HP Engage 2D G2 Barcode Scanner (White)

6Y2V4AA
6Y2V5AA

Introduction

Deliver an efficient customer experience with the reliable, versatile, and efficient HP Engage 2D G2 Barcode Scanner, HP's smallest, slimmest barcode scanner. It reads mobile wallets, digital coupons, and printed barcodes, and can be used by hand or in presentation mode.

Key Features and Benefits

- Quickly scan mobile wallets and digital coupons from customer mobile devices or printed 1D and 2D barcodes. Intuitive feedback confirms a successful read.
- Supports a wide variety of symbologies, including 1D, 2D, and OCR.
- Built into an IP42-sealed and drop-resistant (1.2 m/ 3.94 ft) housing, can stand up to tough environments.
- User-friendly illumination and aiming: Employs highly- visible laser aimer to achieve crisp and accurate targeting while using flicker-free white soft illumination to reduce eye strain and fatigue from long-time operation.
- Powerful data formatting capability: Allows customizing scanned data with ease and provides supporting software to address diverse application needs.

Compatibility

The HP Engage 2D G2 Barcode Scanner is compatible with HP Retail & Industry Solutions systems.

NOTE: Not all Point of Sale system models are available in all regions.

Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP. Additional HP Care Pack Services options are available to extend warranty coverage.

General

| | |
|-----------------------------------|---|
| Scanner Technology | Global Shutter |
| Image Sensor | 1280 x 800 CMOS |
| Light source/ illumination | White LED |
| Aiming | 650 nm red laser diode |
| Read Rate | 60 frames/second |
| Motion Tolerance | 20 cm/second |
| Resolution | >= 3 mil* |
| Field of View | Horizontal: 47°; vertical: 30° |
| Typical Depth of Field | Depth of Field distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent. |

*Test conditions: T=23 °C; Illumination=3001 lux using incandescent lamp; sample barcodes made by Newland.

Typical Performance *

| Narrow Width | Depth of Field |
|--------------|-------------------------|
| Code 39 | 55 mm – 220 mm (5 mil) |
| Data Matrix | 45 mm – 245 mm (10 mil) |
| EAN-13 | 45 mm – 450 mm (13 mil) |
| PDF417 | 55 mm – 195 mm (6.7 mm) |
| QR Code | 20 mm – 320 mm (15 mil) |

* Performance may be impacted by bar code quality and environmental conditions.

Min. Symbol Contrast 20% minimum reflectance difference*

*Test conditions: T=23 °C; Illumination=3001 lux using incandescent lamp; sample barcodes made by Newland.

**Scan Angle*
Roll (tilt)** ± 360°

*Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23 °C; Illumination=3001 lux using incandescent lamp; 2D: QR Code; 10 Bytes; Resolution=1Smil; PCS=0.8.

Pitch ± 55°
Skew ± 60°

Additional Features Data parsing (driver license parsing), data formatter
Symbologies **1D**

AIM 128
Codabar
Code 11 (with one or two check digits)
Code 39 (Regular and including full ASCII)
Code 49
Code 93
Code 128
Code 16K

Coupon
 Febraban
 GS1-128 (UCC/ EAN-128)
 GS1 Composite (EAN UCC Composite)
 GS1 Databar (RSS)
 Industrial 2 of 5
 Interleaved 2 of 5
 ISBN
 ISBT 128
 ISSN
 ITF-6
 ITF-14
 Matrix 25
 MSI- Plessey
 Plessey
 Standard 2 of 5
 UPC/EAN- 8
 UPC/EAN- 13
 UPC/EAN- (A)
 UPC/EAN- (E)

2D

Aztec
 Chinese Sensible Code
 Code One
 Datamatrix
 Datamatrix (2D inversed)
 GM Code
 GS1 DataBar Expanded Stacked
 GS1 DataBar Expanded Omni-directional
 Maxicode
 MicroPDF417
 PDF417
 QR Codes (QR, Micro QR and Multiple QR)

Postal

Australian Post
 China Post 25
 Kix Post (Netherlands)
 Postal Codes
 Royal Mail
 USPS Intelligent Mail
 USPS Planet
 USPS Postnet

Mechanical/ Electrical

| | |
|-------------------------------|--|
| Dimensions (H x W x D) | 160 x 44 x 33 mm (6.30 x 1.73 x 1.18 in) |
| Cable length | 1.8m (5.9 ft) |
| Color | Ebony Black or Ceramic White |
| Power Typical Current | 5V – 255.76 mA |
| Weight | 130g (4.59 oz) |

| | |
|------------------------|----------------|
| Interface | USB |
| Input Voltage | 5.0 Vdc +/- 5% |
| Typical Current | 5V – 255.76 mA |

Environmental

| | |
|------------------------------|---|
| Operating Temperature | -20°C to 60°C (-4°F to 140°F) |
| Storage Temperature | -40°C to 70°C (-40°F to 158 °F) |
| Humidity | 5% to 95% relative humidity, non-condensing |
| ESD | ±15KV (air discharge); ±8KV (contact discharge) |
| Drop | 1.2m (3.94 ft) |
| Sealing | IP42 |

Drivers

Windows USB COM, OPOS, and JPOS

Operating System

Compatible with:

Windows

Win 11 Pro 64-bit
Win 10 Pro 64-bit
Windows 10 IoT Enterprise LTSC 2021 64-bit
Windows 10 IoT Enterprise LTSC 2019 64-bit
Windows 10 IoT Enterprise LTSB 2016 64-bit

Linux

Ubuntu 20.04.1 LTS
Ubuntu-18.04.6-desktop-amd64
Ubuntu-20.04.4.0-desktop-amd64
Ubuntu-22.04.0.0-desktop-amd64
RHEL 9.0-x86_64
SLE-12-SP5-Server-x86_64
SLE-15-SP3-x86_64
Debian-11.3.0-amd64

Agency Certifications

FCC Part 15 Class B, CE EMC Class B, KCC, VCCI

Option Kit Contents

HP Engage 2D G2 Barcode Scanner with attached 5.9 ft (1.8M) USB cable, scanner stand

| Date of change: | Version History: | Description of change: |
|------------------------|-------------------------|-------------------------------|
| February 22, 2023 | From v1 to v2 | Changed Symbologies section |
| March 17, 2023 | From v2 to v3 | Changed Model section |

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.