

Laptop Power Cord, Schuko to C5 - 2.5A, 250V, H05VV-F, 2 m (6.6 ft.), Black

MODEL NUMBER: P058-02M-EU



Connects a notebook computer or laptop with a 3-slot C6 power inlet to a PDU or UPS system with Schuko outlets.

Features

European Computer Power Cord Connects Notebook Computers to a Schuko AC Outlet

This VDE-compliant power cable connects a notebook computer, laptop or other device with a three-slot C6 inlet to a PDU, UPS or surge protector with Schuko outlets. The P058-02M-EU features a CEE 7/7 Schuko end for connecting to an AC power source and an IEC-320-C5 end for connecting to devices.

H05VV-F Jacket Is Fully VDE-Compatible for European Applications

The 0.75mm² enhanced PVC jacket complies with VDE, CE and UKCA standards for data centers, racks, workstations and other IT applications in Europe.

Highlights

- Recommended for powering notebook computers and laptops with C6 inlets
- Ideal replacement for a worn-out or missing laptop adapter power cable
- VDE-compliant H05VV-F jacket allows use in European IT applications

Package Includes

P058-02M-EU C5 to Schuko Computer Power Cable, 2 m (6.6 ft.), Black

Specifications

| OVERVIEW | |
|-----------------------------|----------------------|
| UPC Code | 037332281074 |
| Product Type | Laptop Power Cord |
| Device Compatibility | Laptop; Monitor/HDTV |
| Country/Region | Europe |
| INPUT | |
| Maximum Input Amps | 2.5 |
| Voltage Compatibility (VAC) | 250 |
| CONNECTIONS | |
| Side A - Connector 1 | CEE 7/7 SCHUKO PLUG |



Powering Business Worldwide

TRIPP LITE
SERIES

| | |
|--------------------------------------|-------------------------------|
| Side B - Connector 1 | IEC-320-C5 |
| PHYSICAL | |
| Plug Color | Black |
| Cable Jacket Color | Black |
| Cable Jacket Material | PVC |
| Power Cord Jacket Type | H03VV-F |
| Cable Outer Diameter (OD) | 5.9 mm |
| Number of Conductors | 3 |
| Conductor Gauge | 24/0.20AS |
| Wire Gauge (AWG) | 18 |
| Wire Gauge (OD - mm ²) | 0.75 |
| Power Cord Color | Black |
| Cable Length (ft.) | 6.56 |
| Cable Length (m) | 2.00 |
| Shipping Dimensions (hwd / in.) | 9.02 x 7.01 x 0.50 |
| Shipping Dimensions (hwd / cm) | 22.91 x 17.81 x 1.27 |
| Shipping Weight (lbs.) | 0.37 |
| Shipping Weight (kg) | 0.17 |
| Unit Dimensions (hwd / in.) | 9.020 x 7.010 x 0.500 |
| Unit Packaging Type | Polybag |
| Unit Weight (lbs.) | 0.36 |
| Unit Weight (kg) | 0.16 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 5° to 158°F (-15° to 70°C) |
| Storage Temperature Range | 5° to 140°F (-15° to 60°C) |
| Operating Humidity Range | 20% TO 80% RH, NON-CONDENSING |
| Storage Humidity Range | 20% TO 80% RH, NON-CONDENSING |
| FEATURES & SPECIFICATIONS | |
| Antibacterial | No |
| Armored Cable | No |
| Angled Plug | No |
| High Voltage | Yes |
| Locking Plug | No |
| Coiled Power Cord | No |



Powering Business Worldwide

TRIPP LITE
SERIES

| STANDARDS & COMPLIANCE | |
|-------------------------------------|--------------------------------|
| Product Compliance | CE (Europe); REACH; RoHS; UKCA |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.