

# Universal DC Power Adapter for Industrial USB Hubs - 20V, 3.25A

Product ID: ITB20D3250



This universal DC power adapter has been designed as an alternative, back up or replacement power supply for StarTech.com's line of industrial USB hubs.

## Compatible USB 3.0 Hubs

10-Port Industrial USB 3.0 Hub with External Power Adapter - ESD & 350W Surge Protection ([HB30A10AME](#))

10-Port Industrial USB 3.0 Hub with ESD & 350W Surge Protection ([ST1030USBM](#))

7-Port Industrial USB 3.0 Hub with External Power Adapter - ESD & 350W Surge Protection ([HB30A7AME](#))

7-Port Industrial USB 3.0 Hub with ESD & 350W Surge Protection ([ST7300USBME](#))

4-Port Industrial USB 3.0 Hub with ESD Protection ([ST4300USBM](#)ST4300USBM)

**Compatible USB 2.0 Hubs:**

7-Port Industrial USB 2.0 Hub ESD Protection & 350W Surge Protection (HB20A7AME)

7-Port Industrial USB 2.0 Hub with ESD & 350W Surge Protection (ST7200USBM)

4-Port Industrial USB 2.0 Hub with ESD Protection & 350W Surge Protection (HB20A4AME)

4-Port Industrial USB 2.0 Hub with ESD Protection (ST4200USBM)

The external terminal power adapter can also be used with any other devices that can support 20V power supply including a variety of StarTech.com Ethernet Switches and Serial Adapters.

The ITB20D3250 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Features

- Terminal block power adapter has been designed for StarTech.com industrial products
- Use as an alternative power source, replacement, or back-up power supply when sufficient bus-power is unavailable
- Includes regional plug attachments for NA/JP, EU, UK & ANZ
- Includes an attached two conductor terminal block
- Includes an additional three conductor terminal block

<b>Power</b>	Warranty	1 Year
	Input Current	1.4A Max.
	Input Voltage	110V-240V AC
	Output Current	3.25A
	Output Voltage	20V DC
	Plug Type	Terminal Block (2 Wire)
		Terminal Block (3 Wire)
Power Consumption (In Watts)	65W	
<b>Environmental</b>	Humidity	20% ~ 80% RH
	Operating Temperature	+ 0°C ~ + 40°C
	Storage Temperature	- 20 °C ~ + 80°C
<b>Physical Characteristics</b>	Product Height	0.000
	Product Length	0.000
	Product Width	0.000
	Weight of Product	0.000
<b>Packaging Information</b>	Package Height	55.000
	Package Length	166.000
	Package Width	242.000
	Shipping (Package) Weight	810.000
<b>What's in the Box</b>	Included in Package	1 - Universal 65W Power Adapter
		4 - Power Cords (NA/JP, EU, UK, ANZ)
		1 - Two Conductor Terminal Block Connector (Attached)
		1 - Three Conductor Terminal Block Connector
		1 - Quick Start Guide

Product appearance and specifications are subject to change without notice.