



# 1715L 17-inch LCD

Touchscreen Monitor



**Integrated Touch**



**Commercial Grade**



**3-Year Warranty**

## Product Overview

The Elo 1715L 17-inch standard format touchscreen monitor is designed, developed and built to provide a space-saving and cost-effective touch solution. The 17-inch touchscreen monitor can function as a desktop or wall-mounted unit and includes a VESA mounting option. The touchscreen is factory-sealed against dirt, dust, and liquids and with controls on the side rather than the front, the touchscreen can be locked-out for public use.

**Available with AccuTouch® five-wire resistive and IntelliTouch® surface acoustic wave (SAW) with an anti-glare display and Dual/Serial USB**

**Touchscreen sealed from dirt, dust and liquid**

**Removable base and VESA mounting option**

## 1715L 17-inch LCD Desktop Touchmonitor

Specifications	
Model	1715L
Color	Dark gray
Active Display Area	13.3" x 10.6" (338mm x 270mm)
Monitor Dimensions	15.4" x 14.4" x 8.0" (391mm x 366mm x 203mm)
LCD Technology	Active Matrix TFT LCD with LED backlighting
Diagonal Size	17"
Native Resolution	1280 x 1024
Other Supported Resolutions	1280 x 1024 @ 60 or 75 Hz; 1280 x 960 @ 60 Hz; 1152 x 864 @ 75 Hz; 1024 x 768 @ 60, 65 Hz, 70 or 75 Hz; 832 x 624 @ 75 Hz; 800 x 600 @ 56, 60, 72 or 75 Hz; 720 x 400 @ 70 Hz; 720 x 350 @ 70 Hz; 640 x 480 @ 60, 66 Hz, 72 or 75 Hz
Number of Colors	16.7 million
Number of Touches	Single-touch
Brightness (typical)	LCD panel: 250 nits; IntelliTouch: 225 nits; AccuTouch: 200 nits
Response Time - Total (typical)	5 msec
Viewing Angle (from center)	Horizontal: ±85° or 170° total; Vertical: ±80° or 160° total
Contrast Ratio (typical)	1000:1
Video	Input Connector: 15-pin female D-sub Sync Format: Separate H&V syncs, Composite sync, and Sync-On-Green Displayable horizontal scan frequency range: 31.5 - 80 KHz Displayable vertical scan (frame rate) frequency range: 56.3 - 75 Hz
Power	AC Input - Input Connector: IEC 60320 C6; Input voltage range: 100-240VAC 50/60Hz DC Input - Input Connector: Coaxial power jack (Barrel inner diameter: 6.4 +/- 0.3mm. Pin outer diameter: 2.0 +0.0 -0.1mm. Barrel depth: 8.8 +/- 0.3mm); Input Voltage range: 12V +/- 5%
Power Consumption (Typical):	Monitor only: ON: 10.52 W; SLEEP: 1.34 W; OFF: 0.46 W
Shipping Dimensions	17.99" x 11.42" x 17.32" (457mm x 290mm x 440mm)
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 60°C)
Humidity	Operating 20%-80%; Storage 10%-90% noncondensing
Weight	Actual: 15.2lb (6.9kg); Shipping: 21.2lb (9.6kg)
Regulatory Approvals and Declarations	UL, cUL, FCC, CE, UKCA, VCCI, IC, RCM
User's Controls	Digital OSD. OSD buttons: menu, up, down, select, power; OSD: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall, Language (English, German, Spanish, Japanese, French); OSD disable/enable: power, OSD menu
Mounting Options	Removable base, 100 mm VESA mount; threaded-through mounting holes under base
Warranty	3 years
Extended Warranty	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
MTBF	50,000 hours demonstrated
What's in the Box	QIG, User Manual CD, VGA cable, serial cable (attached if support combo), power cord, USB cable

## Ordering Information

Model	Part Number	Technology	Interface	Surface Treatment	Color	Availability
1715L	E603162	AccuTouch	Serial/USB	Antiglare	Dark Gray	Americas, EMEA
	E719160	IntelliTouch	Serial/USB	Antiglare	Dark Gray	Americas, EMEA

Learn more about Elo at [EloTouch.com](http://EloTouch.com).

### Americas

Tel +1 408 597 8000  
elosales.na@elotouch.com

### Europe (EMEA)

Tel +32 16 930 136  
EMEA.Sales@elotouch.com

### Asia Pacific

Tel +86 (21) 3329 1385  
www.elotouch.com.cn

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, AccuTouch and IntelliTouch are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.  
© 2021 Elo Touch Solutions, Inc. All rights reserved. 21071AES00068

