

# Product data sheet

Specifications



## APC Rack PDU 9000 Switched, ZeroU, 11.5kW, 200-240V, (21) C13/C15 & (3) C19/C21

APDU9981NA3

### Overview

Lead time Usually in Stock

### Main

|                           |  |
|---------------------------|--|
| Color                     | Black  |
| Product or Component Type | PDU  |
| PDU Type                  | Switched   |
| Cord length               | 6 ft (1.8 m)   |
| Number of cables          | 1  |
| Provided Equipment        | Installation guide<br>Rack Mounting brackets<br>Safety guide |

### Complementary

|                             |                        |
|-----------------------------|------------------------|
| Input Voltage               | 415 V 3 phase          |
| Height                      | 70.5 in (179.1 cm)     |
| Width                       | 2.2 in (5.5 cm)        |
| Output Voltage              | 208 V<br>240 V         |
| Depth                       | 1.8 in (4.6 cm)        |
| Net Weight                  | 15.4 lb(US) (7 kg)     |
| Mounting Location           | Side                   |
| Mounting preference         | No preference          |
| Input Plug Type             | IEC 60309 20 A 3P+N+PE |
| Mounting Mode               | Not rack-mountable     |
| Rack units                  | 0U                     |
| USB compatible              | No                     |
| Mounting position           | Vertical               |
| Communication Port Protocol | SNMP<br>Redfish        |
| Line Rated Current          | 16 A                   |
| Max line current            | 20 A                   |
| Input current limits        | 20 A                   |
| Load Capacity               | 11500 VA               |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                                   |                       |
|-----------------------------------|-----------------------|
| <b>Input Frequency</b>            | 50/60 Hz              |
| <b>Outlet type and quantity</b>   | 21C13/C15<br>3C19/C21 |
| <b>Communication Network Type</b> | 10/100/1000BASE-T     |

## Environment

|  |  |
|--|--|
| <b>Product Certifications</b>                | cUL Listed<br>FCC part 15 class A<br>PSE         |
| <b>Standards</b>                             | UL 62368-1                                       |
| <b>Ambient Air Temperature for Operation</b> | 23.0000000000...140.0000000000 °F (-5...60 °C)   |
| <b>Relative Humidity</b>                     | 5...95 %   |
| <b>Operating altitude</b>                    | 0...10000 ft                                     |
| <b>Ambient Air Temperature for Storage</b>   | -13.0000000000...149.0000000000 °F (-25...65 °C) |
| <b>Storage Relative Humidity</b>             | 5...95 %   |
| <b>Storage altitude</b>                      | 0...50000 ft (0.0000000000...15240.0000000000 m) |

## Ordering and shipping details

|             |              |
|-------------|--------------|
| <b>GTIN</b> | 731304404255 |
|-------------|--------------|

## Packing Units

|                                     |                        |
|-------------------------------------|------------------------|
| <b>Unit Type of Package 1</b>       | PCE                    |
| <b>Number of Units in Package 1</b> | 1                      |
| <b>Package 1 Height</b>             | 78.8 in (200.2 cm)     |
| <b>Package 1 Width</b>              | 4.5 in (11.4 cm)       |
| <b>Package 1 Length</b>             | 6.5 in (16.5 cm)       |
| <b>Package 1 Weight</b>             | 19.73 lb(US) (8.95 kg) |

## Contractual warranty

|                 |                           |
|-----------------|---------------------------|
| <b>Warranty</b> | 3 years repair or replace |
|-----------------|---------------------------|

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)