LightScene™ EV-105 Accent Lighting 3LCD Laser Projector



The dynamic laser projector for digital art and signage.

Integrated lighting and digital display — project dynamic, experiential content to engage audiences in retail, hospitality and event spaces, showrooms and museums

Create head-turning digital signage — illuminate and project on virtually any surface or material, for digital art, commercial signage and décor applications



Breakthrough laser technology — provides up to 20,000 hours of virtually maintenance-free operation¹, plus a sealed optical engine, for amazing image quality matched by outstanding performance

Robust content management — via Epson's Web-based application or over the network with Crestron®, Art-Net and more

Scalable, for an array of applications — install multiple LightScene projectors and utilize Edge Blending technology for versatile, breathtaking displays

Easily programmable — includes templates, effects, color filters and customizable options; playlist and playback function allows for seamless content management for single or multiple LightScene projectors

Flexible positioning — 1.58x powered optical zoom, plus powered focus, allows the projector to be installed in both large and small spaces

Expansive connectivity — HDMI[®], RJ-45, wired and wireless LAN, and SD card slot² for direct content storage when needed

Bright visual display system - 2,000 lumens equal color and white brightness for vibrant, rich color³









LightScene™ EV-105 Accent Lighting 3LCD Laser Projector

Specifications

Projection System RGB liquid crystal shutter projection

Projection Method Direct Mounting, Lighting Track (requires Lighting Track option), Floor Standing (requires Floor Stand option)

Driving Method Poly-silicon TFT Active Matrix Pixel Number 1,024,000 dots (1280 x 800) x 3 Color Brightness³ Color Light Output: 2,000 lumens White Brightness³ White Light Output: 2,000 lumens

Aspect Ratio 16:10 widescreen Native Resolution WXGA (1280 x 800) **Light Source** Laser Diode

Laser Life¹ Normal Mode: Up to 20,000 hours

Extended Mode: Up to 30,000 hours Throw Ratio Range 1.38 (Zoom:Wide), 2.19 (Zoom: Tele) Size (Projected Distance)

30" - 133" [0.88 - 4.0 m] (Zoom: Wide) 30" - 133" [1.41 - 6.34 m] (Zoom: Tele)

Keystone Correction Manual Vertical: ± 45 degrees;

Horizontal: ± 40 degrees

Dynamic Contrast Ratio Up to 2,500,000:1 Color Reproduction Up to 16.7 million colors

Project From Nearly Any Angle Movement: Left/Right: 180 degrees, Up/Down: 180 degrees;

Ball-joint Axis Rotation: 360 degrees

Track Compatibility Halo: TEK441, 442, 443 Juno: TEK44FT (Black/White) Global Trac: TEK44-1, 44-2, 44-3

Interfaces

1x HDMI

1x SD Card

1x Stereo Mini Out

1x USB connector Type A: For 1200 mA power supply only. (This port cannot be used to transfer data)

1x USB connector mini Type B: For Firmware update

1x Wired LAN RJ-45

Wireless 802.11b/g/n LAN IEEE 802.11b: 11 Mbps*, IEEE 802.11g: 54 Mbps*, IEEE 802.11n: 130 Mbps*

*Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.

Projection Lens

Type Optical zoom (Powered)/Focus (Powered)

F-number 1.51 – 1.92 **Focal Length** 18.2 – 28.4 mm

Zoom Ratio 1 – 2.21 (Total), (Optical zoom: 1 – 1.58, Digital zoom: 1 - 1.4)

Other

Input Signal HDMI

Operating Temperature 41 ° to 104 °F (5 ° to 40 °C)

(20 - 80% humidity, no condensation)

Power Supply Voltage $100 - 240 \text{ V AC} \pm 10\%$, 50/60 Hz

Power Consumption Normal Mode: 173 W

Quiet Mode: 118 W Standby Mode: 2.0 W Energy-saving Mode: 0.30 W

Fan Noise

Normal Mode: 34 dB Quiet Mode: 22 dB

Security Enterprise Level Security Encryption

Country of Origin China



Dimensions

Power Supply Unit 18" x 4.3" x 2.5" (W x D x H) Weight 15.2 lb (Main unit 11.0 lb, Direct mount unit 4.2 lb)

Remote Control

Features Brightness level, A/V Mute, Focus, Zoom, Volume, Spotlight, HDMI, LAN, SD Card, Keystone, Pattern, Menu, Effect

Operating Angle

Front to Rear: 15 - 60 degrees Right to Left: 60 - 60 degrees Operating Distance 23 ft (7 m)

Eco Features

RoHS compliant Recyclable product4

Epson America, Inc. is a SmartWay® Transport Partner⁵

Support

Epson ConnectionSM

Pre-sales support: U.S. and Canada (800) 463-7766

Internet website: www.epson.com

Service Programs Limited Warranty: 3 years or 20,000 hours, whichever

comes first

Epson Road Service Program with free Next-Business-Day replacement6

PrivateLine®: Dedicated toll-free support (800) 637-7661 (U.S. and Canada only)

What's in the Box

LightScene EV-105 Laser Projector, Fall Protection Wireset, Hexagon Wrench, Projector Remote Control, 2x AA Batteries, Direct Mount Unit, Power Cable Cover, 2x HDMI Cable Clamp, Quick Setup Guide, Direct Mount Installation Guide

Ordering Information

LightScene EV-105 Lighting Track Mount (ELPMB54W) Floor Stand (ELPMB55W)

V11H868120 V12H933B20 V12H888B10



LightScene EV-105 shown with optional Floor Stand, sold separately,

1 20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first. | 2 Memory card not included. | 3 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4: white light output measured in accordance with ISO 21118. | 4 For convenient and reasonable recycling options, visit www.epson. com/recycle | 5 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. 6 Expedited shipping not available in all areas. Road Service orders must be in by 3 p.m. Eastern Time for Next-Business-Day delivery

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future eco.epson.com



Epson Canada Limited Epson America, Inc. www.epson.com 3840 Kilroy Airport Way, Long Beach, CA 90806 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and LightScene are trademarks of Seiko Epson Corporation. PrivateLine is a registered trademark and Epson Connection is a service mark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2018 Epson America, Inc. Com-SS-Oct-13 CPD-55323 3/18

Co	nta	act
OU	1116	ıcı