

# Product data sheet

Specifications



## APC NetShelter Switched Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, 8 C13 outlets, C20 cord

AP7921B

### Overview

<b>Presentation</b>	This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.
---------------------	--

<b>Lead time</b>	Usually in Stock
------------------	------------------

### Main

<b>Color</b>	Black
<b>Product or Component Type</b>	PDU
<b>PDU Type</b>	Switched
<b>Cord length</b>	8.2 ft (2.5 m)
<b>Number of cables</b>	1
<b>Provided Equipment</b>	Installation guide Rack Mounting brackets User Manual

### Complementary

<b>Input Voltage</b>	200 V 208 V 230 V
<b>Height</b>	1.7 in (4.4 cm)
<b>Width</b>	17.5 in (44.5 cm)
<b>Output Voltage</b>	208 V 230 V
<b>Depth</b>	4.3 in (10.8 cm)
<b>Net Weight</b>	5.004 lb(US) (2.27 kg)
<b>Mounting Location</b>	Front Rear
<b>Mounting preference</b>	No preference
<b>Input Plug Type</b>	IEC 60320 C20
<b>Mounting Mode</b>	Rack-mounted
<b>Rack units</b>	1U
<b>Mounting position</b>	Horizontal

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Line Rated Current	16 A
Acceptable Input Voltage	200...240 V
Input current limits	20 A
Load Capacity	3680 VA
Input Frequency	50/60 Hz
Outlet type and quantity	8 IEC 60320 C13

## Environment

Product Certifications	cUL Listed CE CSA GOST IRAM MIC UL Listed VDE VCCI
Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950
Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

GTIN	731304331629
Country of origin	IN

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 in (7 cm)
Package 1 Width	13.5 in (34.3 cm)
Package 1 Length	18.5 in (47 cm)
Package 1 Weight	7.61 lb(US) (3.45 kg)

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

## Resource performance

Energy Efficient Product

Take-Back Program Available

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

**California Proposition 65** WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)