


# HP Color LaserJet CM1015/CM1017 MFP User Guide





# HP Color LaserJet CM1015/CM1017 MFP

---

User Guide



## Copyright and License

© 2006 Copyright Hewlett-Packard Development Company, L.P.

Reproduction, adaptation, or translation without prior written permission is prohibited, except as allowed under the copyright laws.

The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Part number CB394-90907

Edition 1, 10/2006

## Trademark Credits

Adobe Photoshop® and PostScript® are trademarks of Adobe Systems Incorporated.

Microsoft® and Windows® are U.S. registered trademarks of Microsoft Corporation.

Netscape™ and Netscape Navigator™ are U.S. trademarks of Netscape Communications Corporation.

UNIX® is a registered trademark of The Open Group.

ENERGY STAR® and the ENERGY STAR logo® are U.S. registered marks of the United States Environmental Protection Agency. Details on the proper use of the marks are explained in the "Guidelines for Proper use of the ENERGY STAR® Name and International Logo."



# Table of contents

## 1 Multifunction peripheral (MFP) basics

HP Color LaserJet CM1015/CM1017 MFP Series configurations .....	2
HP Color LaserJet CM1015/CM1017 MFP Series features .....	3
Walkaround .....	5
Software .....	8
Software and supported operating systems .....	8
Install software .....	9
Software tips .....	10
Download the latest printing software .....	10
What other software is available? .....	10

## 2 Print media

Media supported on this MFP .....	12
Select print media .....	14
Media that can damage the printer .....	14
Media to avoid .....	14
Special media for printing .....	15
Envelopes .....	15
Labels .....	15
Transparencies .....	16
Glossy paper and photo paper .....	16
Letterhead or preprinted forms .....	16
Heavy paper .....	16

## 3 Control panel

HP Color LaserJet CM1015 MFP control panel features .....	18
Use the two-line display (HP Color LaserJet CM1015 MFP) .....	20
Use the control-panel arrows to navigate on the HP Color LaserJet CM1015 MFP .....	20
HP Color LaserJet CM1017 MFP control panel features .....	21
Use the graphical display (HP Color LaserJet CM1017 MFP) .....	23
Use the control-panel arrows to navigate on the HP Color LaserJet CM1017 MFP .....	23
Control-panel menus .....	24
Use the control-panel menus .....	24
Control-panel menu map .....	24

## 4 Software for Windows

Printer driver recommendations .....	30
User assistance .....	30
Install the PostScript driver using Add Printer .....	31

Software .....	32
Other software .....	33
Change from a direct-connected shared MFP to a network port-connected MFP configuration .....	34
Uninstall the printing software .....	35
Uninstall Windows software via the Program group .....	35
Uninstall Windows software using Add or Remove Programs .....	35
Uninstall a Recommended or Custom installation .....	36
Delete printer drivers from the printers folder .....	36
Windows 2000 or Windows XP .....	36

## 5 Software for Macintosh

Macintosh utility and application support .....	38
Install Macintosh printing system software for networks .....	38
Install Macintosh printing system software for direct connections (USB) .....	39
Macintosh printer drivers .....	40
Supported printer drivers .....	40
Open the printer drivers .....	40
Use features in the Macintosh printer driver .....	41
Create and use presets in Mac OS X .....	41
Print a cover page .....	41
Print multiple pages on one sheet of paper .....	41
Print on both sides of the paper .....	42
Set the color options .....	42
Enable memory .....	43
Manage MFP color options on Macintosh computers .....	44
Print Color as Gray .....	44
Advanced color options for text, graphics, and photographs .....	44
HP Device Configuration (Mac OS X V10.3 and Mac OS X V10.4) .....	45
Solve common Macintosh problems .....	46
Solve Problems with Mac OS X .....	46

## 6 Print

Load trays .....	50
Load tray 1 (single-sheet feed tray) .....	50
Load tray 2 .....	51
Print on special media .....	56
Control print jobs .....	57
Selecting print media settings .....	57
Printer-driver features .....	58
Restore the default printer-driver settings .....	58
Print from Windows .....	59
Printer-driver settings .....	59
Print on both sides of the paper .....	60
Cancel a print job .....	62

## 7 Color

Overview .....	64
HP ImageREt 2400 .....	64
Media selection .....	64

Color options .....	64
Manage color options .....	65
Print in Grayscale .....	65
Automatic versus Manual color adjustment .....	65
Change color options .....	65
Halftone options .....	65
Edge Control .....	66
Standard red-green-blue (sRGB) .....	66
RGB Color .....	66
Neutral Grays .....	67
Match colors .....	68

## 8 Copy

Basic copy functions .....	70
Start a copy job .....	70
Change the number of copies for the current job .....	70
Cancel a copy job .....	70
Copy paper .....	71
Set the MFP to make only black and white copies .....	71
Adjust copy quality .....	71
Adjust the color balance in copies .....	72
Set color balance on a per-job basis .....	73
Adjust the lighter/darker (contrast) setting .....	73
Reduce or enlarge copies .....	74
Copy edge-to-edge originals .....	75

## 9 Scan

Scan methods .....	78
Supported file types .....	79
Scan from the device control panel .....	80
Program the device Scan To button from the control panel .....	80
Scan by using HP Solution Center (Windows) .....	82
To view HP Solution Center .....	82
Scan from the device and HP Director (Macintosh) .....	83
Scanning tasks .....	83
Scan using TWAIN-compliant and WIA-compliant software .....	84
Use TWAIN-compliant and WIA-compliant software .....	84
Scan from a TWAIN-enabled program .....	84
Scan from a WIA-enabled program (Windows XP only) .....	84
Scan by using optical character recognition (OCR) software .....	84
Readiris .....	84
Scan a photo .....	85
Scan edge-to-edge originals .....	85
Cancel a scan job .....	85
Scanner resolution and color .....	85
Resolution and color guidelines .....	86
Color .....	86

## 10 Photo

Insert a memory card .....	88
View or rotate photos from the memory card .....	90
Create a photo slideshow on the graphical display screen .....	91
Enable or disable a memory card .....	92
Print photos directly from the memory card .....	93
Print and scan photos from a proof sheet .....	94
Save photos to the workstation from a memory card .....	95
Print photos using the Photo Features button .....	96
Print a memory card index .....	97

## 11 Network Setup and Administration (HP Color LaserJet CM1017 MFP)

Set up the MFP and use it on the network .....	100
Configure a network port-connected MFP configuration (direct mode or peer-to-peer printing) .....	100
Configure a direct-connected shared MFP (client server printing) .....	100
Manage the network .....	101
View network settings .....	101
Restore the network defaults .....	101
Change network settings .....	101
Change from a direct-connected shared MFP to a network port-connected MFP configuration .....	101
Use the control panel .....	102
Network configuration page .....	102
Configuration page .....	102
IP configuration .....	102
Manually configure a static IP address .....	102
Automatic configuration .....	103
Link speed settings .....	103
Supported network protocols .....	104
TCP/IP .....	105
Internet Protocol (IP) .....	105
Transmission Control Protocol (TCP) .....	105
User Datagram Protocol (UDP) .....	105
IP address .....	105
Configure IP parameters .....	106
Dynamic Host Configuration Protocol (DHCP) .....	106
BOOTP .....	106
Subnets .....	106
Subnet mask .....	106
Gateways .....	107
Default gateway .....	107
Problem Solving .....	107
Verify that the MFP is on and online .....	107
Resolve communication problems with the network .....	108

## 12 How do I?

Control panel and other settings: How do I? .....	112
HP Color LaserJet CM1017 MFP control panel features .....	112
Use the graphical display (HP Color LaserJet CM1017 MFP) .....	113



Use the control-panel arrows to navigate on the HP Color LaserJet CM1017 MFP .....	114
Control-panel menus .....	115
Use the control-panel menus .....	115
Control-panel menu map .....	115
Print: How do I? .....	120
System Settings .....	120
Device information .....	120
Paper handling .....	121
Print quality .....	121
Print density .....	121
Set the system password .....	122
Paper types .....	123
System setup .....	123
Service .....	123
Device Polling Page .....	123
Print Settings .....	123
Printing .....	123
PCL5c .....	124
PostScript .....	124
Memory card (HP Color LaserJet CM1017 MFP only) .....	124
Control print jobs .....	124
Selecting print media settings .....	125
Printer-driver features .....	125
Restore the default printer-driver settings .....	126
Print from Windows .....	126
Printer-driver settings .....	126
Special media for printing .....	127
Envelopes .....	127
Labels .....	128
Transparencies .....	128
Glossy paper and photo paper .....	128
Letterhead or preprinted forms .....	128
Heavy paper .....	129
Copy and Scan: How do I? .....	130
Scan from the device control panel .....	130
Program the device Scan To button from the control panel .....	130
Set the MFP to make only black and white copies .....	131
Photo: How do I? (HP Color LaserJet CM1017 MFP only) .....	132
Print photos directly from the memory card .....	132
Enable or disable a memory card .....	132
Print and scan photos from a proof sheet .....	132
Save photos to the workstation from a memory card .....	133
Network: How do I? (HP Color LaserJet CM1017 MFP only) .....	134
Find the network IP address .....	134
Restore the network defaults .....	134
Maintenance: How do I? .....	135
Set the system password .....	135
Clean the scanner glass .....	136
Change MFP toner warnings .....	136

Calibrate the MFP .....	136
Calibrate the MFP from the front control panel .....	137
Calibrate the MFP from the HP ToolboxFX .....	137
Clean the MFP .....	137
Clean the paper path using HP ToolboxFX .....	138

### 13 Managing and maintaining the multifunction peripheral (MFP)

Information pages .....	140
Demo page .....	140
Configuration page .....	140
Supplies Status page .....	142
Networking page (HP Color LaserJet CM1017 MFP only) .....	143
Fonts pages .....	144
Usage page .....	144
Menu map .....	146
HP ToolboxFX .....	147
View HP ToolboxFX .....	147
Status .....	148
Event log .....	148
Alerts .....	149
Set up status alerts .....	149
Set up e-mail alerts .....	149
Help .....	149
System Settings .....	150
Device information .....	150
Paper handling .....	151
Print quality .....	151
Print density .....	151
Set the system password .....	152
Paper types .....	153
System setup .....	153
Service .....	153
Device Polling Page .....	153
Print Settings .....	153
Printing .....	153
PCL5c .....	154
PostScript .....	154
Memory card (HP Color LaserJet CM1017 MFP only) .....	154
Network settings .....	154
Use the embedded Web server .....	155
Access the embedded Web server using a network connection .....	155
Information tab .....	156
Settings tab .....	156
Networking tab .....	157
Other links found in HP ToolboxFX .....	157
Manage supplies .....	158
Supplies life .....	158
Check and order supplies .....	158
Check supply status and order using the control panel .....	158
Check and order supplies using HP ToolboxFX .....	158

Check and order supplies using HP Solution Center .....	159
Supplies Storage Guidelines .....	159
Replace and recycle supplies .....	159
HP policy on non-HP supplies .....	159
Reset the MFP for non-HP supplies .....	159
HP anti-counterfeit supplies Web site .....	160
Clean the scanner glass .....	161
Clean the MFP .....	162
Clean the paper path using HP ToolboxFX .....	162
Cartridge-out override .....	163
Configuration .....	163
On-going operation .....	163
Change print cartridges .....	164
Change the print cartridge .....	164
Calibrate the MFP .....	168
Calibrate the MFP from the front control panel .....	168
Calibrate the MFP from the HP ToolboxFX .....	168

## 14 Problem solving

Problem solving process .....	170
Problem solving checklist .....	170
Control-panel messages .....	172
Solve print problems .....	179
Print-quality problems .....	179
Identifying and correcting print defects .....	179
Print-quality checklist .....	179
General print quality issues .....	179
Solve issues with printing color documents .....	183
Media-handling problems .....	185
Print-media guidelines .....	185
Solve print-media problems .....	185
Performance problems .....	187
Resolve copy problems .....	189
Resolve scanning problems .....	191
The device control panel display has black lines or dots, or becomes blank .....	194
Was the device exposed to an electric or magnetic field? .....	194
Clear paper jams .....	195
Where to look for jams .....	195
Clear jams from inside the MFP .....	196
Clear jams from tray output area .....	198
Clear jams from the back of the MFP .....	199
Clear jams from tray 2 or optional tray 3 .....	200
Additional problem solving tools .....	202
Device pages and reports .....	202
Demo page .....	202
Configuration page .....	202
Supplies Status page .....	202
HP ToolboxFX .....	202
View HP ToolboxFX .....	202
Service menu .....	202

Restore the factory-set defaults .....	202
Clean the paper path .....	203
Calibrate the MFP .....	203
<b>15 Work with memory</b>	
MFP memory .....	206
Install memory DIMMs .....	207
Check DIMM installation .....	211
Enable memory .....	211
<b>Appendix A Accessories and supplies information</b>	
Supplies .....	214
Memory .....	214
Cable and interface accessories .....	215
Paper handling accessories .....	215
Paper and other print media .....	216
User-replaceable parts .....	216
Supplementary Documentation .....	217
<b>Appendix B Service and support</b>	
Hewlett-Packard limited warranty statement .....	220
Print Cartridge Limited Warranty Statement .....	221
HP Customer Care .....	222
Availability of support and service .....	223
HP Care Pack™ Services and Service Agreements .....	223
Repacking the MFP .....	224
Repack the MFP .....	224
Service information form .....	225
<b>Appendix C Specifications</b>	
Multifunction peripheral (MFP) specifications .....	228
<b>Appendix D Regulatory information</b>	
Introduction .....	232
FCC regulations .....	233
Environmental Product Stewardship program .....	234
Protecting the environment .....	234
Ozone production .....	234
Power consumption .....	234
HP LaserJet printing supplies .....	234
Disposal of waste equipment by users in private households in the European Union ....	236
Material safety data sheet .....	236
Declaration of conformity .....	237
Country/region-specific safety statements .....	238
Laser safety statement .....	238
Canadian DOC statement .....	238
Korean EMI statement .....	238
VCCI statement (Japan) .....	238

Japanese Power Cord Statement ..... 239  
Finnish laser statement ..... 240

**Index ..... 241**




# 1 Multifunction peripheral (MFP) basics


- [HP Color LaserJet CM1015/CM1017 MFP Series configurations](#)
- [HP Color LaserJet CM1015/CM1017 MFP Series features](#)
- [Walkaround](#)
- [Software](#)

# HP Color LaserJet CM1015/CM1017 MFP Series configurations


HP Color LaserJet CM1015 MFP



HP Color LaserJet CM1017 MFP



- **Speed.** Prints 8 pages per minute (ppm) in color or monochrome (black).
  - **Trays.** The MFPs include a single-sheet priority-feed slot (tray 1) and a 250-sheet universal tray (tray 2)
  - **Connectivity.** Hi-Speed USB 2.0 port
  - **Memory.** 96 MB of synchronous dynamic random-access memory (SDRAM).
  - **Display.** Tilt screen two-line display
- All the HP Color LaserJet CM1015 MFP features plus the following:
    - **Memory.** Four memory card slots
    - **Display.** Tilt screen graphical display
    - **Connectivity.** On-board networking



Optional 250-sheet tray 3



# HP Color LaserJet CM1015/CM1017 MFP Series features

HP Color LaserJet CM1015/CM1017 MFP Series	
<b>Color printing</b>	<ul style="list-style-type: none"><li>• Full color laser printing using the four process colors: cyan, magenta, yellow, and black (CMYK).</li></ul>
<b>Excellent print quality</b>	<ul style="list-style-type: none"><li>• HP print cartridges with ColorSphere toner achieve high gloss for a range of bright colors.</li><li>• ImageREt 2400 is a system of key color laser technologies that offer excellent print quality.</li><li>• True 600 by 600 dots per inch (dpi) text and graphics.</li><li>• Adjustable settings to optimize print quality.</li></ul>
<b>Ease of use</b>	<ul style="list-style-type: none"><li>• The few supplies are easy to install.</li><li>• Convenient access to MFP information and settings using the HP Solution Center and HP ToolboxFX software.</li><li>• Convenient access to all supplies and to the paper path through the front door.</li><li>• HP Photosmart Premier</li><li>• Adjust paper trays with one hand.</li></ul>
<b>Flexible paper handling</b>	<ul style="list-style-type: none"><li>• Trays 1 and 2 for letterhead, envelopes, labels, transparencies, custom-sized media, postcards, HP LaserJet glossy paper, HP LaserJet Tough paper, heavy paper, and HP Laser Photo paper.</li><li>• A 125-sheet top output bin.</li><li>• Print on Both Sides (manually). See <a href="#">Print on both sides of the paper</a>.</li></ul>
<b>Printer drivers</b>	<ul style="list-style-type: none"><li>• HP PCL6</li><li>• HP PostScript® Level 3 emulation</li></ul> <p>Includes 35 built-in HP PostScript Level 3 language fonts.</p>
<b>Interface connections</b>	<ul style="list-style-type: none"><li>• Hi-Speed 2.0 USB port.</li><li>• Built-in internal print server for connecting to a 10/100Base-T network. (HP Color LaserJet CM1017 MFP only)</li></ul>
<b>Energy savings</b>	<ul style="list-style-type: none"><li>• The MFP automatically conserves electricity by substantially reducing power consumption when it is not printing.</li><li>• Meets ENERGY STAR® guidelines for energy efficiency.</li></ul>
<b>Economical printing</b>	<ul style="list-style-type: none"><li>• N-up printing (printing more than one page on a sheet) and Printing on Both Sides features save paper. See <a href="#">Print on both sides of the paper</a>.</li></ul>
<b>Archive printing</b>	<p>When printing pages that are to be stored long-term, this option sets the printer to a mode that reduces toner smearing and dusting.</p> <p>The default setting is Off.</p>

---

## HP Color LaserJet CM1015/CM1017 MFP Series


---

<b>Supplies</b>	<ul style="list-style-type: none"><li>● A Supplies Status page with print cartridge gauges that estimate remaining supply level. Not available for non-HP supplies.</li><li>● No-shake cartridge design.</li><li>● Authentication for original HP print cartridges.</li><li>● Easy ordering for replacement supplies.</li></ul>
<b>Accessibility</b>	<ul style="list-style-type: none"><li>● Online user guide compatible with text screen-readers.</li><li>● All doors and covers can be opened by using one hand.</li></ul>
<b>Expandability</b>	<ul style="list-style-type: none"><li>● Optional tray 3. This 250-sheet universal tray prevents the need to frequently add paper to the MFP. Only one additional 250-sheet tray can be installed on the MFP.</li><li>● One DIMM slot for adding memory.</li></ul>
<b>Memory card slots</b> (HP Color LaserJet CM1017 MFP only)	Supports a variety of memory cards. See the <a href="#">Photo</a> chapter for more information.
<b>Copy</b>	<ul style="list-style-type: none"><li>● Provides full-color copying from letter/A4- sized scanner glass.</li><li>● Control panel buttons available for color and monochromatic copying.</li></ul>
<b>Scan</b>	<ul style="list-style-type: none"><li>● Provides 1200 pixels per inch (ppi), 24-bit full-color scanning from letter/A4-sized scanner glass.</li><li>● Scan-to E-mail</li><li>● Scan-to Folder</li></ul>

---


## Walkaround

The following figures show the locations and names of key MFP components.




**Figure 1-1** Front view (HP Color LaserJet CM1017 MFP shown)

1	Scanner
2	Output bin
3	Front door
4	Tray 1 (single sheet priority feed slot)
5	Tray 3 (optional; 250 sheets)
6	Tray 2 (250 sheets)
7	Memory card slots (HP Color LaserJet CM1017 MFP)
8	MFP control panel



**Figure 1-2** Back and side view

1	On/off switch
2	Power connection
3	Jam access door
4	Dust cover
5	DIMM access door
6	Network connection to 10/100 Base-T network (HP Color LaserJet CM1017 MFP only)
7	USB connection



**Figure 1-3** Transfer belt view (HP Color LaserJet CM1015 MFP)

1	Transfer belt (ETB)
---	---------------------

2	Magenta cartridge
3	Cyan cartridge
4	Yellow cartridge
5	Black cartridge



**CAUTION** Do not place anything on the transfer belt, located on the inside of the front door. Otherwise, the MFP can be damaged, adversely affecting print quality.

# Software

## Software and supported operating systems

For MFP setup and access to the full range of MFP features, HP strongly recommends installing the software provided. Not all software is available in all languages. See the *Getting Started Guide* for installation instructions, and see the Install Notes file for the latest software information.

The most recent drivers, additional drivers, and other software are available from the Internet and other sources. When Internet access is not available, see [HP Customer Care](#).

The MFP supports the following operating systems:

- Microsoft® Windows® 2000 and Windows XP (32-bit and x64-bit support)
- Macintosh OS X V10.3 and later
- Microsoft® Windows Server 2003–32-bit and x64-bit support (for drivers only)



**NOTE** Download the printer driver at [http://www.hp.com/support/cljCM1015\\_CM1017](http://www.hp.com/support/cljCM1015_CM1017).

**Table 1-1** HP Color LaserJet CM1015/CM1017 MFP software

Feature	Microsoft Windows Server 2003	Windows 2000 and XP	Macintosh OS X V10.3 and later
Windows Installer		✓	
HP PCL6 printer driver	✓	✓	
HP PostScript Level 3 emulation printer driver	✓	✓	
HP ToolboxFX software		✓	
HP imaging software (HP Color LaserJet CM 1017 MFP only)		✓	
Macintosh Installer			✓
Macintosh printer drivers			✓
Scan driver	✓	✓	✓
Mass Storage Driver (HP Color LaserJet CM 1017 MFP only and with USB connection)	✓	✓	✓
HP Solution Center		✓	
HP Director			✓

## Install software

The HP installer provides two workstation software installation options: Recommended or Custom. A Recommended installation installs software based on the workstation's operating system processor, memory, and disk space. A Custom installation installs only user-specified software options.

The system requirements for the installed software is:

- 300 MB free hard disk space
- CD-ROM drive
- USB port and USB cable or network RJ45 and cable

Requirements for PC systems:

- Windows® 2000, XP, 2003 Server: any Pentium® II processor (Pentium® III or greater recommended), 192 MB RAM (full install).
- G3 processor (G4 processor recommended) 128 MB RAM, 100 MB hard disk space, Mac OS X V10.3 or above.

Software	Installation option	Description
HP printer driver	Recommended and Custom	Allows applications to print to the device
HP Document Viewer	Custom	View and mark up digital photos or scanned documents
HP Photosmart Premier	Custom	Easily use and manage digital photos and scanned images
HP Photosmart Transfer	Recommended (when supported by the operating system, memory, and disk space.)	Provides the capability to easily upload and save images from the device photo card slot. (HP Color LaserJet CM1017 MFP only.)
HP Product Assistant	Recommended (when supported by the operating system, memory, and disk space.)	Detects certain software or device events and attempts to provide solutions
HP Software Update	Recommended (when supported by the operating system, memory, and disk space.)	Updates software capability after installation
HP Solution Center	Recommended (when supported by the operating system, memory, and disk space.)	Provides one place to access MFP capabilities
HP ToolboxFX	Recommended (when supported by the operating system, memory, and disk space.)	Provides status, troubleshooting help and product configuration and also enables scanning from the MFP front panel
HP ReadIris Pro	On separate CD	Provides capability to convert images to text
HP Scan driver	Recommended	Allows applications to scan from the device

## Software tips

Use these tips to learn more about the MFP software.

### Download the latest printing software

Check for and install upgrades to the printing software by downloading the drivers from the World Wide Web or HP's file transfer protocol (FTP) servers.

#### Download drivers

1. Go to [http://www.hp.com/support/cljCM1015\\_CM1017](http://www.hp.com/support/cljCM1015_CM1017). Click **support & drivers** block.
2. The Web page for the drivers might be in English, but the drivers themselves can be downloaded in several languages.

When Internet access is not available, contact HP Customer Care. (See [HP Customer Care](#) or the flyer that came in the MFP box.) See the Install Notes file for additional release information.

### What other software is available?

See the Install Notes file that is provided on the HP Color LaserJet CM1015/CM1017 MFP CD-ROM for information about additional included software.



## 2 Print media

- [Media supported on this MFP](#)
- [Select print media](#)
- [Special media for printing](#)

## Media supported on this MFP

Before purchasing large quantities of print media, always test a sample and make sure that the print media meets the requirements specified in this user guide and in the *HP LaserJet Printer Family Print Media Guide* at <http://www.hp.com/support/ljpaperguide>. For ordering information, see [Accessories and supplies information](#).



**CAUTION** Using print media that does not meet HP specifications can damage the MFP, requiring repair. This repair is not covered by the Hewlett-Packard warranty or service agreements.

**CAUTION** Do not use HP Inkjet photo paper with this MFP.




**NOTE** Remember to choose the correct printer-driver settings and paper settings from the control panel or the HP ToolboxFX when using special media. See [Print on special media](#).

This MFP accepts these types of media:

- Letter
- Legal
- A4
- Executive
- Com10 envelope
- Monarch
- C5 envelope
- DL envelope
- B5 (ISO)
- B5 envelope
- Custom (3"x5"–8.5"x14")
- JIS B5
- J-Postcard
- J-Double Postcard
- A5
- 8.5"x13"
- 16K (7.75" x 10.75")
- 16K (184 x 260 mm)
- 16K (195 x 270 mm)

**Table 2-1** Tray specifications

Media Type	Dimensions <sup>1</sup>	Weight	Capacity <sup>2</sup>
Paper	Minimum: 76 x 127 mm (3 x 5 inches)  Maximum: 216 x 356 mm (8.5 x 14 inches)	60 to 163 g/m <sup>2</sup> (16 to 43 lb)  Up to 176 g/m <sup>2</sup> (47 lb) for postcards	Tray 1: Single sheet of paper  Tray 2: Up to 250 sheets  Tray 3 (optional): Up to 250 sheets
			 <b>NOTE</b> Tray 3 does not accept postcards, envelopes, or other special media.
HP LaserJet glossy paper and HP LaserJet Photo paper <sup>4</sup>	Identical to Paper	75 to 220 g/m <sup>2</sup> (20 to 58 lb)	Tray 1: Single sheet of HP LaserJet glossy paper or HP LaserJet Photo paper  Tray 2: Up to 25 mm (0.99 inch) stack height
HP Premium Cover paper <sup>4</sup>	Identical to Paper	200 g/m <sup>2</sup> (53 lb) cover	Tray 1: Single sheet of HP Cover paper  Tray 2: Up to 25 mm (0.99 inch) stack height
Transparencies and opaque film	Identical to Paper	Thickness: 0.10 to 0.13 mm (3.9 to 5.1 mils)	Tray 1: Single sheet of transparency or opaque film  Tray 2: Up to 50 sheets for tray 2
Labels <sup>3</sup>	Identical to Paper	Thickness: up to 0.23 mm (up to 9 mils)	Tray 1: Single sheet of labels  Tray 2: Up to 25 mm (0.99 inch) stack height
Envelopes		Up to 90 g/m <sup>2</sup> (up to 24 lb)	Tray 1: Single envelope  Tray 2: Up to ten envelopes

<sup>1</sup> The MFP supports a wide range of standard and custom sizes of print media. Check the printer driver for supported sizes.

<sup>2</sup> Capacity can vary depending on media weight and thickness, and environmental conditions.

<sup>3</sup> Smoothness: 100 to 250 (Sheffield).

<sup>4</sup> Hewlett-Packard does not guarantee results when printing with other types of heavy paper.

## Select print media

Consider these factors when choosing print media.

### Media that can damage the printer

Do not use media that can damage the printer.

- Do not use media with staples attached.
- Do not use transparencies, labels, photo, or glossy paper designed for inkjet printers or other low temperature printers. Use only media that is specified for use with HP Color LaserJet printers.
- Do not use paper that is embossed or coated and is not designed for the temperatures of the fuser.
- Do not use letterhead paper with low temperature dyes or thermography. Preprinted forms or letterhead must use inks that are designed for the temperatures of heat of the fuser.
- Do not use any media that produces hazardous emissions, or that melts, offsets, or discolors when exposed to the temperature of the fuser.

To order HP LaserJet printing supplies, go to <http://www.hp.com/go/ljsupplies/> in the U.S. or to <http://www.hp.com/ghp/buyonline.html/> worldwide.

### Media to avoid

Media outside the printer specifications will cause a loss of print quality and increase the occurrence of jams.

- Do not use paper that is too rough. Use paper less than 250 Sheffield smoothness tested.
- Do not use paper with cutouts or perforations other than standard 3-hole punched paper.
- Do not use multi-part or multi-page forms.
- To ensure even color, do not use paper with a watermark if printing solid patterns.

# Special media for printing


This MFP supports printing on special media.

For tray, media orientation, and driver settings, see [Print on special media](#).

For instructions on loading envelopes, see [Load tray 1 \(single-sheet feed tray\)](#) or [Load tray 2](#).

## Envelopes

- Store envelopes flat.
- Envelopes should not be wrinkled, nicked, stuck together, or otherwise damaged. Do not use envelopes that have clasps, snaps, windows, coated linings, self-stick adhesives, or other synthetic materials.
- Only use envelopes where the seam extends all the way to the corner of the envelope as indicated in the following illustration.



1	Acceptable
2	Unacceptable

- Envelopes with a peel-off adhesive strip or with more than one flap that folds over to seal must use adhesives that are compatible with the heat and pressure in the fuser.



**CAUTION** Failure to follow the guidelines above can result in jams.

## Labels

When selecting labels, consider the quality of each component:

- For tray, media orientation, and driver settings, see [Print on special media](#).
- Only use labels with no exposed backing between them.
- Labels must lie flat.
- Do not use labels that have wrinkles, bubbles, or are damaged.
- Use only full sheets of labels; this MFP does not support print partial sheets of labels.
- Use only labels specified for use with HP Color LaserJet printers.

For instructions on loading labels, see [Load tray 1 \(single-sheet feed tray\)](#) or [Load tray 2](#).

## Transparencies

- Use only tray 1 or tray 2 to print on transparencies.
- For tray, media orientation, and driver settings, see [Print on special media](#).
- Place transparencies on a flat surface after removing from the MFP.
- Use only transparencies specified for use with HP Color LaserJet printers.



**CAUTION** To avoid MFP damage, only use transparencies that are recommended for use in laser MFPs. See [Accessories and supplies information](#).

Transparent print media not designed for LaserJet printing melts in the fuser, and damages the fuser.

## Glossy paper and photo paper

- Handle glossy paper and HP LaserJet Photo paper by the edges.
- For tray, media orientation, and driver settings, see [Print on special media](#).
- Use only glossy paper and photo paper specified for use with HP Color LaserJet printers.

## Letterhead or preprinted forms

- Avoid using raised or embossed letterhead.
- Use only non-flammable inks that do not damage the print rollers.
- For tray, media orientation, and driver settings, see [Print on special media](#).

For instructions on loading letterhead, see [Load tray 1 \(single-sheet feed tray\)](#) and [Load tray 2](#).

## Heavy paper

- Do not use paper that is heavier than the recommended media specification for this MFP. See [Media supported on this MFP](#) for more information.
- For tray, media orientation, and driver settings, see [Print on special media](#).

# 3 Control panel


- [HP Color LaserJet CM1015 MFP control panel features](#)
- [Use the two-line display \(HP Color LaserJet CM1015 MFP\)](#)
- [HP Color LaserJet CM1017 MFP control panel features](#)
- [Use the graphical display \(HP Color LaserJet CM1017 MFP\)](#)
- [Control-panel menus](#)

# HP Color LaserJet CM1015 MFP control panel features

The HP Color LaserJet CM1015 MFP contains the following lights and buttons on the control panel:



**NOTE** Print a demo page by pressing the **Scan To** and **Start Scan** buttons simultaneously.



**1** Supplies gauges: Displays consumption levels of print cartridges. Appears when the MFP shows the Ready state with no warnings, or when the MFP shows a warning or error message pertaining to a print cartridge or multiple supplies. When the supply is empty the gauge displays as empty. Flashing indicates a single supply is empty. These messages can display when:

- Missing cartridges
- Incorrectly placed cartridges
- Cartridges with an error
- Some non-HP cartridges



**CAUTION** Printing may continue when a non-HP supply is empty. To prevent MFP damage, frequently check the status of non-HP supplies. See [Hewlett-Packard limited warranty statement](#).



**NOTE** When a "?" displays on-screen, it may be because the supply is missing, it is a non-HP supply, or the status is being determined by the MFP.

**2** **Amber activity light:** An error has occurred. Printer requires attention.

**3** **Right arrow (>):** Press to navigate to the next submenu or the next value in the menu selection list. Also allows cursor movement forward a single position, or increments a numeric entry.



4	<b>Cancel (X)</b> : Whenever the <b>Ready</b> light blinks, press to cancel a print job. Pressing this button also exits the control-panel menus.
5	<b>OK</b> : <ul style="list-style-type: none"> <li>• Selects a menu item</li> <li>• Clears some printer-errors</li> <li>• Acknowledges use of a non-HP supply</li> </ul>
6	<b>Start Scan</b> : Starts scanning to the previously selected e-mail or folder destination. The MFP can also start a scan if a destination is not specified.
7	<b>Quality</b> : Press the <b>Left arrow</b> or the <b>Right arrow</b> to control copy quality.
8	<b># of Copies</b> : Press the <b>Left arrow</b> or the <b>Right arrow</b> to increase or decrease the number of copies produced.
9	<b>Paper</b> : Select the correct output paper size and type settings for the copy.
10	Press <b>Start Copy Color</b> to begin a color copy job.
11	Press <b>Start Copy Black</b> to begin a monochrome copy job.
12	<b>Copy Features</b> : Displays a menu of copy features.
13	<b>Lighter/Darker</b> : Press the <b>Left arrow</b> to lighten the copy or the <b>Right arrow</b> to darken the copy.
14	<b>Reduce/Enlarge</b> : Press the <b>Left arrow</b> to reduce the copy size or the <b>Right arrow</b> to enlarge the copy.
15	<b>Scan To</b> : Displays a list of pre-configured folders and e-mail destinations. To create a new destination, set up the <b>Scan To</b> destination on the workstation.
16	<b>Return to previous menu or menu item button</b> : Backs up one menu screen or one step in the current menu structure.
17	<b>Menu</b> : Opens the main menu system.
18	<b>Left arrow (&lt;)</b> : Press to navigate to the previous submenu or the previous value in the menu selection list. Also allows cursor movement back a single position, deletes the previous character, or decrements a numeric entry.
19	<b>Ready light (green)</b> : Green light is steady when the MFP can accept print jobs or blinks when the MFP receives print data.
20	<b>Message area</b> . Displays two lines of 16 characters each.

## Use the two-line display (HP Color LaserJet CM1015 MFP)

The two-line display shows menus, and messages. The display can be pulled up and angled for better viewing. Use the arrows on the control panel to navigate the menus on the control panel. Status and error messages will be displayed on the screen.

### Use the control-panel arrows to navigate on the HP Color LaserJet CM1015 MFP


- Press the **Left arrow** or **Right arrow** to navigate through all control panel menus.
- Press **Back** to return to the previous menu.
- Press **OK** to make a selection.



# HP Color LaserJet CM1017 MFP control panel features

The HP Color LaserJet CM1017 MFP contains the following lights and buttons on the control panel:



**NOTE** Print a demo page by pressing the **Scan To** and **Start Scan** buttons simultaneously.



<p>1</p>	<p>Graphical display. Message, menus, and supply gauge area.</p> <p>Supplies gauges: Displays consumption levels of print cartridges. Appears when the MFP shows the Ready state with no warnings, or when the MFP shows a warning or error message pertaining to a print cartridge or multiple supplies. When the supply is empty the gauge displays as empty. Flashing indicates a single supply is empty. These messages can display when:</p> <ul style="list-style-type: none"> <li>• Missing cartridges</li> <li>• Incorrectly placed cartridges</li> <li>• Cartridges with an error</li> <li>• Some non-HP cartridges</li> </ul> <p> <b>CAUTION</b> Printing may continue when a non-HP supply is empty. To prevent MFP damage, frequently check the status of non-HP supplies. See Hewlett-Packard limited warranty statement.</p> <p> <b>NOTE</b> When a “?” displays on-screen, it may be because the supply is missing, it is a non-HP supply, or the status is being determined by the MFP.</p>
<p>2</p>	<p><b>Amber activity light:</b> An error has occurred. Printer requires attention.</p>
<p>3</p>	<p><b>Up arrow (^):</b> Press to enter the main menu system or navigate to the previous menu item, or previous item in the selection list.</p>

4	<b>Cancel (X)</b> : Whenever the <b>Ready</b> light blinks, press to cancel a print job. Pressing this button also exits the control-panel menus.
5	<b>Right arrow (&gt;)</b> : Press to navigate to the next submenu or the next value in the menu selection list. Also allows cursor movement forward a single position, or increments a numeric entry.
6	<b>Down arrow (v)</b> : Press to navigate to the menu item below the current menu item.
7	<b>Start Photo</b> : Press to print one or more photos.
8	<b>Proofsheet</b> : Press to print a proofsheets.
9	<b>Start Scan</b> : Starts scanning to the previously selected e-mail or folder destination. The MFP can also start a scan if a destination is not specified.
10	<b># of Copies</b> : Press the navigation arrows to increase or decrease the number of copies produced.
11	<b>Lighter/Darker</b> : Press <b>Left arrow</b> to lighten the copy or the <b>Right arrow</b> to darken the copy.
12	Press <b>Start Copy Color</b> to begin a color copy job.
13	Press <b>Start Copy Black</b> to begin a monochrome copy job.
14	<b>Reduce/Enlarge</b> : Displays a list of temporary copy and size changes.
15	<b>Copy Features</b> : Displays a menu of copy features.
16	<b>Scan To</b> : Displays a list of pre-configured folders and e-mail destinations. To create a new destination, set up the <b>Scan To</b> destination on the workstation.
17	<b>Select Photos</b> : Press to choose one or more photos.
18	<b>Photo Features</b> : Press to navigate to select photo features.
19	<b>Return to previous menu or menu item</b> : Backs up one menu screen or one step in the current menu structure.
20	<b>Left arrow (&lt;)</b> : Press to navigate to the previous submenu or the previous value in the menu selection list. Also allows cursor movement back a single position, deletes the previous character, or decrements a numeric entry.
21	<b>Menu</b> : Opens the main menu system.
22	<b>Ready light (green)</b> : Green light is steady when the MFP can accept print jobs or blinks when the MFP receives print data.
23	<p><b>OK:</b></p> <ul style="list-style-type: none"> <li>● Selects a menu item</li> <li>● Clears some printer-errors</li> <li>● Acknowledges use of a non-HP supply</li> </ul>

# Use the graphical display (HP Color LaserJet CM1017 MFP)

The color graphics display shows menus, photos, and messages. The display can be pulled up and angled for better viewing. Use the arrows on the control panel to navigate the menus on the control panel and to select photos on the panel for printing. Status and error messages will be displayed on the screen.

After 60 minutes of inactivity, the color graphics display goes into Sleep State and the screen shuts off completely. The display turns back on when you perform an operation, such as pressing a control panel button, or inserting a memory card, accessing the HP All-in-One from a connected computer.

## Use the control-panel arrows to navigate on the HP Color LaserJet CM1017 MFP

- Press the **Up arrow** or **Down arrow** to navigate through all control panel menus.
- Press **Back** to return to the previous menu.
- Press **OK** to make a selection.

Press the **Left arrow** or **Right arrow** to complete the following tasks:

- Increase or decrease values on the horizontal scroll bar on various copy and photo menus.
- Browse photos on the graphical display from your memory card.
- Enter an IP address.

# Control-panel menus

## Use the control-panel menus

To gain access to the control-panel menus, use the following steps.

1. Press **Menu**.
  2. On the HP Color LaserJet CM1015 MFP, press **Left arrow** or **Right arrow** to navigate the listings. On the HP Color LaserJet CM1017 MFP, press **Up arrow** or **Down arrow** to navigate the listings.
- Press **OK** to select the appropriate option.
  - Press **Cancel** to cancel an action or return to the Ready state.
  - Press **Back** to move to the previous menu.

## Control-panel menu map

These menus are available from the control panel Main menu:

- Use the **Copy setup** menu to configure basic copy default qualities.
- Use the **Reports** menu to print reports that provide information about the printer.
- Use the **Photo setup** menu to configure defaults for photo printing.
- Use the **System setup** menu to establish basic printer settings. The **System setup** has several sub-menus. Each is described in the table.
- Use the **Service** menu to restore default settings, clean the printer, and activate special modes that affect print output.
- Use the **Network config.** menu to configure network settings.

**Table 3-1 Copy Setup Menu**

Menu item	Sub-menu item	Sub-menu item	Description
<b>Default Quality</b>			Sets the default copy quality.
<b>Default light/dark</b>			Sets the default lighter/darker option.
<b>Default Reduce/Enlarge</b>			Sets the default percentage to reduce or enlarge a copied document.
<b>Default # of copies</b>			Sets the default number of copies.
<b>Advanced</b>	<b>Color Balance</b>	Red	Increases or decreases the amount of these colors in the output.
		Green	
		Blue	
	<b>Background</b>		Increases or decreases the background color in a copy.

**Table 3-1** Copy Setup Menu (continued)

Menu item	Sub-menu item	Sub-menu item	Description
	<b>Contrast</b>		Increases or decreases the differences between whites and blacks of a copy.
	<b>Lightness</b>		Increases or decreases the background color in a copy.
	<b>Grayness</b>		Increases or decreases the color in the color copy of a black and white original.
	<b>Sharpen</b>		Increases or decreases the reproduction details in a copy.
	<b>Restrict color</b>		Permits the enabling or disabling of color copies.
<b>Restore defaults</b>			Sets all customized copy settings to the factory default values.

**Table 3-2** Reports Menu

Menu Item	Description
<b>Demo page</b>	Prints a color page that demonstrates print quality.
<b>Menu structure</b>	Prints a control-panel menu layout map. The active settings for each menu are listed.
<b>Configuration report</b>	Prints a list of all the printer settings. Includes network information when the printer is connected to the network.
<b>Supplies status page</b>	Prints the status of each print cartridge. Includes this information: <ul style="list-style-type: none"> <li>● Estimated pages remaining</li> <li>● Serial number</li> <li>● Number of pages printed</li> </ul>
<b>Network report</b>	Displays status for: <ul style="list-style-type: none"> <li>● Network hardware configuration</li> <li>● Enabled features</li> <li>● TCP/IP and SNMP information</li> <li>● Network statistics</li> </ul>
<b>Usage page</b>	Displays number of pages printed by the MFP.
<b>PCL font list</b>	Prints a list of all installed PCL fonts.
<b>PS font list</b>	Prints a list of all installed PS fonts.

**Table 3-2** Reports Menu (continued)

Menu Item	Description
PCL6 font list	Prints a list of all installed PCL6 fonts.
Service page	Starts the cleaning mode and restores factory settings.

**Table 3-3** Photo Setup Menu (Available only from HP Color LaserJet CM1017 MFP)

Menu Item	Description
Default image size	Set up default image size.
Default light/dark	
Default # of copies	Set up default number of copies.
Default output color	Set up default output color.
Restore defaults	Resets all photo items to their factory defaults. Machine does not power cycle.

**Table 3-4** System Setup Menu

Menu Item	Sub-menu item	Sub-menu item	Description
Language			Select the language in which the control panel displays messages and printer reports.
Paper setup	Default paper size	Letter	Select the size for printing internal reports or any print job that does not specify a size.
		A4	
	Legal		
	Default paper type	Lists available media types.	Select the type for printing internal reports or any print job that does not specify a type.
	Tray 1	Paper size	From the displayed list, select the default size and type for tray 1.
		Paper type	
	Tray 2	Paper size	From the displayed list, select the default size and type for tray 2.
		Paper type	
	Tray 3 (optional)	Paper size	From the displayed list, select the default size and type for optional tray 3.
		Paper type	
	Paper-out action	Wait forever	Determines how the printer reacts when a print job requires a size or type that is unavailable or when a specified tray is empty.
		Override	
		Cancel job	
			Select <b>Wait forever</b> to make the printer wait until the correct media is loaded.



**Table 3-4** System Setup Menu (continued)

Menu Item	Sub-menu item	Sub-menu item	Description
			<p>Press <b>OK</b> to select the default setting.</p> <p>Select <b>Override</b> to print on a different size paper after a specified delay.</p> <p>Select <b>Cancel job</b> to automatically cancel the print job after a specified delay.</p> <p>If either <b>Override</b> or <b>Cancel job</b> is chosen, the control panel prompts for the number of seconds to delay. Press the <b>Right arrow</b> to increase the time up to 3600 seconds. Press <b>Left arrow</b> to decrease the time.</p>
<b>Print quality</b>			
	<b>Calibrate color</b>	<p><b>Calibrate now</b></p> <p><b>Power-on calibration</b></p>	<p><b>Calibrate now:</b> Directs the printer to immediately calibrate. When a job is processing, the printer calibrates after the job is complete. When an error message displays, clear the error before continuing.</p> <p><b>Power-on calibration:</b> Select how quickly the printer should calibrate after it is powered on. The default setting is 15 minutes.</p>
	<b>Cartridge low</b>		Signals that the cartridge is almost empty.
	<b>Replace supplies</b>		Displays message that a supply or supplies need to be replaced.
<b>Courier font</b>			Select courier font values.

**Table 3-5** Service Menu

Menu item	Description
<b>Cleaning mode</b>	<p>This options cleans the printer when specks or other marks appear on printed output. The cleaning process removes dust and excess toner from the paper path.</p> <p>When selected, the printer prompts to load plain paper in tray 1 and then press <b>OK</b> to begin the cleaning process. Wait until the process completes. Discard the page that prints.</p>
<b>Restore defaults</b>	Sets all customized settings to the factory default values.

**Table 3-5** Service Menu (continued)

Menu item	Description
<b>USB speed</b>	
<b>Less paper curl</b>	When printed pages are consistently curled, this option sets the printer to a mode that reduces curl.  The default setting is <b>Off</b> .
<b>Archive print</b>	When printing pages that will be stored for a long time, this option sets the printer to a mode that reduces toner smearing and dusting.  The default setting is <b>Off</b> .

**Table 3-6 Network Configuration Menu** (Available only on HP Color LaserJet CM1017 MFP Series)

Menu item	Sub-menu item	Description
<b>TCP/IP configuration</b>	Automatic	Select <b>Automatic</b> to automatically configure all the TCP/IP settings.
	Manual	Select <b>Manual</b> to manually configure the IP address, subnet mask, and default gateway.  The control panel prompts you to specify values for each address section. Press <b>Right arrow</b> to increase the value. Press <b>Left arrow</b> to decrease the value. Press <b>OK</b> to accept the value and move the cursor to the next field.  As each address is completed, the printer prompts for address confirmation before moving to the next one. After all three addresses are set, the printer automatically restarts.  Select <b>Reset TCP/IP</b> to restore all the TCP/IP settings to the default values.
<b>Link speed</b>	Automatic	The printer automatically detects the correct link speed for the network. Use this menu to set the link speed manually if needed.  After setting the link speed, the printer automatically restarts.
	10T Full	
	10T Half	
	100TX Full	
	100TX Half	
<b>Memory card</b>		Sets memory card slots.
<b>Restore defaults</b>		Resets all network configurations to their factory defaults.

# 4 Software for Windows

When installing Windows software, directly connect the MFP to a computer using a USB cable, or connect the MFP to a network using HP built-in networking. See the *Getting Started Guide* for installation instructions, and see the Install Notes file for the latest software information.

Software is available to all users, regardless of whether a connection to the computer is established through the MFP directly using a USB cable, or to the network through the HP built-in networking internal print server. See [Install software](#) for more information.

- [Printer driver recommendations](#)
- [Install the PostScript driver using Add Printer](#)
- [Software](#)
- [Other software](#)
- [Change from a direct-connected shared MFP to a network port-connected MFP configuration](#)
- [Uninstall the printing software](#)

## Printer driver recommendations

A printer driver allows printing from an application.

Select a printer driver based on the MFP usage.

- To print only in black and white, use the PCL6 printer black and white driver.
- The PCL6 printer driver is recommended to take full advantage of all MFP features.
- The HP PostScript Level 3 emulation print driver is required for compatibility with HP PostScript needs. Certain printer features are not available in this driver. The MFP automatically switches between HP PostScript Level 3 and PCL printer languages depending on the driver selected.

### User assistance


The print driver has **Help** dialog boxes that are activated from the question mark symbol (?) in the upper-right corner of the properties of the print-driver. Right click on the MFP in the **Printers and Faxes** folder and then select **Properties**.

## Install the PostScript driver using Add Printer

The PostScript driver can only be installed using the Microsoft Windows **Add Printer** wizard. For additional help, see the Microsoft help or go to <http://www.hp.com/go/support>.

# Software

This MFP supports these software components:

Software	Description
HP Color LaserJet CM1015/CM1017 MFP drivers	Installs basic driver software your HP Color LaserJet MFP needs to print and scan.
HP Color LaserJet CM1015/CM1017 MFP software	<ul style="list-style-type: none"><li>HP Solution Center. Transfer or scan images to the workstation, use the HP photo software, access other HP products and supplies, change product settings and update product software to the latest version available.</li><li>HP ToolboxFX for product status and configuration, help and troubleshooting, and supplies reordering.</li><li>HP ScanTo setup to enable starting scans from the product control panel.</li></ul>
HP Customer Participation Program	<p>This software provides additional benefits only available to HP printing customers. Once installed, use this software to participate in market research designed to improve HP products and experiences. An invitation will appear on the screen in a few weeks and you can choose whether or not to participate at that time. Customers who do a lot of printing may also receive an invitation to participate in programs with benefits such as special offers, awards and enhanced technical support.</p> <p> <b>NOTE</b> Participation is completely voluntary. This program will provide a full disclosure at the time of invitation. If at that time you choose to participate, the software may occasionally connect to HP when you are online, but will have a negligible impact on processing and connection speed. Personal information is never sent to HP unless you give permission. IP address will be used only to enable the connection and for security purposes. This software is governed by the HP Privacy Policy located at <a href="http://www.hp.com/go/privacy">http://www.hp.com/go/privacy</a>.</p>
HP Software Update	This program can automatically download software updates and onscreen Help updates from the HP Web site. This ensures you have the latest versions. You can reset the HP Software Update tool for manual updates if needed.
HP Photosmart Premier	View photographs, (thumbnails to full-size photos) as slideshows with music, or use very simple one-click editing or more advanced edit tools.
HP Document Viewer	View and manage scanned documents by reviewing them as thumbnails or full-size pages, and zoom in to magnify key parts of any page. Add annotations to a document and even select groups of documents for collectively printing and sending in e-mails, and more. Converting scanned documents to text is also easy.
HP Photosmart Transfer	Use this software to transfer photos from the MFP to a workstation.

## Other software

The MFP provides additional software to monitor and control print features:

- See [HP ToolboxFX](#).
- See [Use the embedded Web server](#).

## Change from a direct-connected shared MFP to a network port-connected MFP configuration

To change from a direct connection to a network configuration, complete the following steps.

1. Uninstall the printing software for the connected MFP. See [Uninstall the printing software](#).
2. Install the software choosing the network as the connection type, then follow the directions in [Manage the network](#).



# Uninstall the printing software

## Uninstall Windows software via the Program group



**NOTE** Uninstalling the software from Windows 2000 and XP requires administrator privileges.

1. Close all applications.
2. On the **Start** menu, point to **Programs**, **HP**, **HP Color LaserJet CM1015/CM1017**, and click **Uninstall**.
3. On the Setup screen, click **Next**.
4. Click **Next**, and follow the directions on the screen. If the message **The following file is a shared file but is not used by any other programs. Would you like to delete it?** appears, click **Yes to All**. The system finishes removing files.
5. If prompted to restart the computer, click **OK**.

## Uninstall Windows software using Add or Remove Programs

An alternate method for uninstalling the MFP software is to use the **Add or Remove Programs** method. This method does *not* require access to the software CD.

1. Click **Start**, select **Settings** (for Windows 2000 only), and open the **Control Panel**.
2. Click **Add or Remove Programs**.
3. Scroll through the list of software programs and click **HP Color LaserJet CM1015/CM1017** or **HP Color LaserJet CM1015/CM1017 PCL6 MFP**.
4. Click **Remove**.

When uninstalling HP Color LaserJet CM1015/CM1017 MFP software, the printing-system, scanning, and HP ToolboxFX software is uninstalled. The uninstall does not delete the following software features:

- HP Solution Center
- HP Document Viewer
- HP Software Update
- HP PhotoSmart Premier
- HP System Diagnostics

For problem solving purposes, it is not necessary to uninstall all software that is associated with the MFP. This software functions independently of the product and can be associated with other HP products and system devices.

To uninstall these programs, use the Add/Remove Programs feature in Windows. When choosing to uninstall the software, there may be warnings that features associated with the software might not function correctly if you proceed.

## Uninstall a Recommended or Custom installation

The following methods can be used to uninstall a Recommended or Custom installation:

- HP Color LaserJet CM1015/CM1017 MFP software **Uninstall** component (recommended)
- Windows **Add or Remove programs** component



---

**NOTE** When uninstalling the software for problem solving purposes, try uninstalling only specific MFP printer or scan drivers. The shared software programs, such as HP PhotoSmart Premier, HP Solution Center, and HP Document Viewer, are unlikely to be the cause of product-specific problems. These shared software programs should not need to be uninstalled, especially if they are being used by another HP product.

---

### Delete printer drivers from the printers folder

#### Windows 2000 or Windows XP

1. Click **Start**, click **Settings**, and then click **Printers**.



---

**NOTE** For Windows XP, click **Start**, and then click **Printers**.

---

2. Right-click the icon for the HP Color LaserJet CM1015/CM1017 MFP and click **Delete**. This removes the icon for the product only, but it does not remove the associated files.
3. To remove the associated files, click **File** from inside the **Printers** folder, then click **Server Properties**.
4. Click the **Driver** tab, click the MFP, then click **Remove**. When prompted to confirm the deletion, click **Yes**.
5. Click **Close** to close the **Server Properties** dialog box and then close the **Printers** folder.

# 5 Software for Macintosh

- [Macintosh utility and application support](#)
- [Macintosh printer drivers](#)
- [Use features in the Macintosh printer driver](#)
- [Manage MFP color options on Macintosh computers](#)
- [HP Device Configuration \(Mac OS X V10.3 and Mac OS X V10.4\)](#)
- [Solve common Macintosh problems](#)

# Macintosh utility and application support

The HP Installer provides PostScript Printer Description (PPD) files, Printer Dialog Extensions (PDEs), and the Macintosh Configure Device for use with Macintosh computers.

If both the MFP and the Macintosh computer are connected to a network, use the MFP embedded Web server (EWS) to configure the MFP. For more information, see [HP Device Configuration \(Mac OS X V10.3 and Mac OS X V10.4\)](#) and [Use the embedded Web server](#).

## Install Macintosh printing system software for networks

The printing system software supports Mac OS X V10.3 and later.

- **Install PostScript Printer Description (PPD) files**

The PPDs, in combination with the Apple PostScript printer drivers, provide access to MFP features. An installation program for the PPDs and other software is provided on the compact disc (CD) that came with the MFP. Use the Apple PostScript printer driver that comes with the computer.

- **HP Device Configuration**

The Macintosh Configure Device provides access to features that are not available in the printer driver. These are examples of things that can be done using the Macintosh Configure Device:

- Name the printer.
- Assign an internet protocol (IP) address to the MFP.
- Configure and set the MFP for network printing.

Use the Macintosh Configure Device when the MFP uses a universal serial bus (USB) or is connected to a TCP/IP-based network.

For more information about using the Macintosh Configure Device, see [HP Device Configuration \(Mac OS X V10.3 and Mac OS X V10.4\)](#).

### Install printer drivers for Mac OS X V10.3 and later

1. Connect the network cable between the HP Color LaserJet CM1015/CM1017 MFP and a network port.
2. Insert the CD into the CD-ROM drive and double-click the CD icon on the desktop.
3. Double-click the **Installer** icon in the HP LaserJet Installer folder.
4. Follow the instructions on the computer screen.
5. On the computer hard drive, open **Applications**, open **Utilities**, then open **Print Center** or **Printer Setup Utility**.
6. Click **Add Printer**.
7. Select **Rendezvous** or **Bonjour** as the connection type.
8. Select the printer from the list.
9. Click **Add Printer**.
10. Close the Print Center or the Printer Setup Utility by clicking the close button in the upper-left corner.

## Install Macintosh printing system software for direct connections (USB)

Install the Apple PostScript driver that came with the Macintosh computer to use the PPD files.

### To install the printing system software

1. Connect a USB cable between the USB port on the MFP and the USB port on the computer. Use a standard 5-meter (16.4 feet) or less, certified USB cable.

2. Insert the MFP CD into the CD-ROM drive and run the installer.

Double-click the CD icon on the desktop.

3. Double-click the **Installer** icon in the HP LaserJet Installer folder.

4. Follow the instructions on the computer screen.



---

**NOTE** For Mac OS X v10.3 and later: USB queues are created automatically when the MFP is attached to the computer. However, the queue uses a generic PPD if the installer has not been run before the USB cable is connected. To change the queue PPD, open the Print Center or MFP Setup Utility, select the correct MFP queue, then click **Show Info** to open the **Printer Info** dialog box. In the pop-up menu, select **Printer Model**, then, in the pop-up menu in which **Generic** is selected, select the correct PPD for the MFP.

---

5. Print a test page or a page from any software program to make sure that the software is correctly installed.

# Macintosh printer drivers

The MFP comes with printer-driver software that uses a printer language to communicate with the MFP. Printer drivers provide access to MFP features, such as printing on custom-sized paper, resizing documents, and inserting watermarks.

## Supported printer drivers

A Macintosh printer driver and the necessary PPD files are included with the MFP.



**NOTE** The most recent drivers are available at [http://www.hp.com/support/cljCM1015\\_CM1017](http://www.hp.com/support/cljCM1015_CM1017).

## Open the printer drivers

Use one of these methods to open the printer drivers from the computer.

Operating System	To change the settings for all print jobs until the software program is closed	To change the print job default settings (for example, turn on Print on Both Sides by default)	To change the configuration settings (for example, add a physical option such as a tray, or turn on or off a driver feature such as Allow Manual Duplexing)
Mac OS X v10.3 or 10.4	<ol style="list-style-type: none"><li>1. On the <b>File</b> menu, click <b>Print</b>.</li><li>2. Change settings on the various pop-up menus.</li></ol>	<ol style="list-style-type: none"><li>1. On the <b>File</b> menu, click <b>Print</b>.</li><li>2. Change settings on the various pop-up menus, then, on the <b>Presets</b> pop-up menu, click <b>Save as</b> and type a name for the preset.</li></ol> <p>These settings are saved in the <b>Presets</b> menu. To use the new settings, select the saved preset option every time you open a program and print.</p>	<ol style="list-style-type: none"><li>1. Open <b>Printer Setup Utility</b> by selecting the hard drive, clicking <b>Applications</b>, clicking <b>Utilities</b>, then double-clicking <b>Printer Setup Utility</b>.</li><li>2. Click on the print queue.</li><li>3. On the <b>Printers</b> menu, click <b>Show Info</b>.</li><li>4. Click the <b>Installable Options</b> menu.</li></ol>

# Use features in the Macintosh printer driver

## Create and use presets in Mac OS X

Use presets to save the current driver settings for reuse.

### To create a preset

1. Open the printer driver (see [Open the printer drivers](#)).
2. Select the print setting to use.
3. In the **Presets** box, click **Save As...**, and type a name for the preset (for example “Quarterly Report” or “My Project Status”).
4. Click **OK**.

### To use presets

1. Open the printer driver (see [Open the printer drivers](#)).
2. In the **Presets** menu, select the preset to use.



---

**NOTE** To restore printer-driver default settings, select **Standard** from the **Presets** pop-up menu.

---

## Print a cover page

Optionally, print a separate cover page for the document that includes a message (such as “Confidential”).

### To print a cover page

1. Open the printer driver (see [Open the printer drivers](#)).
2. On the **Cover Page** or **Paper/Quality** pop-up menu, select whether to print the cover page **Before Document** or **After Document**.
3. In the **Cover Page Type** pop-up menu, select the message to be printed on the cover page.




---

**NOTE** To print a blank cover page, select **Standard** as the **Cover Page Type**.

---

## Print multiple pages on one sheet of paper

A cost-effective way to print documents, including draft pages, is to print more than one page on a single sheet of paper.



### To print multiple pages on one sheet of paper

1. Open the printer driver (see [Open the printer drivers](#)).
2. Click the **Layout** pop-up menu.
3. Next to **Pages per Sheet**, select the number of pages to print on each sheet (1, 2, 4, 6, 9, or 16).
4. If the number of pages is greater than 1, next to **Layout Direction**, select the order and placement of the pages on the sheet.
5. Next to **Borders**, select the type of border to print around each page on the sheet.

## Print on both sides of the paper

### To print on both sides manually

1. Insert enough paper into one of the trays to accommodate the print job. When loading special paper such as letterhead, load it in one of the following ways:
  - For tray 1, load the letterhead paper with the front side up and the bottom-edge feeding into the MFP first.
  - For all other trays, load the letterhead paper with the front side down, and the top-edge at the back of the tray.
2. Open the printer driver (see [Open the printer drivers](#)).
3. On the **Finishing** pop-up menu, select the **Manual Duplex** option.
4. Click **Print**.
5. Go to the MFP. Remove any blank paper that is in tray 2. Insert the printed stack with the printed side up and the bottom-edge feeding into the MFP first. Print the second side from tray 2. Follow the instructions in the pop-up window that appears before replacing the output stack in tray 2 for printing the second half.
6. If a prompt appears on the control-panel display, press a control-panel button to continue.

## Set the color options

Use the **Color Options** pop-up menu to control how colors are interpreted and printed from software programs.



**NOTE** For more information about colors and color options, see [Color options](#) and [Manage MFP color options on Macintosh computers](#).



**NOTE** For more information about using the color options, see [Manage color options](#).

---

### To set the color options

1. Open the printer driver (see [Open the printer drivers](#)).
2. Select **Color Options**.
3. Click **Show Advanced Options**.
4. Manually adjust the individual settings for text, graphics, and photographs.

### Enable memory

1. Open Print Center or Print Setup Utility.
2. Click HP LaserJet print queue to highlight it.
3. Choose **Show Info**.
4. On the **Name and Location** drop-down list, choose **Installable Options**.
5. On the **Total Printer Memory** list, choose the range which applies to the MFP.
6. Click **Apply** to save the changes.

## Manage MFP color options on Macintosh computers

For many documents, setting the color options manually can enhance the way the document appears. Examples of these documents include marketing brochures that contain many images or documents that are printed on a media type that is not listed in the printer driver.

Print color as gray or change the color options using **Printer Features** and **Color Options** pop-up menu in the **Print** dialog box.

For more information about how to gain access to the printer drivers, see [Open the printer drivers](#).

### Print Color as Gray

Selecting the **Print Color as Gray** option from the printer driver prints a document in black and shades of gray. This option is useful for previewing preliminary copies of slides and hardcopy output, or for printing color documents that are photocopied.

### Advanced color options for text, graphics, and photographs

Use manual color adjustment to adjust the **Color** (or **Color Map**) and **Halftoning** options for a print job.

For more information on color selection, see [Color options](#).

# HP Device Configuration (Mac OS X V10.3 and Mac OS X V10.4)

HP Device Configuration is a software program that provides access to information about the MFP (for example, information about supplies status and MFP settings). Use the HP Device Configuration to monitor and manage the MFP from the computer.



---

**NOTE** Perform a complete software installation to use the HP Device Configuration.

---

- Check the MFP status and print information pages.
- Check and change MFP system settings.
- Check default MFP settings.
- Check and change network settings, including Advanced, Bonjour printer name, SNMP, network configuration, and password.

View the HP Device Configuration when an MFP is directly connected to a computer or when it is connected to the network.



---

**NOTE** Internet access is not required to open and use the HP Device Configuration.

---

## To view HP Device Configuration when the MFP is directly connected to the computer

1. Open HP Director by clicking the **HP Director** icon in the dock.
2. In HP Director, click **Settings**.
3. Select **Configure device** to open the HP Device Configuration home page in a browser.

## To view HP Device Configuration when the MFP is connected to a network

1. Open one of the following supported Web browsers:
  - Safari 1.2 or later
  - Microsoft Internet Explorer 5.0 or later
  - Netscape Navigator 4.75 or later
  - Opera 6.05 or later
  - FireFox 1.5 or later
2. Enter the IP address of the MFP into the Web browser to open the HP Device Configuration home page.

# Solve common Macintosh problems

This section lists problems that can occur when using Mac OS X.

## Solve Problems with Mac OS X

**Table 5-1** Problems with Mac OS X

### The printer driver is not listed in the Print Setup Utility.

Cause	Solution
The MFP software has not been installed or was installed incorrectly.	Ensure the printer PPD is in the following hard-drive folder: <code>Library/Printers/PPDs/Contents/Resources/&lt;lang&gt;.lproj</code> , where <code>&lt;lang&gt;</code> is the two-letter language code for the language that you are using. If necessary, reinstall the software. See the <i>Getting Started Guide</i> for instructions.
The PPD file is corrupt.	Delete the PPD file from the following hard-drive folder: <code>Library/Printers/PPDs/Contents/Resources/&lt;lang&gt;.lproj</code> , where <code>&lt;lang&gt;</code> is the two-letter language code for the language that you are using. Reinstall the software. See the <i>Getting Started Guide</i> for instructions.

### The MFP name, IP address, or Rendezvous or Bonjour host name does not appear in the MFP list in the Printer Setup Utility.

Cause	Solution
The MFP might not be ready.	Ensure cables are correctly connected, the MFP is on, and the ready light is on. When connecting through a USB or Ethernet hub, try connecting directly to the computer or use a different port.
The wrong connection type might be selected.	Verify that USB, IP Printing, or Rendezvous or Bonjour is selected, depending on the type of connection that exists between the MFP and the computer.
The wrong MFP name, IP address, or Rendezvous or Bonjour host name is being used.	Print a configuration page to check the MFP name, IP address, or Rendezvous or Bonjour host name. Verify that the name, IP address, or Rendezvous or Bonjour host name on the configuration page matches the MFP name, IP address, or Rendezvous or Bonjour host name in the Printer Setup Utility.
The interface cable might be defective or of poor quality.	Replace the interface cable. Make sure to use a high-quality cable.

### The printer driver does not automatically set up the selected MFP in the Print Setup Utility.

Cause	Solution
The MFP might not be ready.	Verify that cables are correctly connected correctly, the MFP is on, and the ready light is on. When connecting through a USB or Ethernet hub, try connecting directly to the computer or use a different port.
The MFP software has not been installed or was installed incorrectly.	Verify that the MFP PPD is in the following hard-drive folder: <code>Library/Printers/PPDs/Contents/Resources/&lt;lang&gt;.lproj</code> , where <code>&lt;lang&gt;</code> is the two-letter language code for the language that you are using. If necessary, reinstall the software. See the <i>Getting Started Guide</i> for instructions.

**Table 5-1** Problems with Mac OS X (continued)

**The printer driver does not automatically set up the selected MFP in the Print Setup Utility.**

Cause	Solution
The PPD file is corrupt.	Delete the PPD file from the following hard-drive folder: <code>Library/Printers/PPDs/Contents/Resources/&lt;lang&gt;.lproj</code> , where <code>&lt;lang&gt;</code> is the two-letter language code for the language that you are using. Reinstall the software. See the <i>Getting Started Guide</i> for instructions.
The interface cable might be defective or of poor quality.	Replace the interface cable. Make sure to use a high-quality cable.

**A print job was not sent to the correct MFP.**

Cause	Solution
The print queue might be stopped.	Restart the print queue. Open <b>print monitor</b> and select <b>Start Jobs</b> .
The wrong MFP name or IP address is being used. Another MFP with the same or similar name, IP address, or Rendezvous or Bonjour host name might have received the print job.	Print a configuration page to check the MFP name, IP address, or Rendezvous or Bonjour host name. Verify that the name, IP address, or Rendezvous or Bonjour host name on the configuration page matches the MFP name, IP address, or Rendezvous or Bonjour host name in the Printer Setup Utility.

**Unable to print from a third-party USB card.**


Cause	Solution
Occurs when the USB software is not installed on the MFP.	When adding a third-party USB card, try using the Apple USB Adapter Card Support software. The most current Version of this software is available from the Apple Web site.

**When connected with a USB cable, the MFP does not appear in the Printer Setup Utility after the MFP is selected.**

Cause	Solution
This problem is caused by either a software or a hardware component.	<p><b>Resolve software problems</b></p> <ul style="list-style-type: none"><li>● Verify that the Macintosh supports USB.</li><li>● Verify that the Macintosh operating system is Mac OS X V10.3 or later.</li><li>● Verify that the Macintosh has the appropriate USB software from Apple.</li></ul> <p><b>Resolve hardware problem</b></p> <ul style="list-style-type: none"><li>● Verify that the MFP is turned on.</li><li>● Verify that the USB cable is connected correctly.</li><li>● Verify the use of the appropriate high-speed USB cable.</li></ul>

**Table 5-1** Problems with Mac OS X (continued)

**When connected with a USB cable, the MFP does not appear in the Printer Setup Utility after the MFP is selected.**

Cause	Solution
	<ul style="list-style-type: none"><li>• Ensure there are not too many USB devices drawing power from the chain. Disconnect all of the devices from the chain, and connect the cable directly to the USB port on the host computer.</li><li>• Check to see if more than two nonpowered USB hubs are connected in a row on the chain. Disconnect all of the devices from the chain and connect the cable directly to the USB port on the host computer.</li></ul>
	 <b>NOTE</b> The iMac keyboard is a nonpowered USB hub.

# 6 Print

- [Load trays](#)
- [Print on special media](#)
- [Control print jobs](#)
- [Print on both sides of the paper](#)
- [Cancel a print job](#)

The HP ToolboxFX provides information about managing the MFP and its settings. See [HP ToolboxFX](#).

## Load trays

Use special print media, such as envelopes, labels, HP LaserJet glossy paper, HP LaserJet Photo paper, and transparencies only in tray 1 and tray 2.



---

**NOTE** Tray 3 is an accessory. It is referred to as optional tray 3 in this guide.

---




**CAUTION** Do not fan paper before loading it into trays. Avoid overloading trays.

**CAUTION** Do not reuse paper that has been stapled. Staples that remain in reused paper causes damage to the MFP and requires repairs that are not covered under the warranty.

---

### Load tray 1 (single-sheet feed tray)

1. Media guides ensure that the media is correctly fed into the MFP and that the print is not skewed (crooked on the media). Slide the media-width guides slightly wider than the print media.





2. Feed print media into tray 1 with the side to be printed down, and the top, short edge in first. Make sure that the media is inserted far enough into the MFP for the paper-feed mechanism to grab the media.



**NOTE** There is a short pause before the paper is picked up.

**NOTE** When printing on both sides, see [Print on both sides of the paper](#) for loading instructions.

## Load tray 2

Access tray 2 and optional tray 3 from the front of the MFP. Each tray holds up to 250 sheets of paper. Tray 2 also supports other media such as envelopes, postcards, transparencies, HP LaserJet glossy paper, and HP LaserJet Photo paper.




**NOTE** Tray 3 is optional on the HP Color LaserJet CM1015/CM1017 MFP.


**NOTE** Instructions are the same for loading media in tray 2 and optional tray 3.

---


1. Pull tray 2 or optional tray 3 out of the MFP and remove any paper.




2. Move the rear guides to match the paper size. Tray 2 and optional tray 3 accept several standard paper sizes.



3. When printing paper longer than Letter/A4, extend the rear of the tray until it matches the paper size.



4. Slide the media-width guides slightly wider than the print media.




---

**NOTE** Load a maximum of 10 envelopes into tray 2 with the flaps on the right side, the side to be printed facing up, and with the short edge leading into the MFP. If the envelope has a flap on a short edge, this edge must enter the MFP first.


---

5. Load the media.




**NOTE** If this is special paper such as labels, transparencies, HP LaserJet glossy paper, HP LaserJet Photo paper, and letterhead or printed forms, load it with the side to be printed on facing up and the top edge toward the front of the tray. For additional information about printing on special print media, see [Print on special media](#).

6. Make sure that the stack of paper is flat in the tray at all four corners, and keep it below the height tabs on the media-length guide in the rear of the tray.



7. Slide the tray into the MFP. The back of the tray protrudes from the back of the MFP.



**NOTE** When printing on both sides, see [Print on both sides of the paper](#) for loading instructions.

# Print on special media

[Table 6-1 Special media printing guidelines](#) provides guidelines for printing on special media. When printing on a special type of media, printing speeds might be automatically changed to improve the output quality for that specific media.

- See [Multifunction peripheral \(MFP\) specifications](#) for media that is recommended for this MFP.
- See [Media supported on this MFP](#) for information about the size, weight, and capacity of paper and other print media that the trays support.
- See [Load tray 1 \(single-sheet feed tray\)](#) or [Load tray 2](#) for instructions on loading the trays.

**Table 6-1** Special media printing guidelines

Paper type	Maximum amount that can be loaded into tray 2 or optional tray 3	Driver settings, paper quality, type is	Tray 1 paper orientation	Tray 2 or optional tray 3 paper orientation
Normal	Up to 250 sheets	Plain or unspecified	Side to be printed face down	Side to be printed face up
Envelopes	Up to 10 envelopes	Envelope	Short edge leading, flap on right side facing down	Short edge leading, flap on right side facing up
Heavy envelopes	Up to 10 envelopes	Heavy envelope	Short edge leading, flap on right side facing down	Short edge leading, flap on right side facing up
Labels	Up to 25 mm (0.99 inch) stack height	Labels	Side to be printed face down	Side to be printed face up
Transparencies	Up to 50 sheets	Transparencies	Side to be printed face down	Side to be printed face up
Glossy	Up to 25 mm (0.99 inch) stack height	Light glossy, glossy, or heavy glossy	Side to be printed face down	Side to be printed face up
Letterhead	Up to 250 sheets	Letterhead	Side to be printed face down, top of page inserted in MFP	Side to be printed face up, top of page at front of tray
Cardstock	Up to 25 mm (0.99 inch) stack height	Cardstock or heavy	Side to be printed face down	Side to be printed face up


# Control print jobs


When changing print settings, follow the hierarchy of how changes are prioritized. (Note that the names of commands and dialog boxes might vary depending on the software program.)

- **Application Settings dialog box.** This dialog box opens when you click **Application Settings** or a similar command on the **File** menu in the software program. This dialog box is part of the program in which you are working. *Settings that are changed here override settings that are changed anywhere else.*
- **Print dialog box.** This dialog box opens when you click **Print**, **Print Setup**, or a similar command on the **File** menu in the software program. It is also part of the program, but it has a lower priority than the **Application Settings** dialog box. Settings that are changed in the **Print** dialog box *do not* override settings that are changed in the **Application Settings** dialog box. Settings that are changed here *do* override settings that are changed in the printer driver.
- **Printer driver.** The printer driver opens when you click **Properties** in the **Print** dialog box. Settings that are changed here *do not* override settings that are changed anywhere else.

## Selecting print media settings



When a job is sent to the printer, the printer driver controls what paper tray is used to pull media through the printer. By default, the printer automatically selects the tray, but a specific tray can be chosen based on three user specified settings: **Source**, **Type**, and **Size**. These settings are available from the **Application Setting** dialog box, the **Print** dialog box, or the printer driver.

Setting	Description
Source	<p>Directs the printer to pull paper from a user-specified tray. The printer tries to print from this tray, no matter what type or size media is loaded in it. However, if the selected tray is configured from the HP ToolboxFX for a type or size and that does not match the print job, the printer does not print automatically. To begin printing, load the selected tray with the correct type or size of print media for the print job. When loading the tray, the printer begins printing. If the printer does not begin printing:</p> <ul style="list-style-type: none"><li>● Verify the tray configuration matches the size or type of the print job.</li><li>● Press <b>OK</b> to have the printer try to print from another tray.</li></ul>
Type or Size	<p>Directs the printer to pull paper or print media from the first tray that is loaded with the type or size that you selected. <i>Always print by Type for special print media such as labels or transparencies.</i></p> <p> <b>NOTE</b> When the trays have not been configured for a certain type or size from the HP ToolboxFX, load the paper or print media into a tray then select the <b>Type</b> or <b>Size</b> from the <b>Page Setup</b> dialog box, the <b>Print</b> dialog box, or the printer driver.</p>

Setting	Description
	 <p><b>NOTE</b> An Administrator or individual user can set the HP ToolboxFX to direct the MFP to pull from a tray that is pre-configured for a specified <b>Type</b> or <b>Size</b>. This is helpful when frequently printing on the same type of media; a dedicated tray is already pre-configured for printing.</p>

## Printer-driver features

Some printer drivers and some operating systems do not support all of these MFP features.

Task	Driver Tab	Option
Set custom paper	<b>Paper</b>	<b>Size is</b>
Print in grayscale	<b>Color</b>	<b>Print in Grayscale</b>
Create and use watermarks	<b>Effects</b>	<b>Watermark</b>
 <p><b>NOTE</b> For Windows 2000 and XP environments, Administrator privileges are required to create watermarks but are not required to add existing watermarks to documents.</p>		
Print multiple pages on one sheet of paper (N-up printing)	<b>Finishing</b>	<b>Pages per sheet</b>
Reduce or enlarge a document before printing	<b>Effects</b>	<b>Fit to Page</b>
Print the first page on different paper	<b>Paper/Quality</b>	<b>Appropriate paper size</b>
Change color settings	<b>Color</b>	<b>Settings</b>
Create and use Quick Sets. Quick Sets save the current print-driver settings such as the page orientation, N-up printing, or the paper source for later use. Save up to 30 sets.	All. To later retrieve settings, choose <b>Finishing</b>	
 <p><b>NOTE</b> In the Windows 2000 environment, Administrator privileges are required to save Quick Sets.</p>		

For printing using the Print on Both Sides (manually) feature, see [Print on both sides of the paper](#).

### Restore the default printer-driver settings

This feature might be useful when experiencing quality issues, or if the print media is not being selected from the correct tray.

Select **Defaults** in the **Quick Sets** dialog box on the **Finishing** tab of the printer driver.



## Print from Windows

1. Load the print media.
2. On the **File** menu of your application, click **Page Setup** or a similar command. Ensure the settings are correct for this document.
3. From the **File** menu, click **Print**, **Print Setup**, or a similar command. The **Print** dialog box opens.
4. Select the correct MFP and change settings as necessary. Do not change any settings, such as page size or orientation, that were previously set in the **Application Settings** dialog box.
5. If this print job is to be printed on a non-standard size or weight of paper, see [Selecting print media settings](#) for more information.
6. If not already done, click **Properties**. The printer driver opens.
7. On the various tabs, set additional settings that did not appear in the **Application Settings** or **Print** dialog box. For more information about printer-driver settings, see [Printer-driver features](#).
8. Select the **Print** command to print the job.

## Printer-driver settings

The printer driver is a software component that controls, through user-specified options, common printing features when sending print jobs to the MFP. Changes to printer-driver settings can be temporary for print jobs that are run while the program is still open, or changes to the default settings can be permanent; they are in effect now and in the future.

Operating System	Temporarily change settings for jobs that are printed now	Permanently change default settings <sup>1</sup>	Change configuration settings  (For example, to add an optional tray or to enable or disable a driver feature such as "Allow manual duplexing")
Windows 2000 and XP (Classic Start Menu)	On the <b>File</b> menu, click <b>Print</b> , select this printer, then click <b>Properties</b> or <b>Preferences</b> . (The actual steps can vary; this is the most common method.)	Click <b>Start</b> , point to <b>Settings</b> , then click <b>Printers</b> or <b>Printers and Faxes</b> . Right-click the printer icon, then click <b>Printing Preferences</b> .	Click <b>Start</b> , point to <b>Settings</b> , then click <b>Printers</b> or <b>Printers and Faxes</b> . Right-click the printer icon, then click <b>Properties</b> . Click the <b>Configure</b> tab.
Windows XP	On the <b>File</b> menu, click <b>Print</b> , select this printer, then click <b>Properties</b> or <b>Preferences</b> . (The actual steps can vary; this is the most common method.)	Click <b>Start</b> , click <b>Printers and Faxes</b> , right-click the printer name or icon, then click <b>Printing Preferences</b> .	Click <b>Start</b> then click <b>Printers and Faxes</b> . Right-click the printer icon, then click <b>Properties</b> . Click the <b>Configure</b> tab.

<sup>1</sup> Access to default MFP settings might be restricted and therefore unavailable.

## Print on both sides of the paper



**NOTE** For 2-sided printing, load a pre-printed form and letterhead into tray 1 face-up with the top edge of the page loaded into the MFP. Load preprinted forms and letterhead into tray 2 and tray 3 face-down with the top edge at the front of the tray.


**NOTE** Feeding pre-printed forms and letterhead is different than loading for 1-sided printing.




**CAUTION** Do not print on both sides of labels or transparencies. This can damage the MFP and result in jams.

### To print on both sides (manually)

1. Insert enough paper into tray 2 or optional tray 3 to accommodate the print job.




2. In Windows, **Print on both sides (manually)** must be enabled to complete these instructions.
  - In the printer driver, select the **Finishing** tab, select the **Print on both sides (manually)** option, then send the job to print.






**NOTE** Flip paper before continuing.



3. After the job is finished printing, remove any blank paper as prompted by the control panel. Lift the printed stack from the output bin and insert the printed stack without rotating the stack over into the tray that was used for the first part of the job.



4. Press **OK** to continue printing on the second side.

## Cancel a print job

A print job can be canceled from:

- A program
- A print queue
- The **Cancel** button



**NOTE** When a print job appears to have started (it shows in the queue), cancel it from the workstation.

---

### Considerations when canceling printing

- If the MFP has not started printing, cancel the job within the program that sent the print job.
- If the print job is waiting in a print queue or print spooler in Windows 2000 or Windows XP, try to delete the job from the print spooler.
- If the print job is already printing, press **Cancel**. The MFP finishes printing any pages that are already moving through the MFP and deletes the remainder of the print job.
- If more than one print job is in memory, press **Cancel** once for each job after the job starts printing.

The Ready light blinks and **Canceling print** displays in the message area.

# 7 Color

- [Overview](#)
- [Manage color options](#)
- [Match colors](#)

# Overview

The MFP provides carefully designed and tested color tables to provide smooth, accurate color rendition of all printable colors.

HP provides online tools to help businesses of all sizes with their color printing. HP's Office Color Printing Center (<http://www.hp.com/go/color>) identifies solutions and information on creating finished projects.

## HP ImageREt 2400

ImageREt 2400 is a system of key color laser technologies that offer excellent print quality. At the foundation of the system are imaging enhancements, HP Smart supplies, and high-resolution imaging. Optimized for printing on HP color laser high-gloss papers, HP ImageREt provides superior results on all supported media and under a variety of environmental conditions. For more information, see <http://www.hp.com> and search on ImageREt 2400.

## Media selection

For the best color and image quality, select the appropriate media type from the printer-driver properties. See [Media supported on this MFP](#) for more information.

## Color options

In the Windows environment, the **Automatic** and **Manual** color options are on the **Color** tab in the printer driver.

Color options use object tagging, which allows optimal color settings to be used for different objects (text, graphics, and photos) on a page. The printer driver determines which objects are used on a page and uses color settings that provide the best print quality for each object. Object tagging, combined with optimized default settings, produces great color from the MFP without having to establish any special settings.

# Manage color options

Setting color options to **Automatic** typically produces the best possible print quality for color documents. However, in some situations, you might want to print a color document in grayscale (black and shades of gray) or to change one of the MFP's color options.



---

**NOTE** For additional information about modifying color when copying, see [Adjust copy quality](#) and [Adjust the color balance in copies](#).

---

## Print in Grayscale

Selecting the **Print in Grayscale** option from the printer driver prints a document in black and shades of gray. This option is useful for printing color documents that are to be photocopied.

Selecting **Print in Grayscale** in the **Print Quality** options on the **Paper Quality** tab allows for changing the settings to accommodate different types of jobs.

## Automatic versus Manual color adjustment

The **Automatic** color adjustment option optimizes the neutral gray color treatment, and the edge enhancements that are used for each element in a document. For more information, see the printer driver online Help.



---

**NOTE** **Automatic** is the default setting and is recommended for printing all color documents.

---

Use the **Manual** color adjustment option to adjust the neutral gray color treatment, and the edge enhancements for text, graphics, and photographs. To gain access to the Manual color options, on the **Color** tab, click **Manual**, then click **Settings**.

## Change color options

Use the Manual color adjustment to adjust the **Color** (or **Color Map**) options.



---

**NOTE** Some software programs convert text or graphics to raster images. In these cases, the **Photographs** setting also controls the text and graphics.

---

## Halftone options

Halftoning is the method by which the MFP mixes the four primary colors (cyan, magenta, yellow, and black) in varying proportions to create millions of colors. Halftone options affect the resolution and clarity of the color output. The two halftone options are **Smooth** and **Detail**.

- The **Smooth** option provides better results for large, solid-filled print areas. It also enhances photos by smoothing out fine color gradations. Choose this option when uniform and smooth area fills are the most important attributes.
- The **Detail** option is useful for text and graphics that require sharp distinctions among lines or colors, or images that contain a pattern or a high level of detail. Choose this option when sharp edges and details are the most important attributes.

## Edge Control

The **Edge Control** setting determines how edges are rendered. Edge Control consists of two components: Adaptive Halftoning and Trapping. Adaptive Halftoning increases the edge sharpness. Trapping reduces the effect of color-plane misregistration by slightly overlapping the edges of adjacent objects. The following levels of edge control are available:

- **Off** sets Trapping and Adaptive Halftoning to Off.
- **Normal** provides the default trapping settings. Adaptive Halftoning is set to On.
- **Maximum** provides the most trapping. Adaptive Halftoning is set to On.

## Standard red-green-blue (sRGB)

Standard red-green-blue (sRGB) is a worldwide color standard that was originally developed by HP and Microsoft as a common color language for monitors, input devices (scanners and digital cameras), and output devices (MFPs and plotters). It is the default color space that is used for HP products, Microsoft operating systems, the World Wide Web, and most office software that is sold today. The sRGB standard is representative of the typical Windows computer monitor and is the convergence standard for high-definition television.



**NOTE** Factors such as the type of monitor used and the room's lighting can affect the appearance of colors on the screen. For more information, see [Match colors](#).

The latest Versions of Adobe® PhotoShop®, Microsoft Office, and many other applications use sRGB to communicate color. Most importantly, as the default color space in Microsoft operating systems, sRGB has gained broad adoption as a way to exchange color information between software programs and devices by using a common definition that assures typical users experience greatly improved color matching. The sRGB standard improves the ability to match colors between the MFP, the computer monitor, and other input devices (scanners and digital cameras) automatically, without the need to become a color expert.

## RGB Color

The **RGB Color** option determines how colors are rendered.

- Select **Default (sRGB)** for most printing needs. This setting instructs the MFP to interpret RGB color as sRGB, which is the accepted standard of Microsoft and the World Wide Web Organization.
- Select **AdobeRGB** for documents that use the AdobeRGB color space rather than sRGB. For example, some digital cameras capture images in AdobeRGB, and documents that are produced with Adobe PhotoShop use the AdobeRGB color space. When printing from a professional software program that uses AdobeRGB, it is important to turn off the color management in the software program and allow the MFP software to manage the color space.
- **Photo Image** interprets the RGB color as if it were printed as a photograph by using a digital mini-lab. It is designed to render the deeper, more saturated colors differently than Default mode. Use this setting for printing photos.
- **Device** sets the MFP to print RGB data in raw device mode. To render photographs properly when this option is selected, manage color through the software program or in the operating system.
- **Vivid** instructs the MFP to increase the color saturation in the midtones. Less colorful objects are rendered more colorfully. This value is recommended for printing business graphics.



## Neutral Grays

The **Neutral Grays** setting determines the method for creating gray colors that are used in text, graphics, and photographs.

- **Black Only** generates neutral colors (grays and black) by using only black toner. This option guarantees that neutral colors do not have a color cast.
- **4-Color** generates neutral colors by combining all four colors of toner. This option produces smoother gradients and transitions to non-neutral colors. It also produces the darkest possible black.

## Match colors

Matching MFP output color to the computer screen is complex because MFPs and computer monitors use different methods of producing color. Monitors display colors by light pixels using an RGB (red, green, blue) color process, but MFPs print colors using a CMYK (cyan, magenta, yellow and black) process.

The following factors can influence the ability to match printed colors to those on the screen:

- Print media
- MFP colorants (inks or toners, for example)
- Printing process (inkjet, press, or laser technology, for example)
- Overhead lighting
- Programs
- Printer drivers
- Computer operating system
- Monitors
- Video cards and drivers
- Operating environment (very humid or very dry)
- Personal differences in perception of color
- Variations between RGB and CMYK color processing.

Sometimes colors on the screen do not perfectly match the printed colors. The best method for matching colors on the screen to the MFP is to print sRGB colors. The MFP uses sRGB and automatically optimizes color output.

Use the HP ToolboxFX software to print a palette of the Microsoft Office Basic Colors. The palette is used to select the final color in the printed document.

1. In HP ToolboxFX, select the **Help** folder.
2. In the **Print Quality Troubleshooting** section, select **Print Basic Colors**.

This palette shows the actual printed color seen when the basic color option is selected in the Microsoft Office application.

For more information about solving issues that are related to color output, see [Solve issues with printing color documents](#).

# 8 Copy



---

**NOTE** The HP Color LaserJet CM1015/CM1017 MFP does not support copying slides or photo negatives.

---


- [Basic copy functions](#)
- [Copy paper](#)

## Basic copy functions

This MFP can complete these basic copy functions.

### Start a copy job

1. Load the original document onto the flatbed scanner face-down (one page at a time) with the upper-left corner of the document located in the lower-right corner of the glass.
2. Press **Start Copy Black** or **Start Copy Color** on the control panel to start copying.



3. Repeat the process for each copy.

### Change the number of copies for the current job

1. Press **# of Copies** to select the number of copies (between 1 and 99) to make for this current job.
2. Press **Start Copy Black** or **Start Copy Color** to begin copying the job.



**NOTE** The change in the setting remains active for about two minutes after the copy job has been completed. During this time, **Settings=Custom** appears on the MFP control-panel display.

### Cancel a copy job

To cancel a copy job, press **Cancel**. If more than one process is running, pressing **Cancel** clears the process that currently appears on the control-panel display. When a copy job is canceled, clear the original document from the flatbed scanner.

# Copy paper

This MFP supports:

Paper type	Supported paper type
<ul style="list-style-type: none"><li>• Letter</li></ul>	<ul style="list-style-type: none"><li>• Pre-printed</li></ul>
<ul style="list-style-type: none"><li>• Legal</li></ul>	<ul style="list-style-type: none"><li>• Letterhead</li></ul>
<ul style="list-style-type: none"><li>• A4</li></ul>	<ul style="list-style-type: none"><li>• Transparencies</li><li>• Pre-punched</li><li>• Labels</li><li>• Bond</li><li>• Recycled</li><li>• Color</li><li>• Light</li><li>• Heavy</li><li>• Cardstock</li><li>• Glossy</li><li>• Heavy glossy</li><li>• Tough paper</li><li>• Envelope</li><li>• Heavy envelope</li><li>• Light glossy</li><li>• HP Premium Cover</li><li>• HP Laser Photo</li></ul>

## Set the MFP to make only black and white copies

1. Press **Menu**, select **Copy setup**, and click on **Start Copy Color**.
2. Press the navigation arrows and select **On** or **Off**. When set to **Off**, the control panel displays **Restrict color** if **Start Copy Black** or **Start Copy Color** is pressed.
3. Press **OK**.

## Adjust copy quality

Set the quality to describe the original that is being copied.

**Table 8-1** Copy Quality Settings (use the **Quality** button on the HP Color LaserJet CM1015 MFP)

Input type	Description
<b>Mixed</b>	Documents that include both text and graphics. This is the default.
<b>Picture</b>	Copy a printed picture other than a photograph.
<b>Film photo</b>	Copying a processed photograph
<b>Text</b>	Copy jobs that mainly contain text

### Adjust the copy quality for the current job

1. For the HP Color LaserJet CM1015 MFP, on the control panel press **Quality** to see the current quality setting for the copy. For the HP Color LaserJet CM1017 MFP, press **Copy Features** and from the menu, choose the **Copy Quality** option.
2. Press the navigation arrows to scroll through the options.
3. Choose a setting, press **Start Copy Black** or **Start Copy Color** to save the selection and immediately start the copy job, or press **OK** to save the selection without starting the job.



**NOTE** The change in the setting remains active for about two minutes after the copy job has been completed. During this time, **Settings=Custom** appears on the device control-panel display.

### Adjust the default copy quality

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select **Copy setup**, then press **OK**.
3. Press **OK** to choose **Default Quality**.
4. Press the navigation arrows to scroll through the choices.
5. Press **OK** to save the selection.

## Adjust the color balance in copies

Adjusting the color balance settings provide additional control over final print quality.

### To adjust color balance settings

1. Press **Menu**
2. Press **OK** to select **Copy setup** then press **OK**.
3. Press the navigation arrows to select **Advanced**, then press **OK**.
4. Press the navigation arrows to select **Color Balance**.
5. Press the navigation arrows to select one of the color balance options listed in the table below.
6. For the selected color, press **Left arrow** or **Right arrow** to adjust the color.
7. When the color is adjusted, press **OK**.

Color balance option	Description
<ul style="list-style-type: none"> <li>Blue</li> <li>Red</li> <li>Green</li> </ul>	Increases or decreases the amount of this color in a copy output.
Background	Increases or decreases the background color in a copy. For instance, if you are making a copy of a document that was printed on pink paper, this increases or decreases that color in the copy.
Contrast	Increases or decreases the differences between the whites and blacks in the copy.
Lightness	Increases or decreases the lightness of all colors in a copy.
Grayness	Increases or decreases the color in a color copy of a black and white original.
Sharpen	Increases or decreases the reproduction of details in a copy.

## Set color balance on a per-job basis

1. Press **Copy Features** and use the navigation arrows to select **Color Balance**. Press **OK**.
2. Press the navigation arrows and select one of the color balance options and press **OK**.
3. For the selected color balance option, press the **Left arrow** or **Right arrow** to enhance or subtract that color from the copy. Press **OK**.
4. Press the navigational arrows or the **Back** button to select another Copy enhancement option, then press **Start Copy Black** or **Start Copy Color** to make a copy.

## Adjust the lighter/darker (contrast) setting

### To adjust the default lighter/darker setting for all copy jobs

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select **Copy setup**, then press **OK**.
3. Press the navigation arrows to select **Default light/dark**, then press **OK**.
4. Press **Left arrow** or **Right arrow** to adjust the setting. Move the slider to the left to make all of the copies lighter than the original, or move the slider to the right to make all of the copies darker than the original.
5. Press **OK** to save the selection.

### To adjust the lighter/darker setting for the current job only

1. On the control panel, press **Lighter/Darker** to see the current contrast setting.
2. Press **Left arrow** or **Right arrow** to adjust the setting. Move the slider to the left to make the copy lighter than the original, or move the slider to the right to make the copy darker than the original.
3. Press **Start Copy Black** or **Start Copy Color** to save the selection and immediately start the copy job, or press **OK** to save the selection without starting the job.



---

**NOTE** The change in the setting remains active for about two minutes after the copy job has been completed. During this time, **Settings=Custom** appears on the device control-panel display.

---

## Reduce or enlarge copies

### To change the default copy size



---

**NOTE** The default copy size is the size to which copies are normally reduced or enlarged. When keeping the factory default size setting of **Original=100%**, all copies are the same size as the original document.

---

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select **Copy setup**, then press **OK**.
3. Press the navigation arrows to select **Default Reduce/Enlarge**, then press **OK**.
4. Press the navigation arrows to select one of these options for reducing or enlarging copies:
  - **Original=100%**
  - **A4 > Letter=94%**
  - **Letter > A4=97%**
  - **Full Page=91%**
  - **Fit to page**
  - **Custom: 25 to 400%**

When **Custom: 25 to 400%** is selected, type in the percentage of the original size that you normally want for copies.

5. Press **OK** to save the selection.

### Change copy size for the current job

1. On the device control panel, press **Reduce/Enlarge**.
2. Press **Left arrow** or **Right arrow** to select the size to reduce or enlarge the copies. Select one of these sizes:
  - **Original=100%**
  - **A4 > Letter=94%**
  - **Letter > A4=97%**
  - **Full Page=91%**
  - **Fit to page**
  - **Custom: 25 to 400%**
3. Press **Start Copy Black** or **Start Copy Color** to save the selection and immediately start the copy job, or press **OK** to save the selection without starting the job.





---

**NOTE** The change in the setting remains active for about two minutes after the copy job has been completed. During this time, **Settings=Custom** appears on the device control-panel display.

Change the default media size in the media input tray to match the output size, or part of the copy can be cut off.

---

## Copy edge-to-edge originals



---

**NOTE** The printed or copied page has a border of approximately 4 mm (1/6 of an inch). The HP Color LaserJet CM1015/CM1017 MFP does not support edge-to-edge printing or copying.

---

### Considerations for printing or scanning documents with cropped edges:

- When the original is smaller than the output copy size, move the original 4 mm (1/6 inch) away from the bottom and right edges of the scanner glass. Recopy or scan in this position.
- When the original is the size of the desired output, make a copy with smaller edges by:
  - Select **Reduce/Enlarge**, and press the navigation arrows to select **Full Page=91%**, then press **Start Copy Black** or **Start Copy Color**.

The edges and the copy are reduced in size by up to 2 mm.



# 9 Scan



---

**NOTE** The HP Color LaserJet CM1015/CM1017 MFP does not support scanning slides or photo negatives.

---

- [Scan methods](#)
- [Supported file types](#)
- [Scan from the device control panel](#)
- [Scan by using HP Solution Center \(Windows\)](#)
- [Scan from the device and HP Director \(Macintosh\)](#)
- [Scan using TWAIN-compliant and WIA-compliant software](#)

## Scan methods

There are several ways to scan a document.

- **Scan from the device control panel:** Start scanning directly using the control-panel scan buttons. Press [Scan To](#) to scan to a folder (Windows only) or to scan to e-mail.

For more information, see [Scan](#).

- **Scan from HP Solution Center (Windows):** From the workstation start the HP Solution Center software. Pressing [Start Scan](#) to start the HP Solution Center software is not supported when the device is connected to a network (direct-connect only.) It is also possible to click on the HP Solution Center icon to start the HP Solution Center software directly from the computer. See [Scan by using HP Solution Center \(Windows\)](#).
- **Scan from HP Director (Macintosh):** Start the HP Director by clicking the Dock alias (Macintosh OS 10.3 or later). See [Scan from the device and HP Director \(Macintosh\)](#).
- **Scan from TWAIN-compliant or Windows Imaging Application (WIA)-compliant software:** The device scanning software is TWAIN-compliant and WIA-compliant. For more information, see [Scan using TWAIN-compliant and WIA-compliant software](#).
- **Scan from optical character recognition (OCR) software:** Use third-party OCR software to import scanned text into a word-processing program for further editing.

## Supported file types

HP scanning software supports these file types for scans initiated from the control panel:

- .bmp
- .gif
- .jpg
- .pdf
- .png
- .tif (compressed)
- .tif

In addition, HP Solution Center also supports these file types for scans initiated from the workstation:

- .rtf
- .fpx
- .htm
- .pcx
- .txt

# Scan from the device control panel

Use the following instructions to scan directly from the device control panel.



---

**NOTE** The computer connected to the device must be turned on.

---

## Program the device **Scan To** button from the control panel

E-mail addresses and folders must be set up prior to using the **Scan To** button on the control panel. Use HP Solutions Center to program the e-mail and folders for scanning.

### Set up pre-configured destinations on the MFP

1. Open HP Solution Center and select **Settings, Scan Settings**, then press **Scan**.
2. Select the checkbox **Allow me to scan by pressing the scan-to button on the MFP**.
3. The MFP is pre-configured with the following three destinations in the dialog box.
  - Scan a document and attach it to an e-mail
  - Scan a photo and attach it to an e-mail
  - Scan a photo and save it as a file
4. Highlight a destination and click **Right arrow** to move to the destinations currently on the MFP dialog box. Repeat for all three destinations.
5. Click **Update**.

### Add folder destinations

1. Open HP Solution Center and select **Settings, Scan Settings**, then press **Scan**.
2. Select the checkbox **Allow me to scan by pressing the scan-to button on the MFP** and click on **New**.
3. Select **Save it to my computer**, then click **Next**.
4. Enter the file destination name or check to set up the destination on the MFP. Name the default destination and click **Next**.
5. Select the quality and click **Next**.
6. Verify the selections, click **Save**, and then close HP Solution Center.

### Add e-mail destinations

1. Open HP Solution Center and select **Settings, Scan Settings**, then press **Scan**.
2. Select the checkbox **Allow me to scan by pressing the scan-to button on the MFP** and click on **New**.

On the device control panel, press **Scan To**.

3. Select **Attach to a new e-mail** and click **Next**.

4. Select **Save it to my computer** and press **Next**. Type the e-mail address, subject, and note in the text box and click **Next**.
5. Select the quality and click **Next**.
6. Type the e-mail address in the text box. Select the box for **Send the new destination to the MFP**. Type a new name that appears on the MFP control panel and click **Next**.

#### Delete destinations

1. From the **Set up the <Scan To> list for the All-in-One**, select one of the **Available Destinations on this PC** and click **Delete**. The **Delete Destination** dialog box displays.
2. From the **Delete Destination** dialog box, highlight the destination to delete and click **Next**. The **Confirmation** dialog box displays.
3. Click **Delete** to perform the deletion, or click **Cancel** to choose another destination.

## Scan by using HP Solution Center (Windows)

Use the HP Solution Center software program to scan a document or photo.

### To view HP Solution Center

- Double-click the HP Solution Center icon on the Windows desktop.
- OR
- On the Windows taskbar, click **Start, Programs** (or **All Programs** in Windows XP), **HP**, then **HP Solution Center**.

For detailed instructions about scanning from HP Solution Center, see the HP Solution Center online Help.



# Scan from the device and HP Director (Macintosh)

The procedures described in this section are for Macintosh OS X V10.3 and V10.4.

For more information about tasks and settings described in this section, see the HP Director online Help.

## Scanning tasks

To scan to a software program, scan an item using the program itself. Any TWAIN-compliant program can scan an image. If the program is not TWAIN-compliant, save the scanned image to a file then place, open, or import the file in the software program. For more information, see [Scan using TWAIN-compliant and WIA-compliant software](#).

### Use page-by-page scanning

1. Lift the flatbed scanner lid and load the original that is to be scanned face-down on the flatbed scanner with the upper-left corner of the document at the lower-right corner of the glass. Gently close the lid.
2. Double-click the HP Director desktop alias.
3. Click the HP Director, click **Scan** to open the **HP** dialog box.
4. Click **Scan**.
5. To scan multiple pages, load the next page and click **Scan**. Repeat until all pages are scanned.
6. Click **Finish** then **Destinations**.

### Scan to file

1. In **Destinations**, choose **Save To File(s)**.
2. Name the file and specify the destination location.
3. Click **Save**. The original is scanned and saved.

### Scan to e-mail

1. In **Destinations**, choose **E-mail**.
2. A blank e-mail opens with the scanned document as an attachment.
3. Enter an e-mail recipient, add text, or other attachments, then press **Send**.

# Scan using TWAIN-compliant and WIA-compliant software

The MFP is TWAIN-compliant and Windows Imaging Acquisition (WIA)-compliant for Windows XP and beyond. The MFP also supports TWAIN-compliant Macintosh applications.

## Use TWAIN-compliant and WIA-compliant software

When in a TWAIN-enabled or WIA-enabled program, access the scanning feature and scan an image directly into the open program. For more information, see the Help file or the documentation that came with the TWAIN-compliant or WIA-compliant software program.

### Scan from a TWAIN-enabled program



---

**NOTE** The Windows and Macintosh device software complies with TWAIN Version 1.9 requirements.

---

Generally, a software program is TWAIN-enabled if it has a command such as **Acquire**, **File Acquire**, **Scan**, **Import New Object**, **Insert from**, or **Scanner**. When uncertain whether or not the program is compliant or do not know what the command is called, see the software program Help or documentation.

Start the scan from within the TWAIN-enabled program. See the software program Help or documentation for information about the commands and steps to use.

### Scan from a WIA-enabled program (Windows XP only)

WIA is another way to scan an image directly into a software program, such as Microsoft Word. WIA uses Microsoft software to scan, instead of scanning software.

Generally, a software program is WIA-enabled if it has a command such as **Picture/From Scanner or Camera** in the Insert or File menu. If you are unsure whether the program is WIA-enabled, see the software program Help or documentation.

- Start the scan from within the WIA-enabled program. See the software program Help or documentation for information about the commands and steps to use.
- In the Cameras and Scanner folder, double-click the device icon. This opens the standard WIA-enabled software program, which enables a file to be scanned.

### Scan by using optical character recognition (OCR) software


Third-party OCR software (available on a separate CD-ROM) is available to import scanned text into the preferred word-processing program for editing.

#### Readiris

The MFP software includes a separate CD-ROM for the Readiris PRO 10 OCR software. To use the Readiris program, install it from the appropriate software CD-ROM, then follow the instructions in the online Help.

## Scan a photo

1. Place the photo on the flatbed scanner with the picture-side down and the upper-left corner of the photo in the lower-right corner of the glass.



2. Gently close the lid.
3. Scan the photo using one of the scanning methods. See [Scan methods](#) for more information.

## Scan edge-to-edge originals

For information about copying and scanning edge-to-edge originals, see [Copy edge-to-edge originals](#).

## Cancel a scan job

To cancel a scan job, use one of these procedures.

- On the control panel, press **Cancel**.
- Click **Cancel** in the onscreen dialog box.

When canceling a scan job, remove the original from the flatbed scanner.



---

**NOTE** These procedures vary with Macintosh operating systems.

---

## Scanner resolution and color

To improve the print resolution or color for a scanned image, select a resolution or color setting that matches your needs in the scanner software. Resolution and color affect the following features of scanned images:

- Image clarity
- Texture of gradations (smooth or rough)
- Scan time
- File size

Scanning resolution is measured in pixels per inch (ppi). Color, grayscale, and black and white define the number of colors possible. Adjust the scanner hardware resolution to up to 1200 ppi. The software can perform an enhanced resolution up to 19,200 ppi. Also, set color and grayscale at 1 bit (black and white), or at 8 bit (256 levels of gray) to 24 bit (true color).

The resolution and color guidelines table lists simple scanning tips.



**NOTE** Setting the resolution and color to a high value can create large files that take up disk space and slow the scanning process. Before setting the resolution and color, determine how the scanned image is being used.

### Resolution and color guidelines

This table describes the recommended resolution and color settings for different types of scan jobs.

Intended use	Recommended resolution	Recommended color settings
Display on screen	75 ppi	<ul style="list-style-type: none"> <li>• Black and White for text</li> <li>• Grayscale for graphics and photos</li> <li>• Color, if the image is in color</li> </ul>
Print (graphics or text)	600 ppi for complex graphics, or to significantly enlarge the document	<ul style="list-style-type: none"> <li>• Black and White for text and line art</li> <li>• Grayscale for shaded or colored graphics and photos</li> </ul>
	300 ppi for normal graphics and text	
	150 ppi for photos	<ul style="list-style-type: none"> <li>• Color, if the image is in color</li> </ul>
Edit text	300 ppi	<ul style="list-style-type: none"> <li>• Black and White</li> </ul>
E-mail	150 ppi	<ul style="list-style-type: none"> <li>• Black and White, if the image does not require smooth gradation</li> </ul>
		<ul style="list-style-type: none"> <li>• Grayscale, if the image requires smooth gradation</li> </ul>
		<ul style="list-style-type: none"> <li>• Color, if the image is in color</li> </ul>

### Color

Set the color values using these settings when scanning.

Setting	Recommended use
Color	Use this setting for high-quality color photos or documents in which the color is important.
Black and White	Use this setting for text documents.
Grayscale	Use this setting when file size is an issue or when a document or photograph needs to be scanned quickly.

# 10 Photo



---

**NOTE** This section applies only to the HP Color LaserJet CM1017 MFP.

**NOTE** This MFP supports only JPEG format.

---

- [Insert a memory card](#)
- [View or rotate photos from the memory card](#)
- [Create a photo slideshow on the graphical display screen](#)
- [Enable or disable a memory card](#)
- [Print photos directly from the memory card](#)
- [Print and scan photos from a proof sheet](#)
- [Save photos to the workstation from a memory card](#)
- [Print photos using the Photo Features button](#)
- [Print a memory card index](#)

## Insert a memory card

The HP Color LaserJet CM1017 MFP can read the following memory-card types:


- CompactFlash
- Memory Stick and Memory Stick PRO
- MultiMedia
- Secure Digital (SD)
- SmartMedia
- xD



**NOTE** The memory card may have unlimited memory, but the MFP only recognizes up to 9,999 photos per card.

**NOTE** The HP Color LaserJet CM1017 MFP memory card reader recognizes only files in JPEG file format when printing from the control panel. To print other file types, use software such as HP Photosmart Premier, provided on the CD-ROMs that is included with the MFP. See the software online Help for information about how to print photos from the computer. Windows operating system users also can use Windows Explorer to move other file types to their computer then print the files from the computer.

Based on the illustration below, insert the memory card into the appropriate slot on the MFP.



- |   |  |
|---|--|
| 1 | Accepts xD and SmartMedia memory cards.                              |
| 2 | Accepts MultiMedia, Memory Stick, and Memory Stick PRO memory cards. |
| 3 | Accepts CompactFlash memory cards.                                   |
| 4 | Accepts Secure Digital memory cards.                                 |

The MFP reads the card, then the control panel displays **X photos found on card**, where X is the number of recognized JPEG files found on the memory card.

Now print photos using the HP Color LaserJet CM1017 MFP.



---

**NOTE** Insert only one memory card into the MFP at a time. If two or more are inserted, the MFP displays an error message. For more information about memory-card messages, see [Control-panel messages](#).

---

## View or rotate photos from the memory card

After a memory card is inserted into the correct slot, the MFP reports the number of photos on the memory card and shows the first photo on the card in the display screen.



---

**NOTE** If any buttons or keys are not pressed for five minutes the display screen goes blank. To reactivate the display screen, press **Photo Features**.

---

### To view or rotate photos from the memory card:

1. Press **Left arrow** or **Right arrow** to scroll through the images on the card.
2. Press **OK** to select or deselect images on the display screen.
3. To rotate an image, choose the **Rotate photo** option under **Photo Features**.



---

**NOTE** Rotating an image does not alter the original image or print the photo in a rotated view.

---



## Create a photo slideshow on the graphical display screen

After a memory card is inserted into the correct slot, the MFP can read the images to display a slideshow.

### To create a slideshow

1. Press **Photo Features** and choose **Slideshow**. Each image is displayed one-by-one.
2. Press **Cancel** to end the slideshow.

## Enable or disable a memory card

1. In the embedded Web server, select **Print** and **Memory Card**.
2. Select or deselect the label **Enable Memory Card**. When this box is not selected the control panel display says **Memory card slots are disabled** when a memory card is inserted.

# Print photos directly from the memory card

1. After inserting the memory card into the MFP (see [Insert a memory card](#)), select photos by:

- Press the **Left arrow** or the **Right arrow** to scroll through the images.
- Press **OK** to select or deselect the images.

2. You can also press **Select Photos** from the control panel.

Press **Up arrow** or **Down arrow** to select one of the following menu items, and then press **OK**.

- **From display:** Select this option if the memory card was not recently inserted.
- **All photos:** X represents the number of JPEG files the MFP detects on the card. Selecting this option prints all of the JPEG files on the memory card. Press **OK** again to confirm the print job.
- **Individual:** Select this option to choose and print an individual photo. The photos are numbered, starting with number 1.
  - Press **Up arrow** or **Down arrow** to increase or decrease the photo number.
  - Press **OK** to select the photo to print.
- **From a range:** Select this option to choose a range of photos to print. The MFP prompts for the first photo number and the last photo number.
  - Press **Up arrow** or **Down arrow** to increase or decrease the photo numbers.
  - Press **OK** to select the range of photos to print.

3. Press **Start Photo** to print the photos.



---

**NOTE** The JPEG files on the memory card are numbered in alphabetical order. If you do not know the order of the photos on the memory card, print an index that shows the photo order. For more information about printing an index, see [Print a memory card index](#).

---

# Print and scan photos from a proof sheet

Preview images and print photos from a proof sheet. A proof sheet can contain as many as 20 images. This feature has been optimized and tested for use with Genuine HP Toner Supplies.

1. Insert the memory card into the device. See [Insert a memory card](#).
2. Press **Proofsheet** then **Print**.
3. If more than 20 JPEG files exist on the memory card, press **Up arrow** or **Down arrow** to select one of the following menu items, then press **OK**.
  - **All photos**:  $X$  represents the number of JPEG files the MFP detects on the card. Selecting this option prints all JPEG files on the memory card. Press **OK** again to confirm the print job.
  - **Last 20**: Prints the last 20 JPEG files from the alphabetized list on the memory card.
  - **Custom**: Select one or more photos to print by pressing **OK**.
4. Color in the oval or bubble using a dark blue or black pen. Also fill bubbles to indicate the image layout and media type.
5. Place the proof sheet face-down on the flatbed scanner, with the upper-left corner of the document located in the lower-right corner of the glass.
6. Press **Proofsheet**.
7. Press the **Up arrow** or **Down arrow**, select **Start Scan**, then press **OK**. The MFP scans the proof sheet and prints the marked photos. Repeat steps 5 through 7 for each proof sheet.



---

**NOTE** Photos printed using a proofsheets can only be printed in color.

**NOTE** JPEG files on the memory card are displayed in alphabetical order. When the order of photos on the memory card is unknown, print an index. See [Print a memory card index](#).

**NOTE** Photos are still printed in color even when the Color copy option is set to no.

---

## Save photos to the workstation from a memory card

1. Insert the memory card into the MFP. See [Insert a memory card](#).
2. From the workstation, click on **My Computer** and look for the removable drive (memory card). If **My Computer** does not recognize the memory card, enter a IP address (an example, \\192.168.0.15) into the address line. Access the images by clicking **Memory card** and moving to the subfolders containing the images. Map the memory card to a driver letter on the workstation using this method.
3. Use drag and drop or HP Photosmart Transfer to move the photos from the memory card to a folder.

## Print photos using the Photo Features button

1. Insert the memory card into the MFP. See [Insert a memory card](#).
2. Press **Photo Features** and select **Easy photo print**.
3. Press **Up arrow** or **Down arrow** to select one of the following menu items, then press **OK**.
  - **All photos:** X represents the number of JPEG files the MFP detects on the card. Selecting this option prints all of the JPEG files on the memory card. Press **OK** again to confirm the print job.
  - **Individual:** Select this option to choose and print an individual photo. The photos are numbered, starting with number 1.
    - Press **Up arrow** or **Down arrow** to increase or decrease the photo number.
    - Press **OK** to select the photo to print.
  - **From a range:** Select this option to choose a range of photos to print. The MFP prompts for the first photo number and the last photo number.
    - Press **Up arrow** or **Down arrow** to increase or decrease the photo numbers.
    - Press **OK** to select the range of photos to print.
4. Press **Start Photo** to print the photos.

## Print a memory card index

1. Insert the memory card into the MFP. See [Insert a memory card](#). Press **Photo Features** to choose one of these options:
  - **Index print**
  - **Best Photo**
  - **Fast**
2. Press **Up arrow** or **Down arrow** to select **Index print** then press **OK**.
3. Press **Up arrow** or **Down arrow** to select either **Best Photo** or **Fast**, then press **OK**.

The MFP prints an index that includes small preview images for each photo on the memory card. Each index page can contain as many as 30 preview images.





# 11 Network Setup and Administration (HP Color LaserJet CM1017 MFP)

- [Set up the MFP and use it on the network](#)



---

**NOTE** Configuring TCP/IP settings are complicated and should only be performed by experienced network administrators. In order for automatic TCP/IP configuration to take place, either a BOOTP or DHCP Server must be present. For additional help or network configuration, contact the network administrator.

**NOTE** This MFP does not support HP Jetdirect devices.

---

## Set up the MFP and use it on the network

Hewlett-Packard recommends using the HP software installer available on the MFP CD-ROMs to install necessary software in the following network setups.

### Configure a network port-connected MFP configuration (direct mode or peer-to-peer printing)

In this configuration, the MFP is connected directly to the network, and all computers on the network print directly to the MFP.



---

**NOTE** This mode is the recommended network configuration for the MFP.

---

1. Connect the MFP directly to the network by inserting a network cable into the MFP network port. Then power on the MFP.
2. At the MFP, print a configuration report. See [Networking page \(HP Color LaserJet CM1017 MFP only\)](#).
3. Insert the MFP CD-ROM into the computer. If the MFP is already set up, click **Install Software** to start the software installer. If the software installer does not start, navigate to the hpzsetup.exe file on the CD-ROM and double-click the file.
4. On the **Welcome** screen, click **Next** and follow the prompts.
5. For Windows 2000 and XP, on the **Installation Options** screen, choose the installation option. Hewlett-Packard suggests a recommended installation, if the system supports it.



---

**NOTE** For Windows Server 2003, use **Add Printer Wizard** to install the print driver. Scanning is not supported in this network configuration for Windows Server 2003.

---

6. On the **Connection Type** screen, select **Through the network**, then click **Next**.
7. On the **Identify Printer** screen, identify the MFP either by searching or by specifying a hardware or IP address, which is listed on the Configuration page printed earlier. Click **Next**.
8. Allow the installation process to complete.



---

**NOTE** To install additional printer drivers (PS or PCL6 black and white) use the **Add Printer Wizard** and choose the network port that was created during the network installation from the MFP CD-ROM. Additional printer drivers are located on the MFP CD-ROM in the **Drivers** folder.

---

### Configure a direct-connected shared MFP (client server printing)

In this configuration, the MFP is connected to a computer through a USB cable, the computer is connected to the network, and the MFP is shared with other computers on the network.



---

**NOTE** This configuration supports printing from the client workstations. Client are not able to initiate a scan from the MFP.

---

1. Insert the MFP CD-ROM into the computer. If the MFP is already set up, click **Install Software** to start the software installer. If the software installer does not start, navigate to the hpzsetup.exe file on the CD-ROM and double-click the file.
2. On the **Welcome** screen, click **Next** and follow the prompts.
3. For Windows 2000, on the **Installation Options** screen, choose the installation option. Hewlett Packard suggests a recommended installation, if the system supports it.
4. On the **Connection Type** screen, select **Directly to this computer**, then click **Next**.
5. Connect the USB cable when prompted by the software.
6. Allow the installation process to complete.
7. On the Windows taskbar, click **Start**, click **Settings**, then click **Printers**.
  - In Windows XP, click **Start**, click **Control Panel**, then double-click **Printers**.
8. In the dialog box, right-click the printer-driver icon, and select **Sharing**.
9. Select **Share this Printer**, type the MFP name if necessary, then click **OK**.

## Manage the network

### View network settings

Use the embedded Web server or HP ToolboxFX to view the IP configuration settings. For more information, see [HP ToolboxFX](#) or [Use the embedded Web server](#).

### Restore the network defaults

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select **Network config**.
3. Press the navigation arrows to select **Restore defaults**.
4. Press **OK**.

### Change network settings

Use the embedded Web server or HP ToolboxFX to change the IP configuration settings. For more information, see [HP ToolboxFX](#) or [Use the embedded Web server](#).

## Change from a direct-connected shared MFP to a network port-connected MFP configuration

To change from a direct connection to a network configuration, complete the following steps.

1. Uninstall the printing software for the connected MFP. See [Uninstall the printing software](#).
2. Install the software choosing the network as the connection type, then follow the directions in [Manage the network](#).

## Use the control panel

- [Network configuration page](#)
- [Configuration page](#)
- [IP configuration](#)
- [Link speed settings](#)

### Network configuration page

The Network configuration page lists the current network settings and other MFP properties. To print the Network configuration page from the MFP:

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select **Reports**, then press **OK**.
3. Press the navigation arrows to select **Network report**, then press **OK**.

### Configuration page

The Configuration page lists the current MFP settings and properties. It is possible to print a Configuration page from the MFP or HP ToolboxFX. To print the Configuration page from the MFP:

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select **Reports**, then press **OK**.
3. Press the navigation arrows to select **Configuration report**, then press **OK**.

### IP configuration

It is possible to configure the IP address manually or automatically.

#### Manually configure a static IP address



---

**CAUTION** Do not assign identical TCP/IP addresses to two network devices on the same network.

---

To manually configure a static IP address from the control panel:

1. On the control panel, press **Menu**
2. Press the navigation arrows to select **Network config**.
3. Press **OK**.
4. Press the navigation arrows to select the **TCP/IP configuration** menu.
5. Press **OK**.
6. Press the navigation arrows to select **Manual**.
7. Press and hold **OK**.
8. Press **Left arrow** or **Right arrow** to decrement or increment each triplet value.

9. Press **OK** to move the cursor to the next triplet. When the address is complete press **OK** to bring up the confirmation screen.
10. The graphical screen displays **Yes**. Press **OK** to save the configuration, or to delete and re-enter another IP address, press **Left arrow** or **Right arrow**, which changes the display to **No**.
11. After selecting the IP address, enter the subnet mask and default gateway by repeating steps 8–10. To get subnet mask and default gateway information in Windows XP Pro:
  1. Click on **Start**, select **All Programs, Accessories**, then **System Tools**.
  2. Click **System Information, Components, Network**, then **Adapter**. The current PC settings information is displayed. Obtain subnet mask and default gateway information.
12. When all information is entered, the MFP may power cycle.
13. If at any time during the configuration **Cancel** is pressed, the system exits the menu and the addresses are not saved.

### Automatic configuration

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select **Network config**, then press **OK**.
3. Press the navigation arrows to select **TCP/IP configuration**, then press **OK**.
4. Press the navigation arrows to select **Automatic**, then press **OK**.

It can take several minutes before the automatic IP address is ready for use.



**NOTE** To disable or enable specific automatic IP modes (such as BOOTP, DHCP, or AutoIP), use options provided in the embedded Web server or HP ToolboxFX only.

### Link speed settings



**NOTE** Incorrect changes to the link speed and duplex settings might prevent the MFP from communicating with other network devices. For most situations, the MFP should be left in automatic mode. Also note that changes may cause the MFP to power cycle; makes changes only while the MFP is idle.

1. On the control panel press **Menu**.
2. Press the navigation arrows to select **Network config**, then press **OK**.
3. Press the navigation arrows to select **Link speed**, then press **OK**.
4. Press the navigation arrows to select one of the following settings.
  - Automatic
  - 10T Full
  - 10T Half
  - 100T Full
  - 100T Half



**NOTE** The setting must match with the network device to which you are connecting (a network hub, switch, gateway, or computer).

5. Press **OK**. The MFP may power cycle.

## Supported network protocols

This table lists the networking services/protocols supported on the HP Color LaserJet CM1017 MFP.

**Table 11-1** Printing

Service name	Description
port9100 (Direct Mode)	Printing service
Line printer daemon (LPD)	Printing service

**Table 11-2** Network device discovery

Service name	Description
SLP (Service Location Protocol)	Device Discovery Protocol, used to help find and configure network devices. Used primarily by Microsoft based applications.
Bonjour, (commonly referred to as Rendezvous or mDNS (multicast Domain Name Service))	Device Discovery Protocol, used to help find and configure network devices. Used primarily by Apple Macintosh based Applications. For more information, see <a href="#">Software for Macintosh</a> .

**Table 11-3** Messaging and management

Service name	Description
HTTP (Hyper Text Transfer Protocol)	Allows web browsers to communicate with embedded Web server.
SNMP (Simple Network Management Protocol)	Used by network applications for device management. SNMP v1 and standard MIB-II (Management Information Base) objects are supported.

**Table 11-4** IP addressing

Service name	Description
DHCP (Dynamic Host Configuration Protocol)	For Automatic IP address assignment. DHCP server provides device with IP address. Generally requires no user intervention for MFP to obtain IP address from a DHCP server.
BOOTP (Bootstrap Protocol)	For Automatic IP address assignment. BOOTP server provides device with IP address. Requires administrator to input devices MAC hardware address on BOOTP server in order for MFP to obtain an IP address from that server.
Auto IP	For Automatic IP address assignment. If neither a DHCP server nor a BOOTP server is present, this service allows the

**Table 11-4** IP addressing (continued)

Service name	Description
	MFP to generate a unique IP address. For example, the IP address 169.254.0.10 represents a series of triplets ranging from 0 to 254; this address is not manually configurable.

## TCP/IP

TCP/IP (Transmission Control Protocol/Internet Protocol) is a suite of protocols designed to define the way computers and other devices communicate with each other over a network.

TCP/IP is rapidly becoming the most used set of protocols because the Internet is based on TCP/IP. If there is a network that you want to connect to the Internet, use TCP/IP to communicate.



**NOTE** This MFP does not support IP V6.

## Internet Protocol (IP)

When information is sent across the network, the data is broken down into small packets. Each packet is sent independently of one another. Each packet is encoded with IP information, such as the IP address of the sender and receiver. IP packets can be routed over routers and gateways, devices that connect a network with other networks.

IP communications is connectionless. When IP packets are sent, there is no guarantee that they arrive at their destination in the proper sequence. That task can be performed by higher level protocols and applications thereby allowing IP communications to be efficient.

Each node or device that communicates directly onto the network requires an IP address.

## Transmission Control Protocol (TCP)

TCP handles breaking the data into packets and recombining the packets on the receiving end by providing a connection-oriented, reliable, and guaranteed delivery service to another node on the network. When data packets are received at their destination, TCP calculates a checksum for each packet to verify the data is not corrupt. If the data in the packet has been corrupted during transmission, TCP discards the packet and requests that the packet be resent.

## User Datagram Protocol (UDP)

UDP provides similar services to TCP. However, UDP does not acknowledge data receipt and supports request/reply transactions with no added reliability or guarantee of delivery. UDP is used when acknowledgment and reliability are not required, such as during a “discovery broadcast.”

## IP address

Every host (workstation or node) on an IP network requires a unique IP address for each network interface. This address is a software address that is used to identify both the network and specific hosts located on that network. Each IP address can be divided into two separate parts: the network portion and the host portion. It is possible for a host to query a server for a dynamic IP address each time the device boots up (for example, using DHCP and BOOTP).



---

**NOTE** When assigning IP addresses, always consult the IP address administrator. Setting the wrong address can disable other equipment operating on the network or interfere with communications.

---

## Configure IP parameters

TCP/IP parameters (such as IP address, subnet mask, default gateway) can be configured on the MFP manually (for example, through the embedded Web server, and HP management software), or automatically downloaded using DHCP or BOOTP each time the MFP is turned on.

When powered on, a new MFP that is unable to retrieve a valid IP address from the network automatically assigns itself a default IP address. The default IP address depends on the type of network to which the MFP is connected. On a small private network, a technique called link-local addressing is used to assign a unique IP address in the range of 169.254.1.0 to 169.254.254.255, which should be valid. The IP address configured on the MFP can be determined by inspecting the Network Configuration page.

### Dynamic Host Configuration Protocol (DHCP)

DHCP allows a group of devices to use a set of IP addresses that are maintained by a DHCP server. The device or host sends a request to the server, and if an IP address is available, the server assigns it to that device.

### BOOTP

BOOTP is a bootstrap protocol used to download configuration parameters and host information from a network server. BOOTP uses UDP for its transport. In order for devices to boot and load configuration information into RAM, they must communicate through the bootstrap protocol BOOTP as a client with their server.

To configure the device, the client broadcasts a boot request packet containing at least the hardware address of the device (MFP hardware address). The server answers with a boot reply packet containing the information the device needs to configure.

## Subnets

When an IP network address for a particular network class is assigned to an organization, no provision is made for more than one network being present at that location. Local network administrators use subnets to partition a network into several different subnetworks. Splitting a network into subnets can result in better performance and improved use of limited network address space.

### Subnet mask

The subnet mask is a mechanism used to divide a single IP network into several different subnetworks. For a given network class, a portion of an IP address that would normally be used to identify a node is used, instead, to identify a subnetwork. A subnet mask is applied to each IP address to specify the portion used for subnetworks, and the portion used to identify the node. See [Manually configure a static IP address](#) for more information about obtaining subnet mask data.

**Table 11-5** Example: Subnet mask 255.255.0.0 applied to class A network

Class A Network Address	Network 15	xxx	xxx	xxx
Subnet Mask	255	255	0	0
IP Address fields with Subnet Mask applied	Network	Subnet	Host	Host



**Table 11-5** Example: Subnet mask 255.255.0.0 applied to class A network (continued)

Class A Network Address	Network 15	xxx	xxx	xxx
Example of a node's IP Address on Subnet 1	210	1	25	7
Example of a node's IP Address on Subnet 254	210	254	64	2

The Class A IP network address 210 has been assigned to company ABC. To allow additional networks at company ABC's site, the subnet mask of 255.255.0.0 is used. This subnet mask specifies that the second byte of the IP address is used to identify up to 254 subnets. Using this designation, each device is uniquely identified on its own subnet, but company ABC can incorporate up to 254 subnetworks without violating their assigned address space.

## Gateways

Gateways are used to connect networks together. Gateways are devices that act as translators between systems that do not use the same communication protocols, data formatting, structures, languages, or architectures. Gateways repackage the data packets and change the syntax to match that of the destination system. When networks are divided into subnets, gateways are required to connect one subnet to another. A typical gateway IP address could be 192.168.0.1. See [Manually configure a static IP address](#) for more information about obtaining gateways data.

### Default gateway

The default gateway is the gateway that, if not specified, is used to move packets between networks. It is specified by an IP address.

If multiple gateways exist, then the default gateway is typically the address of the first, or nearest, gateway. If no gateways exist, then the default gateway typically assumes the IP address of the network node (such as the workstation or MFP).

## Problem Solving

### Verify that the MFP is on and online

Check the following items to make sure the MFP is ready to print.

## Resolve communication problems with the network

Check the following items to verify the MFP is communicating with the network. This information assumes a Network configuration page has already been printed. See [Networking page \(HP Color LaserJet CM1017 MFP only\)](#).

### 1. Are the network cables connected properly?

Ensure that the MFP is attached to the network using the appropriate port and cable. Verify each cable connection to make sure it is secure and in the right place. If the problem continues, try a different cable or ports on the hub or transceiver. The amber activity light should be blinking and the green link status light should be solid next to the port connection on the MFP back.

### 2. Review the information on the Network Hardware Configuration page. Start with the Network Hardware section:

- **Initializing:** If the printer has not obtained a valid IP address, wait four minutes and reprint the Network Hardware Configuration page.
- **Not Connected:** a printer-cable is not connected to the printer or a cable is defective. Change the network cable and verify that it is properly connected into the network. Verify hub or switch are on and working properly.
- **Connected:** The printer has been assigned a TCP/IP address from BOOTP, DHCP, or AUTOIP.
- **Duplicate IP address detected:** Another networked device has the same IP address assigned. Contact the network administrator to resolve this issue.

Review under the TCP/IP section of the Network Hardware Configuration page the IP configured by method:

- **Manual:** User entered information. Verify the TCP/IP address, subnet mask, and default gateway are correct.
- **DHCP:** Automatically assigned TCP/IP address by the dynamic host controller protocol (DHCP) server.
- **BOOTP:** Manually assigned TCP/IP address by the BOOTP server.
- **AUTOIP:** Default address assigned for Link Local connection (no DHCP or BOOTP server available).

### 3. Can you “ping” the MFP?

Use the command prompt to ping the MFP from the computer. For example:

```
ping 192.168.0.10
```

Ensure that the ping displays round-trip times.

If you can ping the MFP, verify that the IP address configuration for the MFP is correct on the workstation. If it is correct, uninstall and re-install the MFP software.

If the ping command failed, verify that the network hubs are on, then verify that the network settings, the MFP, and the computer are all configured for the same network.

### 4. Are other MFPs able to print?

If yes, the problem is workstation-specific. Verify that both workstations are using the same network settings.



---

**CAUTION** Do not assign identical TCP/IP addresses to two network devices on the same network.

---

5. If network communication is not resolved by using steps 1 through 3, or if other users can not print, reset all network configuration settings to factory-defaults by selecting **Restore defaults** from the control panel. After the MFP automatically power cycles, wait four to six minutes and verify that the network functionality is working properly. Contact the network administrator for more information.



# 12 How do I?

Use this section to perform basic tasks with the HP Color LaserJet CM1015/CM1017 MFP Series.

- [Control panel and other settings: How do I?](#)
- [Control-panel menus](#)
- [Print: How do I?](#)
- [Copy and Scan: How do I?](#)
- [Photo: How do I? \(HP Color LaserJet CM1017 MFP only\)](#)
- [Network: How do I? \(HP Color LaserJet CM1017 MFP only\)](#)
- [Maintenance: How do I?](#)

# Control panel and other settings: How do I?


This section discusses control-panel settings.

## HP Color LaserJet CM1017 MFP control panel features

The HP Color LaserJet CM1017 MFP contains the following lights and buttons on the control panel:



**NOTE** Print a demo page by pressing the **Scan To** and **Start Scan** buttons simultaneously.



1

Graphical display. Message, menus, and supply gauge area.

Supplies gauges: Displays consumption levels of print cartridges. Appears when the MFP shows the Ready state with no warnings, or when the MFP shows a warning or error message pertaining to a print cartridge or multiple supplies. When the supply is empty the gauge displays as empty. Flashing indicates a single supply is empty. These messages can display when:

- Missing cartridges
- Incorrectly placed cartridges
- Cartridges with an error
- Some non-HP cartridges



**CAUTION** Printing may continue when a non-HP supply is empty. To prevent MFP damage, frequently check the status of non-HP supplies. See Hewlett-Packard limited warranty statement.



**NOTE** When a "?" displays on-screen, it may be because the supply is missing, it is a non-HP supply, or the status is being determined by the MFP.

2	<b>Amber activity light:</b> An error has occurred. Printer requires attention.
3	<b>Up arrow (^):</b> Press to enter the main menu system or navigate to the previous menu item, or previous item in the selection list.
4	<b>Cancel (X):</b> Whenever the <b>Ready</b> light blinks, press to cancel a print job. Pressing this button also exits the control-panel menus.
5	<b>Right arrow (&gt;):</b> Press to navigate to the next submenu or the next value in the menu selection list. Also allows cursor movement forward a single position, or increments a numeric entry.
6	<b>Down arrow (v):</b> Press to navigate to the menu item below the current menu item.
7	<b>Start Photo:</b> Press to print one or more photos.
8	<b>Proofsheet:</b> Press to print a proofsheet.
9	<b>Start Scan:</b> Starts scanning to the previously selected e-mail or folder destination. The MFP can also start a scan if a destination is not specified.
10	<b># of Copies:</b> Press the navigation arrows to increase or decrease the number of copies produced.
11	<b>Lighter/Darker:</b> Press <b>Left arrow</b> to lighten the copy or the <b>Right arrow</b> to darken the copy.
12	Press <b>Start Copy Color</b> to begin a color copy job.
13	Press <b>Start Copy Black</b> to begin a monochrome copy job.
14	<b>Reduce/Enlarge:</b> Displays a list of temporary copy and size changes.
15	<b>Copy Features:</b> Displays a menu of copy features.
16	<b>Scan To:</b> Displays a list of pre-configured folders and e-mail destinations. To create a new destination, set up the <b>Scan To</b> destination on the workstation.
17	<b>Select Photos:</b> Press to choose one or more photos.
18	<b>Photo Features:</b> Press to navigate to select photo features.
19	<b>Return to previous menu or menu item:</b> Backs up one menu screen or one step in the current menu structure.
20	<b>Left arrow (&lt;):</b> Press to navigate to the previous submenu or the previous value in the menu selection list. Also allows cursor movement back a single position, deletes the previous character, or decrements a numeric entry.
21	<b>Menu:</b> Opens the main menu system.
22	<b>Ready light (green):</b> Green light is steady when the MFP can accept print jobs or blinks when the MFP receives print data.
23	<b>OK:</b> <ul style="list-style-type: none"> <li>● Selects a menu item</li> <li>● Clears some printer-errors</li> <li>● Acknowledges use of a non-HP supply</li> </ul>

## Use the graphical display (HP Color LaserJet CM1017 MFP)

The color graphics display shows menus, photos, and messages. The display can be pulled up and angled for better viewing. Use the arrows on the control panel to navigate the menus on the control panel and to select photos on the panel for printing. Status and error messages will be displayed on the screen.

After 60 minutes of inactivity, the color graphics display goes into Sleep State and the screen shuts off completely. The display turns back on when you perform an operation, such as pressing a control panel button, or inserting a memory card, accessing the HP All-in-One from a connected computer.

### **Use the control-panel arrows to navigate on the HP Color LaserJet CM1017 MFP**

- Press the **Up arrow** or **Down arrow** to navigate through all control panel menus.
- Press **Back** to return to the previous menu.
- Press **OK** to make a selection.

Press the **Left arrow** or **Right arrow** to complete the following tasks:

- Increase or decrease values on the horizontal scroll bar on various copy and photo menus.
- Browse photos on the graphical display from your memory card.
- Enter an IP address.



# Control-panel menus

## Use the control-panel menus

To gain access to the control-panel menus, use the following steps.

1. Press **Menu**.
  2. On the HP Color LaserJet CM1015 MFP, press **Left arrow** or **Right arrow** to navigate the listings. On the HP Color LaserJet CM1017 MFP, press **Up arrow** or **Down arrow** to navigate the listings.
- Press **OK** to select the appropriate option.
  - Press **Cancel** to cancel an action or return to the Ready state.
  - Press **Back** to move to the previous menu.

## Control-panel menu map

These menus are available from the control panel Main menu:

- Use the **Copy setup** menu to configure basic copy default qualities.
- Use the **Reports** menu to print reports that provide information about the printer.
- Use the **Photo setup** menu to configure defaults for photo printing.
- Use the **System setup** menu to establish basic printer settings. The **System setup** has several sub-menus. Each is described in the table.
- Use the **Service** menu to restore default settings, clean the printer, and activate special modes that affect print output.
- Use the **Network config.** menu to configure network settings.

**Table 12-1 Copy Setup Menu**

Menu item	Sub-menu item	Sub-menu item	Description
Default Quality			Sets the default copy quality.
Default light/dark			Sets the default lighter/darker option.
Default Reduce/Enlarge			Sets the default percentage to reduce or enlarge a copied document.
Default # of copies			Sets the default number of copies.
Advanced	Color Balance	Red	Increases or decreases the amount of these colors in the output.
		Green	
		Blue	
	Background		Increases or decreases the background color in a copy.

**Table 12-1** Copy Setup Menu (continued)

Menu item	Sub-menu item	Sub-menu item	Description
	<b>Contrast</b>		Increases or decreases the differences between whites and blacks of a copy.
	<b>Lightness</b>		Increases or decreases the background color in a copy.
	<b>Grayness</b>		Increases or decreases the color in the color copy of a black and white original.
	<b>Sharpen</b>		Increases or decreases the reproduction details in a copy.
	<b>Restrict color</b>		Permits the enabling or disabling of color copies.
<b>Restore defaults</b>			Sets all customized copy settings to the factory default values.

**Table 12-2** Reports Menu

Menu Item	Description
<b>Demo page</b>	Prints a color page that demonstrates print quality.
<b>Menu structure</b>	Prints a control-panel menu layout map. The active settings for each menu are listed.
<b>Configuration report</b>	Prints a list of all the printer settings. Includes network information when the printer is connected to the network.
<b>Supplies status page</b>	Prints the status of each print cartridge. Includes this information: <ul style="list-style-type: none"> <li>● Estimated pages remaining</li> <li>● Serial number</li> <li>● Number of pages printed</li> </ul>
<b>Network report</b>	Displays status for: <ul style="list-style-type: none"> <li>● Network hardware configuration</li> <li>● Enabled features</li> <li>● TCP/IP and SNMP information</li> <li>● Network statistics</li> </ul>
<b>Usage page</b>	Displays number of pages printed by the MFP.
<b>PCL font list</b>	Prints a list of all installed PCL fonts.
<b>PS font list</b>	Prints a list of all installed PS fonts.

**Table 12-2** Reports Menu (continued)

Menu Item	Description
PCL6 font list	Prints a list of all installed PCL6 fonts.
Service page	Starts the cleaning mode and restores factory settings.

**Table 12-3** Photo Setup Menu (Available only from HP Color LaserJet CM1017 MFP)

Menu Item	Description
Default image size	Set up default image size.
Default light/dark	
Default # of copies	Set up default number of copies.
Default output color	Set up default output color.
Restore defaults	Resets all photo items to their factory defaults. Machine does not power cycle.

**Table 12-4** System Setup Menu

Menu Item	Sub-menu item	Sub-menu item	Description
Language			Select the language in which the control panel displays messages and printer reports.
Paper setup	Default paper size	Letter	Select the size for printing internal reports or any print job that does not specify a size.
		A4	
		Legal	
	Default paper type	Lists available media types.	Select the type for printing internal reports or any print job that does not specify a type.
	Tray 1	Paper size	From the displayed list, select the default size and type for tray 1.
		Paper type	
	Tray 2	Paper size	From the displayed list, select the default size and type for tray 2.
		Paper type	
	Tray 3 (optional)	Paper size	From the displayed list, select the default size and type for optional tray 3.
		Paper type	
	Paper-out action	Wait forever	Determines how the printer reacts when a print job requires a size or type that is unavailable or when a specified tray is empty.  Select <b>Wait forever</b> to make the printer wait until the correct media is loaded.
		Override	
		Cancel job	

**Table 12-4** System Setup Menu (continued)

Menu Item	Sub-menu item	Sub-menu item	Description
			<p>Press <b>OK</b> to select the default setting.</p> <p>Select <b>Override</b> to print on a different size paper after a specified delay.</p> <p>Select <b>Cancel job</b> to automatically cancel the print job after a specified delay.</p> <p>If either <b>Override</b> or <b>Cancel job</b> is chosen, the control panel prompts for the number of seconds to delay. Press the <b>Right arrow</b> to increase the time up to 3600 seconds. Press <b>Left arrow</b> to decrease the time.</p>
<b>Print quality</b>			
	<b>Calibrate color</b>	<b>Calibrate now</b> <b>Power-on calibration</b>	<p><b>Calibrate now:</b> Directs the printer to immediately calibrate. When a job is processing, the printer calibrates after the job is complete. When an error message displays, clear the error before continuing.</p> <p><b>Power-on calibration:</b> Select how quickly the printer should calibrate after it is powered on. The default setting is 15 minutes.</p>
	<b>Cartridge low</b>		Signals that the cartridge is almost empty.
	<b>Replace supplies</b>		Displays message that a supply or supplies need to be replaced.
<b>Courier font</b>			Select courier font values.

**Table 12-5** Service Menu

Menu item	Description
<b>Cleaning mode</b>	<p>This options cleans the printer when specks or other marks appear on printed output. The cleaning process removes dust and excess toner from the paper path.</p> <p>When selected, the printer prompts to load plain paper in tray 1 and then press <b>OK</b> to begin the cleaning process. Wait until the process completes. Discard the page that prints.</p>
<b>Restore defaults</b>	Sets all customized settings to the factory default values.

**Table 12-5** Service Menu (continued)

Menu item	Description
<b>USB speed</b>	
<b>Less paper curl</b>	<p>When printed pages are consistently curled, this option sets the printer to a mode that reduces curl.</p> <p>The default setting is <b>Off</b>.</p>
<b>Archive print</b>	<p>When printing pages that will be stored for a long time, this option sets the printer to a mode that reduces toner smearing and dusting.</p> <p>The default setting is <b>Off</b>.</p>

**Table 12-6** Network Configuration Menu (Available only on HP Color LaserJet CM1017 MFP Series)

Menu item	Sub-menu item	Description
<b>TCP/IP configuration</b>	Automatic	Select <b>Automatic</b> to automatically configure all the TCP/IP settings.
	Manual	<p>Select <b>Manual</b> to manually configure the IP address, subnet mask, and default gateway.</p> <p>The control panel prompts you to specify values for each address section. Press <b>Right arrow</b> to increase the value. Press <b>Left arrow</b> to decrease the value. Press <b>OK</b> to accept the value and move the cursor to the next field.</p> <p>As each address is completed, the printer prompts for address confirmation before moving to the next one. After all three addresses are set, the printer automatically restarts.</p> <p>Select <b>Reset TCP/IP</b> to restore all the TCP/IP settings to the default values.</p>
<b>Link speed</b>	Automatic	The printer automatically detects the correct link speed for the network. Use this menu to set the link speed manually if needed.
	10T Full	
	10T Half	After setting the link speed, the printer automatically restarts.
	100TX Full	
	100TX Half	
<b>Memory card</b>		Sets memory card slots.
<b>Restore defaults</b>		Resets all network configurations to their factory defaults.

# Print: How do I?

Use this section to answer printing questions.

## System Settings

The HP ToolboxFX **System Settings** folder contains links to the following main pages:

- **Device information.** View information about the MFP, such as the description and a contact person.
- **Paper handling.** Change the MFP paper-handling settings, such as default paper size and default paper type.
- **Print quality.** Change the MFP print-quality settings.
- **Print density.** Change the print density settings, such as contrast, highlights, midtones, and shadows.
- **Paper types.** Change the MFP mode settings for each media type, such as letterhead, prepunched, or glossy paper.
- **System Setup.** Change the MFP system settings, such as MFP language and jam recovery.
- **Service.** Gain access to various procedures required to maintain the MFP.
- **Device Polling.** The HP ToolboxFX periodically communicates with your device to determine device status and enabled features.
- **Save and restore settings.** Save the current MFP settings to a file on the computer. Use this file to load the same settings onto another printer or MFP to restore these settings to this MFP at a later time.
- **Password.** If set, the password must be entered to change any of the HP ToolboxFX system settings, email alerts, or network settings.

## Device information

Save the HP ToolboxFX Device information for future reference about the MFP. The information that is typed in these fields appears on the Configuration page. It is possible to type any character in each of these fields.



---

**NOTE** Click **Apply** to make the changes take effect.

---

## Paper handling

Use the HP ToolboxFX paper-handling options to configure the default settings. These are the same options that are available on the **System setup** and **Paper setup** menus on the control panel. For more information, see [Control-panel menus](#).

Three options accommodate handling print jobs when the product is out of media:

- Select **Wait for paper to be loaded**.
- Select **Cancel** from the **Paper out action** drop-down list to cancel the print job.
- Select **Override** from the **Paper out time** drop-down list to send the print job to another paper tray.

The **Paper out time** field specifies how long the MFP waits before acting on your selections. It is possible to specify from 0 to 3600 seconds.



**NOTE** Click **Apply** to make the changes take effect.

## Print quality

Use the HP ToolboxFX print-quality options to improve the print job appearance. These same options are available on the **System setup** and **Print quality** menu on the control panel. For more information, see [Control-panel menus](#).

These options control print quality.

- Color Calibration.
  - Power On Calibration
  - Calibration Timing
  - Calibrate Now
- Grayscale Printing.

Grayscale printing options	Description
<b>Resolution</b>	Select 600 resolution for average print jobs and Fast Res 1200 for higher-quality print jobs. Select ProRes 1200 for the highest-quality print job, but a longer printing time.
<b>REt</b>	Choose REt which HP provides for improved print quality.



**NOTE** Click **Apply** to make the changes take effect.

## Print density

The print density settings control making fine adjustments to the density (amount) of Cyan, Magenta, Yellow, and Black toner in images, pages, and documents.

Print density settings	Description
<b>Contrasts</b>	Contrast is the density difference between light (highlight) and dark (shadow) colors. To increase the difference between light and dark colors (equivalent to a negative highlight adjustment

Print density settings	Description
	and a positive shadow adjustment), use a positive contrast setting. To decrease the difference between light and dark colors (equivalent to a positive highlight adjustment and a negative shadow adjustment), use a negative contrast setting.
<b>Highlights</b>	Highlight colors are colors near white. To make highlight colors darker, use a positive highlight setting, and to make highlight colors lighter use a negative highlight setting. This adjustment does not affect midtone or shadow colors.
<b>Midtones</b>	Midtone colors are about halfway between white and solid density. To make midtone colors darker, use a positive midtone setting, and to make midtone colors lighter use a negative highlight setting. This adjustment does not affect highlight or shadow colors.
<b>Shadows</b>	Shadow colors are colors near solid density. To make shadow colors darker, use a positive shadow setting, and to make shadow colors lighter use a negative shadow setting. This adjustment does not affect highlight or midtone colors.

## Set the system password

Use HP ToolboxFX to set a system password.

1. Open HP ToolboxFX and click **System Settings**.



**NOTE** If a password has been set for the MFP previously, you are prompted to type the password. Type the password, then click **Apply**.

2. Click **Password**.
3. In the **Password** box, type the exact password to set, then in the **Confirm password** box, type the same password again to confirm the choice.
4. Click **Apply** to save the password.

### To remove the system password

1. Open HP ToolboxFX and click **System Settings**.



**NOTE** If a password has been set for the MFP previously, you are prompted to type the password. Type the password, then click **Apply**.

2. Click **Password**.
3. Delete all characters from both the **Password** field and the **Confirm password** field.
4. Click **Apply** to remove the password.

### To reset all MFP settings to factory defaults

If you forget or lose your password, use the following steps to reset all your MFP settings to factory defaults.





---

**WARNING!** Following these steps will clear the password and all of the changes you have made to the MFP settings.

---

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select the **Service** menu.
3. Press **OK**.
4. Press the navigation arrows to select the **Restore defaults** menu.
5. Press **OK**.
6. Press **OK** again to confirm restoring the defaults.

## Paper types

Use these HP ToolboxFX **Paper types** options to configure print modes that correspond to the various media types. When selecting **Restore modes**, all of the modes are reset to the factory settings.



---

**NOTE** Click **Apply** to make the changes take effect.

---

## System setup

Use the HP ToolboxFX system settings options to configure miscellaneous print settings. These settings are not available from the control panel.



---

**NOTE** Click **Apply** to make the changes take effect.

---

## Service

During the printing process, paper, toner, and dust particles can accumulate inside the MFP. Over time, this buildup can cause print-quality problems such as toner specks or smearing. HP ToolboxFX provides an easy method for cleaning the paper path. For more information, see [Clean the paper path using HP ToolboxFX](#).

## Device Polling Page

The HP ToolboxFX periodically communicates with your device to determine device status and enabled features. Use the Polling Page to turn off pop-up alerts and the **Scan To** and **Start Scan** buttons located on the device.

## Print Settings

The HP ToolboxFX Print Settings folder contains links to the following main pages:

### Printing

Use the HP ToolboxFX printing settings options to configure the settings for all print functions. These are the same options that are available on the **Print settings** menu on the control panel. For more information, see [Control-panel menus](#).



---

**NOTE** Click **Apply** to make the changes take effect.

---

## PCL5c

Configure these PCL5c settings:

- Font number
- Font pitch
- Font point size
- Symbol set
- Append CR to LF
- Form length

## PostScript

Use the PostScript option when using the PostScript print personality. When the **Print PostScript error** option is turned on, the PostScript error page automatically prints when PostScript errors occur.



---

**NOTE** Click **Apply** to make the changes take effect.

---

## Memory card (HP Color LaserJet CM1017 MFP only)

Use the three HP ToolboxFX memory card options to configure print settings when using memory cards.

- **Photo image size.** Select the size photos to print from the drop-down list.
- **Photo number of copies.** Type the number of copies from 0 to 99 to print for each image.
- **Photo output color.** Select either **Color** or **Monochrome** from the drop-down list.

Click the **Enable memory cards** checkbox to save the settings.



## Control print jobs

When changing print settings, follow the hierarchy of how changes are prioritized. (Note that the names of commands and dialog boxes might vary depending on the software program.)

- **Application Settings dialog box.** This dialog box opens when you click **Application Settings** or a similar command on the **File** menu in the software program. This dialog box is part of the program in which you are working. *Settings that are changed here override settings that are changed anywhere else.*
- **Print dialog box.** This dialog box opens when you click **Print**, **Print Setup**, or a similar command on the **File** menu in the software program. It is also part of the program, but it has a lower priority than the **Application Settings** dialog box. Settings that are changed in the **Print** dialog box *do not* override settings that are changed in the **Application Settings** dialog box. Settings that are changed here *do* override settings that are changed in the printer driver.
- **Printer driver.** The printer driver opens when you click **Properties** in the **Print** dialog box. Settings that are changed here *do not* override settings that are changed anywhere else.

## Selecting print media settings


When a job is sent to the printer, the printer driver controls what paper tray is used to pull media through the printer. By default, the printer automatically selects the tray, but a specific tray can be chosen based on three user specified settings: **Source**, **Type**, and **Size**. These settings are available from the **Application Setting** dialog box, the **Print** dialog box, or the printer driver.


Setting	Description
Source	<p>Directs the printer to pull paper from a user-specified tray. The printer tries to print from this tray, no matter what type or size media is loaded in it. However, if the selected tray is configured from the HP ToolboxFX for a type or size and that does not match the print job, the printer does not print automatically. To begin printing, load the selected tray with the correct type or size of print media for the print job. When loading the tray, the printer begins printing. If the printer does not begin printing:</p> <ul style="list-style-type: none"> <li>• Verify the tray configuration matches the size or type of the print job.</li> <li>• Press <b>OK</b> to have the printer try to print from another tray.</li> </ul>
Type or Size	<p>Directs the printer to pull paper or print media from the first tray that is loaded with the type or size that you selected. <i>Always print by Type for special print media such as labels or transparencies.</i></p> <p> <b>NOTE</b> When the trays have not been configured for a certain type or size from the HP ToolboxFX, load the paper or print media into a tray then select the <b>Type</b> or <b>Size</b> from the <b>Page Setup</b> dialog box, the <b>Print</b> dialog box, or the printer driver.</p> <p> <b>NOTE</b> An Administrator or individual user can set the HP ToolboxFX to direct the MFP to pull from a tray that is pre-configured for a specified <b>Type</b> or <b>Size</b>. This is helpful when frequently printing on the same type of media; a dedicated tray is already pre-configured for printing.</p>

## Printer-driver features

Some printer drivers and some operating systems do not support all of these MFP features.

Task	Driver Tab	Option
Set custom paper	<b>Paper</b>	<b>Size is</b>
Print in grayscale	<b>Color</b>	<b>Print in Grayscale</b>
Create and use watermarks	<b>Effects</b>	<b>Watermark</b>

 **NOTE** For Windows 2000 and XP environments, Administrator privileges are required to create watermarks but are not required to add existing watermarks to documents.

Task	Driver Tab	Option
Print multiple pages on one sheet of paper (N-up printing)	<b>Finishing</b>	<b>Pages per sheet</b>
Reduce or enlarge a document before printing	<b>Effects</b>	<b>Fit to Page</b>
Print the first page on different paper	<b>Paper/Quality</b>	<b>Appropriate paper size</b>
Change color settings	<b>Color</b>	<b>Settings</b>
Create and use Quick Sets. Quick Sets save the current print-driver settings such as the page orientation, N-up printing, or the paper source for later use. Save up to 30 sets.	All. To later retrieve settings, choose <b>Finishing</b>	
 <b>NOTE</b> In the Windows 2000 environment, Administrator privileges are required to save Quick Sets.		

For printing using the Print on Both Sides (manually) feature, see [Print on both sides of the paper](#).

### Restore the default printer-driver settings

This feature might be useful when experiencing quality issues, or if the print media is not being selected from the correct tray.

Select **Defaults** in the **Quick Sets** dialog box on the **Finishing** tab of the printer driver.

### Print from Windows

1. Load the print media.
2. On the **File** menu of your application, click **Page Setup** or a similar command. Ensure the settings are correct for this document.
3. From the **File** menu, click **Print**, **Print Setup**, or a similar command. The **Print** dialog box opens.
4. Select the correct MFP and change settings as necessary. Do not change any settings, such as page size or orientation, that were previously set in the **Application Settings** dialog box.
5. If this print job is to be printed on a non-standard size or weight of paper, see [Selecting print media settings](#) for more information.
6. If not already done, click **Properties**. The printer driver opens.
7. On the various tabs, set additional settings that did not appear in the **Application Settings** or **Print** dialog box. For more information about printer-driver settings, see [Printer-driver features](#).
8. Select the **Print** command to print the job.

### Printer-driver settings

The printer driver is a software component that controls, through user-specified options, common printing features when sending print jobs to the MFP. Changes to printer-driver settings can be

temporary for print jobs that are run while the program is still open, or changes to the default settings can be permanent; they are in effect now and in the future.

Operating System	Temporarily change settings for jobs that are printed now	Permanently change default settings <sup>1</sup>	Change configuration settings  (For example, to add an optional tray or to enable or disable a driver feature such as “Allow manual duplexing”)
Windows 2000 and XP (Classic Start Menu)	On the <b>File</b> menu, click <b>Print</b> , select this printer, then click <b>Properties</b> or <b>Preferences</b> . (The actual steps can vary; this is the most common method.)	Click <b>Start</b> , point to <b>Settings</b> , then click <b>Printers</b> or <b>Printers and Faxes</b> . Right-click the printer icon, then click <b>Printing Preferences</b> .	Click <b>Start</b> , point to <b>Settings</b> , then click <b>Printers</b> or <b>Printers and Faxes</b> . Right-click the printer icon, then click <b>Properties</b> . Click the <b>Configure</b> tab.
Windows XP	On the <b>File</b> menu, click <b>Print</b> , select this printer, then click <b>Properties</b> or <b>Preferences</b> . (The actual steps can vary; this is the most common method.)	Click <b>Start</b> , click <b>Printers and Faxes</b> , right-click the printer name or icon, then click <b>Printing Preferences</b> .	Click <b>Start</b> then click <b>Printers and Faxes</b> . Right-click the printer icon, then click <b>Properties</b> . Click the <b>Configure</b> tab.

<sup>1</sup> Access to default MFP settings might be restricted and therefore unavailable.

## Special media for printing


This MFP supports printing on special media.

For tray, media orientation, and driver settings, see [Print on special media](#).

For instructions on loading envelopes, see [Load tray 1 \(single-sheet feed tray\)](#) or [Load tray 2](#).

### Envelopes

- Store envelopes flat.
- Envelopes should not be wrinkled, nicked, stuck together, or otherwise damaged. Do not use envelopes that have clasps, snaps, windows, coated linings, self-stick adhesives, or other synthetic materials.
- Only use envelopes where the seam extends all the way to the corner of the envelope as indicated in the following illustration.



1	Acceptable
2	Unacceptable

- Envelopes with a peel-off adhesive strip or with more than one flap that folds over to seal must use adhesives that are compatible with the heat and pressure in the fuser.



---

**CAUTION** Failure to follow the guidelines above can result in jams.

---

## Labels

When selecting labels, consider the quality of each component:

- For tray, media orientation, and driver settings, see [Print on special media](#).
- Only use labels with no exposed backing between them.
- Labels must lie flat.
- Do not use labels that have wrinkles, bubbles, or are damaged.
- Use only full sheets of labels; this MFP does not support print partial sheets of labels.
- Use only labels specified for use with HP Color LaserJet printers.

For instructions on loading labels, see [Load tray 1 \(single-sheet feed tray\)](#) or [Load tray 2](#).

## Transparencies

- Use only tray 1 or tray 2 to print on transparencies.
- For tray, media orientation, and driver settings, see [Print on special media](#).
- Place transparencies on a flat surface after removing from the MFP.
- Use only transparencies specified for use with HP Color LaserJet printers.



---

**CAUTION** To avoid MFP damage, only use transparencies that are recommended for use in laser MFPs. See [Accessories and supplies information](#).

---

Transparent print media not designed for LaserJet printing melts in the fuser, and damages the fuser.

---

## Glossy paper and photo paper

- Handle glossy paper and HP LaserJet Photo paper by the edges.
- For tray, media orientation, and driver settings, see [Print on special media](#).
- Use only glossy paper and photo paper specified for use with HP Color LaserJet printers.

## Letterhead or preprinted forms

- Avoid using raised or embossed letterhead.
- Use only non-flammable inks that do not damage the print rollers.
- For tray, media orientation, and driver settings, see [Print on special media](#).

For instructions on loading letterhead, see [Load tray 1 \(single-sheet feed tray\)](#) and [Load tray 2](#).

## Heavy paper

- Do not use paper that is heavier than the recommended media specification for this MFP. See [Media supported on this MFP](#) for more information.
- For tray, media orientation, and driver settings, see [Print on special media](#).

# Copy and Scan: How do I?

Use this section to answer copy and scanning questions.

## Scan from the device control panel

Use the following instructions to scan directly from the device control panel.



**NOTE** The computer connected to the device must be turned on.

## Program the device **Scan To** button from the control panel

E-mail addresses and folders must be set up prior to using the **Scan To** button on the control panel. Use HP Solutions Center to program the e-mail and folders for scanning.

### Set up pre-configured destinations on the MFP

1. Open HP Solution Center and select **Settings, Scan Settings**, then press **Scan**.
2. Select the checkbox **Allow me to scan by pressing the scan-to button on the MFP**.
3. The MFP is pre-configured with the following three destinations in the dialog box.
  - Scan a document and attach it to an e-mail
  - Scan a photo and attach it to an e-mail
  - Scan a photo and save it as a file
4. Highlight a destination and click **Right arrow** to move to the destinations currently on the MFP dialog box. Repeat for all three destinations.
5. Click **Update**.

### Add folder destinations

1. Open HP Solution Center and select **Settings, Scan Settings**, then press **Scan**.
2. Select the checkbox **Allow me to scan by pressing the scan-to button on the MFP** and click on **New**.
3. Select **Save it to my computer**, then click **Next**.
4. Enter the file destination name or check to set up the destination on the MFP. Name the default destination and click **Next**.
5. Select the quality and click **Next**.
6. Verify the selections, click **Save**, and then close HP Solution Center.

### Add e-mail destinations

1. Open HP Solution Center and select **Settings, Scan Settings**, then press **Scan**.
2. Select the checkbox **Allow me to scan by pressing the scan-to button on the MFP** and click on **New**.

On the device control panel, press **Scan To**.



3. Select **Attach to a new e-mail** and click **Next**.
4. Select **Save it to my computer** and press **Next**. Type the e-mail address, subject, and note in the text box and click **Next**.
5. Select the quality and click **Next**.
6. Type the e-mail address in the text box. Select the box for **Send the new destination to the MFP**. Type a new name that appears on the MFP control panel and click **Next**.

### Delete destinations

1. From the **Set up the <Scan To> list for the All-in-One**, select one of the **Available Destinations on this PC** and click **Delete**. The **Delete Destination** dialog box displays.
2. From the **Delete Destination** dialog box, highlight the destination to delete and click **Next**. The **Confirmation** dialog box displays.
3. Click **Delete** to perform the deletion, or click **Cancel** to choose another destination.

### Set the MFP to make only black and white copies

1. Press **Menu**, select **Copy setup**, and click on **Start Copy Color**.
2. Press the navigation arrows and select **On** or **Off**. When set to **Off**, the control panel displays **Restrict color** if **Start Copy Black** or **Start Copy Color** is pressed.
3. Press **OK**.

# Photo: How do I? (HP Color LaserJet CM1017 MFP only)

Use this section to answer photo questions.

## Print photos directly from the memory card

1. After inserting the memory card into the MFP (see [Insert a memory card](#)), select photos by:

- Press the **Left arrow** or the **Right arrow** to scroll through the images.
- Press **OK** to select or deselect the images.

2. You can also press **Select Photos** from the control panel.

Press **Up arrow** or **Down arrow** to select one of the following menu items, and then press **OK**.

- **From display:** Select this option if the memory card was not recently inserted.
- **All photos:** *X* represents the number of JPEG files the MFP detects on the card. Selecting this option prints all of the JPEG files on the memory card. Press **OK** again to confirm the print job.
- **Individual:** Select this option to choose and print an individual photo. The photos are numbered, starting with number 1.
  - Press **Up arrow** or **Down arrow** to increase or decrease the photo number.
  - Press **OK** to select the photo to print.
- **From a range:** Select this option to choose a range of photos to print. The MFP prompts for the first photo number and the last photo number.
  - Press **Up arrow** or **Down arrow** to increase or decrease the photo numbers.
  - Press **OK** to select the range of photos to print.

3. Press **Start Photo** to print the photos.



---

**NOTE** The JPEG files on the memory card are numbered in alphabetical order. If you do not know the order of the photos on the memory card, print an index that shows the photo order. For more information about printing an index, see [Print a memory card index](#).

---

## Enable or disable a memory card

1. In the embedded Web server, select **Print** and **Memory Card**.

2. Select or deselect the label **Enable Memory Card**. When this box is not selected the control panel display says **Memory card slots are disabled** when a memory card is inserted.

## Print and scan photos from a proof sheet

Preview images and print photos from a proof sheet. A proof sheet can contain as many as 20 images. This feature has been optimized and tested for use with Genuine HP Toner Supplies.

1. Insert the memory card into the device. See [Insert a memory card](#).
2. Press **Proofsheet** then **Print**.

3. If more than 20 JPEG files exist on the memory card, press **Up arrow** or **Down arrow** to select one of the following menu items, then press **OK**.
  - **All photos**: X represents the number of JPEG files the MFP detects on the card. Selecting this option prints all JPEG files on the memory card. Press **OK** again to confirm the print job.
  - **Last 20**: Prints the last 20 JPEG files from the alphabetized list on the memory card.
  - **Custom**: Select one or more photos to print by pressing **OK**.
4. Color in the oval or bubble using a dark blue or black pen. Also fill bubbles to indicate the image layout and media type.
5. Place the proof sheet face-down on the flatbed scanner, with the upper-left corner of the document located in the lower-right corner of the glass.
6. Press **Proofsheet**.
7. Press the **Up arrow** or **Down arrow**, select **Start Scan**, then press **OK**. The MFP scans the proof sheet and prints the marked photos. Repeat steps 5 through 7 for each proof sheet.



---

**NOTE** Photos printed using a proofsheets can only be printed in color.

**NOTE** JPEG files on the memory card are displayed in alphabetical order. When the order of photos on the memory card is unknown, print an index. See [Print a memory card index](#).

**NOTE** Photos are still printed in color even when the Color copy option is set to no.

---

## Save photos to the workstation from a memory card

1. Insert the memory card into the MFP. See [Insert a memory card](#).
2. From the workstation, click on **My Computer** and look for the removable drive (memory card). If **My Computer** does not recognize the memory card, enter a IP address (an example, \\192.168.0.15) into the address line. Access the images by clicking **Memory card** and moving to the subfolders containing the images. Map the memory card to a driver letter on the workstation using this method.
3. Use drag and drop or HP Photosmart Transfer to move the photos from the memory card to a folder.

# Network: How do I? (HP Color LaserJet CM1017 MFP only)

Use this section to answer network questions.

## Find the network IP address

The network IP address is located on the Network report page. To print a Network report page from the control panel:

1. On the control panel, press **Menu**.
2. Press **Left arrow** or **Right arrow** to select the **Reports** menu.
3. Press **OK**.
4. Press **Left arrow** or **Right arrow** to select **Network report**.
5. Press **OK** to print the Network Configuration Report page.

## Restore the network defaults

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select **Network config**.
3. Press the navigation arrows to select **Restore defaults**.
4. Press **OK**.

# Maintenance: How do I?

Use this section to answer MFP maintenance questions.

## Set the system password

Use HP ToolboxFX to set a system password.

1. Open HP ToolboxFX and click **System Settings**.



---

**NOTE** If a password has been set for the MFP previously, you are prompted to type the password. Type the password, then click **Apply**.

---

2. Click **Password**.
3. In the **Password** box, type the exact password to set, then in the **Confirm password** box, type the same password again to confirm the choice.
4. Click **Apply** to save the password.

### To remove the system password

1. Open HP ToolboxFX and click **System Settings**.



---

**NOTE** If a password has been set for the MFP previously, you are prompted to type the password. Type the password, then click **Apply**.

---

2. Click **Password**.
3. Delete all characters from both the **Password** field and the **Confirm password** field.
4. Click **Apply** to remove the password.

### To reset all MFP settings to factory defaults

If you forget or lose your password, use the following steps to reset all your MFP settings to factory defaults.



---

**WARNING!** Following these steps will clear the password and all of the changes you have made to the MFP settings.


---

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select the **Service** menu.
3. Press **OK**.
4. Press the navigation arrows to select the **Restore defaults** menu.
5. Press **OK**.
6. Press **OK** again to confirm restoring the defaults.

## Clean the scanner glass

Dirty glass from debris may cause scan and copy image defects.

1. Turn device off, unplug the power cord from the electrical socket, and raise the lid.
2. Clean the glass by using a soft lint-free cloth that has been moistened with nonabrasive glass cleaner.



**CAUTION** Do not use abrasives, acetone, benzene, ammonia, ethyl alcohol, or carbon tetrachloride on any part of the device; these can damage the device. Do not place liquids directly on the glass. They might seep under it and damage the device.

3. To prevent spotting, dry the glass using a soft lint-free cloth.

## Change MFP toner warnings

Supplies gauges display consumption levels of print cartridges. The display appears when the MFP shows the Ready state with no warnings, or when the MFP shows a warning or error message pertaining to a print cartridge or multiple supplies. When the supply is empty the gauge displays as empty. Flashing indicates a single supply is empty. These messages can display when:

- Missing cartridge
- Incorrectly placed cartridges
- Cartridges with an error
- Some non-HP cartridges

## Calibrate the MFP

The MFP automatically self-calibrates, but calibration settings can be manually adjusted by using the HP ToolboxFX.

Environmental differences or aging print cartridges might cause fluctuations in image density. The MFP accounts for this with image stabilization control. The MFP automatically calibrates at various times to maintain the highest level of print quality. Also request a calibration by using the HP ToolboxFX.

The MFP does not interrupt a print job to calibrate. It waits until the job is complete before calibrating or cleaning. While the MFP is calibrating, it pauses printing for the time that is required to complete the calibration.



**NOTE** This calibration process calibrates the printer. It does not calibrate the image scanner.

## Calibrate the MFP from the front control panel


1. Press **Menu**.
2. Press the navigation arrows until the display reads **System setup**. Press **OK**.
3. Press the navigation arrows until the display reads **Print quality**. Press **OK**.
4. Press the navigation arrows until the display reads **Calibrate color**. Press **OK**.
5. Press the navigation arrows until the display reads **Calibrate now**. Press **OK**.
6. Press **OK** to confirm **Calibrate now**.

## Calibrate the MFP from the HP ToolboxFX

1. Open the HP ToolboxFX in one of these ways:
  - On the desktop, double-click the **HP ToolboxFX** icon.
  - On the Windows **Start** menu, click **Programs (All Programs in Windows XP)**, click **HP**, click **HP Color LaserJet CM1015/CM1017 Series**, click **HP ToolboxFX**, then click **Help**.
2. Click the **System Settings** tab then click **Print Quality**.
3. In the Calibration section, click **Calibrate**.

## Clean the MFP

During the printing process, paper, toner and dust particles can accumulate inside the MFP. Over time, this buildup can cause print-quality problems such as toner specks or smearing. This MFP has a cleaning mode that can correct and prevent these types of problems.





## Clean the paper path using HP ToolboxFX



**NOTE** Use the following procedure to clean the paper path using the HP ToolboxFX. To clean the engine when the computer is running an operating system that does not support HP ToolboxFX, find \util\cleanpage on the MFP CD-ROM for instructions on the cleaning page.

1. Ensure the MFP is turned on and in the Ready state.
2. Open the HP ToolboxFX.
3. On the **Help** tab, click **Troubleshooting**. Follow the instructions under the Cleaning Page section.



# 13 Managing and maintaining the multifunction peripheral (MFP)

This MFP includes several software tools that help monitor, troubleshoot problems, and maintain the MFP. Information about using these tools is in the following sections:

- [Information pages](#)
- [Menu map](#)
- [HP ToolboxFX](#)
- [Use the embedded Web server](#)
- [Manage supplies](#)
- [Clean the scanner glass](#)
- [Clean the MFP](#)
- [Cartridge-out override](#)
- [Change print cartridges](#)
- [Calibrate the MFP](#)

## Information pages

Special pages reside within the MFP memory. These pages help diagnose and solve MFP problems.

If the MFP language was not correctly set during installation, set the language manually so that the pages print in one of the supported languages. Change the language by using the HP ToolboxFX.

### Demo page



To print the Demo page, press **Scan To** and **Start Scan** simultaneously. A demo page can also be printed from the HP ToolboxFX.

### Configuration page

The Configuration page lists the current MFP settings and properties. Print a Configuration page from the MFP or the HP ToolboxFX.

#### To print the Configuration page from the control panel

1. Press **Menu**.
2. Use the navigation arrows to select the **Reports** menu.
3. Press **OK**.
4. Press **Left arrow** or **Right arrow** to select **Configuration report**.
5. Press **OK** to print the Configuration Report page.



- 1. Product Information.** Displays basic information about the MFP, such as the product name and the serial number.
- 2. Memory.** Lists memory-related information, such as the total memory that is installed.

3. **Paper Settings.** Lists information about the media type for each tray and about the type settings for all the media that the MFP supports.
4. **Copy Settings.** Lists current MFP default copy information.
5. **Product Settings.** Lists information about the MFP, including the language and the company name.
6. **Installed Personalities and Options.** Contains current MFP font, DIMM memory, and memory card information.
7. **Printer Settings.** Displays MFP printer settings, such as color options, copies, and jam recovery information.
8. **Status Log.** Displays information about MFP errors.
9. **Photo Settings.** Displays default photo information such as image size, number of copies, and output color.

## Supplies Status page

The Supplies Status page lists the remaining life of HP print cartridges. It also lists the estimated pages remaining, number of pages printed, and other supplies information. A Supplies Status page can be obtained from the MFP or the HP ToolboxFX.

### To print the Supplies Status page from the control panel


1. Press **Menu**.
2. Use the navigation arrows to select the **Reports** menu.
3. Press **OK**.
4. Use the navigation arrows to select **Supplies status page**.
5. Press **OK** to print the Supplies Status page.



---

**NOTE** Supplies information is also available through the HP ToolboxFX.

---




1. **Print cartridge area.** Displays a section for each of the print cartridges and provides information about HP print cartridges. This information includes the part number for each print cartridge, whether each print cartridge is low, and the life remaining for each print cartridge, which is expressed as a percentage, as a graphic, and as the estimated number of pages remaining. This information might not be provided for non-HP supplies. In some cases, if a non-HP supply is installed, an alert message displays instead.
2. **Ordering Information.** Displays basic information about how to order new HP supplies.
3. **Return & Recycling.** Displays a link to the Web site that contains information about recycling.

## Networking page (HP Color LaserJet CM1017 MFP only)

The Networking report option prints a Network configuration report.

### To print the Network configuration report from the control panel

1. Press **Menu**.
2. Press the navigation arrows to select the **Reports** menu.
3. Press **OK**.
4. Press the navigation arrows to select **Network report**.
5. Press **OK** to print the Network Configuration page.



1. **Network Hardware Configuration.** Displays current MFP hardware configuration such as status, hardware address, firmware datecode, link speed information, and connection timeout.
2. **Enabled Features.** Displays password, network protocol, memory card, LPD printing, Bonjour, and HPSLP settings.
3. **TCP/IP.** Displays host, domain, and printer name, and other IP information.
4. **SNMP.** Displays status, version, and set/get community names.
5. **Network Statistics.** Displays packet and collision information.

## Fonts pages

The Fonts pages provide lists of the available fonts on the MFP, including HP PostScript Level 3 fonts, PCL fonts, and PCL6 fonts.

### To print a fonts page from the control panel

1. Press **Menu**.
2. Use the navigation arrows to select the **Reports** menu.
3. Press **OK**.
4. Use the navigation arrows to select **PS font list**, or **PCL font list**.
5. Press **OK** to print the selected Fonts page.

## Usage page

The Usage Page provides information on the number and types of pages printed by the MFP.

Print the usage page by:

1. Press **Menu**.
2. Press the navigation arrows to select the **Reports** menu.
3. Press **OK**.
4. Press the navigation arrows to select the **Usage page**.
5. Press **OK** to print the Usage Page.

## Menu map

The menu map lists the menu structure for each option available on the control panel.

### To print a menu map

1. Press **Menu**.
2. Use the navigation arrows to select the **Reports** menu.
3. Press **OK**.
4. Use the navigation arrows to select **Menu structure**.
5. Press **OK** to print the Menu map.



# HP ToolboxFX

HP ToolboxFX is a software program that performs these tasks:

- Checks the MFP status.
- Configures the MFP settings.
- Displays problem solving information.
- Displays online documentation.

View the HP ToolboxFX when the MFP is directly connected to the computer or when it is connected to the network. Perform a software installation using the HP ToolboxFX.



---

**NOTE** HP ToolboxFX is not supported for Windows Server 2003 or Macintosh operating systems.

**NOTE** Internet access is not required to open and use the HP ToolboxFX.

---

## View HP ToolboxFX

Open HP ToolboxFX in one of these ways:

- In the Windows program group entry and the system tray icon, double-click HP ToolboxFX icon.
- On the Windows **Start** menu, click **Programs** (or **All Programs** in Windows XP), click **HP**, then click **HP ToolboxFX**.

The HP ToolboxFX software contains the following sections:

- [Status](#)
- [Alerts](#)
- [Help](#)
- [System Settings](#)
- [Print Settings](#)
- [Network settings](#)

## Status

The HP ToolboxFX **Status** folder contains links to the following main pages:

- **Device Status:** View MFP status information. This page indicates MFP conditions such as a jam or an empty tray. When a problem is corrected with the MFP, click **Refresh** button to update the MFP status.
- **Supplies Status Page:** View detailed supplies status such as the estimated percent of toner remaining in the print cartridge and the number of pages that have been printed with the current print cartridge. This page also has links to order supplies and to find recycling information.
- **Device Configuration:** View a detailed description of the current MFP configuration, including the amount of memory installed and whether optional trays are installed.
- **Network configuration:** View a detailed description of the current network configuration, including the IP address and network status.
- **Print Info Pages:** Print the Configuration page and various other information pages that are available for the MFP, such as the Supplies Status page and the Demo page.
- **Event Log:** View a history of MFP errors. The most recent error is at the top of the list.

## Event log

The Event log is a four-column table where the MFP events are logged for reference. The log contains codes that correspond to the error messages that appears on the MFP control-panel display. The number in the Page Count column specifies the total number of pages that the MFP had printed when the error occurred. The Event log also contains a brief description of the error. For more information about error messages, see [Control-panel messages](#).

## Alerts

The HP ToolboxFX **Alerts** folder contains links to the following main pages:

- **Set Up Status Alerts:** Set up the MFP to send pop-up alerts for certain events, such as low toner levels.
- **Set Up Email Alerts:** Set up the MFP to send e-mail alert messages for certain events, such as low toner levels.

### Set up status alerts

Use the HP ToolboxFX to set up the MFP so that it issues pop-up alerts to the computer when certain events occur. Events that trigger alerts include jams, low levels of toner in HP print cartridges, non-HP print cartridge in use, empty input trays, and specific error messages.

Select the pop-up format, the system tray icon format, the desktop format, or all three for the alerts. The pop-up alerts only appear when the MFP is printing from the computer on which you set up the alerts.



---

**NOTE** Click **Apply** to make the changes take effect.

---

### Set up e-mail alerts

Use HP ToolboxFX to configure a maximum of two e-mail addresses to receive alerts when certain events occur. It is possible to specify different events for each e-mail address. Enter the information for the e-mail server that will send out the e-mail alert messages for the MFP.



---

**NOTE** Click **Apply** to make the changes take effect.

---

## Help

The HP ToolboxFX **Help** folder contains links to the following main pages:

- **Troubleshooting:** Print troubleshooting pages, clean the MFP, and display Microsoft Office Basic Colors. For more information on Microsoft Office Basic colors, see [Match colors](#).
- **How Do I:** View the How Do I? Help.
- **Animated Demonstrations**
- **User Guide:** View information about the MFP usage, warranty, specifications, and support. The user guide is available in both HTML and PDF format.

# System Settings

The HP ToolboxFX **System Settings** folder contains links to the following main pages:

- **Device information.** View information about the MFP, such as the description and a contact person.
- **Paper handling.** Change the MFP paper-handling settings, such as default paper size and default paper type.
- **Print quality.** Change the MFP print-quality settings.
- **Print density.** Change the print density settings, such as contrast, highlights, midtones, and shadows.
- **Paper types.** Change the MFP mode settings for each media type, such as letterhead, prepunched, or glossy paper.
- **System Setup.** Change the MFP system settings, such as MFP language and jam recovery.
- **Service.** Gain access to various procedures required to maintain the MFP.
- **Device Polling.** The HP ToolboxFX periodically communicates with your device to determine device status and enabled features.
- **Save and restore settings.** Save the current MFP settings to a file on the computer. Use this file to load the same settings onto another printer or MFP to restore these settings to this MFP at a later time.
- **Password.** If set, the password must be entered to change any of the HP ToolboxFX system settings, email alerts, or network settings.

## Device information

Save the HP ToolboxFX Device information for future reference about the MFP. The information that is typed in these fields appears on the Configuration page. It is possible to type any character in each of these fields.



---

**NOTE** Click **Apply** to make the changes take effect.

---

## Paper handling

Use the HP ToolboxFX paper-handling options to configure the default settings. These are the same options that are available on the **System setup** and **Paper setup** menus on the control panel. For more information, see [Control-panel menus](#).

Three options accommodate handling print jobs when the product is out of media:

- Select **Wait for paper to be loaded**.
- Select **Cancel** from the **Paper out action** drop-down list to cancel the print job.
- Select **Override** from the **Paper out time** drop-down list to send the print job to another paper tray.

The **Paper out time** field specifies how long the MFP waits before acting on your selections. It is possible to specify from 0 to 3600 seconds.



**NOTE** Click **Apply** to make the changes take effect.

## Print quality

Use the HP ToolboxFX print-quality options to improve the print job appearance. These same options are available on the **System setup** and **Print quality** menu on the control panel. For more information, see [Control-panel menus](#).

These options control print quality.

- Color Calibration.
  - Power On Calibration
  - Calibration Timing
  - Calibrate Now
- Grayscale Printing.

Grayscale printing options	Description
<b>Resolution</b>	Select 600 resolution for average print jobs and Fast Res 1200 for higher-quality print jobs. Select ProRes 1200 for the highest-quality print job, but a longer printing time.
<b>REt</b>	Choose REt which HP provides for improved print quality.



**NOTE** Click **Apply** to make the changes take effect.

## Print density

The print density settings control making fine adjustments to the density (amount) of Cyan, Magenta, Yellow, and Black toner in images, pages, and documents.

Print density settings	Description
<b>Contrasts</b>	Contrast is the density difference between light (highlight) and dark (shadow) colors. To increase the difference between light and dark colors (equivalent to a negative highlight adjustment

Print density settings	Description
	and a positive shadow adjustment), use a positive contrast setting. To decrease the difference between light and dark colors (equivalent to a positive highlight adjustment and a negative shadow adjustment), use a negative contrast setting.
<b>Highlights</b>	Highlight colors are colors near white. To make highlight colors darker, use a positive highlight setting, and to make highlight colors lighter use a negative highlight setting. This adjustment does not affect midtone or shadow colors.
<b>Midtones</b>	Midtone colors are about halfway between white and solid density. To make midtone colors darker, use a positive midtone setting, and to make midtone colors lighter use a negative highlight setting. This adjustment does not affect highlight or shadow colors.
<b>Shadows</b>	Shadow colors are colors near solid density. To make shadow colors darker, use a positive shadow setting, and to make shadow colors lighter use a negative shadow setting. This adjustment does not affect highlight or midtone colors.

## Set the system password

Use HP ToolboxFX to set a system password.

1. Open HP ToolboxFX and click **System Settings**.



**NOTE** If a password has been set for the MFP previously, you are prompted to type the password. Type the password, then click **Apply**.

2. Click **Password**.
3. In the **Password** box, type the exact password to set, then in the **Confirm password** box, type the same password again to confirm the choice.
4. Click **Apply** to save the password.

### To remove the system password

1. Open HP ToolboxFX and click **System Settings**.



**NOTE** If a password has been set for the MFP previously, you are prompted to type the password. Type the password, then click **Apply**.

2. Click **Password**.
3. Delete all characters from both the **Password** field and the **Confirm password** field.
4. Click **Apply** to remove the password.

### To reset all MFP settings to factory defaults

If you forget or lose your password, use the following steps to reset all your MFP settings to factory defaults.



---

**WARNING!** Following these steps will clear the password and all of the changes you have made to the MFP settings.

---

1. On the control panel, press **Menu**.
2. Press the navigation arrows to select the **Service** menu.
3. Press **OK**.
4. Press the navigation arrows to select the **Restore defaults** menu.
5. Press **OK**.
6. Press **OK** again to confirm restoring the defaults.

## Paper types

Use these HP ToolboxFX **Paper types** options to configure print modes that correspond to the various media types. When selecting **Restore modes**, all of the modes are reset to the factory settings.



---

**NOTE** Click **Apply** to make the changes take effect.

---

## System setup

Use the HP ToolboxFX system settings options to configure miscellaneous print settings. These settings are not available from the control panel.



---

**NOTE** Click **Apply** to make the changes take effect.

---

## Service

During the printing process, paper, toner, and dust particles can accumulate inside the MFP. Over time, this buildup can cause print-quality problems such as toner specks or smearing. HP ToolboxFX provides an easy method for cleaning the paper path. For more information, see [Clean the paper path using HP ToolboxFX](#).

## Device Polling Page

The HP ToolboxFX periodically communicates with your device to determine device status and enabled features. Use the Polling Page to turn off pop-up alerts and the **Scan To** and **Start Scan** buttons located on the device.

## Print Settings

The HP ToolboxFX Print Settings folder contains links to the following main pages:

### Printing

Use the HP ToolboxFX printing settings options to configure the settings for all print functions. These are the same options that are available on the **Print settings** menu on the control panel. For more information, see [Control-panel menus](#).



---

**NOTE** Click **Apply** to make the changes take effect.

---

## PCL5c

Configure these PCL5c settings:

- Font number
- Font pitch
- Font point size
- Symbol set
- Append CR to LF
- Form length

## PostScript

Use the PostScript option when using the PostScript print personality. When the **Print PostScript error** option is turned on, the PostScript error page automatically prints when PostScript errors occur.



---

**NOTE** Click **Apply** to make the changes take effect.

---

## Memory card (HP Color LaserJet CM1017 MFP only)

Use the three HP ToolboxFX memory card options to configure print settings when using memory cards.

- **Photo image size.** Select the size photos to print from the drop-down list.
- **Photo number of copies.** Type the number of copies from 0 to 99 to print for each image.
- **Photo output color.** Select either **Color** or **Monochrome** from the drop-down list.

Click the **Enable memory cards** checkbox to save the settings.

## Network settings

The network administrator can use the HP ToolboxFX **Network Settings Tab** folder to control the network-related MFP settings when it is connected to an IP-based network.

The settings are:

- IP Configuration
- Advanced
- SNMP
- Network Configuration



## Use the embedded Web server

When the MFP is directly connected to a computer, use the HP ToolboxFX to view Web pages for the MFP status.

When the MFP is connected to the network, the embedded Web server is automatically available. Access the embedded Web server from any supported browser.

The embedded Web server displays MFP and network status and manages printing functions from the computer instead of using the control panel. Below are examples of embedded Web server functions:

- View MFP status information.
- Set the type of paper loaded in each tray.
- Determine the remaining life on all supplies and order new ones.
- View and change tray configurations.
- View and change MFP settings.
- View and print internal information pages.
- View and change network configuration.

The embedded Web server supports these browsers for Windows:

Windows	Macintosh
Microsoft Internet Explorer 6.0 and later	Safari 1.2 or later
Netscape 7.0 or later	Netscape 7.0 or later
Opera 7.0 or later	Opera 7.0 or later
Firefox 1.0 or later	Firefox 1.0 or later
Mozilla 1.6 or later	Mozilla 1.6 or later

The embedded Web server works when the MFP is connected to an IP-based network. The embedded Web server does not support IPX-based or AppleTalk MFP connections. Internet access is not required to open and use the embedded Web server.

### Access the embedded Web server using a network connection

Using a supported Web browser, type the IP address for the MFP in the address/URL field. (To find the IP address, print a configuration page. For more information about printing a configuration page, see [Configuration page](#).)



**NOTE** If there is no access to the embedded Web server using the IP address, try using the host name.

**NOTE** Once the URL is open, bookmark it for easy return.

---

1. The embedded Web server has three tabs that contain MFP settings and information:
  - **Information** tab
  - **Settings** tab
  - **Networking** tab
2. Click the appropriate tab.

## Information tab

The **Information** pages group consists of the following pages.

- **Device Status:** Displays MFP status and shows the remaining life of HP supplies. Zero percent (0%) indicates that a supply is empty. The page also displays the type and size of print media set for each tray.
- **Configuration:** Displays the network and product information found on the MFP Configuration page, such as page counts, print settings, and paper options.
- **Supplies Status:** Displays the remaining life of HP supplies. Zero percent (0%) indicates that a supply is empty. This page also displays supplies part numbers. To order new supplies, click **Order Supplies** in the **Other Links** area on the left side of the window. Internet access is required to visit any Web site.
- **Print Info Pages:** Provides a remote way to print an internal page for a MFP.

## Settings tab

This tab allows MFP configuration from a computer. The **Settings** tab can be password protected. If this MFP is networked, always consult with the MFP administrator before changing settings on this tab.

The **Settings** tab contains these pages

- **Paper Handling:** Configure paper handling settings from this page.
- **Printing:** Configure the IO Timeout from this page.
- **Print Quality:** Configure color calibration and optimize settings.
- **Print Density:** Configure print density settings including contrast, highlights, midtones, and shadows.
- **Paper Type Settings:** Configure paper types
- **Print Modes:** Configure print mode settings.
- **System Setup:** Sets up system settings, including jam recovery, auto continue, display contrast, and MFP language.
- **Service:** Starts the cleaning mode and restores factory settings.
- **Password:** Sets or changes the administrator password.

## Networking tab

This tab allows the network administrator to control MFP network-related settings when it is connected to an IP-based network.

- **IP Configuration:** Sets the IP configuration.
- **Advanced:** Enables network features such as SLP Config, DHCP, BOOTP, and AutoIP.
- **mDNS:** Sets the mDNS. These settings to turn on or off Rendezvous or Bonjour discovery.
- **SNMP:** Sets SNMP protocols.

## Other links found in HP ToolboxFX

Internet access is required to use any of these links. When using a dial-up connection and a connection to the embedded web server was not first opened, connect to the embedded Web server before visiting these Web sites. Connecting might require closing and reopening the embedded Web server.

- **HP Instant Support™:** Connects to the HP Web site to help find solutions. This service analyzes the MFP error log and configuration information to provide diagnostic and support information specific to the MFP.
- **Product Registration:** Click to connect with the HP Web site to register the product.
- **Order Supplies:** Click to connect with the HP Web site and order genuine HP supplies, such as print cartridges and paper.
- **Product Support:** Connects to the support site for the HP Color LaserJet CM1015/CM1017 MFP to search for help regarding general topics.

# Manage supplies

For warranty information about these supplies, see [Print Cartridge Limited Warranty Statement](#).

## Supplies life

The life of a print cartridge depends on the amount of toner that print jobs require. When printing text at approximately 5% coverage, a cyan, magenta, or yellow print cartridge for the HP Color LaserJet CM1015/CM1017 MFP lasts an average of 2,000 pages, and a black print cartridge lasts an average of 2,500 pages. A typical business letter has 5% coverage.

## Check and order supplies

Check the supplies status from the control panel by printing a Supplies Status page, or viewing the HP ToolboxFX; Hewlett-Packard recommends placing an order for a replacement print cartridge when the Low message for a print cartridge first displays. For typical use, the Order message indicates that approximately two weeks of life remains. When using a new, authentic HP print cartridge, it is possible to obtain the following types of supplies information:

- Amount of cartridge remaining
- Estimated number of pages remaining
- Number of pages printed
- Other supplies information



---

**NOTE** If the MFP is connected to the network, it is possible to set the HP ToolboxFX to send e-mail notification when a print cartridge is low or is near the end of its useful life. If the MFP is directly connected to a computer, set the HP ToolboxFX to notify you when supplies are low.

---

## Check supply status and order using the control panel

Do one of the following:

- Check the supplies status gauges on the control panel. These gauges indicate when a print cartridge is low or empty. The “?” also indicates when a non-HP print cartridge is first installed.
- To print the Supplies Status page from the MFP, select **Reports Menu**, then **Supplies Status**. See [Supplies Status page](#) for more information.

If the supplies levels are low, reorder supplies through the local HP dealer, by telephone, or online. See [Accessories and supplies information](#) for part numbers. See <http://www.hp.com/go/ljsupplies> to order online.

## Check and order supplies using HP ToolboxFX

Configure the HP ToolboxFX to send an alert when the supplies are low. Receive alerts as an e-mail, a pop-up message, or a taskbar icon. Order supplies from the HP ToolboxFX by choosing from the **Other Links** area, and clicking **Order supplies**. Internet access is required to connect to the web site.

For more information, see [HP ToolboxFX](#).

## Check and order supplies using HP Solution Center

In HP Solution Center, select the MFP. The device status page shows supplies information. To order use the HP ToolboxFX.

## Supplies Storage Guidelines

Follow these guidelines for storing print cartridges:

- Do not remove the print cartridge from its package until it is ready for use.



---

**CAUTION** To prevent damage, do not expose the print cartridge to light for more than a few minutes.

---

- See [Table C-5 Environmental specifications](#) for operating and storage temperature ranges.
- Store the supply in a horizontal position.
- Store the supply in a dark, dry location away from heat and magnetic sources.

## Replace and recycle supplies

When installing a new HP print cartridge, follow the instructions included on the new supply's box, or see the *Getting Started Guide*.

When recycling supplies:

- Place the used supply in the box in which the new supply arrived
- Complete the enclosed return label
- Send the used supply to HP for recycling

For complete information, see the recycling guide included with each new HP supply item. See [HP LaserJet printing supplies](#) for more information about HP's recycling program.

## HP policy on non-HP supplies

Hewlett-Packard Company cannot recommend the use of non-HP supplies, either new or remanufactured. When they are not HP products, HP cannot influence the product design or quality. Service or repair required as a result of using a non-HP supply is *not* covered under the MFP warranty.

When inserting a supply into the MFP, the MFP displays whether or not the supply is a genuine HP supply. When a genuine HP is inserted and that supply has reached the low state from another HP MFP, the MFP identifies the supply as non-HP. Simply return the supply to the original MFP to reactivate HP features and functionality.

## Reset the MFP for non-HP supplies

When a non-HP print cartridge is installed, a question mark appears in the displays above the cartridge that is non-HP. To print with this supply press **OK** the first time this non-HP supply is installed. The status gauges do not indicate when this type of supply is low or empty.



---

**CAUTION** The MFP may not stop printing with non-HP supplies. MFP damage can occur if the MFP prints with an empty print cartridge. See [Hewlett-Packard limited warranty statement](#) and [Print Cartridge Limited Warranty Statement](#).

---


## HP anti-counterfeit supplies Web site

Visit the HP anti-counterfeit supplies Web site at <http://www.hp.com/go/anticounterfeit> if the supplies status gauges or HP ToolboxFX indicates that the print cartridge is not an HP print cartridge and you think that it is genuine.

## Clean the scanner glass

Dirty glass from debris may cause scan and copy image defects.

1. Turn device off, unplug the power cord from the electrical socket, and raise the lid.
2. Clean the glass by using a soft lint-free cloth that has been moistened with nonabrasive glass cleaner.



---


**CAUTION** Do not use abrasives, acetone, benzene, ammonia, ethyl alcohol, or carbon tetrachloride on any part of the device; these can damage the device. Do not place liquids directly on the glass. They might seep under it and damage the device.

---

3. To prevent spotting, dry the glass using a soft lint-free cloth.

## Clean the MFP

During the printing process, paper, toner and dust particles can accumulate inside the MFP. Over time, this buildup can cause print-quality problems such as toner specks or smearing. This MFP has a cleaning mode that can correct and prevent these types of problems.



### Clean the paper path using HP ToolboxFX



**NOTE** Use the following procedure to clean the paper path using the HP ToolboxFX. To clean the engine when the computer is running an operating system that does not support HP ToolboxFX, find \util\cleanpage on the MFP CD-ROM for instructions on the cleaning page.

1. Ensure the MFP is turned on and in the Ready state.
2. Open the HP ToolboxFX.
3. On the **Help** tab, click **Troubleshooting**. Follow the instructions under the Cleaning Page section.



# Cartridge-out override

The HP Color LaserJet CM1015/CM1017 MFP displays an **Order supplies** message when a cartridge is running low and a **Replace supplies** message when a cartridge has been depleted. **To ensure optimal print quality, HP recommends replacing a cartridge when the Replace supplies message is displayed.** Replacing the cartridge at this point can help prevent waste of media or other cartridges when one cartridge produces poor print quality.

The Cartridge-out override feature allows the MFP to continue to use a cartridge that has reached the recommended replacement point.



---

**WARNING!** Using override can result in unsatisfactory print quality and unavailability of certain features (such as toner remaining information).

**WARNING!** All print defects or supply failures incurred when an HP supply is used in override are not considered defects in materials or workmanship in the supply under HP's Print Cartridge Limited Warranty Statement. For Warranty information, see [Print Cartridge Limited Warranty Statement](#).

---

## Configuration

Cartridge-out override can only be enabled from the control-panel menu.

1. From the main menu, press the navigation arrows to choose **System setup** and press **OK**.
2. Press the navigation arrows to choose **Print quality** and press **OK**.
3. Press the navigation arrows to choose **Replace supplies** and press **OK**.
4. Press the navigation arrows to choose **Override out** and press **OK**.
5. Press **OK**.

If **Stop at out** is chosen, the MFP stops printing when a cartridge reaches the recommended replacement point. When **Override out** is selected, the MFP continues printing when a cartridge reaches the recommended replacement point. The factory default setting is **Stop at out**.

## On-going operation

Override can be enabled or disabled at any time, and does not have to be re-enabled for each cartridge. The MFP automatically continues printing when a cartridge reaches recommended replacement. The MFP displays the message **Replace supply. Override in use.** while a cartridge is used in Override mode. When the cartridge is replaced with a new supply, Override de-activates until another cartridge reaches recommended replacement.

## Change print cartridges

When a print cartridge approaches the end of useful life, the control panel displays a message recommending ordering a replacement. The MFP can continue to print using the current print cartridge until the control panel displays a message instructing cartridge replacement.

The MFP uses four colors and has a different print cartridge for each color: black (K), cyan (C), magenta (M), and yellow (Y).



---

**NOTE** In order to print, this MFP requires all print cartridges to be installed.

---


Replace the appropriate color print cartridge when the control panel displays one of the following messages:

- **Replace yellow cartridge**
- **Replace magenta cartridge**
- **Replace cyan cartridge**
- **Replace black cartridge**

The control panel display also indicates the color that should be replaced (unless a genuine HP cartridge is not currently installed).

### Change the print cartridge

1. Open the front door.




---


**CAUTION** Do not place anything on the transfer belt (ETB), which is located on the inside of the front door.

---

2. Remove the used print cartridge from the MFP.




3. Remove the new print cartridge from the bag. Place the used print cartridge in the bag for recycling.




4. Grasp both sides of the print cartridge by the blue handles and distribute the toner by gently rocking the print cartridge from side to side.


---

 **CAUTION** Do not touch the shutter or the surface of the roller.


---




5. Remove the shipping locks and the shipping tape from the new print cartridge. Discard the shipping tape and shipping locks according to local regulations.



6. Align the print cartridge with the tracks inside the MFP, and using the handles, insert the print cartridge until it is firmly seated.



7. Firmly close the front door.



After a short time, the control panel should display **Ready**.



**NOTE** If a cartridge is in the wrong slot or is the wrong type for the MFP, the control panel displays one of the following messages: **Incorrect yellow cartridge**, **Incorrect magenta cartridge**, **Incorrect cyan cartridge**, **Incorrect black cartridge**, or **Incorrect supplies**.

8. Installation is complete. Place the used print cartridge in the box in which the new cartridge arrived. See the enclosed recycling guide for recycling instructions.
9. When using a non-HP print cartridge, check the MFP control panel for further instructions.

For additional help, go to [http://www.hp.com/support/clj1015\\_1017](http://www.hp.com/support/clj1015_1017).



---

**NOTE** After replacing or changing a black print cartridge, a cleaning page automatically prints. This helps prevent speckles on the front or back of printed documents. For a more thorough cleaning, see [Clean the paper path using HP ToolboxFX](#).

---

# Calibrate the MFP

The MFP automatically self-calibrates, but calibration settings can be manually adjusted by using the HP ToolboxFX.

Environmental differences or aging print cartridges might cause fluctuations in image density. The MFP accounts for this with image stabilization control. The MFP automatically calibrates at various times to maintain the highest level of print quality. Also request a calibration by using the HP ToolboxFX.

The MFP does not interrupt a print job to calibrate. It waits until the job is complete before calibrating or cleaning. While the MFP is calibrating, it pauses printing for the time that is required to complete the calibration.



---

**NOTE** This calibration process calibrates the printer. It does not calibrate the image scanner.

---

## Calibrate the MFP from the front control panel

1. Press **Menu**.
2. Press the navigation arrows until the display reads **System setup**. Press **OK**.
3. Press the navigation arrows until the display reads **Print quality**. Press **OK**.
4. Press the navigation arrows until the display reads **Calibrate color**. Press **OK**.
5. Press the navigation arrows until the display reads **Calibrate now**. Press **OK**.
6. Press **OK** to confirm **Calibrate now**.

## Calibrate the MFP from the HP ToolboxFX

1. Open the HP ToolboxFX in one of these ways:
  - On the desktop, double-click the **HP ToolboxFX** icon.
  - On the Windows **Start** menu, click **Programs (All Programs** in Windows XP), click **HP**, click **HP Color LaserJet CM1015/CM1017 Series**, click **HP ToolboxFX**, then click **Help**.
2. Click the **System Settings** tab then click **Print Quality**.
3. In the Calibration section, click **Calibrate**.

# 14 Problem solving

- [Problem solving process](#)
- [Control-panel messages](#)
- [Solve print problems](#)
- [Resolve copy problems](#)
- [Resolve scanning problems](#)
- [The device control panel display has black lines or dots, or becomes blank](#)
- [Clear paper jams](#)
- [Additional problem solving tools](#)

# Problem solving process

Use the problem solving checklist to resolve MFP issues.

## Problem solving checklist

Follow these steps when trying to solve an MFP problem.

Step number	Verification step	Possible problems	Solutions
1	<p><b>Is the power on?</b></p> <p>When the MFP is connected to a grounded power source, the control panel shows <b>Hewlett-Packard</b> with both the Ready and Attention lights blinking. The control panel then displays <b>Initializing...</b> then <b>Ready</b>, at which time only the green light is on.</p>	No power due to failed power source, cable, switch, or fuse.	<ol style="list-style-type: none"> <li>1. Verify that the MFP is plugged in.</li> <li>2. Verify that the power cable is functional and that the power switch is on.</li> <li>3. Check the power source by plugging the MFP directly into the wall or into a different outlet.</li> <li>4. Test the outlet or connect another device to the outlet to verify that the outlet is functioning.</li> </ol>
2	<p><b>Does Ready appear in the control panel or screen?</b></p> <p>The control panel should function without error messages.</p>	Control panel shows an error.	<p>See <a href="#">Control-panel messages</a> for a list of common messages that can help correct the error.</p> <p>If the error persists, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>
3	<p><b>Do information pages print?</b></p> <p>Print a Configuration page.</p>	<p>Control panel displays an error message.</p> <hr/> <p>Media does not move smoothly through the MFP paper path.</p> <hr/> <p>Poor print quality.</p>	<p>See <a href="#">Control-panel messages</a> for a list of common messages that can help correct the error.</p> <hr/> <p>Clean the paper path.</p> <hr/> <p>See <a href="#">Print-quality problems</a>.</p> <p>If the error persists, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>
4	<p><b>Does the device copy?</b></p> <p>Place the Configuration page onto the flatbed glass and make a copy. Copies should print without print-quality problems.</p>	Poor copy quality from flatbed.	<ol style="list-style-type: none"> <li>1. If the print quality from the internal tests and the copy from the scanner were acceptable, clean the flatbed glass.</li> <li>2. If, after performing maintenance, the problem persists, see <a href="#">Resolve copy problems</a></li> </ol> <p>If the problem persists, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>



Step number	Verification step	Possible problems	Solutions
5	<p><b>Does the MFP print from the computer?</b></p> <p>Connect the network cable or USB cable to the MFP and the computer. Use a word-processing application to send a print job to the MFP.</p>	Software is not installed correctly or an error occurred during software installation.	Run the uninstall via the program group. Reinstall using the software CD.
		The cable is not connected correctly.	Reconnect the cable.
		An incorrect driver is selected.	Select the proper driver.
		Other devices are connected to the USB port.	Disconnect the other devices and try again to print.
		There is a port driver problem in Microsoft Windows.	Run the uninstall via the program group. Reinstall using the software CD.
		If the error persists, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.	
6	<p><b>Does the device scan to the computer?</b></p> <p>Initiate a scan from the desktop software on the workstation.</p>	The cable is not connected properly.	Reconnect the cable.
		Software is not installed correctly or an error occurred during software installation.	Run the uninstall via the program group. Reinstall using the software CD.
		<p>If the error persists, turn off the device, then turn the device on again.</p> <p>If the error still persists, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the device box.</p>	
7	<p><b>Does the MFP recognize and print from a memory card?</b></p> <p>Insert a memory card and print an index page.</p>	The MFP does not recognize the card.	Remove the card and reinsert it into the memory card slot. Verify that the card is fully inserted into the slot.
		<p>Verify that the memory card type is a supported type.</p> <p>Verify that only one card is inserted in the memory-card slots.</p>	
		The MFP does not print certain images.	Verify that the files on the memory card are in the correct format. The MFP recognizes only SRGB format JPEG files.

## Control-panel messages

The following are control-panel warning icons that may be seen on the HP Color LaserJet CM1017 MFP.




General error



Memory card error



Paper error



Paper jam



Attention



Scanner error

---

The majority of the control-panel messages are intended to guide the user through typical operation. The control-panel messages indicate the status of the current operation, and include a page count on the second line of the display, if appropriate. In addition, alert messages, warning messages, and critical error messages indicate situations that might require some action.

Alert and warning messages appear temporarily and might require the user to acknowledge the message by pressing **OK** to resume or by pressing **Cancel** to cancel the job. With certain warnings, the job might not complete or the print quality might be affected. If the alert or warning message is related to printing and the auto-continue feature is on, the MFP attempts to resume the printing job after the warning has appeared for 10 seconds without acknowledgement.


Critical error messages can indicate some kind of failure. Cycling the power might fix the problem. If a critical error persists, the MFP might require service.

Control panel message	Description	Recommended action
<b>10.000x Supply Error</b>	E-label cannot be read or print cartridge is not properly installed. 10.0000 = Black print cartridge 10.0001 = Cyan print cartridge 10.0002 = Magenta print cartridge 10.0003 = Yellow print cartridge	<ol style="list-style-type: none"> <li>1. Remove the print cartridge and verify that the E-label reader guide pin is not broken.</li> <li>2. Reinstall print cartridge.</li> <li>3. Turn on the printer.</li> <li>4. If the problem is not solved, replace the cartridge.</li> </ol>
<b>10.100x Supply Error</b>  <b>Reinstall</b>  The supplies gauge displays the consumption levels of print cartridges.	A print cartridge is missing.  10.1000 = Black print cartridge 10.1001 = Cyan print cartridge 10.1002 = Magenta print cartridge 10.1003 = Yellow print cartridge	Install the correct print cartridge.
<b>50.x Fuser Error</b>	The device has experienced an internal hardware error.  <b>50.1 Fuser Error</b> —low temperature  <b>50.3 Fuser Error</b> —slow fuser  <b>50.2 Fuser Error</b> —high temperature	<p>Turn off the power by using the power switch and if a surge protector is being used, remove it. Plug the device directly into the wall socket. Use the power switch to turn on the device.</p> <p>Turn off the device, wait at least 25 minutes, then turn on the device.</p> <p>If the error persists, contact HP customer support. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>
<b>51.20 Error</b>	The device has experienced an internal hardware error.  <b>51.20 Error</b> —black scanner error  <b>51.21 Error</b> —cyan scanner error  <b>51.22 Error</b> —magenta scanner error  <b>51.23 Error</b> —yellow scanner error	<p>Turn off the power by using the power switch, wait at least 30 seconds, then turn on the power and wait for the device to initialize.</p> <p>Turn off the power by using the power switch and if a surge protector is being used, remove it. Plug the device directly into the wall socket. Use the power switch to turn the device on.</p> <p>If the error persists, contact HP customer support. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>
<b>54.xx Error</b>	Toner sensor error.	Turn off the device, wait at least 30 seconds, then turn on the power and wait for the device to initialize. If the error persists, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the device box.
<b>55.0 Error</b>	DC controller error. The device has experienced an internal hardware error.	<p>Turn off the power by using the power switch, wait at least 30 seconds, then turn on the power and wait for the device to initialize.</p> <p>Turn off the power by using the power switch and if a surge protector is being used, remove it. Plug the device directly into the wall socket. Use the power switch to turn the device on.</p> <p>If the error persists, contact HP customer support. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>

Control panel message	Description	Recommended action
<b>57 Fan Error</b>  <b>Turn off then turn on</b>	The device has experienced a problem with its internal fan.	<p>Turn off the power by using the power switch, wait at least 30 seconds, then turn on the power and wait for the device to initialize.</p> <p>If the error persists, contact HP customer support. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>
<b>59.xx Error</b>	The device has experienced an internal hardware error.	<p>Turn off the power by using the power switch, wait at least 30 seconds, and then turn on the power and wait for the device to initialize.</p> <p>If a surge protector is being used, remove it. Plug the device directly into the wall socket. Use the power switch to turn the device on.</p> <p>If the error persists, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the device box.</p>
<b>79 Error</b>  <b>Turn off then turn on</b>	The device has experienced an internal firmware error.	<p>Turn off the power by using the power switch, wait at least 30 seconds, and then turn on the power and wait for the device to initialize.</p> <p>If you have recently installed a memory DIMM in the device, turn off the device, remove the memory DIMM, reinstall the DIMM to verify that it is seated properly, and then turn on the device.</p> <p>Turn off the power by using the power switch and if a surge protector is being used, remove it. Plug the device directly into the wall socket. Use the power switch to turn the device on.</p> <p>If the error persists, upgrade the firmware. See <a href="#">HP Customer Care</a> or the support flyer that came in the device box.</p> <p>If the error persists, replace the formatter. See <a href="#">HP Customer Care</a> or the support flyer that came in the device box.</p>
<b>Calibrating...</b>	The printer is calibrating.	No action is required. This task may take several minutes.
<b>Cleaning...</b>	The printer is in cleaning mode.	No action is required. This task may take several minutes.
<b>Device error.</b>  <b>Press [OK].</b>	An internal error occurred in the device.	Press <b>OK</b> to resume the job. Turn off the power by using the power switch, wait at least 30 seconds, then turn on the power and wait for the device to initialize. If these actions do not resolve the problem, contact HP Customer care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.
<b>Door open</b>	The MFP door is open.	The door must be closed before printing can continue.
<b>Engine communication error</b>	The device experienced an internal communication error.	This is a warning message only. Job output might be affected.

Control panel message	Description	Recommended action
<b>HP supplies installed</b>	The printer transitioned from having one or more non-HP supplies to having all HP supplies installed.	No action required.
<b>Incorrect &lt;color&gt; cartridge</b>	The <color> print cartridge may be crooked, or installed in the wrong print cartridge slot.  One of the following messages may display:  <b>Incorrect black cartridge</b>  <b>Incorrect cyan cartridge</b>  <b>Incorrect magenta cartridge</b>  <b>Incorrect yellow cartridge</b>	Reinstall the <color> print cartridge.
<b>Insert only 1 memory card at a time</b>	More than one memory card has been inserted.	Remove all but one memory card.
<b>Install &lt;color&gt; cartridge</b>  The supply gauge indicates the supply or supplies that are out of toner.	One of the following messages may display:  <ul style="list-style-type: none"> <li>● <b>Install black cartridge</b></li> <li>● <b>Install cyan cartridge</b></li> <li>● <b>Install magenta cartridge</b></li> <li>● <b>Install yellow cartridge</b></li> </ul>	The supply or supplies must be installed before printing can continue.
<b>Install supplies</b>  The supplies gauge displays the consumption levels of print cartridges.	Multiple supplies are not installed.	Install correct print cartridges.
<b>Invalid driver. Press [OK].</b>	The printer driver is incorrect.	Re-select the printer driver appropriate for the device.
<b>Invalid entry</b>	Invalid data or response.	Correct the entry.
<b>Jam in...</b>	A jam occurred in: <ul style="list-style-type: none"> <li>● the print/paper path</li> <li>● tray 1</li> <li>● tray 2</li> <li>● output bin</li> </ul>	Clear the jam, then press <b>OK</b> .
<b>Load paper</b>	The HP Color LaserJet CM1015/CM1017 MFP is out of paper.	Please load specified paper type into the tray indicated.
<b>Load Tray X [TYPE] [SIZE]</b>	The MFP is processing the job, but the tray indicator is empty.	Please load specified paper type and size into the tray indicated.
<b>Manual feed Press [OK]</b>	The MFP is waiting for paper in the tray indicated.	Load the paper as indicated.
<b>Memory card is in backwards</b>	The memory card was inserted backwards into the card slot.	Remove, turn, and reinsert the card.

Control panel message	Description	Recommended action
<b>Memory card is unsupported</b>	The memory card that you have inserted is not a type that is supported.	<p>Insert a card that is supported. The HP Color LaserJet CM1017 MFP supports the following cards:</p> <ul style="list-style-type: none"> <li>● CompactFlash</li> <li>● Ultra CompactFlash</li> <li>● Smart Media</li> <li>● Memory Stick</li> <li>● Secure Digital</li> <li>● Multi Media Card</li> <li>● xD Card</li> </ul>
<b>Memory card slots are disabled</b>	The memory card slots have been disabled.	Contact your system administrator.
<b>Memory is low. Press [OK]. Press [OK]</b>	The device memory has been almost completely filled or is full.	<p>Allow the device to finish the job, or press <b>OK</b> to cancel the job.</p> <p>Power cycle the machine.</p> <p>Break the job into smaller jobs that contain fewer pages.</p> <p>If the error persists, add a memory DIMM to the printer. For more information, see <a href="http://www.hp.com">http://www.hp.com</a> for more information about DIMMs and accessories.</p>
<b>Memory low. Only one copy made.</b>	The device does not have enough memory to complete the collated copy job.	<p>Break the job into smaller jobs that contain fewer pages.</p> <p>If the error persists, turn off the device and then turn on the device.</p> <p>If the error persists, add memory to the device.</p>
<b>Misprint. Press [OK]. Press [OK]</b>	The printed pages have been incorrectly placed on the paper.	To continue, press <b>OK</b> .
<b>No media pickup. Press [OK].</b>	The print engine has failed to pick up a piece of media.	<p>In tray 1, verify that the media was inserted far enough into the tray. In tray 2 or optional tray 3, verify that the paper-length guide is in the correct position for the media size that being used.</p> <p>Reload the media in the input tray and press <b>OK</b> to continue the job.</p> <p>If the error persists, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>

Control panel message	Description	Recommended action
<p><b>Non-HP &lt;color&gt; installed</b></p>	<p>A non-HP &lt;color&gt; cartridge is installed. Displays one of the following messages:</p> <ul style="list-style-type: none"> <li>• Non-HP black installed. Press <b>OK</b> to accept.</li> <li>• Non-HP magenta installed. Press <b>OK</b> to accept.</li> <li>• Non-HP cyan installed. Press <b>OK</b> to accept.</li> <li>• Non-HP yellow installed. Press <b>OK</b> to accept.</li> </ul>	<p>If you believe you purchased an HP supply, please visit the HP fraud Web site at <a href="http://www.hp.com/go/anticounterfeit">http://www.hp.com/go/anticounterfeit</a>. Service or repairs required as a result of using non-HP supplies is not covered under HP warranty.</p> <p> <b>NOTE</b> Any printer repair required as a result of using a non-HP or unauthorized supply is not covered under warranty.</p> <p>Verify that all cartridges are installed in the correct slot.</p> <p>To use this cartridge, override by pressing <b>OK</b>.</p> <p>Replace the supply</p>
<p><b>Non-HP supply in use</b></p> <p><b>Ready</b></p> <p>The supplies gauge displays the consumption levels of print cartridges.</p>	<p>A non-HP (cloned or refilled) supply has been installed and was overridden.</p>	<p>If you believe you purchased an HP supply, please visit the HP fraud Web site at <a href="http://www.hp.com/go/anticounterfeit">http://www.hp.com/go/anticounterfeit</a>. Service or repairs required as a result of using non-HP supplies is not covered under HP warranty.</p>
<p><b>Order supplies</b></p> <p><b>Ready</b></p> <p>The supplies gauge displays the consumption levels of print cartridges.</p>	<p>Multiple supplies are low.</p>	<p>For more information go to the HP Color LaserJet CM1015/CM1017 MFP toolbox and click <b>Supplies Status</b>. To order supplies online, click <b>Order Supplies</b>.</p>
<p><b>Page too complex.</b></p> <p><b>Press [OK].</b></p>	<p>The device could not print the current page because of its complexity.</p>	<p>Press <b>OK</b> to clear the message.</p> <p>Allow the device to finish the job, or press <b>OK</b> to cancel the job.</p>
<p><b>Replace &lt;color&gt; cartridge</b></p>	<p>The &lt;color&gt; print cartridge is low. One of the following messages may display:</p> <ul style="list-style-type: none"> <li>• <b>Order black cartridge. Ready</b> light is on.</li> <li>• <b>Order cyan cartridge. Ready</b> light is on.</li> <li>• <b>Order magenta cartridge. Ready</b> light is on.</li> <li>• <b>Order yellow cartridge. Ready</b> light is on.</li> </ul>	<p>For more information go to the HP Color LaserJet CM1015/CM1017 MFP toolbox and click <b>Supplies Status</b>. To order supplies online, click <b>Order Supplies</b>.</p>
<p><b>Replace supplies</b></p> <p>The supplies gauge displays the consumption levels of print cartridges.</p>	<p>The cartridge is out of toner.</p>	<p>Replace the supplies that are low.</p>
<p><b>Replace supplies.</b></p> <p><b>Override in use.</b></p>	<p>Supply override in use. The user has decided to continue printing beyond the out point. A</p>	<p>Replace the supplies that are low.</p>

Control panel message	Description	Recommended action
<p><b>Ready</b></p> <p>The supplies gauge displays the consumption levels of print cartridges. This is the message that displays when the non-HP supply is first installed.</p>	<p>supply is low and using Override may result in unsatisfactory print quality.</p> <p>This message displays the entire time multiple non-HP supplies are used in the MFP.</p>	
<p><b>Replace supply.</b></p> <p><b>Override in use.</b></p> <p><b>Ready</b></p> <p>The supplies gauge displays the consumption levels of print cartridges.</p>	<p>This message displays the entire time a single non-HP supply is used. It displays after the Unauthorized Supply message displays and after the user presses the override.</p> <ul style="list-style-type: none"> <li>Supply override in use. The user has decided to continue printing beyond the out point. A supply is low and using Override may result in unsatisfactory print quality.</li> </ul>	<p>Replace the supply.</p>
<p><b>Scanner Error X</b></p>	<p>The device experienced a scanner error.</p>	<p>Turn off the power by using the power switch, wait at least 30 seconds, and then turn on the power and wait for the device to initialize. If the error persists, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the device box.</p>
<p><b>Scanning error.</b></p> <p><b>Cannot connect.</b></p>	<p>The device cannot transmit scan information to a computer.</p>	<p>Verify that network or USB cables are securely connected and that the MFP software is properly installed.</p>
<p><b>Unauthorized supply in use</b></p> <p>alternates with</p> <p><b>Ready</b></p> <p>The supplies gauge displays the consumption levels of print cartridges.</p>	<p>Displays this message when the non-HP supply is first installed:</p> <ul style="list-style-type: none"> <li>A new non-HP supply has been installed and was overridden.</li> </ul>	<p>If you believe you purchased an HP supply, please visit the HP fraud Web site at <a href="http://www.hp.com/go/anticounterfeit">http://www.hp.com/go/anticounterfeit</a>. Service or repairs required as a result of using non-HP supplies is not covered under HP warranty.</p>
<p><b>Unauthorized &lt;color&gt;</b></p>	<p>A new non-HP supply has been installed. One of these four messages is displayed until an HP supply is installed or until <b>OK</b> is pressed.</p> <ul style="list-style-type: none"> <li><b>Unauthorized black cartridge</b></li> <li><b>Unauthorized magenta cartridge</b></li> <li><b>Unauthorized cyan cartridge</b></li> <li><b>Unauthorized yellow cartridge</b></li> </ul>	<p>If you believe you purchased an HP supply, please visit the HP fraud Web site at <a href="http://www.hp.com/go/anticounterfeit">http://www.hp.com/go/anticounterfeit</a>. Service or repairs required as a result of using non-HP supplies is not covered under HP warranty.</p> <p>To continue printing, press <b>OK</b>.</p>
<p><b>Unexpected size in tray X</b></p>	<p>Unexpected paper size error. The media size loaded in the tray does not match the media size configured for the tray.</p>	<p>Verify that the print settings are set to the specified media in the tray.</p>
<p><b>Unknown Memory Card Error</b></p>	<p>There is an issue with either the memory card or the device memory-card reader.</p>	<p>Reinsert the card. If the error persists, insert a different card.</p>



# Solve print problems

## Print-quality problems

The following sections help identify and resolve print-quality issues.

### Identifying and correcting print defects

Use the checklist and print-quality issues charts in this section to solve print-quality problems.

#### Print-quality checklist

Resolve general print-quality problems by using this checklist:





1. Ensure the paper or print media used meets specifications. Generally, smoother paper provides better results.
2. When using a special print media such as labels, transparencies, glossy, or letterhead, ensure that you have printed by type.
3. Remove any toner build-up and run a cleaning page.
4. Print a Configuration page and Supplies Status page at the MFP. See [Information pages](#).
  - Check the Supplies Status page to verify that supplies are not low or empty. No information is provided for non-HP print cartridges.
  - If the Configuration and Supplies Status pages do not print correctly, suspect a problem with the MFP printing components. Contact HP Customer Care. See [HP Customer Care](#) or the flyer that came in the MFP box.
5. Print a Demo page from the HP ToolboxFX. If the page prints, the problem is with the printer driver. Try printing from the other printer driver. For example, when using the PCL6 printer driver, print from the HP PostScript level 3 printer driver.





Use the Add Printer Wizard in the **Printers** folder in Windows XP dialog box to install the HP PostScript level 3 driver.





6. Try printing from a different program. If the page prints correctly, the problem is with the program from which you were printing.
7. Restart the computer and the MFP and try printing again. If the problem is not resolved, choose one of these options:
  - If the problem is affecting all printed pages, see [General print quality issues](#).
  - If the problem is affecting only pages printed in color, see [Solve issues with printing color documents](#).




#### General print quality issues

The following examples depict letter-size paper that has passed through the MFP short edge first. These examples illustrate problems that could affect all of the pages that printed, whether it is color printing or black only. These topics list the typical cause and solution for each of these examples.

Problem	Cause	Solution
<p>Print is light or faded.</p> 	<p>The media might not meet HP specifications.</p> <hr/> <p>One or more print cartridges might be low. When using non-HP print cartridges, no messages appear on the control panel or in the HP ToolboxFX.</p>	<p>Use media that meets HP specifications.</p> <hr/> <p>Replace any low print cartridges.</p> <p>If none of the print cartridges is low or empty, remove the print cartridges one at a time and inspect the toner roller in each to see if the roller is damaged. If so, replace the print cartridge.</p> <hr/> <p>Print the Supplies Status page to check the remaining life. See <a href="#">Supplies Status page</a>.</p>
<p>Toner specks appear.</p> 	<p>The media might not meet HP specifications.</p> <hr/> <p>The paper path might need cleaning.</p>	<p>Use media that meets HP specifications.</p> <hr/> <p>Clean the paper path. See the HP ToolboxFX online Help.</p>
<p>Dropouts appear.</p> 	<p>A single sheet of print media might be defective.</p> <hr/> <p>The moisture content of the paper is uneven or the paper has moist spots on its surface.</p> <hr/> <p>The paper lot is flawed. The manufacturing processes can cause some areas to reject toner.</p>	<p>Try reprinting the job.</p> <hr/> <p>Try different paper, such as high-quality paper that is intended for color laser MFPs.</p> <hr/> <p>Try different paper, such as high-quality paper that is intended for color laser MFPs.</p>
<p>Vertical streaks or bands appear on the page.</p> 	<p>One or more print cartridges might be low or defective. If non-HP print cartridges are used, no messages appear on the control panel or in the HP ToolboxFX.</p>	<p>Replace any low print cartridges.</p>





Problem	Cause	Solution
<p>The amount of background toner shading becomes unacceptable.</p> 	<p>The media might not meet HP specifications.</p> <p>Very dry (low humidity) conditions can increase the amount of background shading.</p> <p>One or more print cartridges might be low. If non-HP print cartridges are used, no messages appear on the control panel or in the HP ToolboxFX.</p>	<p>Use a different paper with a lighter basis weight.</p> <p>Check the MFP environment.</p> <p>Replace any low print cartridges.</p>
<p>Toner smears appear on the media.</p> 	<p>The media might not meet HP specifications.</p> <p>If toner smears appear on the leading edge of the paper, the media guides are dirty, or debris has accumulated in the print path.</p>	<p>Use media that meets HP specifications.</p> <p>Clean the media guides and the paper path.</p>
<p>The toner smears easily when touched.</p> 	<p>The MFP is not set to print on the type of media on which you want to print.</p> <p>The media might not meet HP specifications.</p> <p>The paper path might need cleaning.</p>	<p>In the printer driver, select the <b>Paper</b> tab and set <b>Type is</b> to match the type of media on which you want to print. Print speed might be slower when using heavy paper.</p> <p>Use media that meets HP specifications.</p> <p>Clean the MFP.</p>
<p>Marks repeatedly appear at even intervals on the printed side of the page.</p> 	<p>The MFP is not set to print on the type of media on which you want to print.</p> <p>Internal parts might have toner on them.</p> <p>The paper path might need cleaning.</p> <p>The fuser might be damaged or dirty.</p> <p>A print cartridge might have a problem.</p>	<p>In the printer driver, select the <b>Paper</b> tab and set <b>Type is</b> to match the type of media on which you want to print. Print speed might be slower when using heavy paper.</p> <p>The problem typically corrects itself after a few more pages.</p> <p>Clean the MFP.</p> <p>Clean using instructions in HP ToolboxFX.</p> <p>Contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p> <p>To determine which cartridge has a problem, print the PQ diagnostics page from HP ToolboxFX.</p>


Problem	Cause	Solution
<p>Marks repeatedly appear at even intervals on the unprinted side of the page.</p> 	<p>Internal parts might have toner on them.</p> <hr/> <p>The paper path might need cleaning.</p> <hr/> <p>The fuser might be damaged or dirty.</p>	<p>The problem typically corrects itself after a few more pages.</p> <hr/> <p>Clean the MFP.</p> <hr/> <p>Clean using instructions in HP ToolboxFX.</p> <p>Contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>
<p>The printed page contains misformed characters.</p> 	<p>The media might not meet HP specifications.</p> <hr/> <p>If characters are incorrectly formed so that they produce a wavy effect, the laser scanner might need service.</p>	<p>Use a different paper, such as high-quality paper that is intended for color laser MFPs.</p> <hr/> <p>Verify that the problem also occurs on the Configuration page. If so, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>
<p>The printed page is curled or wavy.</p> 	<p>The MFP is not set to print on the type of media on which you want to print.</p> <hr/> <p>The media might not meet HP specifications.</p> <hr/> <p>Both high temperature and humidity can cause paper curl.</p>	<p>In the printer driver, select the <b>Paper</b> tab and set <b>Type is</b> to match the type of paper on which you want to print. Print speed might be slower when using heavy paper.</p> <hr/> <p>Use a different paper, such as high-quality paper that is intended for color laser MFPs.</p> <hr/> <p>Check the MFP environment.</p>
<p>Text or graphics are skewed on the printed page.</p> 	<p>The media might be loaded incorrectly.</p> <hr/> <p>The media might not meet HP specifications.</p>	<p>Make sure that the paper or other print media is loaded correctly and that the media guides are not too tight or too loose against the stack. See <a href="#">Load trays</a>.</p> <hr/> <p>Use a different paper, such as high-quality paper that is intended for color laser MFPs.</p>

Problem	Cause	Solution
<p>The printed page contains wrinkles or creases.</p> 	<p>The media might be loaded incorrectly.</p> <hr/> <p>The media might not meet HP specifications.</p>	<p>Verify that the media is loaded correctly and that the media guides are not too tight or too loose against the stack. See <a href="#">Load trays</a>.</p> <hr/> <p>Turn over the stack of paper in the input tray, or try rotating the paper 180° in the input tray.</p> <hr/> <p>Use a different paper, such as high-quality paper that is intended for color laser MFPs.</p>
<p>Toner appears around the printed characters.</p> 	<p>The media might be loaded incorrectly.</p> <hr/> <p>If large amounts of toner have scattered around the characters, the paper might have high resistivity.</p>	<p>Turn over the stack of paper in the tray.</p> <hr/> <p>Use a different paper, such as high-quality paper that is intended for color laser MFPs.</p>
<p>An image that appears at the top of the page (in solid black) repeats farther down the page (in a gray field).</p> 	<p>Software settings might affect image printing.</p> <hr/> <p>The order of images printed might affect printing.</p> <hr/> <p>A power surge might have affected the MFP.</p>	<p>In the software program, change the tone (darkness) of the field in which the repeated image appears.</p> <hr/> <p>In the software program, rotate the whole page 180° to print the lighter image first.</p> <hr/> <p>Change the order in which the images are printed. For example, have the lighter image at the top of the page, and the darker image farther down the page.</p> <hr/> <p>If the defect occurs later in a print job, turn the MFP off for 10 minutes, then turn on the MFP to restart the print job.</p>

### Solve issues with printing color documents

This section describes issues that can occur when printing in color.

Problem	Cause	Solution
<p>Only black is printing when the document should be printing in color.</p> 	<p>Color mode is not selected in the program or printer driver.</p> <p>The correct printer driver might not be selected in the program.</p> <p>The MFP might not be correctly configured.</p>	<p>Select color mode instead of grayscale mode.</p> <p>Select the correct printer driver.</p> <p>Print a Configuration page. If no color appears on the Configuration page, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>
<p>One or more colors are not printing, or are inaccurate.</p> 	<p>Sealing tape might be on the print cartridges.</p> <p>The media might not meet HP specifications.</p> <p>The MFP might be operating in excessively humid conditions.</p> <p>One or more print cartridges might be low. When using non-HP print cartridges, no messages appear on the control panel or in the HP ToolboxFX.</p> <p>The control panel is set for override.</p>	<p>Verify that the sealing tape has been completely removed from the print cartridges.</p> <p>Use a different paper, such as high-quality paper that is intended for color laser MFPs.</p> <p>Verify that the MFP environment is within humidity specifications.</p> <p>Replace any low print cartridges.</p> <p>Replace low or empty print cartridges.</p>
<p>A color is printing inconsistently after loading a new print cartridge.</p> 	<p>Another print cartridge might be low. When using a non-HP print cartridge, it might be low or empty but you receive no indication.</p> <p>The control panel is set for override.</p>	<p>Remove the print cartridge for the color that is printing inconsistently and reinstall it.</p> <p>Replace low or empty print cartridges.</p>
<p>The colors on the printed page do not match the colors as they appear on the screen.</p> 	<p>The colors on the computer monitor might differ from the MFP output.</p> <p>If extremely light colors or extremely dark colors on screen are not printing, the software program might interpret extremely light colors as white or extremely dark colors as black.</p> <p>The media might not meet HP specifications.</p>	<p>Select <b>Screen Match</b> in the <b>Color</b> tab of the printer driver.</p> <p>If possible, avoid using extremely light or extremely dark colors.</p> <p>Use a different paper, such as high-quality paper that is intended for color laser MFPs.</p>

Problem	Cause	Solution
<p>The finish on the printed color page is inconsistent.</p> 	The media might be too rough.	Use a smooth paper or print media, such as a high-quality paper that is made for color laser MFPs. Generally, smoother media produces better the results.
<p>The finish on the printed or copied color page has light colored spots.</p>	The media may have been bent when loaded, or the ETB may be damaged.	<p>Load new paper and reprint or copy the document.</p> <p>If the problem persists, contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.</p>

## Media-handling problems

Use the information in this section when the MFP experiences media-handling problems.

### Print-media guidelines

- For best results, make sure that the paper is of good quality, and free of cuts, nicks, tears, spots, loose particles, dust, wrinkles, voids, staples, and curled or bent edges.
- For best-quality color printing, use a smooth type of paper. Generally, smoother media produces better results.
- Check the paper package label to ensure the type of paper you are loading (such as bond or recycled) is correct.
- Do not use media that is designed for Inkjet MFPs only. Use media that is designed for color LaserJet MFPs.
- Do not use letterhead paper that is printed with low-temperature inks, such as those used in some types of thermography.
- Do not use raised or embossed letterhead.
- The MFP uses heat and pressure to fuse toner to the paper. Make sure that any colored paper or preprinted forms use inks that are compatible with this fusing temperature 210°C (410°F) for 0.1 seconds).



**CAUTION** Failure to follow these guidelines could cause jams or damage to the MFP.

### Solve print-media problems

The following problems with paper cause print-quality deviations, jamming, or even damage to the MFP.

Problem	Cause	Solution
Poor print quality or toner adhesion	The paper is too moist, too rough, too heavy or too smooth, or it is embossed or from a faulty paper lot.	Verify that the appropriate media type was selected in the printer driver.  Try another kind of paper, between 100 and 250 Sheffield, 4% to 6% moisture content.
Dropouts, jamming, or curl	The paper has been stored incorrectly.	Store paper flat in its moisture-proof wrapping.
	The paper has variability from one side to the other.	Turn the paper over.
Excessive curl	The paper is too moist, has the wrong grain direction, or is of short-grain construction.	Verify that the appropriate media type was selected in the printer driver.  Try printing on media from a new or different package.  Use long-grain paper.
	The paper varies from side-to-side.	Turn the paper over.
Jamming, damage to MFP	The paper has cutouts or perforations.	Use paper that is free of cutouts or perforations.
Problems with feeding	The paper has ragged edges.	Use high-quality paper that is made for color laser printers.
	The paper varies from side-to-side.	Turn the paper over.
	The paper is too moist, too rough, too heavy or too smooth, has the wrong grain direction, or is of short-grain construction or it is embossed or from a faulty paper lot.	Try another kind of paper, between 100 and 250 Sheffield, 4 to 6% moisture content.  Use long-grain paper.
Print is skewed (crooked)	The media guides might be incorrectly adjusted.	Remove all media from the input tray, straighten the stack, then load the media in the input tray again. Adjust the media guides to the width and length of the media being used and try printing again.
More than one sheet feeds at one time.	The media tray might be overloaded.	Remove some of the media from the tray. See <a href="#">Load trays</a> .
	The media might be wrinkled, folded, or damaged.	Verify that the media is not wrinkled, folded, or damaged. Try printing on media from a new or different package.



Problem	Cause	Solution
MFP does not pull media from the media input tray.	The MFP might be in manual feed mode.	<ul style="list-style-type: none"> <li>If <b>Manual feed</b> appears on the MFP control-panel display, press <b>OK</b> to print the job.</li> <li>Verify that the MFP is not in manual feed mode and print the job again.</li> </ul>
	The media tray might be overloaded.	Remove some of the media from the tray. See <a href="#">Load trays</a> .
	The paper-length adjustment control in tray 2 or optional tray 3 is set at a length that is greater than the media size.	Adjust the paper-length adjustment control to the correct length.
	The pickup roller might be dirty or damaged.	Contact HP Customer Care. See <a href="#">HP Customer Care</a> or the support flyer that came in the MFP box.

## Performance problems

Try the tips in this section if pages exit the MFP but have nothing printed on them, or when the MFP does not print any pages.

Problem	Cause	Solution
Pages print but are totally blank.	The sealing tape might still be in the print cartridges.	Verify that the sealing tape has been completely removed from the print cartridges.
	The document might contain blank pages.	Check the document that is printing to see if content appears on all of the pages.
	The MFP might be malfunctioning.	To check the MFP, print a Configuration page.
Pages print very slowly.	Heavier media types can slow the print job.	Print on a different type of media.
	Complex pages print more slowly.	Proper fusing requires a slower print speed to ensure the best print quality.


Problem	Cause	Solution
Pages did not print.	The MFP might not be pulling media correctly.	See <a href="#">Media-handling problems</a> .
	The media is jamming in the MFP.	Clear the jam.
	The USB cable might be defective or incorrectly connected.	<ul style="list-style-type: none"> <li>● Disconnect the USB cable at both ends and reconnect it.</li> <li>● Try printing a job that has printed in the past.</li> <li>● Try using a different USB cable.</li> </ul>
	Other devices are running on the computer.	The device might not share a USB port. When there is an external hard drive or network switchbox connected to the same port as the MFP, the other device might be interfering. To connect and use the MFP, disconnect the other device or use two USB ports on the computer.



# Resolve copy problems

The following are a few simple steps that can improve copy quality:

- Use quality originals.
- Adjust the control-panel settings for the type of original.
  - Use the **Text** setting for items that contain mostly text.
  - Use the **Film photo** setting when making a copy of a photograph.
  - Use **Picture** when making a copy of a graphic.
  - Use the **Mixed** setting for documents that include both text and graphics.

Use the table to Identify and resolve imaging problems.

Problem	Cause	Solution
Copy edges are cropped. 	Original is edge-to-edge or has margins smaller than those supported by this MFP.	<ol style="list-style-type: none"> <li>1. Position the original 1/6" away from the top and right edges of the scanner glass.</li> <li>2. Select <b>Reduce/Enlarge</b>, and press the navigation arrows to select <b>Full Page=91%</b>, then press <b>Start Copy Black</b> or <b>Start Copy Color</b>.</li> </ol>
Images are missing or faded. See <a href="#">Calibrate the MFP</a> .	One or more print cartridges might be low.	Replace any low print cartridges.
	The device might have calibrated incorrectly after installing a print cartridge.	Calibrate the device. See <a href="#">Calibrate the MFP</a> .
	The original might be of poor quality.	If the original is too light or damaged, the copy might not be able to compensate, even when adjusting the contrast. If possible, find an original document in better condition.
	The original might have a colored background.	Colored backgrounds might cause images in the foreground to blend into the background, or the background might appear in a different shade. If possible, use an original document without a colored background.

Problem	Cause	Solution
<p>Vertical white or faded stripes appear on the copy.</p> 	<p>The media might not meet HP specifications.</p> <hr/> <p>One or more print cartridges might be low.</p> <hr/> <p>If the error persists contact HP customer support. See <a href="#">HP Customer Care</a>, or the support flyer that came in the MFP box.</p>	<p>Use media that meets HP specifications. See <a href="#">Media supported on this MFP</a>.</p> <hr/> <p>Replace any low print cartridges. If the error persists, inspect the print cartridges for defects in the printing area.</p> <hr/>
<p>Unwanted lines appear on the copy.</p> 	<p>Tray 1 might not be placed correctly.</p> <hr/> <p>The flatbed scanner might be dirty.</p> <hr/> <p>An image exists on the back of the original, or defects exist on the scanner cover.</p> <hr/> <p>If the error persists, contact HP customer support. See <a href="#">HP Customer Care</a>, or the support flyer that came in the MFP box.</p>	<p>Verify that tray 1 is in place.</p> <hr/> <p>Clean the paper path. See <a href="#">Clean the MFP</a>.</p> <hr/> <p>On the flatbed scanner, place three sheets of clean paper on top of the original, close the flatbed scanner cover, then re-scan the original.</p> <hr/>
<p>Black dots or streaks appear on the copy.</p>	<p>Ink, glue, correction fluid, or an unwanted substance might be on the flatbed scanner.</p>	<p>Clean the device. See <a href="#">Clean the MFP</a>.</p>
<p>Copies are too light or dark.</p>	<p>The device settings may be incorrect.</p> <hr/> <p>The device might not be calibrated correctly.</p>	<p>Verify that the quality settings are correct on the device control panel.</p> <p>See the device software Help for more information about changing the settings.</p> <hr/> <p>Calibrate the device. See <a href="#">Calibrate the MFP</a>.</p>
<p>Text is unclear.</p>	<p>The device settings may be incorrect.</p> <hr/> <p>The device might not be calibrated correctly.</p> <hr/> <p>The original is of poor quality.</p> <hr/> <p>If the error persists contact HP customer support. See <a href="#">HP Customer Care</a>, or the support flyer that came in the MFP box.</p>	<p>Verify that the quality settings are correct on the device control panel.</p> <p>See the device software Help for more information about changing the settings.</p> <hr/> <p>Calibrate the device. See <a href="#">Calibrate the MFP</a>.</p> <hr/> <p>Try copying another document. If the copy is free of defects, obtain a better-quality original.</p> <hr/>

# Resolve scanning problems

Use the table to solve image-scan issues.

Problem	Cause	Solution
The scanned image is of poor quality.	The original might be a second-generation photo or picture.	<ul style="list-style-type: none"> <li>To eliminate the patterns, try reducing the size of the image after scanning.</li> <li>Print the scanned image to see if the quality is better.</li> <li>Verify that the resolution and color settings are correct for the type of scan job being performed.</li> </ul>
	If the scanned page has a background but the original document does not, the original might be too thin to scan or copy cleanly.	On the flatbed scanner, place three sheets of clean paper on top of the original, close the flatbed scanner cover, then re-scan the original.
	The image that appears on the screen might not be an accurate representation of the quality of the scan.	<ul style="list-style-type: none"> <li>Try adjusting the computer monitor settings to use more colors (or levels of gray). Make this adjustment by opening <b>Display</b> in Windows Control Panel.</li> <li>Try adjusting the resolution and color settings in the scanner software.</li> </ul>
	The original might have been loaded incorrectly.	Verify originals are properly loaded onto the flatbed scanner. See <a href="#">Scan methods</a> .
	The scanner might be dirty.	Clean the scanner.
	The graphics settings might not be suitable for the type of scan job that being performed.	Try changing the graphics settings or the scan mode.
Part of the image did not scan.	The original might have been loaded incorrectly.	Verify originals are properly loaded onto the flatbed scanner.
	A colored background might be causing images in the foreground to blend into the background.	Try adjusting the settings before scanning the original or enhancing the image after scanning the original.
	The original is longer than 298 mm (11.75 in).	The maximum flatbed scannable length is 298 mm (11.75 in). If the page exceeds the maximum length, the scanner stops.
	The original is too small.	The minimum size that the flatbed scanner supports is 25 by 25 mm (1 by 1 inches).
	The media size is incorrect.	In Scan settings, make sure that the input media size is large enough for the document that being scanned.

Problem	Cause	Solution
The scan takes too long.	The resolution or color level is set too high.	Change the resolution and color level settings to the correct settings for the job.
	The software is set to scan in color.	The system default is color, which takes longer to scan even when scanning a monochrome original. If you acquire an image through TWAIN or WIA, you can change the settings so that the original scans in grayscale or black-and-white. See the device software Help for details.
	A print job or copy job was sent before you tried to scan.	If someone sent a print job or copy job before you tried to scan, the scan starts if the scanner is not busy. However, because the printer and scanner share memory, the scan might be slower.

Resolve scan-quality problems using the table.

Problem	Cause	Solution
Blank pages	The original might have been loaded upside down.	On the flatbed scanner, place the original document face-down with the upper-left corner of the document at the lower-right corner of the glass.
	The scanner bulb might not be working.	If the scanner bulb does not light, verify that the cables from the scanner to the formatter are connected correctly. If the error persists, replace parts one at a time in the following order until the problem is resolved: scanner assembly, and finally the formatter.
Too light or dark	The resolution and color levels may be set incorrectly.	<p>Verify the resolution and color settings.</p> <ul style="list-style-type: none"> <li>● Use the <b>Text</b> setting for items that contain mostly text.</li> <li>● Use the <b>Film photo</b> setting when making a copy of a photograph.</li> <li>● Use <b>Picture</b> when making a copy of a graphic.</li> <li>● Use the <b>Mixed</b> setting for documents that include both text and graphics.</li> <li>● Use the <b>Draft</b> setting if conserve toner or if the copy quality is not as important.</li> </ul>
Black dots or streaks	Ink, glue, correction fluid, or an unwanted substance might be on the glass.	Clean the flatbed scanner surface.
Unclear text	The resolution and color levels may be set incorrectly.	Verify the correct resolution and color settings.
The scanned page has a background but the original document does not.	The original might be too thin to scan cleanly.	On the flatbed scanner, place three sheets of clean paper on top of the

Problem	Cause	Solution
		original, close the flatbed scanner cover, then re-scan the original.

## The device control panel display has black lines or dots, or becomes blank



---

**CAUTION** Static electricity can cause unexpected black lines or dots to appear on the device control panel display. Do not touch the device control panel display if there is a chance that you have collected a static electric charge (for example, by walking on carpet in a low-humidity environment).

---

### Was the device exposed to an electric or magnetic field?

Unexpected lines or dots might appear on the device control panel display, or the display might become blank if the device is exposed to an electric or magnetic field. To resolve this problem, perform the following procedure:

1. Turn the device off.
2. Remove the device from the electric or magnetic field.
3. Turn the device on again.



# Clear paper jams

Occasionally, paper or other print media can become jammed during a print job. Some causes include the following events:



---

**CAUTION** Do **NOT** use any tool or sharp object to help remove paper jams.

---

- The input trays are loaded improperly or overfilled.
- Tray 2 or optional tray 3 is opened during a print job.
- Too many sheets accumulated in the output area, or sheets blocked the output area.
- The print media being used does not meet HP specifications. See [Print on special media](#).
- The environment in which the print media was stored is too humid or too dry. See [Print on special media](#).

## Where to look for jams

Jams can occur in these locations:

- Inside the MFP. See [Clear jams from inside the MFP](#).
- In input areas. See [Clear jams from tray 2 or optional tray 3](#).
- In the output area. See [Clear jams from tray output area](#).

Find and remove the jam by using the instructions on the following pages. If the location of the jam is not obvious, first look inside the MFP.


Loose toner might remain in the MFP after a jam. This problem should resolve itself after a few sheets have been printed.

Each section below corresponds to an area where a paper jam could occur. Use the following procedures to clear the jam. In all cases, grasp the jammed paper by both corners and pull slowly to remove the paper.

## Clear jams from inside the MFP



**CAUTION** Jams in this area might result in loose toner on the page. If toner gets on clothes or hands, wash them in cold water. (Hot water sets the toner into the fabric.)

1. Open the front door.




**CAUTION** Do not place anything on the transfer belt, which is located on the inside of the front door. Otherwise the MFP can be adversely damaged, affecting print quality.

2. Carefully grasp the jammed paper by both corners and pull slowly to remove the paper.




3. Close the front door.




## Clear jams from tray output area

**CAUTION** Jams in these areas might result in loose toner on the page. If toner gets on clothes or hands, wash them in cold water. (Hot water sets the toner into the fabric.)

1. Carefully grasp the jammed paper by both corners and pull slowly to remove the paper from the top bin.




2. Open and close the front door.




## Clear jams from the back of the MFP


1. Open the back cover.



2. Remove any jammed paper.



3. Close the back cover.




## Clear jams from tray 2 or optional tray 3




**NOTE** Before attempting to clear jams from tray 2 or optional tray 3, remove any jams inside the MFP.

1. Pull tray 2 or optional tray 3 out of the MFP.




2. Carefully grasp the jammed paper by both corners and pull slowly to remove the paper.

3. Slide the tray into the MFP.



4. Open and close the front door.



# Additional problem solving tools

The section describes the tools that can help solve problems with the MFP.

## Device pages and reports

This section describes the pages and reports that help diagnose and solve MFP problems.

### Demo page

To verify that the MFP is functioning properly, print a Demo page. For more information about the Demo page, see [Demo page](#).

### Configuration page

The Configuration page lists the current settings and properties of the MFP. Use this page to check for color plane registration and cartridge half tones. It is possible to print a Configuration page from the MFP or HP ToolboxFX.

For more information about the Configuration page, see [Configuration page](#).

### Supplies Status page

The Supplies Status page lists the remaining life of the HP print cartridges. It also lists the estimated pages remaining, number of pages printed, and other supplies information. Print a Supplies Status page from the MFP or HP ToolboxFX.

For more information about the Supplies Status page, see [Supplies Status page](#).

## HP ToolboxFX

HP ToolboxFX is a software application used for problem solving tasks.

### View HP ToolboxFX

Open HP ToolboxFX in one of these ways:

- On the Windows desktop, double-click the HP ToolboxFX system tray icon or program group entry.
- On the Windows **Start** menu, click **Programs (All Programs in Windows XP)**, click **HP**, click **HP Color LaserJet CM1015/CM1017 Series**, click **HP ToolboxFX**, then click **Help**.

## Service menu

Use the control-panel **Service** menu to troubleshoot MFP problems.

### Restore the factory-set defaults

Restoring the factory-set defaults returns all of the settings to the factory defaults.



### To restore the factory-set defaults

1. Press **Menu**.
2. Press the navigation arrows to select **Service**, then press **OK**.
3. Press the navigation arrows to select **Restore defaults**, then press **OK**.

The MFP automatically restarts.

### Clean the paper path

The MFP features a special cleaning mode to clean the paper path.



---

**NOTE** If you have access to HP ToolboxFX, HP recommends cleaning the paper path by using HP ToolboxFX.

---

### To clean the paper path

1. Press **Menu**.
2. Press the navigation arrows to select **Service**, then press **OK**.
3. Press the navigation arrows to select **Cleaning mode**, then press **OK**.

A page feeds slowly through the MFP. Discard the page when the process is completed.

4. Load plain letter or A4 paper when prompted.
5. Press **OK** again to confirm and begin the cleaning process.

A page feeds through the MFP slowly. Discard the page when the process is completed.

### Calibrate the MFP

Calibrations are performed at regular intervals. For best print quality, a calibration can be performed from the control panel. For more information about calibrating the MFP, see [Calibrate the MFP from the front control panel](#).



# 15 Work with memory

This section provides information about the following topics:

- [MFP memory](#)
- [Install memory DIMMs](#)
- [Check DIMM installation](#)
- [Enable memory](#)

## MFP memory

The HP Color LaserJet CM1015/CM1017 MFP has one dual inline memory module (DIMM) slot for upgrading the MFP capabilities with the following options:

- More MFP memory. DIMMs are available in 64 MB, 128 MB, and 256 MB for a maximum of 354 MB.
- DIMM-based macros, and patterns

Consider adding more memory to the MFP if print jobs often include complex graphics or HP PostScript Level 3 documents, or use many downloaded fonts. Additional memory also allows the MFP to print multiple, collated copies at the maximum speed.


Before ordering additional memory, see how much is currently installed by printing a Configuration page. Press **OK** and **Cancel** simultaneously, or use the HP ToolboxFX. To order DIMMs, see [Accessories and supplies information](#). Single inline memory modules (SIMMs) used on previous HP LaserJet MFPs are not compatible with the MFP.

## Install memory DIMMs


When installing more memory for the MFP, it is possible to install a DIMM to print characters for languages such as Chinese, or for the Cyrillic alphabet.

**CAUTION** Static electricity can damage DIMMs. When handling DIMMs, wear an antistatic wrist strap, or frequently touch the surface of the DIMM antistatic package then touch bare metal on the MFP.


1. Print a Configuration page by pressing **OK** and **Cancel** simultaneously. (A Supplies Status page may also print.) If the Configuration page does not print in your language, see [Information pages](#).
2. After the Configuration page prints, turn the MFP off and disconnect the power cable.




3. On the left rear side of the MFP, open the DIMM door.




4. Release the locks on each side of the DIMM slot.




5. Remove the DIMM from the antistatic package.




6. Holding the DIMM by the edges as shown in the illustration, align the notches on the DIMM with the DIMM slot.




7. Firmly press the DIMM straight into the slot. Firmly close the locks on each side of the DIMM until they snap into place.



8. Close the DIMM door.



9. Reconnect the power cable and turn on the MFP.



10. Go to [Check DIMM installation](#).



# Check DIMM installation

Check that the DIMMs are installed correctly and working.

1. Turn the MFP on. Check that the Ready light is on after the MFP has completed the startup sequence. If an error message appears, a DIMM might have been incorrectly installed.
2. Print a Configuration page by pressing **OK** and **Cancel** simultaneously. (A Supplies Status page may also print.)
3. Check the Installed Personalities and Options section on the Configuration page and compare it with the Configuration page printed before the DIMM installation.
4. If the amount of recognized memory has not increased or the DIMM is not recognized, the following conditions might exist:
  - The DIMM might not be installed correctly. Repeat the installation procedure.
  - The DIMM might be defective. Try installing a different DIMM.
5. After the DIMM is installed correctly, go to [Enable memory](#) if a memory DIMM was installed.

# Enable memory

If the MFP has a new memory DIMM installed, all Windows users of the MFP must set the printer driver to recognize the newly added memory. Macintosh computers automatically recognize new memory.

## To enable memory for Windows

1. On the **Start** menu, point to **Settings**, and click **Printers** or **Printers and Faxes**.
2. Select this MFP and select **Properties**.
3. On the **Configure** tab, click **More**.
4. In the **Total Memory** field, type the total amount of memory that is now installed.
5. Click **OK**.



# A Accessories and supplies information

The lists of accessories in this section was current at the time of printing. Ordering information and availability of the accessories might change during the life of the MFP. For the most current ordering information, visit <http://www.hp.com>.

- [Supplies](#)
- [Memory](#)
- [Cable and interface accessories](#)
- [Paper handling accessories](#)
- [Paper and other print media](#)
- [User-replaceable parts](#)
- [Supplementary Documentation](#)

## Supplies

Product name	Description	Part number
Black print cartridge	Life of 2,500 pages at approximately 5% coverage.	Q6000A
Cyan print cartridge	Life of 2,000 pages at approximately 5% coverage.	Q6001A
Yellow print cartridge	Life of 2,000 pages at approximately 5% coverage.	Q6002A
Magenta print cartridge	Life of 2,000 pages at approximately 5% coverage.	Q6003A



**NOTE** Actual yields vary according to usage.

## Memory



**NOTE** There is no limitation on memory for photos, but there is a photo card limit of 9,999 photos per card.

Product name	Description	Part number
Memory upgrades (DIMMs)	64 MB-100 pin, 100 MHz SDRAM DIMM	Q7708A
Memory upgrades (DIMMs)	128 MB-100 pin, 100 MHz SDRAM DIMM	Q7709A
Memory upgrades (DIMMs)	256 MB 32bit 100 pin SDRAM	

## Cable and interface accessories

Product name	Description	Part number
USB cable	2-meter standard USB-compatible device connector	C6518A

## Paper handling accessories

Product name	Description	Part number
Tray 3 (Optional)	Optional 250-sheet universal input tray (included with the HP Color LaserJet CM1015/CM1017). Only one optional 250-sheet tray can be installed.	Q6459A

## Paper and other print media

Product name	Description	Part number
HP Multipurpose paper	75 g/m <sup>2</sup> (20 lb), 96 bright	HPM1120 (letter)
		HPM1420 (legal)
HP All-in-One Printing Paper	81 g/m <sup>2</sup> (22 lb), 96 bright	HPT 115 (letter)
HP LaserJet Paper	90 g/m <sup>2</sup> (24 lb), 96 bright 90 g/m <sup>2</sup> (24 lb), 153 whiteness	HPJ1124 (letter)
		CHP310 (A4)
		HPJ1424 (legal)
HP Premium Choice Paper	120 g/m <sup>2</sup> (32 lb), 98 bright 120 g/m <sup>2</sup> (32 lb), 158 whiteness	HPU1132 (letter)
		CHP410 (A4)
HP Presentation Laser Paper, glossy	130 g/m <sup>2</sup> (34 lb), 96 bright	Q2546A (letter)
HP Professional Paper, glossy	130 g/m <sup>2</sup> (34 lb), 130 whiteness	Q2552A (A4)
HP Photo & Imaging Laser Paper, matte	200 g/m <sup>2</sup> (54 lb), 96 bright	Q6549A (letter)
HP Brochure laser paper, matte	160 g/m <sup>2</sup> (52 lb), 96 bright	Q6543A (letter) 150 sheets
HP Tough paper	5 mil thick, Water/Tear proof	Q1298A (letter)
		Q1298B (A4)
HP Color LaserJet transparencies	5 mil thick	C2934A (letter) 50 sheets
		C2936A (A4) 50 sheets

## User-replaceable parts

Product name	Description	Part number
Separation pad and pick-up rollers	Replace when the MFP is picking up multiple sheets or no sheets. Trying different paper did not resolve the problem.	Q5956-67902
Paper tray	A 250-sheet paper tray cassette.	Q5956-67901
Dust cover	Protects the output of paper cassette from dust.	Q5956-67903
Scanner flatbed cover	Replacement part	CB394-60106
Control-panel over lay (various countries/regions)	Replacement part (localized)	Order at <a href="http://www.hp.com/support/cljCM1015_CM1017">http://www.hp.com/support/cljCM1015_CM1017</a>
Output tray	Replacement part	Order at <a href="http://www.hp.com/support/cljCM1015_CM1017">http://www.hp.com/support/cljCM1015_CM1017</a>

## Supplementary Documentation

A printed copy of this user guide is available in the following languages.

**Table A-1** User guides

Language	Part number
English	CB394-90907
Catalan	CB394-90908
Chinese (Simplified)	CB394-90928
Chinese (Traditional)	CB394-90929
Czech	CB394-90909
Danish	CB394-90910
Dutch	CB394-90919
Finnish	CB394-90913
French	CB394-90914
German	CB394-90911
Hungarian	CB394-90915
Indonesian (Bahasa)	CB394-90916
Italian	CB394-90917
Korean	CB394-90918
Norwegian	CB394-90920
Portuguese (Brazilian)	CB394-90922
Polish	CB394-90921
Romanian	CB394-90923
Russian	CB394-90924
Spanish	CB394-90912
Swedish	CB394-90925
Thai	CB394-90926
Turkish	CB394-90927





## **B Service and support**

# Hewlett-Packard limited warranty statement

HP PRODUCT

HP Color LaserJet CM1015/CM1017 MFP

DURATION OF LIMITED WARRANTY

1 year, Limited Warranty

HP warrants to you, the end-user customer, that HP hardware and accessories will be free from defects in materials and workmanship after the date of purchase, for the period specified above. If HP receives notice of such defects during the warranty period, HP will, at its option, either repair or replace products which prove to be defective. Replacement products can be either new or equivalent in performance to new.

HP warrants to you that HP software will not fail to execute its programming instructions after the date of purchase, for the period specified above, due to defects in material and workmanship when properly installed and used. If HP receives notice of such defects during the warranty period, HP will replace software which does not execute its programming instructions due to such defects.

HP does not warrant that the operation of HP products will be uninterrupted or error free. If HP is unable, within a reasonable time, to repair or replace any product to a condition as warranted, you will be entitled to a refund of the purchase price upon prompt return of the product.

HP products contain remanufactured parts equivalent to new in performance or have been subject to incidental use.

Warranty does not apply to defects resulting from (a) improper or inadequate maintenance or calibration, (b) software, interfacing, parts or supplies not supplied by HP, (c) unauthorized modification or misuse, (d) operation outside of the published environmental specifications for the product, or (e) improper site preparation or maintenance.

TO THE EXTENT ALLOWED BY LOCAL LAW, THE ABOVE WARRANTIES ARE EXCLUSIVE AND NO OTHER WARRANTY OR CONDITION, WHETHER WRITTEN OR ORAL, IS EXPRESSED OR IMPLIED AND HP SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY, SATISFACTORY QUALITY, AND FITNESS FOR A PARTICULAR PURPOSE. Some countries/regions, states or provinces do not allow limitations on the duration of an implied warranty, so the above limitation or exclusion might not apply to you. This warranty gives you specific legal rights and you might also have other rights that vary from country/region to country/region, state to state, or province to province. HP's limited warranty is valid in any country/region or locality where HP has a support presence for this product and where HP has marketed this product. The level of warranty service you receive vary according to local standards. HP will not alter form, fit or function of the product to make it operate in a country/region for which it was never intended to function for legal or regulatory reasons.

TO THE EXTENT ALLOWED BY LOCAL LAW, THE REMEDIES IN THIS WARRANTY STATEMENT ARE YOUR SOLE AND EXCLUSIVE REMEDIES. EXCEPT AS INDICATED ABOVE, IN NO EVENT WILL HP OR ITS SUPPLIERS BE LIABLE FOR LOSS OF DATA OR FOR DIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFIT OR DATA), OR OTHER DAMAGE, WHETHER BASED IN CONTRACT, TORT, OR OTHERWISE. Some countries/regions, states or provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion not apply to you.

THE WARRANTY TERMS CONTAINED IN THIS STATEMENT, EXCEPT TO THE EXTENT LAWFULLY PERMITTED, DO NOT EXCLUDE, RESTRICT OR MODIFY AND ARE IN ADDITION TO THE MANDATORY STATUTORY RIGHTS APPLICABLE TO THE SALE OF THIS PRODUCT TO YOU.

# Print Cartridge Limited Warranty Statement

This HP product is warranted to be free from defects in materials and workmanship.

This warranty does not apply to products that (a) have been refilled, refurbished, remanufactured or tampered with in any way, (b) experience problems resulting from misuse, improper storage, or operation outside of the published environmental specifications for the MFP product or (c) exhibit wear from ordinary use.

To obtain warranty service, please return the product to place of purchase (with a written description of the problem and print samples) or contact HP Customer Support. At HP's option, HP will either replace products that prove to be defective or refund your purchase price.

TO THE EXTENT ALLOWED BY LOCAL LAW, THE ABOVE WARRANTY IS EXCLUSIVE AND NO OTHER WARRANTY OR CONDITION, WHETHER WRITTEN OR ORAL, IS EXPRESSED OR IMPLIED AND HP SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY, SATISFACTORY QUALITY, AND FITNESS FOR A PARTICULAR PURPOSE.

TO THE EXTENT ALLOWED BY LOCAL LAW, IN NO EVENT WILL HP OR ITS SUPPLIERS BE LIABLE FOR DIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFIT OR DATA), OR OTHER DAMAGE, WHETHER BASED IN CONTRACT, TORT, OR OTHERWISE.

THE WARRANTY TERMS CONTAINED IN THIS STATEMENT, EXCEPT TO THE EXTENT LAWFULLY PERMITTED, DO NOT EXCLUDE, RESTRICT OR MODIFY AND ARE IN ADDITION TO THE MANDATORY STATUTORY RIGHTS APPLICABLE TO THE SALE OF THIS PRODUCT TO YOU.

# HP Customer Care

## Online services

*For 24-hour access to information by using a modem or Internet connection*

World Wide Web: Updated HP MFP software, product and support information, and printer drivers in several languages can be obtained from [http://www.hp.com/support/cljCM1015\\_CM1017](http://www.hp.com/support/cljCM1015_CM1017). (The site is in English.)

## Online troubleshooting tools

HP Instant Support Professional Edition (ISPE) is a suite of Web-based problem solving tools for desktop computing and printing products. ISPE helps you quickly identify, diagnose, and resolve computing and printing problems. The ISPE tools can be accessed from <http://instantsupport.hp.com>.

## Telephone support

Hewlett-Packard provides free telephone support during the warranty period. When you call, you will be connected to a responsive team that is waiting to help you. For the telephone number for your country/region, see the flyer that came in the box with the product, or visit <http://www.hp.com> then click **Contact HP**. Before calling HP, have the following information ready: product name and serial number, date of purchase, and description of the problem.

You can also find support on the Internet at [http://www.hp.com/support/cljCM1015\\_CM1017](http://www.hp.com/support/cljCM1015_CM1017). Click the **support & drivers** block.

## Software utilities, drivers, and electronic information

Go to [http://www.hp.com/support/cljCM1015\\_CM1017](http://www.hp.com/support/cljCM1015_CM1017). (The site is in English, but printer drivers can be downloaded in several languages.)

For information over the telephone, see the flyer that came in the box with the MFP.

## HP direct ordering for accessories or supplies

Order supplies from the following Web sites:

North America: <https://www.hp.com/post-embed/ordersupplies-na>

Latin America: <https://www.hp.com/post-embed/ordersupplies-la>

Europe and Middle East: <https://www.hp.com/post-embed/ordersupplies-emea>

Asia Pacific countries/regions: <https://www.hp.com/post-embed/ordersupplies-ap>

Order accessories from <http://www.hp.com> and click **Supplies & Accessories**. For more information, see [Accessories and supplies information](#).

To order supplies or accessories over the telephone, call the following numbers:

United States: 1-800-538-8787

Canada: 1-800-387-3154

To find the telephone numbers for other countries/regions, see the flyer that came in the box with the MFP.

## HP service information

To locate HP-Authorized Dealers in the United States or Canada, call 1-800-243-9816 (United States) or 1-800-387-3867 (Canada). Or, go to <http://www.hp.com/go/cposupportguide>.

For service for your HP product in other countries/regions, call the HP Customer Support telephone number for your country/region. See the flyer that came in the box with the MFP.

### **HP service agreements**

Call: 1-800-HPINVENT [1-800-474-6836 (U.S.)] or 1-800-268-1221 (Canada).

Out-of-Warranty Service: 1-800-633-3600.

Extended Service: Call 1-800-HPINVENT [1-800-474-6836 (U.S.)] or 1-800-268-1221 (Canada). Or, go to the HP Supportpack and Carepaq™ Services Web site at <http://www.hpexpress-services.com/10467a>.

### **HP ToolboxFX**

To check the MFP status and settings and to view problem solving information and online documentation, use the HP ToolboxFX software. You can view the HP ToolboxFX when the MFP is directly connected to your computer or when it is connected to a network. You must have performed a complete software installation to use the HP ToolboxFX. See [Managing and maintaining the multifunction peripheral \(MFP\)](#).

## **Availability of support and service**

Around the world, HP provides a variety of service and support options for purchase. Availability of these programs will vary depending upon your location.

### **HP Care Pack™ Services and Service Agreements**

HP has various service and support options that meet a wide range of needs. These options are not part of the standard warranty. Support services vary by location. For most MFPs HP offers both in-warranty and post-warranty HP Care Pack Services and Service Agreements.

To identify service and support options for this MFP go to <http://www.hpexpress-services.com/10467a> and type the MFP model number. In North America, Service Agreement information can be obtained through HP Customer Care. Call 1-800-HPINVENT [1-800-474-6836 (U.S.)] or 1-800-268-1221 (Canada). In other countries/regions please contact your country/region specific HP Customer Care Center. See the inbox flyer or go to <http://www.hp.com> for the HP Customer Care telephone number in your country/region.

# Repacking the MFP

If your MFP needs to be moved or shipped to another location, perform the following procedure to repack the MFP.



**CAUTION** Shipping damage as a result of inadequate packing is the customer's responsibility. To ensure proper protection during shipment, the MFP must be repackaged properly using the original cushions.

## Repack the MFP



**CAUTION** It is *extremely important* to remove the print cartridges before shipping the MFP. Print cartridges left in the MFP during shipping will leak and entirely cover the MFP engine and other parts with toner.

To prevent damage to the print cartridge, avoid touching the roller, and store the print cartridge in its original packing material or so that it is not exposed to light.

1. Remove all four print cartridges.
2. If you have added optional tray 3, remove and retain.
3. Remove and retain the power cable and interface cable.
4. Remove and retain the output tray.
5. If possible, include print samples and 50 to 100 sheets of paper or other print media that did not print correctly.
6. Use the original shipping container and packing material, if possible. If you have already disposed of the MFP packing material, contact a local mailing service for information about repacking the MFP. HP recommends insuring the equipment for shipment.
7. Include a completed copy of the [Service information form](#).

# Service information form

---

**WHO IS RETURNING THE EQUIPMENT?**

Date:

Person to contact:

Phone:

Alternate contact:

Phone:

Return shipping address:

Special shipping instructions:

---

**WHAT ARE YOU SENDING?**

Model name:

Model number:

Serial number:

Please attach any relevant printouts. Do NOT ship accessories (manuals, cleaning supplies, and so on) that are not required to complete the repair.

---

**HAVE YOU REMOVED THE PRINT CARTRIDGES?**

You must remove them before shipping the MFP, unless a mechanical problem prevents you from doing so.

 Yes. No, I cannot remove them.

---

**WHAT NEEDS TO BE DONE?** (Attach a separate sheet if necessary.)

1. Describe the conditions of the failure. (What was the failure? What were you doing when the failure occurred? What software were you running? Is the failure repeatable?)

2. If the failure is intermittent, how much time elapses between failures?

3. If the unit connected to any of the following, give the manufacturer and model number.

Personal computer:

Modem:

Network:

4. Additional comments:

---

**HOW WILL YOU PAY FOR THE REPAIR?** Under warranty

Purchase/received date:

(Attach proof of purchase or receiving document with original received date.)

 Maintenance contract number: Purchase order number:

**Except for contract and warranty service, a purchase order number and/or authorized signature must accompany any request for service.** If standard repair prices do not apply, a minimum purchase order is required. Standard repair prices can be obtained by contacting an HP-authorized repair center.

Authorized signature:

Phone:

Billing address:

Special billing instructions:





# C Specifications

This section contains information about MFP specifications.

- [Multifunction peripheral \(MFP\) specifications](#)

# Multifunction peripheral (MFP) specifications

**Table C-1** Physical Specifications

Specifications	HP Color LaserJet CM1015 MFP	HP Color LaserJet CM1017 MFP
Device weight (without cartridges)	19.4 kg (42.75 lb)	19.6 kg (43.2 lb)
Device weight, including 4 cartridges	22 kg (48.5 lb)	22.2 kg (48.9 lb)
Device height, desktop to top of fully tilted display <sup>1</sup>	525 mm (20.7 in)	540 mm (21.3 in)
Device height, desktop to top of scanner cover with display folded down	490 mm (19.3 in)	490 mm (19.3 in)
Device height, desktop to top edge of open scanner lid	750 mm (29.55 in)	750 mm (29.55 in)
Depth from front of removable face up output tray to the back of the main input tray, letter paper (input tray extended)	508 mm (20.0 in)	508 mm (20.0 in)
Depth, from front of removable face up output tray to back of main input tray, legal paper (input tray extended)	563 mm (22.2 in)	563 mm (22.2 in)
Depth, from front of fully extended open input tray to back of device	790 mm (31.1 in)	790 mm (31.1 in)
Device width at the scanner	437 mm (17.25 in)	437 mm (17.25 in)

<sup>1</sup> Only dimensional difference between HP Color LaserJet CM1015 MFP and HP Color LaserJet CM1017 MFP.

**Table C-2** Supplies specifications

Print-cartridge life (based on approximately 5% coverage)	Black: 2,500 pages Yellow, cyan, and magenta: 2,000 pages each
---	---

**Table C-3** Electrical specifications

Item	110-Volt models	220-Volt models
<b>Power requirements<sup>1</sup></b>	110-127V (+/-10%)	220-240V (+/-10%)
	50/60 Hz (+/- 2 Hz)	50/60 Hz (+/- 2 Hz)
<b>Rated current</b>	4.0 Amps	2.5 Amps

**Table C-4 Power consumption (average, in watts)<sup>1</sup>**

Product model	Printing (Color) <sup>2</sup>	Printing (Black and White) <sup>2</sup>	Copying <sup>2</sup>	Ready <sup>2</sup>	Power Save	Off
HP Color LaserJet CM1015 MFP	200 W	190 W	150 W	18 W	18 W	0 W
HP Color LaserJet CM1017 MFP	200 W	190 W	150 W	18 W	18 W	0 W

<sup>1</sup> Values subject to change, see [http://www.hp.com/support/cljCM1015\\_CM1017](http://www.hp.com/support/cljCM1015_CM1017) for current information.

<sup>2</sup> Power reported is highest values measured for color and monochrome printing/copying using all standard voltages.

<sup>3</sup> Default time from Ready Mode to Power Save = 0 minutes.

<sup>4</sup> Recovery time from Power Save to start of printing = 14 seconds

<sup>5</sup> Maximum heat dissipation for all models in Ready Mode = 62 BTU/Hour

<sup>6</sup> HP Color LaserJet CM1015 MFP and HP Color LaserJet CM1017 MFP speed is 8 PPM Letter and A4 size.



**WARNING!** Power requirements are based on the country/region where the MFP is sold. Do not convert operating voltages. This can damage the MFP and void the product warranty.

**Table C-5 Environmental specifications**

	Recommended <sup>1</sup>	Operating <sup>1</sup>	Storage <sup>1</sup>
(MFP and print cartridge) Temperature	20° to 27°C (68° to 81°F)	15° to 32.5°C (59° to 90.5°F)	-20° to 40°C (-4° to 104°F)
Relative humidity	20% to 70%	10% to 80%	95% or less

<sup>1</sup> Values are subject to change. See [http://www.hp.com/support/cljCM1015\\_CM1017](http://www.hp.com/support/cljCM1015_CM1017) for current information.

**Table C-6 Acoustic emissions<sup>1</sup>**

Sound Power Level	Declared Per ISO 9296 <sup>1</sup>
Printing/Copying (8 PPM) <sup>2</sup>	L <sub>WAd</sub> = 5.8 Bels (A) [58 dB (A)]
Ready	Inaudible
Sound Pressure Level (SPL)-Bystander Position	Declared Per ISO 9296 <sup>1</sup>
Printing/Copying (8 PPM) <sup>2</sup>	L <sub>pAm</sub> = 46 dB(A)
Ready	Inaudible

<sup>1</sup> Values are subject to change. See [http://www.hp.com/support/cljCM1015\\_CM1017](http://www.hp.com/support/cljCM1015_CM1017) for current information.

<sup>2</sup> Configuration tested: HP Color LaserJet CM1017 MFP, continuous monochrome printing on A4 paper at 8 PPM.

<sup>3</sup> HP Color LaserJet CM1015 MFP and HP Color LaserJet CM1017 MFP speed is 8 PPM Letter and A4 size.

**Table C-7 Paper and print media support specifications table**

Category	Specifications
Acid content	5.5 pH to 8.0 pH
Caliper	0.094 to 0.18 mm (3.0 to 7.0 mils)

**Table C-7** Paper and print media support specifications table (continued)

Category	Specifications
Curl in ream	Flat within 5 mm (0.2 inch)
Cut-edge conditions	Cut with sharp blades with no visible fray
Fusing compatibility	Must not scorch, melt, offset, or release hazardous emissions when heated to 210°C (410°F) for 0.1 second
Grain	Long Grain
Moisture content	4% to 6% by weight
Smoothness	100 to 250 Sheffield

For complete print media specifications for all HP LaserJet Printers, see the *HP LaserJet PrinterFamily Print Media Guide*. To download the guide in PDF format, go to <http://www.hp.com/support/ljpaperguide>.

# D Regulatory information

This section contains the following information:

- [Introduction](#)
- [FCC regulations](#)
- [Environmental Product Stewardship program](#)
- [Declaration of conformity](#)
- [Country/region-specific safety statements](#)

# Introduction

This section contains the following regulatory information:

- [FCC regulations](#)
- [Environmental Product Stewardship program](#)
- [Service and support](#)
- [Declaration of conformity](#)
- [Laser safety statement](#)
- [Canadian DOC statement](#)
- [Korean EMI statement](#)
- [VCCI statement \(Japan\)](#)
- [Finnish laser statement](#)

# FCC regulations

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy. If this equipment is not installed and used in accordance with the instructions, it can cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation; the presence of interference can be determined by turning the equipment off and on. If this equipment does cause harmful interference to radio or television communications, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase distance between equipment and receiver.
- Connect equipment to an outlet on a circuit different from that to which the receiver is located.
- Consult your dealer or an experienced radio/television technician.



---

**NOTE** Any changes or modifications to the MFP that are not expressly approved by HP could void the user's authority to operate this equipment.

Use of a shielded interface cable is required to comply with the Class B limits of Part 15 of FCC rules.

---

# Environmental Product Stewardship program

## Protecting the environment

Hewlett-Packard Company is committed to providing quality products in an environmentally sound manner. This product has been designed with several attributes to minimize impacts on our environment.

## Ozone production

This product generates no appreciable ozone gas (O<sub>3</sub>).

## Power consumption

Power usage drops significantly while in sleep mode, which saves natural resources and saves money without affecting the high performance of this product. This product qualifies for ENERGY STAR® (Version 3.0), which is a voluntary program to encourage the development of energy-efficient office products.



ENERGY STAR® and the ENERGY STAR mark are U.S. registered marks. As an ENERGY STAR® partner, Hewlett-Packard Company has determined that this product meets ENERGY STAR® Guidelines for energy efficiency. For more information, see <http://www.energystar.gov/>.

## Paper use

This product's duplex feature (two-sided printing); see [Print on both sides of the paper](#) and N-up printing [multiple pages printed on one page] capability can reduce paper usage and the resulting demands on natural resources.

## Plastics

Plastic parts over 25 grams are marked according to international standards that enhance the ability to identify plastics for recycling purposes at the end of the product's life.

## HP LaserJet printing supplies

It is easy to return and recycle your empty HP LaserJet print cartridges—free of charge—with HP Planet Partners. HP is committed to providing inventive, high-quality products and services that are environmentally sound, from product design and manufacturing to distribution, operation and recycling processes. We ensure your returned HP LaserJet print cartridges are recycled properly, processing them to recover valuable plastics and metals for new products and diverting millions of tons of waste from landfills. Since this cartridge is being recycled and used in new materials, it will not be returned to you. Your empty HP LaserJet print cartridges are recycled responsibly when you participate in the HP Planet Partners program. Thank you for being environmentally responsible!

In many countries/regions, this product's printing supplies (for example, print cartridge) can be returned to HP through the HP Printing Supplies Returns and Recycling Program. An easy-to-use and free takeback program is available in over 35 countries/regions. Multi-lingual program information and instructions are included in every new HP LaserJet print cartridge and supplies package.



## **HP Printing Supplies Returns and Recycling Program Information**

Since 1992, HP has offered HP LaserJet supplies return and recycling free of charge. In 2004, HP Planet Partners for LaserJet Supplies was available in 85% of the world market where HP LaserJet supplies are sold. Postage-paid and pre-addressed labels are included within the instruction guide in most HP LaserJet print cartridge boxes. Labels and bulk boxes are also available through the Web site: <http://www.hp.com/recycle>.

Use the label to return empty, original HP LaserJet cartridges only. Please do not use this label for, non-HP cartridges, refilled or remanufactured cartridges or warranty returns. Printing supplies or other objects inadvertently sent to the HP Planet Partners program cannot be returned.

More than 10 million HP LaserJet print cartridges were recycled globally in 2004 through the HP Planet Partners supplies recycling program. This record number represents 26 million pounds of print cartridge materials diverted from landfills. Worldwide, in 2004, HP recycled an average of 59% of the print cartridge by weight consisting primarily of plastic and metals. Plastics and metals are used to make new products such as HP products, plastic trays and spools. The remaining materials are disposed of in an environmentally responsible manner.

### **U.S. returns**

For a more environmentally responsible return of used cartridges and supplies, HP encourages the use of bulk returns. Simply bundle two or more cartridges together and use the single, pre-paid, pre-addressed UPS label that is supplied in the package. For more information in the U.S., call 1-800-340-2445 or visit the HP Printing Supplies Returns and Recycling Program Web site at: <http://www.hp.com/go/recycle>.

### **Non-U.S. returns**

Non-U.S. customers should visit the <http://www.hp.com/go/recycle> Web site for further information regarding availability of the HP Supplies Returns and Recycling program.

### **Paper**

This product is capable of using recycled papers, when the paper meets the guidelines outlined in the *HP LaserJet Printer Family Print Media Guide*. Go to <http://www.hp.com/support/ljpaperguide> to download this guide in PDF format. This product is suitable for the use of recycled paper according to EN12281:2002.


### **Material restrictions**

This product does not contain added mercury.

This product does not contain batteries.

For recycling information, you can contact <http://www.hp.com/go/recycle> or contact your local authorities or the Electronics Industry Alliance at <http://www.eiae.org>.

## Disposal of waste equipment by users in private households in the European Union



This symbol on the product or on its packaging indicates that this product must not be disposed of with your other household waste. Instead, it is your responsibility to dispose of your waste equipment by handing it over to a designated collection point for the recycling of waste electrical and electronic equipment. The separate collection and recycling of your waste equipment at the time of disposal will help to conserve natural resources and ensure that it is recycled in a manner that protects human health and the environment. For more information about where you can drop off your waste equipment for recycling, please contact your local city office, your household waste disposal service or the shop where you purchased the product.

### Material safety data sheet

Material Safety Data Sheets (MSDS) for supplies containing chemical substances, such as toner, can be obtained by contacting the HP Web site at <http://www.hp.com/go/msds> or <http://www.hp.com/hpinfo/community/environment/productinfo/safety>.

### Extended warranty

HP Care Pack provides coverage for the HP hardware product and all HP supplied internal components, excluding consumable items. The hardware maintenance covers a specified period of time from date of the HP product purchase. The customer can either purchase HP Care Pack within the standard HP product warranty period, or purchase a post-warranty Care Pack if the standard warranty has expired. For more information, contact the HP Customer Care Service and HP Customer Support group.

Spare parts and consumable supplies for this product will be available for at least five years after production has stopped.

### For more information

To obtain information about these environmental topics:

- Product environmental profile sheet for this and many related HP products
- HP's commitment to the environment
- HP's environmental management system
- HP's end-of-life product return and recycling program
- MSDS

See: <http://www.hp.com/go/environment> or <http://www.hp.com/hpinfo/community/environment/productinfo/safety>.

# Declaration of conformity

## Declaration of Conformity

according to ISO/IEC Guide 22 and EN 45014

**Manufacturer's Name:** Hewlett-Packard Company  
**Manufacturer's Address:** 11311 Chinden Boulevard,  
Boise, Idaho 83714-1021, USA

**declares, that the product**

**Product Name:** HP Color LaserJet CM1015/CM1017 MFP  
**Regulatory Model Number<sup>3)</sup>:** BOISB-0409-03

**Product Options:** Including: Q6459A —Optional 250-Sheet Input Tray  
All  
**Print Cartridges:** Q6000A, Q6001A, Q6002A, Q6003A

**conforms to the following Product Specifications:**

**Safety:** IEC 60950-1:2001 / EN60950-1:2001 +A11  
IEC 60825-1:1993 +A1 +A2/  
EN 60825-1:1994 +A1 +A2 (Class 1 Laser/LED Product)  
GB4943-2001

**EMC:** CISPR22:1993 +A1 +A2 / EN55022:1994 +A1 +A2 Class B<sup>1)</sup>  
EN 61000-3-2:2000  
EN 61000-3-3:1995 +A1  
EN 55024:1998 +A1 +A2  
FCC Title 47 CFR, Part 15 Class B<sup>2)</sup> / ICES-003, Issue 4  
GB9254-1998, GB17625.1-2003

### Supplementary Information:

The product herewith complies with the requirements of the EMC Directive 89/336/EEC and the Low Voltage Directive 73/23/EEC, and carries the CE-Marking accordingly.

- 1) The product was tested in a typical configuration with Hewlett-Packard Personal Computer Systems.
- 2) This Device complies with Part 15 of the FCC Rules. Operation is subject to the following two Conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
- 3) For regulatory purposes, this product is assigned a Regulatory model number. This number should not be confused with the product name or the product number(s).

Boise, Idaho 83714-1021, USA

**January 4, 2006**

### For regulatory topics only:

**Australia Contact:** Product Regulations Manager, Hewlett-Packard Australia Ltd., 31-41 Joseph Street, Blackburn, Victoria 3130, Australia.  
**European Contact:** Your Local Hewlett-Packard Sales and Service Office or Hewlett-Packard GmbH, Department HQ-TRE / Standards Europe, Herrenberger Strasse 140, D-71034 Böblingen, Germany, (FAX: +49-7031-14-3143)  
**USA Contact:** Product Regulations Manager, Hewlett-Packard Company, PO Box 15, Mail Stop 160, Boise, Idaho 83707-0015, USA, (Phone: 208-396-6000)

## Country/region-specific safety statements

### Laser safety statement

The Center for Devices and Radiological Health (CDRH) of the U.S. Food and Drug Administration has implemented regulations for laser products manufactured since August 1, 1976. Compliance is mandatory for products marketed in the United States. The MFP is certified as a “Class 1” laser product under the U.S. Department of Health and Human Services (DHHS) Radiation Performance Standard according to the Radiation Control for Health and Safety Act of 1968.

Since radiation emitted inside the MFP is completely confined within protective housings and external covers, the laser beam cannot escape during any phase of normal user operation.



**WARNING!** Using controls, making adjustments, or performing procedures other than those specified in this user guide can result in exposure to hazardous radiation.

### Canadian DOC statement

Complies with Canadian EMC Class B requirements.

« Conforme à la classe B des normes canadiennes de compatibilité électromagnétiques (CEM). »

### Korean EMI statement

B급 기기 (가정용 정보통신기기)

이 기기는 가정용으로 전자파적합등록을 한 기기로서  
주거지역에서는 물론 모든지역에서 사용할 수 있습니다.

### VCCI statement (Japan)

この装置は、情報処理装置等電波障害自主規制協議会（VCCI）の基準に基づくクラスB情報技術装置です。この装置は、家庭環境で使用することを目的としていますが、この装置がラジオやテレビジョン受信機に近接して使用されると、受信障害を引き起こすことがあります。

取扱説明書に従って正しい取り扱いをして下さい。

## Japanese Power Cord Statement

製品には、同梱された電源コードをお使い下さい。  
同梱された電源コードは、他の製品では使用出来ません。

# **Finnish laser statement**

## **LASERTURVALLISUUS**

### **LUOKAN 1 LASERLAITE**

#### **KLASS 1 LASER APPARAT**

HP Color LaserJet CM1015/CM1017 -laserkirjoitin on käyttäjän kannalta turvallinen luokan 1 laserlaite. Normaalisissa käytössä kirjoittimen suojakotelointi estää lasersäteen pääsyn laitteen ulkopuolelle.

Laitteen turvallisuusluokka on määritetty standardin EN60825-1 (1994) mukaisesti.

#### **VAROITUS!**

Laitteen käyttäminen muulla kuin käyttöohjeessa mainitulla tavalla saattaa altistaa käyttäjän turvallisuusluokan 1 ylittävälle näkymättömälle lasersäteilylle.

#### **VARNING!**

Om apparaten används på annat sätt än i bruksanvisning specificerats, kan användaren utsättas för osynlig laserstrålning, som överskrider gränsen för laserklass 1.

#### **HUOLTO**

HP Color LaserJet CM1015/CM1017 MFP -kirjoittimen sisällä ei ole käyttäjän huollettavissa olevia kohteita. Laitteen saa avata ja huoltaa ainoastaan sen huoltamiseen koulutettu henkilö. Tällaiseksi huoltotoimenpiteeksi ei katsota väriainekasetin vaihtamista, paperiradan puhdistusta tai muita käyttäjän käsikirjassa lueteltuja, käyttäjän tehtäväksi tarkoitettuja ylläpitotoimia, jotka voidaan suorittaa ilman erikoistyökaluja.

#### **VARO!**

Mikäli kirjoittimen suojakotelo avataan, olet alttiina näkymättömälle lasersäteilylle laitteen ollessa toiminnassa. Älä katso säteeseen.

#### **VARNING!**

Om laserprinterns skyddshölje öppnas då apparaten är i funktion, utsättas användaren för osynlig laserstrålning. Betrakta ej strålen.

Tiedot laitteessa käytettävän laserdiodin säteilyominaisuuksista:

Aallonpituus 770-800 nm

Teho 5 mW

Luokan 3B laser

# Index

## Symbols/Numerics

4-Color option 67

## A

accessories

part numbers 214

Adaptive Halftoning options 66

add

folder destinations

(Windows) 80, 130

adding memory 206

adding paper 50

address, MFP

Macintosh, resolve

problems 46

adhesive labels

specifications 13, 15, 128

agreements, maintenance 223,  
236

alerts, setting up 148

## B

background, gray 181

bands, resolve problems 180

battery specifications 235

bins, output

features 3

jams, clearing 198

black and white printing

resolve problems 184

black and white scanning 86

Black cartridge

life expectancy 158

part number 214

Black Only option 67

blank pages, resolve

problems 187

blank scans, resolve

problems 192

BOOTP 106

both sides, printing on 42, 60

built-in networking

information page, printing 140

buttons, control panel 18

buttons, HP Color LaserJet

CM1017 MFP control panel 21,

112

## C

cables

USB, resolve problems 188

calibrating MFP 136, 168

Cancel Job 62

canceling

scan jobs 85

cardstock

specifications 13

cartridge out override 163

cartridges

HP fraud hotline 160

life expectancy 158

part numbers 214

recycling 234

replacing 159

status page, printing 142

status, viewing with

HP ToolboxFX 148

storage specifications 229

characters, resolve problems 182

checking DIMM installation 211

clearing jams

common locations 195

input areas 200

inside MFP 196, 199

output areas 198

color

calibration 136, 168

features 64

HP ImageREt 2400 64

managing options 44

Manual adjustment options 65

matching 68

printing in grayscale 44

resolve problems 183

scanning settings 85

setting options 43

settings, changing 65

sRGB 68

Color tab settings 42

components

locating 5

Configuration page

printing 140

configurations

network 99

configurations, MFP 2

consumables

life expectancies 158

part numbers 214

recycling 234

specifications 228

status page, printing 142

contracts, maintenance 223, 236

contrast settings

copy 73

control panel

HP ToolboxFX settings 123,  
153

messages, resolve

problems 172

scanning from (Macintosh) 83

scanning from (Windows) 80,  
130

copies

lines, unwanted 190

copying

cancel a job 70

contrast, adjusting 73

enlarging 74

- quality, adjusting 71
  - reducing 74
- cover pages 41
- covers 41
- covers, document
  - paper specifications 13
- creases, resolve problems 183
- crooked pages 182, 186
- curled media 182
- customer support
  - maintenance
    - agreements 223, 236
    - repacking MFP 224
    - service information form 225
- Cyan cartridge
  - life expectancy 158
  - part number 214

**D**

- dark copies, resolve
  - problems 190
- darkness, contrast settings
  - copy 73
- declaration of conformity 237
- default settings, restoring 58, 126
- deleting print jobs 62
- Demo page, printing 140
- destinations
  - to e-mail (Windows) 80, 130
- destinations, add folder
  - Windows 80, 130
- Detail halftone option 65
- device discovery 104
- digital cameras, color
  - matching 68
- DIMM
  - checking installation 205, 211
- documentation 217
- Documentation tab,
  - HP ToolboxFX 149
- dots per inch (dpi)
  - HP ImageREt 2400 64
  - specifications 3
- dots, resolve problems 180
- double-sided printing 42, 60
- downloading drivers 10
- dpi (dots per inch)
  - HP ImageREt 2400 64
  - specifications 3

- drivers
  - accessing 40
  - downloading 10
  - features 41, 58, 125
  - Macintosh, resolve
    - problems 46
  - opening 57, 124
  - operating systems
    - supported 8
  - presets 41
  - restoring default settings 58, 126
  - settings, changing 59, 126
  - uninstalling 35
  - Windows, features 30
- duplex-printing accessory
  - loading 42
- duplexing 60

**E**

- E-label reader 173
- Edge Control 66
- electrical specifications 228
- embedded Web server
  - using 155
- enabling memory
  - Windows 211
- energy consumption 228
- engine, cleaning 137, 162
- enlarging
  - copies 74
- envelopes
  - printing 56
  - specifications 13, 15, 127
- environmental
  - features 234
  - MFP specifications 229
- error messages
  - control panel 172
- Event log 148
- extended warranty 223, 236
- e-mail alerts, setting up 148
- e-mail, add scanning destinations
  - Windows 80, 130
- e-mail, scanning to
  - Macintosh 83
  - resolution settings 86

**F**

- faded print 180

- FCC statements 233
- features
  - color 64
  - drivers 41, 58, 125
- feeding problems, resolve
  - problems 186
- file, scanning to
  - Macintosh 83
- first page, use different paper 41
- 4-Color option 67
- fraud hotline 160

**G**

- gateways
  - overview 107
- gray background, resolve
  - problems 181
- grayscale
  - resolve problems 184
  - scanning 86
- grayscale printing 44

**H**

- halftone options 65
- heavy paper
  - specifications 13
- Help tab, HP ToolboxFX 149
- HP built-in networking
  - information page, printing 140
- HP Color LaserJet CM1015 MFP
  - control panel
    - lights and buttons,
      - description 18
- HP Color LaserJet CM1017 MFP
  - control panel
    - lights and buttons,
      - description 21, 112
- HP customer care 222
- HP Device Configuration 45
- HP Director 8
- HP fraud hotline 160
- HP ImageREt 2400 64
- HP LaserJet glossy paper
  - printing 16, 128
- HP LaserJet paper 216
- HP LaserJet photo paper
  - media 16, 128
- HP LaserJet Tough paper 16, 129
- HP multipurpose paper 216



- HP Printing Supplies Returns and Recycling Program 234
- HP Solution Center 8
- HP SupportPack 223, 236
- HP ToolboxFX
  - calibrating MFP 136, 137, 168
  - Documentation tab 149
  - Help tab 149
  - Network Settings tab 154
  - operating systems supported 8
  - Status tab 148
  - System Settings tab 120, 150
  - toner level, checking from 158
- humidity specifications
  - MFP environment 229
- I**
- image quality
  - HP ImageREt 2400 64
  - HP ToolboxFX settings 121, 151
  - print, resolve problems 179
  - scans, resolve problems 191
- ImageREt 2400 64
- index printing 87
- index, photo 97
- information pages
  - Configuration 102
  - Network configuration 102
- information pages, printing 140
- input trays
  - features 3
  - feeding problems, resolve problems 186
  - jams, clearing 200
  - loading 50
  - part numbers 215
- installing
  - Macintosh printer drivers 38
  - Macintosh software 38, 39
- installing DIMM 207
- installing memory 207
- interface ports
  - cables, ordering 215
  - types included 3
- Internet protocol (IP)
  - overview 105

- IP address
  - BOOTP 106
  - Macintosh, resolve problems 46
  - overview 105
- IP addressing 104
- J**
- jams
  - back of MFP 199
  - causes of 195
  - input areas 200
  - inside MFP 196
  - output areas 198
  - top output area 199

- K**
- keys, control panel 18
- keys, HP Color LaserJet CM1017
  - MFP control panel 21, 112

- L**
- labels
  - specifications 13, 15, 128
- language
  - information pages 140
- laser safety statements 238
- LaserJet paper 216
- letterhead
  - printing 16, 128
- life expectancies, supplies 158
- light copies, resolve problems 190
- light print, resolve problems 180
- lightness
  - copy contrast 73
  - faded print resolve problems 180
- lights
  - locating 18, 21, 112
- lines
  - copies 190
- lines, resolve problems
  - printed pages 180
- loading media
  - tray 1 50
  - tray 2 51
- loose toner, resolve problems 181

- M**
- Macintosh
  - drivers 8
  - drivers, accessing 40
  - drivers, resolve problems 46
  - features supported 8
  - MFP software 37
  - problems, resolve 46
  - scan driver 8
  - scanning from control panel 83
  - scanning from TWAIN-compliant software 84
  - scanning page-by-page 83
  - scanning to e-mail 83
  - scanning to file 83
  - USB card, resolve problems 47
- Macintosh Installer
  - operating systems supported 8
- Magenta cartridge
  - life expectancy 158
  - part number 214
- mailing labels
  - specifications 13, 15, 128
- maintenance
  - agreements 223, 236
  - replacing print cartridges 158
- managing network 101
- Manual color options 65
- manual duplexing 60
- manuals 217
- matching, color 68
- Material Safety Data Sheet 236
- media
  - curled, resolve problems 182
  - envelopes 15, 56, 127
  - first page 41
  - HP LaserJet glossy paper 16, 128
  - HP LaserJet photo paper 16, 128
  - HP Solution Center settings 123, 153
  - HP, ordering 216
  - jams 195
  - labels 15, 128
  - letterhead 16, 128
  - loading trays 50

- pages per sheet 41
- resolve problems 185
- selecting 12
- specifications 229
- transparencies 16, 128
- types that may damage the printer 14
- types to avoid 14
- wrinkled 183
- memory
  - enabling 43, 205, 211
  - installation 205
  - installing 207
  - slots 4
  - working with 205
- memory card
  - view photo 90
- memory cards
  - error messages 178
- memory cards insertion 87
- memory cards, photo
  - inserting 88
- mercury specifications 235
- messages
  - control panel 172
- messaging and management, network 104
- MFP
  - drivers 40
- MFP memory
  - addition 206
- MFP software
  - Macintosh 37
- monitors, color matching 68
- multiple pages per sheet 41
- multipurpose paper, HP 216

**N**

- n-up printing 41
- network
  - configuration 99
  - configuring 99
  - device discovery 104
  - IP address 134
  - IP addressing 104
  - messaging and management 104
  - MFP control panel 99
  - resolve problems 99

- supported protocols 99, 104
- using MFP control panel 102
- network configuration
  - direct printing 100
  - making changes 34, 101
  - shared printing 100
- Network configuration page 102
- network password
  - changing 101
  - setting 101
- network settings
  - changing 101
  - viewing 101
- Network Settings tab, HP ToolboxFX 154
- network setup 100
- networks
  - information pages, printing 140
- Neutral Grays options 67
- non-HP print cartridges 159

**O**

- OCR software
  - installing 84
- on-site service agreements 236
- online customer support 222
- operating environment, specifications 229
- operating systems supported 8
- optical character recognition software
  - installing 84
- ordering accessories
  - information 213
- ordering supplies and accessories 214
- output bin
  - features 3
- output bin extender 5
- output bins
  - jams, clearing 198
- output quality
  - HP ImageREt 2400 64
  - HP ToolboxFX settings 121, 151
  - print, resolve problems 179
  - scan, resolve problems 191
- overhead transparencies
  - specifications 13, 16, 128

- ozone specifications 234

**P**

- packaging MFP 224
- Page Setup 57, 124
- page-by-page scanning (Macintosh) 83
- pages
  - blank 187
  - not printing 188
  - printing slowly 187
  - skewed 182, 186
- pages per sheet 41
- paper
  - curled, resolve problems 182
  - first page 41
  - HP LaserJet Tough paper 16, 129
  - HP Solution Center settings 123, 153
  - HP, ordering 216
  - jams 195
  - letterhead 16, 128
  - loading trays 50
  - pages per sheet 41
  - resolve problems 185
  - selecting 12
  - specifications 229
  - wrinkled 183
- paper input trays
  - features 3
  - feeding problems, resolve problems 186
  - jams, clearing 200
  - loading 50
  - part numbers 215
- paper output bin
  - features 3
- paper output bins
  - jams, clearing 198
- part numbers
  - accessories 213
- parts
  - part numbers 214
  - user-replaceable 216
- phone numbers
  - HP fraud hotline 160
  - HP Printing Supplies Returns and Recycling Program 235
  - support 222

- photo
  - rotate from display screen 90
  - view from memory card 90
- photo index 87
- photo memory cards 4
- photo printing 87
- photos
  - memory cards, inserting 88
  - printing an index 97
  - printing directly from the memory card 93, 132
- photos, resolve problems
  - scanning 191
- pick-up rollers, ordering 216
- pixels per inch (ppi)
  - scanning 85
- platforms supported 8
- ports
  - cables, ordering 215
  - solve Macintosh problems 47
  - types included 3
- PostScript driver, HP ToolboxFX
  - settings 124, 154
- power
  - requirements 228
- ppi (pixels per inch)
  - scanning 85
- preprinted paper
  - printing on 16, 128
- presets 41
- print cartridge
  - replacing 164
- print cartridges
  - HP fraud hotline 160
  - life expectancy 158
  - part numbers 214
  - recycling 234
  - replacing 159
  - status page, printing 142
  - status, viewing with
    - HP ToolboxFX 148
  - storage specifications 229
- Print dialog box 57, 124
- print driver
  - PostScript 3
- print quality
  - HP ImageREt 2400 64
  - HP ToolboxFX settings 121, 151
  - resolve problems 179
  - specifications 3
- print servers
  - information page, printing 140
- printer drivers
  - Macintosh 38
  - uninstalling 35
- printer-drivers
  - downloading 10
  - features 58, 125
  - opening 57, 124
  - operating systems
    - supported 8
  - restoring default settings 58, 126
  - settings, changing 59, 126
  - Windows, features 30
- printing
  - both sides 60
  - canceling 62
  - photos, from the memory card 93, 132
  - photos, index of 97
  - resolve problems 187, 188
  - Windows 59, 126
- printing environment 104

**Q**

- quality
  - HP ImageREt 2400 64
  - HP ToolboxFX settings 121, 151
  - print, resolve problems 179
  - scans, resolve problems 191
  - specifications 3

**R**

- Readiris OCR software
  - installing 84
- rear output door
  - features 3
- recycling
  - plastics 234
  - print cartridges 234
- reducing
  - copies 74
- refilled print cartridges 159
- refilling paper 50
- regulatory statements
  - declaration of conformity 237
  - FCC 233
  - laser safety 238
  - Material Safety Data Sheet 236
- repacking MFP 224
- repetitive defects, resolve problems 183
- replacing print cartridges 159
- reports, MFP
  - Configuration page 102
  - Network configuration page 102
- reports, printing 140
- resizing documents
  - copying 74
- resolution
  - HP ImageREt 2400 64
  - scanning 85
  - specifications 3
- resolve problems
  - blank pages 187
  - calibrating MFP 136, 168
  - color 183
  - Configuration page, printing 102, 140
  - control panel messages 172
  - curled media 182
  - Demo page, printing 140
  - faded print 180
  - feeding problems 186
  - jams 195
  - lines, printed pages 180
  - loose toner 181
  - Network configuration page, printing 102
  - pages not printing 188
  - pages printing slowly 187
  - paper 185
  - print quality 179
  - repetitive defects 183
  - replacing print cartridges 159
  - scan quality 191
  - skewed pages 182, 186
  - text 182
  - toner scatter 183
  - toner smear 181
  - toner specks 180
  - USB cables 188
  - wrinkles 183
- restoring default settings 58, 126

- RGB color options 66, 68
- rollers, ordering 216
- S**
- scaling documents
  - copying 74
- Scan To button,
  - programming 80, 130
- scanners, color matching 68
- scanning
  - black and white 86
  - blank pages, resolve problems 192
  - canceling 85
  - color 85
  - from device control panel (Macintosh) 83
  - from device control panel (Windows) 80, 130
  - grayscale 86
  - HP Solution Center (Windows) 82
  - methods 78
  - page-by-page (Macintosh) 83
  - photos 85
  - quality, resolve problems 191
  - resolution 85
  - speed, resolve problems 192
  - to e-mail (Macintosh) 83
  - to file (Macintosh) 83
  - TWAIN-compliant software 84
  - WIA-compliant software 84
- scatter, resolve problems 183
- screen color matching 68
- selection guidelines
  - media 12
- separation pad, ordering 216
- servers
  - information page, printing 140
- service
  - agreements 223, 236
  - HP ToolboxFX settings 123, 153
  - information form 225
  - part numbers 214
  - repacking MFP 224
- settings
  - changing 59, 126
  - color 65
  - Configuration page 102
  - driver presets 41
  - HP ToolboxFX 120, 150
  - Network configuration page 102
  - restoring defaults 58, 126
- shipping MFP 224
- size, copy
  - reducing or enlarging 74
- sizes, media
  - selecting trays 57, 125
- skewed pages 182, 186
- slots
  - memory 4
- slow speed, resolve problems
  - scanning 192
- smearred toner, resolve problems 181
- Smooth halftone option 65
- software
  - downloading 10
  - features 58, 125
  - HP Device Configuration 45
  - HP ToolboxFX 147
  - Macintosh 38
  - operating systems supported 8
  - Readiris OCR, installing 84
  - scanning from TWAIN or WIA 84
  - settings, changing 59, 126
  - uninstalling 35
  - Windows, features 30
- solve problems
  - Macintosh 46
- special media
  - envelopes 15, 56, 127
  - HP LaserJet glossy paper 16, 128
  - labels 15, 128
  - letterhead 16, 128, 129
  - specifications 13
  - transparencies 16, 128
- specifications
  - envelopes 15, 127
  - environmental 229
  - labels 15, 128
  - Material Safety Data Sheet 236
  - MFP 228
  - MFP features 3
  - paper 229
  - transparencies 16, 128
- specks, resolve problems 180
- speed
  - scanning, resolve problems 192
- spots, resolve problems 180
- sRGB 66, 68
- status
  - alerts, HP ToolboxFX 148
  - Supplies Status page, printing 142
  - viewing with HP ToolboxFX 148
- Status tab, HP ToolboxFX 148
- stopping printing 62
- storing
  - MFP 229
  - print cartridges 159
- streaks, resolve problems 180
- subnet mask
  - overview 106
- subnets
  - overview 106
- Supplementary Documentation
  - part numbers 213
- supplies
  - life expectancies 158
  - recycling 234
  - specifications 228
  - status page 142
  - status, viewing with HP ToolboxFX 148
- supplies and consumables
  - part numbers 213
- support
  - maintenance
    - agreements 223, 236
    - part numbers 214
    - repacking MFP 224
    - service information form 225
  - supported network protocols 104
  - SupportPack, HP 223, 236
  - System Settings tab, HP ToolboxFX 120, 150
- T**
- technical support
  - maintenance
    - agreements 223, 236

- part numbers 214
- repacking MFP 224
- service information form 225
- telephone numbers
  - HP fraud hotline 160
  - HP Printing Supplies Returns and Recycling Program 235
  - support 222
- temperature specifications
  - MFP environment 229
- text, resolve problems
  - misformed characters 182
- toner
  - loose, resolve problems 181
  - scatter, resolve problems 183
  - smearred, resolve problems 181
  - specks, 180
- Toolbox. See HP ToolboxFX
- top output bin
  - features 3
- Transmission Control Protocol (TCP)
  - overview 105
- transparencies
  - specifications 13, 16, 128
- Trapping options 66
- tray 1
  - loading 50
- tray 2
  - loading 51
- tray 3
  - loading 51
  - part number 215
- trays
  - double-sided printing 42
  - features 3
  - feeding problems, resolve problems 186
  - jams, clearing 200
  - loading 50
  - part numbers 215
- TWAIN-compliant software, scanning from 84
- two-sided printing 42, 60
- types, media
  - HP Solution Center settings 123, 153
  - selecting trays by 57, 125

**U**

- uninstalling software
  - using Windows OS 35
- USB port
  - resolve problems 188
  - solve Macintosh problems 47
  - type included 3
- User Datagram Protocol (UDP)
  - overview 105
- user guide
  - part numbers 217
- user-replaceable parts 213, 216

**V**

- vertical lines, resolve problems 180
- vertical white or faded stripes 190
- voltage requirements 228

**W**

- warranty
  - extended 223, 236
  - print cartridge 221
  - product 219, 220
- watermarks
  - cover page 41
- wavy paper, resolve problems 182
- Web sites
  - customer support 222
  - HP Printing Supplies Returns and Recycling Program 235
  - Material Safety Data Sheet 236
- white or faded stripes 190
- WIA-compliant software, scanning from 84
- Windows
  - add scan-to e-mail or folder destinations 80, 130
  - add scanning e-mail destinations 80, 130
  - driver features 58, 125
  - enabling memory 211
  - printing from 59, 126
  - scan by using HP Solution Center 82
  - scan driver 8

- scanning from device control panel 80, 130
- scanning from TWAIN or WIA software 84
- uninstalling software 35
- Versions supported 8
- wrinkles, resolve problems 183

**Y**

- Yellow cartridge
  - life expectancy 158
  - part number 214





© 2006 Hewlett-Packard Development Company, L.P.

[www.hp.com](http://www.hp.com)



CB394-90907