

MPN: LVO231815UNI

# Fiber patch cords LC Uniboot to LC Uniboot duplex OM4 10m 3.0mm LSZH (Grade C)


This Uniboot cable comes with a lot of great features to take your networking setup to the next level, Uniboot cables comes with both the fibre leads coated in a single jacket, meaning there is more room for airflow in the rack. This also means the insertion loss is low.

Another special feature of the Uniboot cable is the option to switch polarities, simply remove the top cover and you can swap the connectors to change the polarity, no need to swap to another cable with Uniboot.

This cable lives up to the OM4 fibre standard to connect to high speed and legacy networks like 10/40/100 gigabit. This cable standard is ideal for for connecting 40G BIDI SR, 10G SR, QSFP+, SFP+ transceivers etc.

The cable is made of LSZH material to live up to Telecordia, EIA TIA or IEC standards.

- UniBoot to minimize insertionloss
- Easy to handle
- LSZH (Low Smoke Zero Halogen) and flame retardant
- Pre tested with test report
- Reverse Polarity—with a few simple steps, the connectors polarity of the LC Uniboot fiber patch cables can be reversed without need of connector re-termination.
- Quick Release Latch—the latch of LC Uniboot fiber patch cable allows for the quick and easy release of this connector from the adapter panel, which makes great sense in the growing trend of high density applications.



## Specifikationer

Battery	Battery Type	NONE - Only use for non-battery items
Features	Cable length	10 m
	Cable type	Duplex
	Certification	Rohs
	Cladding diameter	125 um
	Connector 1	LC/UPC
	Connector 1 gender	Male
	Connector 2	LC/UPC
	Connector 2 gender	Male
	Connector gender	Male/Male
	Ethernet interface type	10 Gigabit Ethernet, 40 Gigabit Ethernet, 100 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet
	Fiber mode structure	Multi-mode
	Fibre optic type	OM4
	Full duplex	Yes

Features	Halogen-free	Yes
	Insertion loss	0,18 dB
	Jacket material	Low smoke zero halogen (LSZH)
	Plug and Play	Yes
	Product colour	Blue
	Wavelengths supported	850, 1300 nm
Package dimensions	Depth (package,cm)	8 cm
	Gross Weight (Package, kg)	0,035 kg
	Height (package,cm)	15 cm
	Width (package,cm)	15 cm
Packaging data	Quantity per pack	1 styck
Product dimensions	Net Weight (Product, kg)	0,034 kg
	Product Height	1000 cm
	Product Width	0,3 cm
Technical details	Doesn't contain	Halogen
	Sustainability certificates	RoHS
	Sustainability compliance	Yes
Vendor information	Brand Name	Lanview
	Warranty	5 År
Weight & dimensions	Cable diameter	3 mm

## Andra produkter i denna serie

Cable length	
1,0	LVO231810UNI
2,0	LVO231811UNI
3,0	LVO231812UNI
5,0	LVO231813UNI
10,0	LVO231815UNI
15,0	LVO231820UNI
20,0	LVO231825UNI
25,0	LVO231823UNI

## Andra bilder

