# Epson TM-P60II Series

## DATASHEET





The Epson TM-P60II is a second-generation, wireless mobile receipt printer from the world's leading POS printer manufacturer <sup>1</sup>. Offering a brilliantly simple printing solution, the hand-held TM-P60II prints directly from mobile devices<sup>2</sup> – no drivers needed.

Unique, built-in intelligence, called Epson ePOS-Print, enables the TM-P60II to receive XML commands from web applications, and to print directly from popular web browsers. This makes integration and maintenance easy.

To help serve customers quickly, the high-performance TM-P60II prints receipts at up to 100mm/sec. Drop-in paper loading ensures there are no delays.

The TM-P60II is designed for maximum reliability, with a rugged case. Its battery lasts for up to 46 hours in Bluetooth mode, and up to four batteries can be charged simultaneously using the optional charging unit.

## **KEY FEATURES**

- Wireless, hand-held POS printing
- Prints receipts at up to 100mm/sec
- Compact and robust design
- XML command compatible
- No drivers to install or update



#### **PRODUCT SPECIFICATIONS**

Print method     Thermal line printing       Print speed     100 mm/sec       FONTS & STYLES     Column capacity     Paper width 60 mm       PAPER     Paper size     58.00 ± 60.00 (W) mm x dia 51.00 mm       FONTS & STYLES     Print Speed     100 mm/sec       Print Speed     100 mm/sec     Print Speed       Print Speed     100 mm/sec     Print Speed       Print Speed receipt     100 mm/sec     Print Speed receipt       Column capacity receipt     Paper width 60 mm     Column capacity is 203 dpi 204 dpi 2		
FONTS & STYLES         Column capacity       Paper width 60 mm         PAPER         Paper size       56.00 ± 60.00 (W) mm x dia 51.00 mm         FONTS & STYLES         Print Speed       100 mm/sec         Print Speed receipt       100 mm/sec         Print Speed receipt       200 mm/sec         Print Speed receipt       203 dpi x 203 dpi         Column capacity receipt       Paper width 60 mm         Dot density       203 dpi x 203 dpi         Color Printing       Black         InterfaceS       USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)         DATA BUFFER       Data Buffer         Data Buffer       0 kB or 4,096 Bytes         POWER       PowerSupply         Power Supply       PS-11         Battery Life       WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours         Operatingvoltage       24 V         GeneralL       Product dimensions         Product dimensions       103 x 159 x 65 mm (Width x Depth x Height)         Product weight       0.63 kg         Color       Black (EBCK)         Noise Level       Operation 10% - 90%         Standards       UL, CSA, EN         OTHER FEATURES	Print method	Thermal line printing
Column capacity     Paper width 60 mm       PAPER     Paper size       Paper size     58.00 ± 60.00 (W) mm x dia 51.00 mm       FONTS & STYLES     Finit Speed       Print Speed receipt     100 mm/sec       Printing Font     ANK       Column capacity receipt     Paper width 60 mm       Dot density     203 dpi x 203 dpi       Color Printing     Black       InterfaceS     USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)       DATA BUFFER     Data Buffer       Data Buffer     0 kB or 4,096 Bytes       POWER     Power Supply       Power Supply     PS-11       Battery Life     WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours       Operatingvoltage     24 V       GENERAL     Operation: 53 dB (A)       Product dimensions     103 x 159 x 65 mm (Width x Depth x Height)       Product dimensions     103 x 159 x 65 mm (Width x Depth x Height)       Product weight     0.63 kg       Color     Black (EBCK)       Noise Level     Operation: 53 dB (A)       Humidity     Operation: 53 dB (A)       Humidity     Operation: 53 dB (A)       Humidity     UL, CSA, EN       OtHER     FCC class A, CE marking       Safety standards     UL, CSA, EN	Print speed	100 mm/sec
PAPER         Paper size       58.00 ± 60.00 (W) mm x dia 51.00 mm         FONTS & STYLES         Print Speed       100 mm/sec         Print Speed receipt       100 mm/sec         Printing Font       ANK         Column capacity receipt       Paper width 60 mm         Dot density       203 dpi x 203 dpi         Color Printing       Black         INTERFACES       Interfaces         Interfaces       USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)         DATA BUFFER       Data Buffer         Data Buffer       0 kB or 4,096 Bytes         POWER       Power Supply         Power Supply       PS-11         Battery Life       WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours         Operatingvoltage       24 V         GENERAL       Product dimensions         Product dimensions       103 x 159 x 65 mm (Width x Depth x Height)         Product weight       0.63 kg         Color       Black (EBCK)         Noise Level       Operation: 53 dB (A)         Humidity       Operation: 53 dB (A)         Humidity       Operation: 53 dE (A)         Charter       FCC class A, CE marking         Safety standard	FONTS & STYLES	
Paper size       58.00 ± 60.00 (W) mm x dia 51.00 mm         FONTS & STYLES         Print Speed       100 mm/sec         Print Speed receipt       100 mm/sec         Printing Font       ANK         Column capacity receipt       Paper width 60 mm         Dot density       203 dpi x 203 dpi         Colum capacity receipt       Black         INTERFACES       USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)         Interfaces       USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)         DATA BUFFER       Data Buffer       0 kB or 4,096 Bytes         POWER       Power Supply       PS-11         Battery Life       WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours         Operatingvoltage       24 V         GENERAL       Product dimensions       103 x 159 x 65 mm (Width x Depth x Height)         Product weight       0.63 kg       Color       Golor         Solack (EBCK)       Noise Level       Operation: 53 dB (A)       Humidity       Operation: 53 dB (A)         Humidity       Operation 10% - 90%       Standards       UL, CSA, EN         CHER FEATURES       EMC Standards       UL, CSA, EN         Chter       Partial Cut       Chter	Column capacity	Paper width 60 mm
FONTS & STYLES         Print Speed       100 mm/sec         Print Speed receipt       100 mm/sec         Printing Font       ANK         Colum capacity receipt       Paper width 60 mm         Dot density       203 dpi x 203 dpi         Color Printing       Black         InterfaceS       USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)         DATA BUFFER       Data Buffer         Data Buffer       0 kB or 4,096 Bytes         POWER       Power Supply         Power Supply       PS-11         Battery Life       WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours         Operatingvoltage       24 V         GENERAL       Product dimensions         Product dimensions       103 x 159 x 65 mm (Width x Depth x Height)         Product weight       0.63 kg         Color       Black (EBCK)         Noise Level       Operation: 53 dB (A)         Humidity       Operation: 10% - 90%         StantQards       FCC class A, CE marking         Safety standards       UL, CSA, EN         OTHER FEATURES       Cutter         Other Partial Cut       Other         Other Partial Cut       Other         Othe	PAPER	
Print Speed100 mm/secPrint Speed receipt100 mm/secPrinting FontANKColumn capacity receiptPaper width 60 mmDot density203 dpi x 203 dpiColor PrintingBlackInterfacesUSB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)DATA BUFFERInterfacesData Buffer0 kB or 4,096 BytesPOWERPower SupplyPower SupplyPS-11Battery LifeWiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 HoursOperatingvoltage24 VGENEFALProduct dimensionsProduct dimensions103 x 159 x 65 mm (Width x Depth x Height)Product weight0.63 kgColorBlack (EBCK)Noise LevelOperation: 53 dB (A)HumidityOperation 10% - 90%Statey standardsUL, CSA, ENCHER FEATURESFCC class A, CE markingSafety standardsUL, CSA, ENChterPartial CutChterPartial Cut	Paper size	58.00 ± 60.00 (W) mm x dia 51.00 mm
Print100 mm/secPrinting FontANKColumn capacity receiptPaper width 60 mmDot density203 dpi x 203 dpiColor PrintingBlackINTERFACESInterfacesInterfacesUSB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)DATA BUFFERData BufferData Buffer0 kB or 4,096 BytesPOWERPower SupplyPower SupplyPS-11Battery LifeWiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 HoursOperatingvoltage24 VGENERAL0.63 kgProduct dimensions103 x 159 x 65 mm (Width x Depth x Height)Product weight0.63 kgColorBlack (EBCK)Noise LevelOperation: 53 dB (A)HumidityOperation 10% - 90%STANDARDS COMPLIANCEEMC StandardsEMC StandardsUL, CSA, ENOTHER FEATURESCutterPartial CutFATAI CutOTHERPartial Cut	FONTS & STYLES	
Printing FontANKColumn capacity receiptPaper width 60 mmDot density203 dpi x 203 dpiColor PrintingBlackInterfacesUSB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)DATA BUFFERbut set a s	Print Speed	100 mm/sec
Column capacity receiptPaper width 60 mmDot density203 dpi x 203 dpiColor PrintingBlackINTERFACESInterfacesInterfacesUSB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)DATA BUFFERData BufferData Buffer0 kB or 4,096 BytesPOWERPOWERPower SupplyPS-11Battery LifeWiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 HoursOperatingvoltage24 VGENERALProduct dimensionsProduct dimensions103 x 159 x 65 mm (Width x Depth x Height)Product weight0.63 kgColorBlack (EBCK)Noise LevelOperation: 53 dB (A)HumidityOperation 10% - 90%STANDARDS COMPLIANCEEEMC StandardsFCC class A, CE marking Safety standardsOTHER FEATURESCutterPartial CutOtherOTHERPartial Cut	Print Speed receipt	100 mm/sec
Dot density203 dpi x 203 dpiColor PrintingBlackInterfacesUSB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)DATA BUFFERData BufferData Buffer0 kB or 4,096 BytesPOWERPower SupplyPower SupplyPS-11Battery LifeWiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 HoursOperatingvoltage24 VGENERALProduct dimensions103 x 159 x 65 mm (Width x Depth x Height)Product weight0.63 kgColorBlack (EBCK)Noise LevelOperation: 53 dB (A)HumidityOperation 10% - 90%STANDARDS COMPLIANCEFCC class A, CE marking Safety standardsEMC StandardsFCC class A, CE marking Safety standardsCutterPartial CutOTHER FEATURESPartial Cut	Printing Font	ANK
Color Printing     Black       INTERFACES Interfaces     USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)       DATA BUFFER     Data Buffer     0 kB or 4,096 Bytes       POWER     Power Supply     PS-11       Battery Life     WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours       Operatingvoltage     24 V       GENERAL     Product dimensions     103 x 159 x 65 mm (Width x Depth x Height)       Product weight     0.63 kg       Color     Black (EBCK)       Noise Level     Operation: 53 dB (A)       Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE     EMC Standards       EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES     Cutter       Partial Cut     OTHER	Column capacity receipt	Paper width 60 mm
INTERFACES         Interfaces       USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)         DATA BUFFER       Data Buffer       0 kB or 4,096 Bytes         POWER       POWER       Power Supply       PS-11         Battery Life       WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours       Operatingvoltage         Operatingvoltage       24 V       GENERAL         Product dimensions       103 x 159 x 65 mm (Width x Depth x Height)         Product weight       0.63 kg         Color       Black (EBCK)         Noise Level       Operation: 53 dB (A)         Humidity       Operation 10% - 90%         STANDARDS COMPLIANCE       EMC Standards         EMC Standards       FCC class A, CE marking         Safety standards       UL, CSA, EN         OTHER FEATURES       Cutter         Partial Cut       OTHER	Dot density	203 dpi x 203 dpi
Interfaces USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)           DATA BUFFER           Data Buffer         0 kB or 4,096 Bytes           POWER         Power Supply         PS-11           Battery Life         WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours           Operatingvoltage         24 V           GENERAL         Vifi 139 x 65 mm (Width x Depth x Height)           Product dimensions         103 x 159 x 65 mm (Width x Depth x Height)           Product weight         0.63 kg           Color         Black (EBCK)           Noise Level         Operation 10% - 90%           STANDARDS COMPLIANCE         EMC Standards         FCC class A, CE marking           Safety standards         UL, CSA, EN         Other FEATURES           Cutter         Partial Cut         Other Partial Cut	Color Printing	Black
Interfaces USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)           DATA BUFFER           Data Buffer         0 kB or 4,096 Bytes           POWER         Power Supply         PS-11           Battery Life         WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours           Operatingvoltage         24 V           GENERAL         Product dimensions         103 x 159 x 65 mm (Width x Depth x Height)           Product weight         0.63 kg         Operation: 53 dB (A)           Humidity         Operation 10% - 90%         Standards           Standards         FCC class A, CE marking         Stafety standards         U., CSA, EN           Other FEATURES         Cutter         Partial Cut         Partial Cut	INTERFACES	
Data Buffer     0 kB or 4,096 Bytes       POWER     Power Supply       Power Supply     PS-11       Battery Life     WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours       Operatingvoltage     24 V       GENERAL     Product dimensions       Product dimensions     103 x 159 x 65 mm (Width x Depth x Height)       Product weight     0.63 kg       Color     Black (EBCK)       Noise Level     Operation: 53 dB (A)       Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES       Cutter     Partial Cut	Interfaces	USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)
Data Buffer     0 kB or 4,096 Bytes       POWER     Power Supply       Power Supply     PS-11       Battery Life     WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours       Operatingvoltage     24 V       GENERAL     Product dimensions       Product dimensions     103 x 159 x 65 mm (Width x Depth x Height)       Product weight     0.63 kg       Color     Black (EBCK)       Noise Level     Operation: 53 dB (A)       Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES       Cutter     Partial Cut		
POWER     Power Supply     PS-11       Battery Life     WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours       Operatingvoltage     24 V       GENERAL     Product dimensions     103 x 159 x 65 mm (Width x Depth x Height)       Product weight     0.63 kg       Color     Black (EBCK)       Noise Level     Operation: 53 dB (A)       Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE     EMC Standards       EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES     Cutter       Partial Cut     OTHER		
Power Supply     PS-11       Battery Life     WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours       Operatingvoltage     24 V       GENERAL     Product dimensions       Product dimensions     103 x 159 x 65 mm (Width x Depth x Height)       Product weight     0.63 kg       Color     Black (EBCK)       Noise Level     Operation : 53 dB (A)       Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE     EMC Standards       EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES     Cutter       Partial Cut     OTHER	Data Buffer	U KB or 4,096 Bytes
Battery Life     WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours       Operatingvoltage     24 V       GENERAL     Product dimensions     103 x 159 x 65 mm (Width x Depth x Height)       Product weight     0.63 kg       Color     Black (EBCK)       Noise Level     Operation : 53 dB (A)       Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE       EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES       Cutter     Partial Cut	POWER	
Operatingvoltage     24 V       GENERAL     Product dimensions       Product dimensions     103 x 159 x 65 mm (Width x Depth x Height)       Product weight     0.63 kg       Color     Black (EBCK)       Noise Level     Operation: 53 dB (A)       Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE     EMC Standards       EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES       Cutter     Partial Cut	Power Supply	PS-11
GENERAL         Product dimensions       103 x 159 x 65 mm (Width x Depth x Height)         Product weight       0.63 kg         Color       Black (EBCK)         Noise Level       Operation: 53 dB (A)         Humidity       Operation 10% - 90%         STANDARDS COMPLIANCE       EMC Standards         EMC Standards       FCC class A, CE marking         Safety standards       UL, CSA, EN         OTHER FEATURES         Cutter       Partial Cut         OTHER	Battery Life	WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours
Product dimensions 103 x 159 x 65 mm (Width x Depth x Height) Product weight 0.63 kg Color Black (EBCK) Noise Level Operation: 53 dB (A) Humidity Operation 10% - 90% STANDARDS COMPLIANCE EMC Standards FCC class A, CE marking Safety standards UL, CSA, EN OTHER FEATURES Cutter Partial Cut OTHER	Operatingvoltage	24 V
Product weight     0.63 kg       Color     Black (EBCK)       Noise Level     Operation: 53 dB (A)       Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE       EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES       Cutter     Partial Cut       OTHER	GENERAL	
Color     Black (EBCK)       Noise Level     Operation: 53 dB (A)       Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE       EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES       Cutter     Partial Cut       OTHER	Product dimensions	103 x 159 x 65 mm (Width x Depth x Height)
Noise Level     Operation: 53 dB (A)       Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE     EMC Standards       EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES     Cutter       Partial Cut     OTHER	Product weight	0.63 kg
Humidity     Operation 10% - 90%       STANDARDS COMPLIANCE       EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES       Cutter     Partial Cut       OTHER	Color	Black (EBCK)
STANDARDS COMPLIANCE       EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES       Cutter     Partial Cut       OTHER	Noise Level	Operation: 53 dB (A)
EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES       Cutter     Partial Cut       OTHER	Humidity	Operation 10% - 90%
EMC Standards     FCC class A, CE marking       Safety standards     UL, CSA, EN       OTHER FEATURES       Cutter     Partial Cut       OTHER	STANDARDS COMPLIANCE	
Safety standards UL, CSA, EN OTHER FEATURES Cutter Partial Cut OTHER		
OTHER FEATURES Cutter Partial Cut OTHER		
Cutter Partial Cut OTHER	•	
OTHER	OTHER FEATURES	
	Cutter	Partial Cut
Warranty 12 months Carry in	OTHER	
	Warranty	12 months Carry in
	-	

## LOGISTICS INFORMATION

Dimensions Single Carton	229 x 185 x 104 mm
Carton Weight	1 Kg
Multiple Order Quantity	1 Units
Pallet Size Euro	432 Units (54 x 8)



For more information please contact:

Telephone:	0871 222 6702 (UK)+ 01 436 7742 (Republic of Ireland)
E-mail:	enquiries@epson.co.uk
Chat:	etalk.epson-europe.com
Fax:	0871 222 6740

Web: www.epson.co.uk www.epson.ie Epson TM-P60II Series

#### WHAT'S IN THE BOX

- Battery (OY-BY60II)
- Belt clip
- Cable fixation saddle
- Main unit
- Roll paper
- USB cable

### **OPTIONAL ACCESSORIES**

- OT-CH60II (374): Multi battery charger for TM-P60II C32C825374
- PS-11 (375): Power supply for TM-P60II C32C825375
- OT-BY60II (091): Lithium-ion battery for TM-P60II C32C831091

1. Source: Futuresource Consulting Limited, www.futuresource-consulting.com 2. ePOS-Print is available in WLAN mode only



+ Calls cost 10p per minute plus network extras.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.