



10-Port USB 3.x (5Gbps) / USB 2.0 Combo Hub -USB Charging, 2 USB 3.x & 8 USB 2.0 Ports

MODEL NUMBER: U360-010C-2X3





Adds 10 USB ports to your computer, laptop, MacBook or Chromebook for connecting hard drives, tablets, webcams and other USB devices.

Features

USB 3.0/2.0 Hub Adds 10 USB Devices to Your Computer, MacBook or Chromebook

This 10-port USB 3.0 hub connects directly to the USB-Å port on your computer, laptop, MacBook, Ultrabook or Chromebook. It allows you to use as many as 10 USB devices, such as flash drives, external hard drives, printers, barcode scanners, webcams, keyboards/mice and power meters, all at the same time.

Supports SuperSpeed USB 3.0 to Ensure Fast Data Transfers

Two USB 3.0 ports support data transfer rates up to 5 Gbps, which is 10 times faster than USB 2.0 and recommended for high-bandwidth USB 3.0 devices, such as security cameras and high-resolution webcams. Eight USB 2.0 ports transfer data at speeds up to 480 Mbps. All 10 ports are backward compatible with previous USB generations, so you can continue using older peripherals while getting high-speed performance from new devices.

Charge a Device Even When Your Computer or Laptop Is Not in Use

The first USB 3.0 port, which is labeled with a charge symbol, can charge a mobile device, such as a smartphone or tablet, when the source device is in Suspend mode only. A blue LED indicates the hub is receiving sufficient power to support all connected devices.

Plug-and-Play Hub Comes Ready to Connect Right Away

The U360-010C-2X3 works with Windows and Mac computers and requires no software or drivers to download and install. The included external power supply comes with four international plug adapters that ensure you can use the hub almost anywhere. Most of the time, the hub will receive plenty of power from your computer or laptop. The included power supply should only be necessary when connecting high-current, power-hungry USB peripherals.

Sleek and Slim Housing Designed for Everyday Workspace Use or Connecting on the Go

The compact unit is designed for convenient positioning within your reach, making USB ports accessible while not taking up much workspace. It is slim enough to pack in your pocket, purse or laptop bag for use in a hotel, conference room or airport.

Specifications

Highlights

- Turns your computer or laptop into a mini workstation with 10 extra USB ports
- USB 3.0 ports support SuperSpeed rates up to 5 Gbps to ensure fast data transfers
- Charging port charges mobile device when your computer/laptop is in Suspend mode
- Slim aluminum hub fits easily in your backpack or laptop bag for connecting on the go
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Connect up to 10 USB peripherals, such as an external hard drive, MP3 player, power meter and printer, to your MacBook or Chromebook
- Transfer files quickly to and from a USB thumb drive
- Attach a USB headset/microphone for recording your podcast
- Write a report using a USB keyboard with your tablet or Android smartphone
- Download photos from a digital camera

System Requirements

 Compatible with all USBenabled operating systems (USB 3.0 port needed to achieve USB 3.0 speeds)

Package Includes

- U360-010C-2X3 10-Port USB 3.0 / USB 2.0 Combo Hub
- USB-A to USB Micro-B 3.0 cable, 3 ft.
- External power supply (Input: 100–240V, 50/60 Hz, 1.5A; Output: 5V 4A)
- (4) International plug adapters (North America, U.K., Europe, Australia)





UPC Code 037332242196 Product Type Hub Technology USB 2.0 (High Speed); USB 3.x Host Connector USB A (MALE) Vision of Monitors Supported Non-meter No Extended Mode No Morror Mode No DisplayPort Alt Mode No Data Ports Data Ports (10) USB A (FEMALE) Data Ports (2) USB-A - USB 3.2 Gen 1 (6 Gbps); (8) USB-A - USB 2.0 NOV AC Power Adaptor Plug(s) AS/NZS 3112 Australia: BS 1363 UK: CEE 7/16 Schuke; NEMA 1-15P North America AC Power Adaptor Plug(s) AS/NZS 3112 Australia: BS 1363 UK: CEE 7/16 Schuke; NEMA 1-15P North America AC Power Adaptor Plug(s) AS/NZS 3112 Australia: BS 1363 UK: CEE 7/16 Schuke; NEMA 1-15P North America AC Power Adaptor Plug(s) AS/NZS 3112 Australia: BS 1363 UK: CEE 7/16 Schuke; NEMA 1-15P North America AC Power Adaptor Coult Length (h) 5 Poduet Length (h)		
Product Type Hub Tachnology USB 2.0 (High Speed); USB 3.x Host Connector USB A (MALE) VIDEO Video Numbor of Monitors Supported 0 Extended Mode No Mirror Mode No Display Pon AR Mode No Data Ports (10) USB A (FEMALE) Data Ports (2) USB-A - USB 3.2 Gen 1 (5 Gbps); (8) USB-A - USB 2.0 NPUT (2) USB-A USB 3.12 Australia; BS 1363 UK: CEE 7/16 Schuko: NEMA 1-15P North America AC Power Adapter Plug(s) ASNZS 3112 Australia; BS 1363 UK: CEE 7/16 Schuko: NEMA 1-15P North America AC Power Adapter Dupuls Specs (V/ KL/A) 100-240V / 50060Hz / 1.5A AC Power Adapter Output Specs (V/ KL/A) 5 AC Power Adapter Cord Length (ht.) 5 AC Power Adapter Cord Length (ht.) 5 AC Power Adapter Cord Length (ht.) 5 Product Length (n.) 8.701 Product Length (n.) <td< td=""><td>OVERVIEW</td><td></td></td<>	OVERVIEW	
Tachnology USB 2 0 (High Speed); USB 3.x Hest Connector USB A (MALE) VIDEO Video Number of Monitors Supported 0 Extended Mode No DisplayPort At Mode No DisplayPort At Mode No DisplayPort At Mode No Data Ports (10) USB A (FEMALE) Data Ports (2) USB-A - USB 3.2 Gen 1 (6 Gbps): (8) USB-A - USB 2.0 INPUT Video Adapter Plug(s) ASINZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America ACP Power Adapter Plug(s) ASINZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America ACP Power Adapter Output Specs (V/ AC/ Adapter Cord Length (th.) 5 ACP Ower Adapter Output Specs (V/ AC/ Adapter Cord Length (th.) 5 ACP Ower Adapter Cord Length (th.) 5 Product Length (n.) 8.701 Product Length (n.) 8.701 Product Length (n.) 8.701 Product Length (n.) 0.210 Product Length (n.) 0.210 Product Length (n.) 0.210 Product Length (n.) 0.240 </td <td>UPC Code</td> <td>037332242136</td>	UPC Code	037332242136
Heat Connector USB A (MALE) VIDEO Vinwhor of Monitors Supported Number of Monitors Supported 0 Extended Mode No Mirror Mode No DisplayPort Alt Mode No DisplayPort Alt Mode No Data Ports (10) USB A (FEMALE) Data Ports Details (2) USB A- USB 3.2 Gen 1 (5 Gbps); (8) USB A- USB 2.0 NPUT AC Power Adapter Plug(s) AS/NZS 3112 Australia: BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/NZS 3112 Australia: BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/NZS 3112 Australia: BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Coulput Specs (V) 100-240V / 50/60Hz / 1.5A AC Power Adapter Coulput Specs (V) 5V / 4A AC Power Adapter Coulput Specs (V) 5V / 4A AC Power Adapter Coulput Specs (V) 5V / 4A AC Power Adapter Coulput Mither 5 Product Length (ru) 5 Bus Powerd 100: 110: 120: 125; 127, 200; 208; 220; 230: 240 Bus Powerd Yes Product Length (ru) <t< td=""><td>Product Type</td><td>Hub</td></t<>	Product Type	Hub
VIDEO Number of Monitors Supported 0 Extended Mode No Mirror Mode No DisplayPort Alt Mode No Data No Data Ports (10) USB A (FEMALE) Data Ports (2) USB-A - USB 3.2 Gen 1 (5 Gbps); (8) USB-A - USB 2.0 INPUT AC Power Adapter Plug(s) AC Power Adapter Plug(s) AS/N2S 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/N2S 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Output Specs (V/ (A) 100-240V / 50/60Hz / 1.5A AC Power Adapter Cord Length (ft) 5 AC Power Adapter Cord Length (ft) 5 Bus Powered Yes Product Length (m.) 8.701 Product Length (m.) 8.701 Product Length (m.) 0.21 Product Length (m.) 0.221 Power AC Adapter Product Length (m.) 0.21 Power Source Type AC Adapter AC Adapter Input: 100-240V; 50/60Hz, 1.5A; Ouput: 5V, 4A DC B	Technology	USB 2.0 (High Speed); USB 3.x
Number of Monitors Supported 0 Extended Mode No Mirror Mode No DisplayPort Alt Mode No Data On Data Ports (10) USB A (FEMALE) Data Ports Details (2) USB-A - USB 3.2 Gen 1 (6 Gbps); (8) USB-A - USB 2.0 INPUT AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Input Specs (V/ Hz / A) 100-240V / 50/60Hz / 1.5A AC Power Adapter Cord Length (IL) 5 AC Power Adapter Cord Length (IL) 5 Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powerd Yes Product Length (m) 5.701 Product Length (m) 0.725 Product Length (m) 0.221 Product Length (m) 0.221 Power AC Adapter Power R Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A C Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A C Barrel Plug	Host Connector	USB A (MALE)
Extended Mode No Mirror Mode No DisplayPort Alt Mode No Data Onto Data Onto Data Ports (10) USB A (FEMALE) Data Ports Details (2) USB-A - USB 3.2 Gen 1 (5 Gbps); (8) USB-A - USB 2.0 INPUT AC Power Adapter Plug(s) AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Cord Length (th) 5 AC Power Adapter Cord Length (th) 5 AC Power Adapter Cord Length (th) 5 Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (m) 0.725 Product Length (m) 0.2210 Powers AC Adapter Power Source Type AC Adapter	VIDEO	
Miror Mode No DisplayPort Alt Mode No DisplayPort Alt Mode No Data Construction Data Ports (10) USB A (FEMALE) Data Ports Details (2) USB-A - USB 3.2 Gen 1 (5 Gbps); (8) USB-A - USB 2.0 INPUT AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Output Specs (V/ A) fov_240v / 50/60Hz / 1.5A AC Power Adapter Cord Length (t) 5 AC Power Adapter Cord Length (t) 5 AC Power Adapter Cord Length (t) 5 Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (m.) 8.701 Product Length (m.) 0.725 Product Length (m.) 0.221 Power Source Type AC Adapter AC Adapter Ac Adapter Consect Type AC Adapter Pin, Negative Sleeve Power Source Type AC Adapter DC Barrel Plug 0	Number of Monitors Supported	0
DisplayPort Alt Mode No Data Ports (10) USB A (FEMALE) Data Ports (2) USB-A - USB 3.2 Gen 1 (5 Gbps); (8) USB-A - USB 2.0 INPUT AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Cord Length (ht.) 5 AC Power Adapter Cord Length (ht.) 5 AC Power Adapter Cord Length (ht.) 5 Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (hr.) 8,701 Product Length (hr.) 0,725 Product Length (hr.) 0,725 Product Length (hr.) 0,21 Power Source Type AC Adapter AC Adapter 00: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve Power Source Type NC Adapter	Extended Mode	No
DATA Data Ports (10) USB A (FEMALE) Data Ports Details (2) USB-A - USB 3.2 Gen 1 (5 Gbps); (8) USB-A - USB 2.0 INPUT AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Input Specs (V / Hz / A) 100-240V / 50/60Hz / 1.5A AC AC Power Adapter Output Specs (V / A) 5V / 4A 5V / 4A AC Power Adapter Output Specs (V / A) 5V / 4A 5V AC Power Adapter Output Specs (V / A) 5V / 4A 5V AC Power Adapter Cord Length (ft.) 5 5V / 4A AC Power Adapter Cord Length (ft.) 5 5V / 4A AC Power Adapter Cord Length (ft.) 5 5V / 4A AC Power Adapter Cord Length (ft.) 5 5V / 4A AC Power Adapter Cord Length (ft.) 5 5V / 4A Product Length (in.) 1.5 5V / 4A Product Length (in.) 8.701 5V / 4A Product Length (in.) 0.725 5V / 4A Product Length (in.) 0.221 5V /	Mirror Mode	No
Data Ports (10) USB A (FEMALE) Data Ports Details (2) USB-A - USB 3.2 Gen 1 (5 Gbps); (8) USB-A - USB 2.0 INPUT AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Input Specs (V/ 100-240V / 50/60Hz / 1.5A AC Power Adapter Output Specs (V) 5V / 4A AC Power Adapter Cord Length (ft.) 5 AC Power Adapter Cord Length (ft.) 5 Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (in.) 8.701 Product Length (in.) 8.701 Product Length (ft.) 0.725 Product Length (ft.) 0.21 Product Length (ft.) 0.221 Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A D C Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	DisplayPort Alt Mode	No
Data Ports Details (2) USB-A - USB 3.2 Gen 1 (5 Gbps); (8) USB-A - USB 2.0 INPUT AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Input Specs (V/ thz / A) 100-240V / 50/60Hz / 1.5A 100-240V / 50/60Hz / 1.5A AC Power Adapter Output Specs (V/ A) 5V / 4A 5 AC Power Adapter Cord Length (ft.) 5 AC Power Adapter Cord Length (ft.) 5 AC Power Adapter Cord Length (ft.) 5 Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (fn.) 8.701 Product Length (ft.) 0.725 Product Length (ft.) 0.221 Product Length (ft.) 0.221 Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	DATA	
INPUT AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Input Specs (V / 100-240V / 50/60Hz / 1.5A AC Power Adapter Output Specs (V / 5V / 4A AC Power Adapter Output Specs (V / 5V / 4A AC Power Adapter Cord Length (ft.) 5 AC Power Adapter Cord Length (m) 1.5 Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (m.) 8.701 Product Length (m.) 2.101 Product Length (m) 0.725 Product Length (m) 0.221 Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	Data Ports	(10) USB A (FEMALE)
AC Power Adapter Plug(s) AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America AC Power Adapter Input Specs (V/ 100-240V / 50/60Hz / 1.5A AC Power Adapter Output Specs (V) 5V / 4A AC Power Adapter Cord Length (ft.) 5 AC Power Adapter Cord Length (m) 1.5 Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (in.) 8.701 Product Length (m) 22.101 Product Length (m) 0.725 Product Length (m) 0.221 Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A D C Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	Data Ports Details	(2) USB-A - USB 3.2 Gen 1 (5 Gbps); (8) USB-A - USB 2.0
AC Power Adapter Input Specs (V/ 100-240V / 50/60Hz / 1.5A AC Power Adapter Output Specs (V 5V / 4A AC Power Adapter Cord Length (It.) 5 AC Power Adapter Cord Length (It.) 5 AC Power Adapter Cord Length (It.) 5 AC Power Adapter Cord Length (It.) 100:110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (In.) 8.701 Product Length (It.) 0.725 Product Length (It.) 0.725 Product Length (It.) 0.221 Power Source Type AC Adapter Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	INPUT	
Hz / A) Iteration is a constrained on the first of the first on	AC Power Adapter Plug(s)	AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America
(A) SV FR AC Power Adapter Cord Length (ft.) 5 AC Power Adapter Cord Length (m) 1.5 Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (in.) 8.701 Product Length (cm.) 22.101 Product Length (ft.) 0.725 Product Length (m) 0.221 Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	AC Power Adapter Input Specs (V / Hz / A)	100-240V / 50/60Hz / 1.5A
AC Power Adapter Cord Length (m) 1.5 Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (in.) 8.701 Product Length (cm.) 22.101 Product Length (ft.) 0.725 Product Length (m) 0.221 Power Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	AC Power Adapter Output Specs (V / A)	5V / 4A
Voltage Compatibility (VAC) 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 Bus Powered Yes Product Length (in.) 8.701 Product Length (cm.) 22.101 Product Length (ft.) 0.725 Product Length (m) 0.221 Power Source Type AC Adapter Power Source Type AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	AC Power Adapter Cord Length (ft.)	5
Bus Powered Yes Product Length (in.) 8.701 Product Length (cm.) 22.101 Product Length (ft.) 0.725 Product Length (m) 0.221 POWER Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	AC Power Adapter Cord Length (m)	1.5
Product Length (in.) 8.701 Product Length (cm.) 22.101 Product Length (ft.) 0.725 Product Length (m) 0.221 POWER Power Source Type AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve CONNECTIONS	Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240
Product Length (cm.) 22.101 Product Length (ft.) 0.725 Product Length (m) 0.221 POWER Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	Bus Powered	Yes
Product Length (ft.) 0.725 Product Length (m) 0.221 POWER Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	Product Length (in.)	8.701
Product Length (m) 0.221 POWER Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	Product Length (cm.)	22.101
POWER Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	Product Length (ft.)	0.725
Power Source Type AC Adapter AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	Product Length (m)	0.221
AC Adapter Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve CONNECTIONS	POWER	
DC Barrel Plug OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	Power Source Type	AC Adapter
CONNECTIONS	AC Adapter	Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A
	DC Barrel Plug	OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve
Number of Ports 10	CONNECTIONS	
	Number of Ports	10





TAA Compliant Option	Ν	
STANDARDS & COMPLIANCE		
Driver Required	No	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps)	
Number of USB Hub Ports	10	
USB Hub Ports	Yes	
FEATURES & SPECIFICATIONS		
Power Provided to Connected Device(s)	5V 0.9A (4.5W) when bus powered	
Relative Humidity	5% to 85% RH, Non-Condensing	
Storage Temperature Range	23° to 158°F (-5° to 70°C)	
Operating Temperature Range	32° to 113°F (0° to 45°C)	
ENVIRONMENTAL		
Unit Weight (kg)	0.08	
Unit Weight (Ibs.)	0.18	
Unit Packaging Type	Box	
Unit Dimensions (hwd / in.)	0.630 x 8.660 x 1.280	
Material of Construction	Plastic	
Color	White	
PHYSICAL		
Charging Ports / Amps	(1) 1.5A	
Charging Ports Details	USB Charging Port supports BC 1.2 (5V 1.5A)	
Charging Ports	(1) USB-A: 5V 1.5A (7.5W)	
CHARGING		
LED Indicators	Blue (Power)	
USER INTERFACE, ALERTS & CON	TROLS	
Connector Plating	Nickel	
Side B - Connector 2	(2) USB 3.0 A (FEMALE)	
Side B - Connector 1	(8) USB A (FEMALE)	



https://tripplite.eaton.com



WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	
1000 Eaton Boulevard	© 2025 Eaton. All Rights Reserved.	
Cleveland, OH 44122	Eaton is a registered trademark. All other trademarks	
United States	are the property of their respective owners.	