



Sometimes sharing
isn't much fun.

Sometimes it is.

Lexmark X342n

Fast, affordable multifunction
for small workgroups!

Plug and print ... and share

Network-ready, with optional input capacity of up to 800 sheets, the X342n is a reliable team player for your small-workgroup environment.

Up to 25 ppm

Small workgroup
Home office

Network ready

A boost in productivity

Advanced workflow functions include high-speed faxing, colour scanning in multiple formats, and fast laser printing at up to 25 ppm.

Easier on your budget

Besides its exceptionally low acquisition price, it also offers high-yield 6K cartridges to help drive down your total cost of printing.

We make printing easy

LEXMARK
TM

Lexmark X342n MFP

Full functionality you'll enjoy sharing!

Network-ready and loaded with handy features, the Lexmark X342n is designed for small workgroups looking for an affordable multifunction solution. It offers high-speed mono printing, copying, faxing and colour scanning.

Fast and efficient

No bottlenecks here! The Lexmark X342n reaches output speeds up to 25 ppm, and offers a rich range of time-saving features, including multiple fax shortcuts, a 50-page Automatic Document Feeder, and colour scanning in various file formats, including editable text.

Simple for everyone

More than just easy on your budget, the Lexmark X342n is also easy to set up and operate. The cartridges take just seconds to install. And the intuitive backlit display with two lines of text helps end-users carry out printing and maintenance tasks by themselves – with virtually no training!

Print Technology

Monochrome Laser

Function

Colour Scanning, Copying, Faxing, Network Scanning, Printing

Print Speed (A4, Black)

Up to 25 ppm

Print Speed (Letter, Black)

Up to 27 ppm

Time to First Page (Black)

as fast as 10 seconds

Copy Speed (A4, Black)

Up to 25 cpm

Time to First Copy (Black)

as fast as 12 seconds

Print Resolution, Black

600 x 600 dpi

Scanning Resolution

600 X 600 dpi, 600 X 300 dpi (color)

Processor

150 MHz

Memory, Standard

64 MB

Memory, Maximum

64 MB

Expandable Memory Options

No

Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0

Microsoft Windows Operating Systems Supported

2000 (Professional/Server/Advanced Server), XP (Home, Professional), XP Professional x64, Server 2003 (Standard, Enterprise), Server 2003 (Standard, Enterprise) x64 Edition, Server 2003 x64 Edition (Standard, Enterprise) running Terminal Services, 2000 Server running Terminal Services, Server 2003 (Standard, Enterprise) running Terminal Server

Paper Handling Standard

150-Sheet Output Bin, Single Sheet Exit, Single Sheet Manual

Feed Slot, 250-Sheet Input Tray

Paper Handling Optional

550-Sheet Drawer

Paper Input Capacity (Standard)

250 pages 20 lb or 75 gsm bond

Paper Input Capacity (Maximum)

800 pages 20 lb or 75 gsm bond

Paper Output Capacity (Standard)

150 pages 20 lb or 75 gsm bond

Paper Output Capacity (Maximum)

150 pages 20 lb or 75 gsm bond

Copy/Fax/Scan (ADF) Paper Input Capacity

Up to 50 pages 20 lb or 75 gsm bond

Envelope Capacity

1

Finishing Option

No

Number of Paper Inputs

1

Number of Paper Inputs, Maximum

2

Media Types Supported

Card Stock, Paper Labels, Envelopes, Transparencies, Refer to the Card Stock & Label Guide, Plain Paper

Media Sizes Supported

10 Envelope, Executive, Statement, Letter, Legal, JIS-B5, Folio, DL Envelope, 9 Envelope, A5, B5 Envelope, C5 Envelope, A4, 7 3/4 Envelope (98 x 191 mm - 216 x 355 mm)

Standard Ports

Ethernet 10/100BaseTX (RJ-45), USB 2.0 Specification Hi-Speed Certified

Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), External Gigabit Ethernet, External 802.11g Wireless

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), IPP (Internet Printing Protocol), HTTP, FTP, TFTP

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6

Printable Area

4.0 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 6 Emulation

Reduce / Enlarge Range

25 - 400 %

Scan Area, Maximum

216 x 355.6 mm

Modem Speed

33.6 Kbps

Packaged Size (mm - H x W x D)

550 x 590 x 495 mm

Size (mm - H x W x D)

521 x 530 x 394 mm

Weight (kg)

16.33 kg

Noise Level, Idle

27 dBA

Print Noise Level, Operating

51 dBA

Copy Noise Level, Operating

52 dBA

Scan Noise Level, Operating

49 dBA

Product Guarantee

One Year Exchange

Product Certifications

Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 320-1, ECMA-74, CE Class A, CB IEC 60950 1, IEC 61000-3-2, -3-3, EN 55022, EN 55024, CISPIR 22 Class A, GS (TÜV)-EN 60950-1, SEMKO, UL AR, CS, TÜV Rh, N Mark, C-tick Class A, CCC Class A, RPC, PSB, MIC, EK - K60950

Duty Cycle

Up to 15,000 one-time maximum Impressions per month

Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F)

Supplies

Ships with 2,5K* pages Return Programme toner cartridge

6K* pages High Yield Return Programme toner cartridge (aftermarket). Regular cartridge is also available

- Printers and supplies are designed for use in Europe, Middle East and Africa only

* Average cartridge yield. Declared yield value in accordance with ISO/IEC 19752.

Cost saving & environmental features

Energy Star compliant
Taiwan Green Mark
WEEE
RoHS



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit www.lexmark.com/recycle



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and or other countries. All other trademarks are the properties of their respective owners.

www.lexmark.com

LEXMARK
TM