

## DataShield Serial In-Line Surge Protector, DB9

MODEL NUMBER: DB9



### Highlights

- Complete serial port (DB9) surge protection
- Protects against the effects of electrostatic discharge

### Package Includes

- 1 DB9 Surge Suppressor

Is your DB9 serial connection protected? If not, your equipment is vulnerable to damage and performance problems. Surges and line noise don't just affect the power line; they can enter your equipment on any connection. So protect your DB9 serial equipment with the DataShield™ DB9 In-Line Surge Suppressor. It's the ideal choice for protecting PCs, printers, modems and anything with a DB9 connection.

### Description

This DB9 offers dataline surge suppression for DB9 serial ports of data terminal and data communications equipment, including PCs, printers, modems and more. User-configurable for use with male or female captive DB9 ports. Offers protection on all nine lines, plus D shell chassis. Convenient DB9 input and output connects directly to the protected port, obtaining a ground outlet from the computer chassis. Surge suppression is handled with balanced arrays of high-speed avalanche diodes that divert excess energies created by electrostatic discharges away from network interface connections. Network surge suppressors reduce blown interface cards, garbled transmissions, system lock-ups and hard equipment failure by safely shunting dataline surges to ground.

### Features

- DB9 protects 9 pin serial connections for dataline surge suppression of data terminal, data communications equipment and PCs, printers, modems and more
- Reversible for use with male or female captive DB9 ports
- Offers protection on all 9 data lines, plus D shell chassis
- Surge suppression utilizing high speed avalanche diodes divert excess energies on the network to ground

## Specifications

| OVERVIEW                           |                  |
|------------------------------------|------------------|
| UPC Code                           | 037332010834     |
| INPUT                              |                  |
| Nominal Input Voltage(s) Supported | 120V AC; 230V AC |
| Recommended Electrical Service     | 120V, 230V       |
| Input Cord Length (ft.)            | 0                |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                              |                       |
|----------------------------------------------|-----------------------|
| Right-Angle Plug                             | No                    |
| Input Cord Length (m)                        | 0.00                  |
| Integrated Cord Clip                         | No                    |
| <b>OUTPUT</b>                                |                       |
| Output Receptacles                           | (1) Network           |
| Circuit Breaker (amps)                       | 340                   |
| Right-Angle Outlets                          | No                    |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                       |
| Diagnostic LED(s)                            | No                    |
| <b>SURGE / NOISE SUPPRESSION</b>             |                       |
| AC Suppression Joule Rating                  | 0                     |
| Automatic Shut-Off                           | No                    |
| <b>DATALINE SURGE SUPPRESSION</b>            |                       |
| Cable (Coax) Protection                      | No                    |
| Network (Ethernet) Protection                | No                    |
| Additional Dataline Protection               | 1-9 & Chassis         |
| Telephone/DSL Protection                     | No                    |
| <b>PHYSICAL</b>                              |                       |
| Housing Color                                | Light Gray            |
| Mounting Holes or Slots                      | No                    |
| Shipping Dimensions (hwd / in.)              | 5.00 x 3.00 x 2.00    |
| Shipping Dimensions (hwd / cm)               | 12.70 x 7.62 x 5.08   |
| Shipping Weight (lbs.)                       | 0.16                  |
| Shipping Weight (kg)                         | 0.07                  |
| Unit Dimensions (hwd / in.)                  | 0.640 x 1.380 x 2.850 |
| Unit Weight (lbs.)                           | 0.34                  |
| Unit Weight (kg)                             | 0.15                  |
| <b>FEATURES &amp; SPECIFICATIONS</b>         |                       |
| Rotatable Outlets                            | No                    |
| Antimicrobial                                | No                    |
| <b>STANDARDS &amp; COMPLIANCE</b>            |                       |
| Product Compliance                           | RoHS                  |

WARRANTY & SUPPORT

|                                        |                           |
|----------------------------------------|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|----------------------------------------|---------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.