

MPN: MO-C-B53011-3CL10

SFP 155 Mbps, SMF, 20 km, DDMI Support, Compatible with Cisco GLC-FE-100BX-D

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- ****100% Cisco Compatible****



Specifications

Features	Certification	MSA
	Compatible products	Cisco GLC-FE-100BX-D
	Easy to install	Yes
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	Operating temperature (T-T)	-45 - 75 °C
	Storage relative humidity (H-H)	10 - 85 %
	Storage temperature (T-T)	-40 - 85 °C
Package dimensions	Gross Weight (Package, kg)	0,02 kg
Packaging data	Number of products included	1 pc(s)
Performance	Cabling technology	100BASE-BX10-D
	Digital Diagnostics Monitoring (DDM)	Yes
	Duplex system	Full
	Fiber optic connector	LC
	Fiber ports quantity	1
	Interface type	SFP
	Maximum data transfer rate	155 Mbit/s
	Multi-mode fiber (MMF) supported	No
	Rx wavelength (min)	1310 nm
	SFP transceiver standard	BX
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Yes
	Tx wavelength (min)	1550 nm

Product dimensions

Net Weight (Product, kg)	0,01 kg
---------------------------------	---------

Vendor information

Brand Name	Lanview
Warranty	3 Year(s)