

# Product datasheet

Specifications



## APC NetShelter SX, Server Rack Enclosure, 24U, Shock Packaging, 1250 lbs, Black, 1200H x 600W x 1070D mm

AR3104SP1

### Overview

**Presentation** NetShelter SX cabinet and packaging system designed to safely integrate, transport, unload and deploy up to 1250 lbs (566 kg) of IT equipment. The cabinet is paired with a shock absorbing pallet, unloading ramp, and impact resistant shell. The system has been engineered, tested and approved for secure shipment of fully converged systems such as being certified with Cisco® for pre-racking and shipping Cisco Unified Computing System (UCS).

**Lead time** Usually in Stock

### Main

**Product or component type** Rack enclosure

**number of rack unit** 24U

**Provided equipment**

- Baying hardware
- Doors
- Installation guide
- Keyed-alike doors and side panels
- Leveling feet
- Mounting hardware
- Pallet ramps
- Pre-installed casters
- Reusable packaging
- Roof
- Side panels

### Physical

**Height** 120 cm

**Width** 60 cm

**Depth** 107 cm

**Net weight** 89.09 kg

**Colour** Black

**Mounting preference** No preference

**Mounting mode** Not rack-mountable

**Maximum mounting depth** 91.49 cm

**minimum mounting depth** 19.1 cm

**rack width** 19"

**Marking**

- 14 gauge EIA mounting rail
- 16 gauge front door
- 16 gauge post
- 18 gauge rear door
- 18 gauge roof
- 18 gauge side panels

**Permanent permissible load**

- 1020.6 kg dynamic
- 1360.8 kg static

## Conformance

---

|           |                                   |
|-----------|-----------------------------------|
| Standards | UL 2416<br>UL 60950-1<br>EIA-310E |
|-----------|-----------------------------------|

## Packing Units

---

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

---

|                              |   |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

---

|                  |        |
|------------------|--------|
| Package 1 Height | 135 cm |
|------------------|--------|

---

|                 |          |
|-----------------|----------|
| Package 1 Width | 121.9 cm |
|-----------------|----------|

---

|                  |         |
|------------------|---------|
| Package 1 Length | 89.9 cm |
|------------------|---------|

---

|                  |           |
|------------------|-----------|
| Package 1 Weight | 106.82 kg |
|------------------|-----------|

## Contractual warranty

---

|          |                          |
|----------|--------------------------|
| Warranty | 5 year repair or replace |
|----------|--------------------------|

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Take-back Transparency RoHS/REACH

## Resource performance


 Take-Back Program Available

## Well-being performance

 Reach Free Of Svhc

 Toxic Heavy Metal Free

 Mercury Free

 Rohs Exemption Information [Yes](#)

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

**Eu Rohs Directive** Pro-active compliance (Product out of EU RoHS legal scope)  
[EU RoHS Declaration](#)

**Environmental Disclosure** [Product Environmental Profile](#)

**Circularity Profile** [End of Life Information](#)