

ThinkCentre M90n-1 Nano 11AD0000EE

Product

ThinkCentre M90n-1 Nano

Region

EET

Country/Region

Hungary

Machine Type

11AD

TopSeller

TopSeller

Processor

Core i5-8365U (4C / 8T, 1.6 / 4.1GHz, 6MB)

Graphics

Integrated Intel UHD Graphics 620

Monitor Cable

None

Memory

8GB Soldered DDR4-2666

Storage

256GB SSD M.2 2280 PCIe x4 NVMe Opal

Optical

None

WLAN + Bluetooth

Intel 9560 11ac, 2x2 + BT5.0, vPro

Ethernet

Intel I219-LM, 1x RJ45

Chassis Intrusion Switch

Chassis Intrusion Switch

Kensington Cable Lock

None

Adapter Cage

None

Speaker

1Wx1

Dust Filter

None

VESA Mount

None

Stand

None

Keyboard / Mouse

USB / USB

Power Supply

65W 88% Adapter

TUV Low Noise

None

System Management

Intel vPro

Operating System

Windows 10 Pro 64

Bundled Software

None

Base Warranty

1-year, Onsite

Upsell Service Bundles

None

End of Support

2025-08-02

Announce Date

2019-07-02



WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication “as is” without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<https://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2019. All rights reserved.



Lenovo™

ThinkCentre M90n-1 Nano Platform Specifications

Product Specifications Reference (PSREF)

Processor	Intel® 8th Generation Intel Core™ i3 / i5 / i7 Processor						Manageability Security chip Security features	Intel vPro technology on some models (require choosing a vPro-support Wi-Fi adapter to enable vPro function through wireless connection) Discrete TPM 2.0, TCG Certified <ul style="list-style-type: none">Security slot (in rear for optional Kensington® MicroSaver® cable)Chassis intrusion switchPower-on passwordAdministrator passwordHard disk passwordBoot sequence controlBoot without keyboard and mouseIndividual USB port disablementSmart USB protection, allows keyboard/mouse only, blocks all storage devices							
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics									
	Core i3-8145U	2 / 4	2.1G / 3.9G	4 MB	DDR4-2400	UHD 620									
	Core i5-8265U	4 / 8	1.6G / 3.9G	6 MB	DDR4-2400	UHD 620									
	Core i5-8365U	4 / 8	1.6G / 4.1G	6 MB	DDR4-2400	UHD 620									
Core i7-8665U	4 / 8	1.9G / 4.8G	8 MB	DDR4-2400	UHD 620										
Memory	8GB or 16GB / DDR4-2666* / soldered to systemboard, no sockets, non-ECC * System automatically clocks down for the processors with lower memory controller						Keyboard	Some: Lenovo Calliope Keyboard (USB connector), black Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black							
Storage	Support up to two M.2 SSD Some: M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 4* Some: M.2 2242 SSD / PCIe NVMe, PCIe 3.0 x 2 Some: Intel Optane™ Memory H10 with Solid State Storage, M.2 2280, PCIe NVMe 3.0 x 4 (not support Celeron) * M.2 SSD / Optane with SSD in PCIe 3.0 x 2 M.2 slot can only run at PCIe 3.0 x2 RAID 0/1 support (RAID preset only available via special bid model) None						Mouse	Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black							
RAID	Intel UHD Graphics 620 in processor, uses main memory, DirectX® 12, one DisplayPort™, one USB 3.1 Type-C Gen2 with display function, up to 2 independent displays; Max resolution: 4096x2304 (DP)@60Hz; 4096x2304 (Type-C)@60Hz; Optional DP to VGA dongle, DP to HDMI dongle, Type-C to VGA dongle, Type-C to HDMI dongle, Type-C to DP dongle						Mechanical	Nano (0.35L), black color; metal case Three M.2 slots: two for M.2 SSD (one PCIe 3.0 x4 and one PCIe 3.0 x2) and one for WLAN							
Optical							<table><tr><td></td><td>Dimensions (WxDxH)</td><td>Weight (Approx.)</td></tr><tr><td>M90n-1 Nano (with fan, 0.35L)</td><td>7.05" X 3.46" X 0.87" 179mm X 88mm X 22mm</td><td>1.11 lb (0.505 kg), vary by config</td></tr></table>				Dimensions (WxDxH)	Weight (Approx.)	M90n-1 Nano (with fan, 0.35L)	7.05" X 3.46" X 0.87" 179mm X 88mm X 22mm	1.11 lb (0.505 kg), vary by config
							Dimensions (WxDxH)	Weight (Approx.)							
M90n-1 Nano (with fan, 0.35L)	7.05" X 3.46" X 0.87" 179mm X 88mm X 22mm	1.11 lb (0.505 kg), vary by config													
Graphics	Some: VESA mount bracket kit, supports VESA 75mm Some: VESA mount bracket kit with adapter holder, supports VESA 75mm Some: DIN rail mount bracket kit None														
Monitor cable	Intel SoC (System on Chip) platform						Floor Stand	None							
Chipset	2x USB 3.1 Gen2, 1x USB 3.1 Type-C Gen 2, one headphone / microphone combo jack (3.5mm)						Power supply	65 watts AC/DC adapter, autosensing, 88% PSU (Not for TIO models)							
Front ports (Std.)*	2x USB 3.1 Gen2, 1x USB 3.1 Type-C Gen 2 (with display function, support power-in [20V and >45W]), 1x ethernet (RJ-45), 1x DisplayPort * Depending on many factors, actual data transfer speed may be lower than theoretical speed						Limited warranty	Some: 1-year, limited onsite service / service upgrades available Some: 3-year, limited onsite service / service upgrades available							
Rear ports (Std.)*	Realtek ALC233VB / internal speaker (1watt)						Preload	Preloaded operating system Some: Windows® 10 Pro 64-bit Some: Windows 10 Home 64-bit							
Audio support	Some: 11ac wireless, M.2 Card, Realtek RTL8822CE (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Realtek RTL8822CE (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9462 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9560 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9560 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, Intel vPro technology support, 2x2						Environment	ENERGY STAR® 7.1, EPEAT™ Silver rating (North America), ErP Lot 3, TCO 8.0, TUV ultra low noise verified (on some models), RoHS, WEEE, REACH							
WLAN	Some: Bluetooth 5.0 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Intel Ethernet Connection I219-LM(Jacksonville), Wake on LAN®						MIL-SPEC test	MIL-STD-810H (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Solar Radiation)							
Bluetooth							Accessories	For compatible accessories, please go to http://smartfind.lenovo.com							
Ethernet															

Note: The specifications above may not be available in all regions.

Lenovo, July 2019

Lenovo

ThinkCentre M90n-1 Nano

