

4XEM's 33W Wall Charger Dual Output 4XEM

Part- 4XGAN00533WB



4XEM's 33W USB-C offers amazing charging power and speed with two USB ports capable of charging a variety of devices simultaneously. USB-A has long been a standard port allowing for charging or power to legacy and current devices; however, USB-C is rapidly becoming the new standard for charging devices, allowing for up to 33W charging for power at faster speeds. This device features 1x USB-C ports and 1x USB-A port. Keep your USB devices charged on the go or at home reliably with 4XEM's USB-C and A Charger.

Problem it solves: Charge one or two USB devices with reliable power and speed using 4XEM's 33W Charger.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)



## Features:

- 33-Watt power budget
- 1x USB-C port
- 1x USB-A port
- Wall mounted charger
- Compatible with any USB charged device
- Compact travel size
- Rounded edges
- Fast Charging



## Applications:

- Home
- Office
- Travel
- Meetings
- Classrooms
- Quick Charging

**4XEM Products Are Available At Your Favorite Online Retailers**



Warranty Information	Warranty	1 Year	
Connector(s)	Charging Port(s)	1x USB Type-C Female 1x USB Type-A Female	
	Power Source	Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Fixed with Retractable Prongs	
Performance	Industry Standards	USB-PD 3.0 PPS	
	Certifications	CE ROHS ETL CB CCC	
Physical Characteristics	Colour	Black	
	Display	None	
	LED Indicator(s)	None	
	Power Cable Length	N/A	
	Product Height	1.54 in [39.2 mm]	
	Product Width	1.33 in [33.7 mm]	
	Product Length	1.58 in [40.2 mm]	
	Weight of Product	2.21 in [56.2 mm] (with power prongs out ) 2.05 oz [58 g]	
	Power	Total Power Budget	33W
		Power Delivery	33W Max
Input Voltage		100-240VAC, 50Hz-60Hz @ 0.85A	
Output Voltage (C1)		30W: 5/9V 3A, 12V 2.5A, 15V 2A, 20V 1.5A 33W PPS: 3.3V-11V 3A, 3.3V-16V 2A	
Output Voltage (A1)		30W: 5/9V 3A, 12V 2.5A	
Environmental	Output Voltage (C1 + A1)	20W: 5V 4A (Shared)	
	Operating Temperature	32°F to 104°F [0°C to 40°C]	
	Storage Temperature	-4°F to 176°F [-20°C to 80°C]	
Packaging Information	Humidity	5% to 90% (non-condensing)	
	Package Type	Poly-Bag	
	Package Height	4.00 in [101.6 mm]	
	Package Width	3.00 in [76.2 mm]	
	Package Length	1.33 in [33.9 mm]	
What's in the Box	Shipping (Package) Weight	2.12 oz [60 g]	
	Included in Package	1x 33W USB-C + USB-A GaN Charger	

\* Product appearance and specifications are subject to change without notice.  
 \* Same day shipping is only available for orders shipping within the United States.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Todd Schaus 4XEM sales Rep**  
**1-866-999-4936 Ext.104    tschaus@4xem.com**

