

USB-C Multiport Video Adapter - 3-in-1 - 4K 30Hz - Black

Product ID: CDPVGDVHDBP

This USB-C multiport video adapter offers a portable solution for connecting your USB Type-C laptop to a VGA, DVI or HDMI display.

Avoid the hassle of carrying different adapters for different displays with this 3-in-1 USB-C adapter. With VGA, DVI and HDMI output, you can connect your laptop to virtually any display.

The HDMI output on this USB-C video adapter supports UHD 4K resolutions, providing four times the picture quality of high-definition 1080p. All of the outputs (HDMI, VGA, DVI) can support high-definition resolutions of up to 1920 x 1200.

The convenient plug-and-play USB-C dongle is the perfect travel accessory. Fitting easily into your laptop bag, and offering three video output options, the USB-C display adapter is an ideal solution for Bring Your Own Device (BYOD) applications, wherever you go.

The CDPVGDVHDBP is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- · Connect to virtually any display while traveling
- Connect your BYOD laptop to a provided VGA, DVI or HDMI display at work or school
- · Connect a VGA, DVI or HDMI monitor to your USB-C computer to use as a secondary monitor

Features

- Maximize your video compatibility with a 3-in-1 USB-C display adapter: USB-C to VGA, DVI, or HDMI
- Get astonishing picture quality with support for UHD resolutions up to 4K 30Hz
- Thunderbolt 3 and USB Type-C with DP Alt Mode Compatible
- Easy to set up, use, and store

Hardware		
	Warranty	3 Years
	Active or Passive Adapter	Active
	AV Input	USB-C
	AV Output	DVI-I (Digital Only) - Single-Link



VGA

HDMI - 1.4

Performance

Maximum Cable Distance 49.9 ft [15.2 m]

To Display

Video Revision

DisplayPort 1.2

Maximum Analog

Resolutions

1920 x 1200 @ 60Hz

Maximum Digital

Resolutions

3840 x 2160 @ 30Hz

Supported Resolutions

HDMI output: 3840 x 2160 (@ 30 Hz), 2560 x 1600, 2048 x 1280 (@

60 Hz), 1920 x 1200, 1920 x 1080, 1280 x 720

VGA and DVI output: 1920 x 1200 (@ 60 Hz), 1920 x 1080, 1280 x

720

Wide Screen Supported Yes

Audio Specifications HDMI - 7.1 Channel Audio

DVI - No Audio Support

VGA - No Audio Support

General Specifications Only one video output is supported on the video adapter at a time. If

multiple connections are made, only one of the outputs will function.

Connector(s)

Connector A USB-C (24 pin) DisplayPort Alt Mode

Connector B HDMI (19 pin)

DVI-I (29 pin)

VGA (15 pin, High Density D-Sub)

Special Notes / Requirements

> System and Cable Requirements

Your USB-C port must support DisplayPort over USB-C (DP Alt mode)

in order to work with this adapter.

Note Maximum Cable Distance to Display refers to digital video. VGA



distance capabilities are dependent upon the quality of your cabling

_				
Ln	/IFC	nm	anta	м
	VIIC	,,,,,,,	enta	ш

Operating Temperature 0C to 45C (32F to 113F)

Storage Temperature -10C to 70C (14F to 158F)

Humidity 10%-85% RH

Physical Characteristics

Color Black

Cable Length 5.9 in [15 cm]

Product Length 3.3 in [85.0 mm]

Product Width 1.8 in [45.0 mm]

Product Height 0.6 in [15.0 mm]

Weight of Product 1.8 oz [51.0 g]

Packaging Information

Package Length 8.9 in [22.5 cm]

Package Width 4.9 in [12.5 cm]

Package Height 0.8 in [20.0 mm]

Shipping (Package)

Weight

What's in the Box

Included in Package USB-C travel adapter

1.9 oz [55.0 g]

^{*}Product appearance and specifications are subject to change without notice.