



# XA65 XA60

		XA65	XA60	XA45	XA40	XA15
<b>Sensor</b>		1/2.3-inch 4K UHD CMOS sensor				1/2.84-inch HD CMOS PRO sensor
<b>Lens</b>	<b>Zooming ratio, focal length (35 mm camera equivalent)</b>	20x optical zoom, approx. 29.3 - 601mm 4K UHD (Dynamic IS off/Standard IS on) / approx. 30.5 - 627mm Full HD (Dynamic IS off/Standard IS on)				20x optical zoom, 26.8 (IS off)/ 28.8 (IS on) - 576mm
	<b>Aperture</b>	8 blades				
	<b>Image Stabilizer</b>	Optical + electronic correction				
<b>Infrared camera supported</b>		YES				
<b>Monitor</b>		3.5-inch (approx. 2.76 million dots), LCD, Capacitive touch panel		3.0-inch (approx. 0.46 million dots), LCD, Capacitive touch panel		
<b>EVF</b>		0.36-inch (approx. 1.77 million dots), OLED, tiltable		0.24-inch (approx. 1.56 million dots), tiltable		
<b>Looks</b>		Standard				Standard, Wide DR, Highlight Priority
<b>Movie recording</b>	<b>MXF</b>	YES (XF-AVC)				NO
	<b>AVCHD</b>	NO				YES
	<b>MP4</b>	YES				
	<b>LPCM 4ch audio</b>	YES (not available during 720 recording)				NO
	<b>Simultaneous Recording</b>	Double recording				Double recording, AVCHD+MP4 simultaneous recording
	<b>OSD Recording</b>	YES		NO		
	<b>Slow and Fast (S&amp;F) Motion Recording</b>	YES				YES (MP4)
	<b>Cinema-look filters</b>	NO				7 filters (Nostalgic and Dynamic B/W not provided)
<b>Recording Media</b>	<b>Built-in memory</b>	NO				
	<b>Memory card</b>	SD card (2 slots)				



# XA65 XA60

		XA65	XA60	XA45	XA40	XA15
Professional use terminals	SDI terminal	YES (3G-SDI)	NO	YES (3G-SDI)	NO	YES (HD-SDI)
	GENLOCK, TC	NO				
	XLR terminal (INPUT 1, INPUT 2)	YES				
Other terminals		HDMI, separate headphones, USB (USB Type-C), DC IN (USB Type-C), remote and MIC terminal (supports plug-in power)		HDMI, separate headphones, USB, emote A (LANC compatible) and MIC terminal (supports plug-in power)		HDMI, AV, separate headphones, USB, remote and Microphone terminals
Accessory shoe		Handle unit: Cold shoe				
Detachable handle		YES (XLR terminal, built-in infrared light, mic holder, cold shoe, zoom lever, trigger, tally lamp)				
Wi-Fi		NO				
GPS		NO (Accessories supported)				
Lens hood with barrier		YES				
Dimensions		Approx. 4.3 x 3.3 x 7.2 in. / 109 x 84 x 182mm		Approx. 4.3 x 3.3 x 7.2 in. / 109 x 84 x 182mm		Approx. 4.3 x 3.3 x 7.2 in. / 109 x 84 x 182mm
Body weight	Body only	Approx. 1.65 lbs. / 750 g	Approx. 1.63 lbs. / 740 g	Approx. 1.6 lbs. / 740 g	Approx. 1.6 lbs. / 730 g	Approx. 1.7 lbs. / 750 g
	Lens hood, mic holder unit, handle unit, BP-820 and memory card (1 pc) included	Approx. 2.51 lbs. / 1140 g	Approx. 2.50 lbs. / 1135 g	Approx. 2.5 lbs. / 1130 g	Approx. 2.5 lbs. / 1120 g	Approx. 2.5 lbs. / 1140g