

LQ-630



Get even more from this reliable, low cost A4 printer with flatbed technology and a three-button/LED control panel.

LQ-630 is a small and reliable printer especially for counter application. With its small design with 80 columns, LQ-630 fits perfectly in environments where space is rather limited. The ejection of both, continuous paper and cut sheets at front side enables easy handling of the print outs only at the front side of the printer. Due to the printer's flatbed technology, LQ-630 can print even smallest cut sheet forms and stickers down to 9 cm x 7 cm. LQ-630 can ideally be used with retail stores, banks, post offices, doctors' surgeries, ticket shops, cinemas, pizza services. Moreover the printer is perfect for label and protocol printing with trade industrial firms.

KEY FEATURES

- Fast print speed up to 360 cps
- Compact and robust design
- Handles up to 1 original plus 3 copies
- Flatbed technology for ergonomic front paper feed
- Mean Volume Between Failures: 12 mill. lines

PRODUCT SPECIFICATIONS

TECHNOLOGY

| | |
|-------------------|------------|
| Number of Pins | 24 pins |
| Number of columns | 80 columns |

PRINT

| | |
|---------------------|---|
| Printing Speed | HighSpeed-Draft: 10 cpi: 300 chars/s, 12 cpi: 360 chars/s, Draft: 10 cpi: 225 chars/s, LQ: 10 cpi: 79 chars/s |
| Carbon Copies | 4 plus one original |
| Printing Resolution | 360 x 180 DPI |

CONNECTIVITY

| | |
|------------|--|
| Interfaces | Bidirectional parallel, USB 2.0 Type B |
|------------|--|

PAPER / MEDIA HANDLING

| | |
|---------------|---|
| Document Feed | Single sheet front, Continuous media rear, Paper output front |
| Paper Formats | Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper |

GENERAL

| | |
|------------------------------|--|
| Power consumption | 20 Watt, 4.8 Watt (standby) |
| Product dimensions | 386 x 306 x 185 mm (Width x Depth x Height) |
| Product weight | 3.5 kg |
| Supported Temperature | Operation 5° C - 35° C |
| Compatible Operating Systems | Windows 2000, Windows 7, Windows 8, Windows 98, Windows XP |
| Included Software | Epson Status Monitor |
| Mean Time Between Failures | 10,000 hours |
| Print Head Life | 400 Million Strokes/Wire |
| Noise | Operation: 57 dB (A) |
| Memory | 32 kB Included |
| Ribbon Yield | 2000000 characters Black Draft |
| Supported Humidity | Operation 10% - 80% |

OTHER FEATURES

| | |
|------------|------------------|
| Emulations | ESC/P2, IBM PPDS |
|------------|------------------|

OTHER

| | |
|----------|---|
| Warranty | 12 months Carry in Optional warranty extension available |
|----------|---|

LOGISTICS INFORMATION

| | |
|-------------------|---------------|
| SKU | C11C480141A0 |
| EAN code | 8715946540566 |
| Country of Origin | Indonesia |
| Layer | 5 Units |
| Layer Block | 7 Units |

LQ-630

WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Warranty document
- Power cable
- Ribbon

SUPPLIES

- Epson SIDM Black Ribbon Cartridge for LQ-630 (C13S015307) (C13S015307)

For more information please contact:

Home users: 0343 90 37766
Business users*: 0871 42 37766
Republic of Ireland: 01 436 7742
Or visit us at <https://www.epson.co.uk/contactus>
* 10p per minute plus network extras.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.
Last extracted: 2018-12-13

EPSON[®]