

## Safe-IT 6-Outlet Surge Protector, 2 USB Charging Ports, 10 ft. Cord, 5-15P Plug, 990 Joules, Antimicrobial Protection, Black

MODEL NUMBER: TLP610BUAM



Surge protector with antimicrobial protection safeguards your valuable electronics against dangerous surges, spikes and line noise.

### Features

#### 6-Outlet Surge Protector with USB Safeguards Your Sensitive Electronics

Ideal for your home, office, retail or industrial workstation, this Safe-IT™ surge protector features a surge protection rating of 990 joules to defend your valuable electronic components against power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP610BUAM protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

#### NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your computer, printer, wireless router, desk lamp and other home/office electronics into six NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. One outlet allows connection of a bulky transformer without blocking adjacent outlets.

#### 2 USB Ports Share 2.4 Amps of Charging Power

Two USB-A ports are available for charging your smartphone, tablet or other USB mobile devices. They share 2.4A for charging multiple devices at the same time.

#### Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

This surge protector filters out disruptive EMI (electromagnetic interference) and RFI (radio frequency interference) line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

#### Includes the Latest Safety Features to Maintain Your Equipment's Well-Being

The lighted on/off switch allows you easy one-touch control over equipment connected to the strip. A green LED confirms at a glance that your connected equipment is protected. An integrated 15-amp resettable circuit breaker helps prevent equipment damage due to overloads. Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required.

#### Antimicrobial Protection Helps Provide a Safer, Cleaner and Healthier Work Environment

The TLP610BUAM features antimicrobial protection that helps resist the growth of bacteria, viruses, fungi, mold and mildew.

### Highlights

- 6 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 990 joules protect your valuable electronics against dangerous surges and spikes
- USB-A ports share 2.4A for fast charging of phones and other mobile devices
- 10 ft. braided input cord allows flexibility in placing devices away from wall outlet
- Antimicrobial protection helps resist the growth of bacteria, viruses, fungi, mold and mildew

### Applications

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

### Package Includes

- TLP610BUAM 6-Outlet Surge Protector, Black
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

#### Versatile Surge Protector Provides Multiple Installation Options

This surge protector with 10-foot (3-meter) braided AC input cord and NEMA 5-15P plug gives you flexibility in placing the unit away from the nearest wall outlet. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black plastic housing.

## Specifications

| OVERVIEW                           |                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------|
| UPC Code                           | 037332263612                                                                      |
| Product Type                       | Surge Protector                                                                   |
| Charging Form Factor               | Strip                                                                             |
| Device Compatibility               | Phone; Tablet; Amazon Kindle                                                      |
| INPUT                              |                                                                                   |
| Nominal Input Voltage(s) Supported | 120V AC                                                                           |
| Recommended Electrical Service     | 120V (110-125V)                                                                   |
| Input Cord Gauge Type              | 14 gauge; SJT                                                                     |
| Voltage Compatibility (VAC)        | 120                                                                               |
| Input Plug Type                    | NEMA 5-15P                                                                        |
| Input Cord Length (ft.)            | 10                                                                                |
| Right-Angle Plug                   | No                                                                                |
| Input Cord Length (m)              | 3.05                                                                              |
| Integrated Cord Clip               | No                                                                                |
| OUTPUT                             |                                                                                   |
| Frequency Compatibility            | 60 Hz                                                                             |
| Output (Watts)                     | 1875                                                                              |
| Output Receptacles                 | (6) 5-15R                                                                         |
| Circuit Breaker (amps)             | 15                                                                                |
| Overload Protection                | 15A resettable illuminated combo switch / circuit breaker                         |
| Transformer Accommodation          | (2) Yes                                                                           |
| Outlet Orientation                 | Single row of 6 outlets                                                           |
| Right-Angle Outlets                | No                                                                                |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                                   |
| Diagnostic LED(s)                  | Yes                                                                               |
| Switches                           | Combination AC circuit breaker and 2 position red illuminated on/off power switch |
| Diagnostic LED Details             | Built-in LED confirms suppressor "protection present" (green) status              |



Powering Business Worldwide

TRIPP LITE  
SERIES

| CHARGING                               |                                                                              |
|----------------------------------------|------------------------------------------------------------------------------|
| Number of Charging Ports               | 2                                                                            |
| Total Charging Watts                   | 12                                                                           |
| Charging Method                        | USB                                                                          |
| Charging Port Type                     | USB A (FEMALE)                                                               |
| Charging Ports / Amps                  | (2) 2.4A                                                                     |
| Overcharge Protection                  | No                                                                           |
| SURGE / NOISE SUPPRESSION              |                                                                              |
| AC Suppression Joule Rating            | 990                                                                          |
| AC Suppression Response Time           | < 1 ns                                                                       |
| Protection Modes                       | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| UL1449 Let Through Rating              | 500V                                                                         |
| EMI / RFI Filtering                    | Yes                                                                          |
| Automatic Shut-Off                     | Yes                                                                          |
| DATALINE SURGE SUPPRESSION             |                                                                              |
| Cable (Coax) Protection                | No                                                                           |
| Network (Ethernet) Protection          | No                                                                           |
| Telephone/DSL Protection               | No                                                                           |
| PHYSICAL                               |                                                                              |
| Material of Construction               | Plastic                                                                      |
| Power Cord Color                       | Black/Gray braided cord                                                      |
| Housing Color                          | Black                                                                        |
| Mounting Holes or Slots                | Yes                                                                          |
| Outlets Measurement (Center to Center) | 28.5mm                                                                       |
| Receptacle Color                       | Black                                                                        |
| Shipping Dimensions (hwd / in.)        | 5.90 x 1.77 x 14.60                                                          |
| Shipping Dimensions (hwd / cm)         | 14.99 x 4.50 x 37.08                                                         |
| Shipping Weight (lbs.)                 | 1.62                                                                         |
| Shipping Weight (kg)                   | 0.73                                                                         |
| Unit Dimensions (hwd / in.)            | 1.250 x 1.870 x 13.000                                                       |
| FEATURES & SPECIFICATIONS              |                                                                              |
| Rotatable Outlets                      | No                                                                           |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                                            |                                                                                                                         |
|------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Antimicrobial                                              | Yes                                                                                                                     |
| GaN Technology                                             | No                                                                                                                      |
| Antibacterial                                              | No                                                                                                                      |
| STANDARDS & COMPLIANCE                                     |                                                                                                                         |
| Product Certifications                                     | cUL Listed; UL 1449; UL 1363; UL Listed                                                                                 |
| Product Compliance                                         | RoHS                                                                                                                    |
| WARRANTY & SUPPORT                                         |                                                                                                                         |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                                                                                               |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$25,000 <a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.