

Tripp Lite
1111 W. 35th Street

Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

400G Multimode 50/125 OM4 Switchable Fiber Optic Cable (Duplex LC-PC M/M), LSZH, Aqua, 2 m (6.6 ft.)

MODEL NUMBER: N820X-02M-OM4









400 GbE Ethernet cable supports high bandwidths necessary for next-generation cloud services, hyperscale data centers and telecom carriers.

Features

400 GbE Cable Supports Higher Bandwidths Needed for Next-Generation Data Networking

As the amount of traffic in data networks grows, so does the need for next-gen devices and fiber cables to support higher bandwidths in cloud services, hyperscale data centers, telecom applications and equipment OEM companies. This multimode 50/125 OM4 cable is an ideal choice for 400G Ethernet applications up to 100 meters (328 feet) at 850 nm. It is also backward compatible with 40 Gb and 100 Gb networks, so you can future-proof your current application for an eventual upgrade to 400 Gb.

Switchable LC Connectors Allow Easy Polarity Conversions

The switchable LC duplex connectors on both ends of the cable let you easily switch the fiber polarity without tools or the need to re-terminate the connectors. This can allow for stacked LC adapters, eliminating the need for dual zip cords and reducing overall bulk cabling in high-density situations. Just remove the clipped piece holding the connector ends together on each side, identify the send and receive ends, and switch the polarity of those ends based on your application needs.

Aqua-Colored Jacket Helps Avoid Misidentification That Can Cause Costly Downtime

The OM4-rated cable has an aqua jacket to identify it as multimode in a crowded patch panel or switch and prevent it from becoming accidentally disconnected. The round low-smoke zero-halogen (LSZH) jacket limits the amount of toxic smoke emitted in case of combustion, making it suitable for poorly ventilated areas.

Specifications

| OVERVIEW | |
|------------|--------------|
| UPC Code | 037332272805 |
| Technology | Multimode |

Highlights

- OM4-rated cable recommended for 400 Gb speeds up to 100 meters (@ 850 nm)
- Switchable connector ends allow polarity conversion without tools or re-termination
- Allows use of stacked LC adapters to increase population density
- Backward compatible with 40/100 Gb networks to facilitate future-proofing
- Aqua LSZH jacket allows fast, easy identification in a crowded switch or patch panel

Package Includes

N820X-02M-OM4 400G Multimode 50/125 OM4 Switchable Fiber Optic Cable, Aqua, 2 m (6.6 ft.)



| Optical Mode | OM4 | |
|------------------------------------|---|--|
| Mode Type | Multimode | |
| PHYSICAL | | |
| Cable Jacket Color | Aqua | |
| Connector Color | Aqua | |
| Cable Jacket Material | LSZH | |
| Cable Jacket Rating | OFNR | |
| Cable Outer Diameter (OD) | 2mm x 4.1mm | |
| Clad Diameter (microns) | 125.0 | |
| Core Diameter (microns) | 50.0 | |
| Primary Coating Diameter (microns) | 600.0 | |
| Number of Fibers | 2 | |
| Cable Length (ft.) | 6.56 | |
| Cable Length (m) | 2.00 | |
| Cable Length (in.) | 78.7 | |
| Minimum Bend Radius | 20MM (DYNAMIC); 10MM (STATIC) | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -4 TO 140 F (-20 TO 60 C) | |
| Storage Temperature Range | -4 TO 140 F (-20 TO 60 C) | |
| Operating Humidity Range | 5% TO 85% RH, NON-CONDENSING | |
| Storage Humidity Range | 5% TO 85% RH, NON-CONDENSING | |
| COMMUNICATIONS | | |
| Network Compatibility | 10 Gbps; 25 Gbps; 40 Gbps; 100 Gbps; 400 Gbps | |
| Wavelength | 1300nm; 850nm | |
| Attenuation @ 850NM | 3.5dB/KM | |
| Attenuation @ 1300NM | 1.5dB/KM | |
| Insertion Loss | LESS THAN OR EQUAL TO 0.20dB | |
| CONNECTIONS | | |
| Side A - Connector 1 | LC DUPLEX (MALE) | |
| Side B - Connector 1 | LC DUPLEX (MALE) | |
| Endface Polish | PC | |
| FEATURES & SPECIFICATIONS | | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

| Push/Pull Tabs | No | |
|-------------------------------------|---------------------------|--|
| Optical Port | LC | |
| Breakout | No | |
| Trunk | No | |
| STANDARDS & COMPLIANCE | | |
| Certifications | RoHS, REACH, CE, UL1666 | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies