

# Product data sheet

Specifications



## Rack PDU 2G, Switched, ZeroU, 20A, 100-120V, (24) 5-20R

AP8930

### Overview

#### Presentation

APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

#### Lead time

Usually in Stock

### Main

#### Colour

Black

#### product or component type

PDU

#### PDU type

Switched

#### Cord length

9.84 ft (3.00 m)

#### Number of cables

1

#### provided equipment

Installation guide  
Rack mounting brackets  
Serial configuration cable  
Safety guide

### Complementary

#### Input Voltage

120 V

#### Height

70.5 in (179.1 cm)

#### Width

2.2 in (5.5 cm)

#### Output Voltage

120 V

#### Depth

1.8 in (4.6 cm)

#### net weight

14.37 lb(US) (6.52 kg)

#### mounting location

Side

#### Mounting preference

No preference

#### Input Plug Type

NEMA L5-20P

#### mounting mode

Not rack-mountable

#### Rack units

0U

Mounting position	Vertical
[In] rated current	16 A
Permissible voltage	100...120 V
Input current limits	20 A
Load capacity	1920 VA
Network frequency	50/60 Hz
Outlet type and quantity	24 NEMA 5-20R

## Environment

Product certifications	cUL listed UL listed
Standards	FCC part 15 class A ICES-003 UL 60950-1
Ambient air temperature for operation	23.0000000000...140.0000000000 °F (-5...60 °C)
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13.0000000000...149.0000000000 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	79.0 in (200.6 cm)
Package 1 Width	4.26 in (10.83 cm)
Package 1 Length	6.48 in (16.47 cm)
Package 1 Weight	19.0 lb(US) (8.6 kg)

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

## Resource performance

 Energy Efficient Product

---


 Take-Back Program Available

---


## Well-being performance

 Lead Free

---

 Mercury Free

---

 Rohs Exemption Information [Yes](#)

---

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive Compliant with Exemptions

---

Environmental Disclosure [Product Environmental Profile](#)

---

Circularity Profile [End of Life Information](#)

---