


SmartRack 10U Vertical Hinged Wall-Mount Standard-Depth Rack Enclosure Cabinet, Plexiglass Front Door Insert

MODEL NUMBER: **SRW10USG**



Description

The SRW10USG SmartRack 10U Vertical Hinged Wall-Mount Standard-Depth Rack Enclosure Cabinet is ideal for storing standard 19-inch rack equipment in network closets, point-of-sale stations, offices, classrooms and other areas with limited floor space where you need equipment to be secure and out of the way.

The front door features a plexiglass window that lets you monitor equipment readouts without having to open the cabinet. The enclosure swings away from the wall on a sturdy hinge, allowing easy access to equipment and cabling. Constructed from heavy-duty steel in a durable black powder-coat finish, the SRW10USG supports a maximum load capacity of 200 pounds.

To ensure your valuable equipment stays safe and secure, the reversible front door locks with the included keys. The lockable, removable side panels are ventilated, which allows air to flow freely through the rack to keep equipment cool. Vented top and bottom panels help remove warm air from the enclosure and draw in cool air by convection. The front door can open left or right by rotating the SRW10USG 180° before mounting. Convenient top and bottom ports allow easy cable routing through the enclosure.

The SRW10USG comes fully assembled and ready to mount using the included hardware. Installing equipment within the enclosure is easy enough with its square and threaded mounting holes and numbered rack spaces. The front and rear vertical mounting rails adjust in 1/4-inch increments from 3 to 20.5 inches deep.

Features

Saves Valuable Workspace

- Perfect for network closets, point-of-sale stations, offices, classrooms and other areas with limited floor space where you need equipment to be secure and out of the way
- Houses any standard 19 in. rack equipment in 10U of space
- Supports maximum load capacity of 200 lb.
- Hinged cabinet swings away from the wall to allow easy access to equipment and cabling

Highlights

- Supports a maximum load capacity of 200 lb.
- Swings away from wall for easy equipment access
- Allows constant view of components through plexiglass front door
- Vertical mounting rails adjust from 3 to 20.5 in.
- Locks securely to help prevent damage or theft

Package Includes

- SRW10USG SmartRack 10U Vertical Hinged Wall-Mount Standard-Depth Rack Enclosure Cabinet
- (24) M6 screws
- (24) M6 cage nuts
- (24) M6 washers
- (24) 12-24 screws
- Removable mounting plate
- (3) Mounting plate screws
- (2) Keys
- Owner's Manual



Keeps Important Equipment Secure

- Plexiglass front door lets you monitor equipment readouts at a glance
- Enclosure can be rotated 180° so lockable front door can open left or right
- Lockable, removable side panels are ventilated to allow generous airflow that keeps equipment cool
- Vented top and bottom panels help remove warm air and draw in cool air
- Convenient ports with removable covers allow cable routing through top and bottom

Easy Enclosure and Equipment Installation

- Ships fully assembled for quick installation
- Mounting plate's holes spaced 16 in. apart to accommodate standard wall stud placement
- Front and rear mounting rails adjust in 1/4-in. increments from 3 to 20.5 in. deep
- Rails adjust easily—unscrew them, slide them to desired depth, and screw them back in
- Rails support square-hole or threaded-hole mounting
- Rack spaces numbered for easy reference

Meets Payment Card Industry Standards

- Provides physical equipment and media security required for PCI DSS (Payment Card Industry Data Security Standard) compliance

Specifications

| PHYSICAL | |
|---|---|
| Installed Whole System Maximum Rack Depth (in.) | 20.5 |
| Installed Whole System Maximum Rack Depth (cm) | 52.07 |
| Installed Whole System Minimum Rack Depth (in.) | 3 |
| Installed Whole System Minimum Rack Depth (cm) | 7.62 |
| Rack Height (U Spaces) | 10 |
| Shipping Dimensions (hwd / in.) | 24.25 x 26.38 x 24.13 |
| Shipping Dimensions (hwd / cm) | 61.6 x 67.01 x 61.29 |
| Shipping Weight (lbs.) | 59.22 |
| Shipping Weight (kg) | 26.64 |
| Unit Dimensions (hwd / in.) | 21.56 x 23.63 x 21.63 |
| Unit Dimensions (hwd / cm) | 54.77 x 60.02 x 59.94 |
| Unit Weight (lbs.) | 53.4 |
| Unit Weight (kg) | 24.03 |
| Unit Dimensions (cm) | EXTERNAL DIMENSIONS: 54.8 x 60 x 60 (HWD) |
| Color | Black |



| | |
|--|--|
| Weight Capacity - Stationary (lbs.) | 200 |
| Weight Capacity - Stationary (kg) | 90.7 |
| Factory Preset Rack Depth (in.) | 10.42 |
| Factory Preset Rack Depth (cm) | 26.47 |
| Hinged (Swings Away from Wall Bracket) | Yes |
| SPECIAL FEATURES | |
| Grounding Lug | Front and Back door frames |
| Seismic Rack | No |
| CERTIFICATIONS | |
| NOM (Mexico) | Tested to NOM (Mexico) |
| Approvals | EIA-310-D, IEC 60297-3-100, DIN 41494, IP20 Protection, RoHS |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 5-year limited warranty |

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>