

Product data sheet

Specifications



APC NetShelter Basic Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x12 C13 outlets, C20 cord

AP9565

Overview

Presentation Reliable rack power distribution designed to increase manageability and efficiency in the data center. The output and input connections are (12)C13. Real-time remote monitoring of connected loads. User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Basic

Cord length 8.2 ft (2.5 m)

Number of cables 1

Provided Equipment Installation guide
Rack Mounting brackets

Complementary

Input Voltage 200 V
208 V
230 V

Height 1.7 in (4.4 cm)

Width 17.6 in (44.7 cm)

Output Voltage 208 V
230 V

Depth 2.2 in (5.7 cm)

Net Weight 4.52 lb(US) (2.05 kg)

Mounting Location Front
Rear

Mounting preference No preference

Input Plug Type IEC 60320 C20

Mounting Mode Rack-mounted

Rack units 1U

Mounting position Horizontal

Input current limits 16 A

Load Capacity 3680 VA

Input Frequency 50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Outlet type and quantity	12 IEC 60320 C13
--------------------------	------------------

Environment

Product Certifications	cUL Listed CE Queensland Australia UL Listed VDE
Standards	UL 60950
Ambient Air Temperature for Operation	32.0000000000...113.0000000000 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13.0000000000...149.0000000000 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304213055
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 in (7 cm)
Package 1 Width	18.3 in (46.4 cm)
Package 1 Length	9.02 in (22.9 cm)
Package 1 Weight	8.007 lb(US) (3.632 kg)

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile

[End of Life Information](#)

California Proposition 65

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov