

# Product data sheet

Specifications



APC Back-UPS Pro for Gaming, 2200VA/1320W, Tower, 230V, 6x Australian outlets, RGB Lights, Pure Sine Wave, Midnight (Black)

BGM2200B-AZ

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage 230 V AC 1 phase

Other Input Voltage 230 V

Main Output Voltage 230 V 1 phase

Rated power in W 1320 W

Rated power in VA 2200 VA

Product or component type Uninterruptible power supply (UPS)

Input Connection Type Australian

output connection type 3 Australian  
3 Australian surge

Cable length 1.5 m

Number of cables 1

Battery type Lead-acid battery

## Batteries & Runtime

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Number of battery filled slots 1

Number of battery free slots 0

Battery recharge time 16 h

Number of battery replacement quantity 1

Battery voltage 24 V

Overcurrent protection 15 A

Battery charger power 12 W rated

Battery life 3...5 year(s)

## General

Provided equipment safety guide  
USB cable  
power cable

product web sub-family Gaming performance

Number preinstalled power module	0
Number of power module free slots	0
Redundant	No

## Physical

Colour	Black
Height	292.1 mm
Width	104.1 mm
Depth	408.9 mm
Net weight	12.56 kg
Mounting support	Floor
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

## Input

Network frequency	50/60 Hz +/- 3 Hz
Plug standard	Australian
Input voltage limits	168...302 V
Maximum input current	12 A
Switching current capacity	15 A
Input harmonic distortion	Less than 3 % for full load
Input protection type	Circuit breaker

## Output

Maximum configurable power in W	1320 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Full load runtime	00:30:00
Half load runtime	00:05:30
Maximum configurable power in VA	2200 VA
Transfer time	8 ms typical : 10 ms maximum

## Conformance

Product certifications	CE CB
Equipment protection policy	Lifetime : \$150000

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...3048.0000000000 m
Acoustic level	45 dBA
IP degree of protection	IP20

## Communications & Management

Free slots	0
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rate	1080 J
Noise suppression	Full time multi-pole noise filtering : 5% of IEEE surge let-through : zero clamping response time: instantaneous

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	35.5 cm
Package 1 Length	48 cm
Package 1 Weight	14.38 kg

## Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>