HP LaserJet Enterprise MFP M430f



HP's entry-level Enterprise-class MFP with speeds up to 40 ppm⁹ and strongest security.¹





Easy to use, simple to manage

- HP FutureSmart firmware can be updated with the latest features² to optimize your investment for years to come.
- Centralize control of your printing environment with HP Web Jetadmin—and help build business efficiency.³
- Easily enable workflows across your fleet with a consistent user experience and intuitive, tablet-like icons.
- Set up this MFP fast, and easily manage device settings to help increase efficiency.



The world's most secure printing¹

- The operating code (BIOS) is automatically checked during startup and repairs itself if compromised.
- Common Criteria certified⁴ to continually monitor memory activity to detect and stop attacks in real time.
- Firmware is automatically checked during startup to determine if it's authentic code—digitally signed by HP.
- The printer's outgoing network connections are inspected to stop suspicious requests and thwart malware.



Enhanced productivity to empower work teams

- Give workgroups what they need to succeed with hundreds of HP and third-party solutions and card reader support.
- Optimize workflows, reduce steps and errors, and support mobile workers with optional MFP apps that meet your specific business needs.
- Help ensure the security of confidential information with PIN/Pull printing to retrieve print jobs.
- Stay connected with an optional accessory for wireless, ⁶ Bluetooth [®] Low Energy, and NFC touch-to-print.



Sustainability is smart business

- Help save paper right out of the box. Two-sided (duplex) printing is set at default for automatic savings.⁷
- Help reduce wasted paper and toner by only printing jobs that are truly needed, using HP Roam for Business.⁸
- Save energy without sacrificing performance—this MFP is ENERGY STAR® and Blue Angel certified.
- Leverage HP End of Life Solutions to ensure your Hardware and Supplies are sustainably retired.

Technical specifications

Production (Company) Fig. 1992. Fig. 199		
INCLUDIO SERVICIO DE CONTROLO	Product name	<u> </u>
Abstraction of Abstract Medical Designation of Abstract Medica		
Anterior (1994) Anteri		Print, copy, scan, lax
See A process of the Comment of the		Automatic (default)
The proof of the Control of the Cont		
Text instances Text Control C	Print speed ⁸	
Personalization of Control Con	First page out ⁹	Black (A4, ready): As fast as 6.5 sec; Black (A4, sleep): As fast as 8.8 sec
New sections referencedly Mine (ADM) of the Company of the Compan	Print technology	Laser
The card professionarised in Table 20 (Control of Part 20 (Control	Print resolution	
Terrest martine immunes Terrest martine immunes Terrest market martine immunes Terrest market martine Terrest market market martine Terrest market mark	Print resolution technology	300 dpi, 600 dpi, HP FastRes 1200, HP ProRes 1200
The content of the content of the Province of the Content of the C	Print cartridges number	
The many or security of the security of the security for the first development of the product of	Standard print languages	
Service (1974)	Printer management	
Some specified, City Control (Control Control (Control Control (Control Control Contro		Naveral (Ad), U. v. 20 and (45 for 160 Å), v. v. 20 and (25 for 140 Å), v. v. 20 and (25 for 140 Å), v. v. 20 for 140 Å
And the second and second accounts of the sec	Scan speed.	
South March 1990 (2) 200 Sept.	Scanner specifications	(flatbed): $216 \times 297 \text{ mm}$; Optical scan resolution: Up to 600 dpi; Enhanced Scan Resolution: Up to 600 dpi; Hardware resolution: Up to $600 \times 600 \times 600$
Despite Company of Seat MA mortal (U.S.) a Special Section from 200 Loss of Company Seat Act And pulsed 10:00 3.3 cm; Black Act And pulsed 10:00 3.3 cm; Black Act Act And pulsed 10:00 3.3 cm; Black Act	Scanner advanced features	
Find copyrison Book MM, morph Am Lond on 27 acro. Black MM, steps 25 in cell and 9 in cell and an an an analysis of the cell and analysis of the cell analysis of the cell and analysis of the cell and analysis of the cell an	Сору	
The specifications 32-66 type Recomment 1-64 Mate (Schlad) / 3 sex par page Recommendation 10 miles and provided and provided of the specification 10 miles and provided	Copy speed	Black (A4, normal): Up to 38 cpm; Black (letter, normal): Up to 40 cpm; Black (A4, duplex): Up to 31 cpm; Black (letter, duplex): Up to 33 cpm
To speed 3.3 6 flors formerment) 4.3 6 flors formerment) From report of the properties of the prope	First copy out	Black (A4, ready): As fast as 7.2 sec; Black (A4, sleep): As fast as 9.5 sec; Black (letter, ready): As fast as 6.8 sec
Factorization of the personal of available date scales Factorization (a) \$1,000 x 300 x 400 familiary (a) \$1,000 x 100 x	Fax ⁶	
is conscillation in goldetic ton apported by its park investigating apported by the activation of the construction of the cons	Fax speed	33.6 kbps (maximum); 14.4 kbps (default) / 3 sec per page
Connectivity 2-14-Speard LSS 2-2 Holison 114-Speard LSS 2-2 November 1 Spydel Ethernet 16/100/10037 reheards: 1 Sex 9-24-Speard LSS 2-2 Holison 114-Speard LSS 2-2 November 1 Spydel Ethernet 16/100/10037 reheards: 1 Sex 9-24-Speard LSS 2-2 Holison 114-Speard LSS 2-2 November 1 Spydel Ethernet Holison 10/100/10037 reheards: 1 Sex 9-24-Speard LSS 2-2 Holison 114-Speard LSS 2-2 November 1 Spydel LSM 2-2 N	Fax specifications	ring detection supported: No; Fax forwarding supported: Yes; Junk barrier supported: Yes, as blocked fax numbers; Maximum speed dialing numbers: Up to 1000 numbers; PC interface
Connectivity 2. Hi Speed USB 2.0 Pleat; 1 H	Fax smart software features	
whole empting quadrillor ² #P ePrint, Apple APrint ² , Nepron ² Certified, WHEP Direct Printing DET Double growth and public for expenditure of public control of public co	Connectivity	
Cottomic marked in purchase of a wineless between accessory to all board Wineless Sation and Win Filters Contractionality available with Hill Hadders 3100x BE EMPC Wineless Accessory 3, 38,000 Micros (capabilities). Ver, us of Published Employment of Section 1997,	Standard connectivity	2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Fax
Sample of the control	Mobile printing capability ⁵	
second colorations (SOL 11 Arbitylin entalesies networking (Optional), second Ethernel port (Optional). Whereasy Standard 2-66 Maximum 2016 Storage apachy) 16 68 AMPC Storage apachy) 16 68 AMPC Storage apachy) 18 100 Sec Storage apachy 18 10 Sec Storage	Wireless capability	3,0694
Serang consolety 16.5 de eWell. 18.5	Network capabilities	802.11a/b/g/n wireless networking (Optional); second Ethernet port (Optional).
Next on blink Not available in on the product Processor speed 80 MeV Note that Direct Processor Speed 80 MeV Note of paper that Direct Processor Speed 80 MeV Note of paper that Direct Processor Speed 80 MeV Note of paper that Spee		· · · · · · · · · · · · · · · · · · ·
Processor gened ### Warmup Dime ### 100 sec ### Paper handling ### Dub vicus (monthly) ###		
Norman Duline 180 sec Paper Inanding Duby cycle Immorthly Duby Cycle Im		
Paper yack formorthly Duty cycle (monthly)	<u>.</u>	
Duby cycle from/thly AB Up to 100,000 pages. Recommended monthly page volume 900 to 8,000 Pages produced in the product tray 1.50 of heet		Tou Sec
report opacity 100-sheet tray 1, 250-sheet Automatic Document Feeder (ADF), Optional Third 550-sheet tray Murches of paper trays Sandard: 2, Monimum: 3 Sandard: 2, Monimum: 3 Sandard: 2, Monimum: 3 Sandard: 2, Monimum: 3 Tray 1, 50 to 175 g/m²; tray 2, 500 not 550-sheet tray 3, 50 to 120 g/m² Feed is usegift Tray 1, 50 to 175 g/m²; tray 2, 500 not 550-sheet tray 3, 50 to 120 g/m² Long 1, 50 pr. 1, 50 pr. 1, 50 pr. 1, 75 g/m²; tray 2, 500 not 550-sheet tray 3, 50 to 120 g/m² Long 1, 50 pr. 1, 50 pr. 1, 50 pr. 1, 75 g/m²; tray 2, 500 not 550-sheet tray 3, 50 to 120 g/m² Long 1, 50 pr. 1, 50 pr. 1, 75 g/m²; tray 2, 50 pr. 1, 75 p		Duty cycle (monthly Ad): United 100,000 pages: Peronmended monthly page volume: 900 to 4,900 Pages
Debut Capacity 150 - Sheet coupt bits Paper (plan, coefficient, light, heavy bord, colored, letterhead, pre-purched, recycled, rough); envelopes, labels Red by poer (plan, coefficient, light, heavy bord, colored, letterhead, pre-purched, recycled, rough); envelopes, labels Toy 1, 500 1.17 (gint Price 2), epition (15 gint Price 2), epition		
Number of paper trays Sandard Z. Madmurn 3 Weds types Paper [bilds, excelding, light, heavy, bond, colored, letterhead, pre-printed, pre-punched, recycled, roughly, envelopes, labels Tray 1: 60 to 175 g/m²; tray 2, colored 550-sheet may 3: 60 to 120 g/m² Count fewtolt) Tray 1: 67 to 175 g/m²; tray 2, colored 550-sheet may 3: 60 to 120 g/m² Count fewtolt) Tray 1: 67 to 175 g/m²; tray 2, colored 550-sheet may 3: 60 to 120 g/m² Count fewtolt) Tray 1: 67 to 79 f/m²; tray 2, colored 550-sheet may 3: 60 to 120 g/m² Reda size Count fewtolt) Tray 1: 67 to 79 f/m²; tray 2, colored 550-sheet may 3: 60 to 120 g/m²; tray 2, colored 550, d/m²; tray 3: 60 to 120 g/m²;		
Media weight Tray 1: 601 o 175 g/m²- tray 2, optional 550-5heet tray 3: 60 to 120 g/m² Custom (metric) Tray 1: 7.6x 1/2 to 216 x 356 mm; Cuptom 1 (ap. 105 x 148 to 216 x 356 mm; Supported (metric). Tray 1: A4, RA4, A5, B5 (SIS), B6 (US), A6, 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 356 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 366 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 366 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 366 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 366 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 366 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 366 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 366 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6 (US), A6; 164 x 366 mm; Optional Tray 3: A4, RA4, A5, B5 (US), B6	Number of paper trays	Standard: 2; Maximum: 3
Custom (metric). Tray 1: 76 x 12 ft at 21 ft x 35 ft mm; Tray 2: 10 x 12 ft at 21 ft x 35 ft mm; Tray 2: 10 x 12 ft at 21 ft x 35 ft mm; Tray 2: 144, A5 (8) (5) (5) (6) (10) A; 13 ft m A5 (16) (6) (6) (6) (6) (6) (6) (6) (6) (7) (6) (7) (6) (7) (7) (8) (10) (8) (10) (10) (10) (10) (10) (10) (10) (10	Media types	Paper (plain, ecoefficient, light, heavy, bond, colored, letterhead, pre-printed, pre-punched, recycled, rough); envelopes; labels
Nedia size 10 x 1 5 cm, A6, 16 K, envelopes (85, C5 S0, C6, DL S0); (ustom: 76 x 127 to 216 x 356 mm, Tay 2: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; RAA, 48, 85 USI), B6 CUIS, A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; A6; 16 K; 10 5 x 148 to 216 x 356 mm, Optional Tray 3: A4; A6; 16 K; 10 5 x 148 to 216	Media weight	
Printer weight Software included No software solutions are included in the Box only on http://hp.com or http://h23.hp.com Minks in the box' HP Laser/let Enterprise MFP M430f printer; HP Black Original Laser/let Toner Cartridge (~3,000 pages); Getting started Guide; 1 Power cord Warranty One-year, On-site Repair 24-hour / 7 day a week; phone support Compatible operating systems Windows Client OS (32/64 bit); Win 1Q, Wins 1, Win 7 Ultimate, Mobile OS-, (0S, Android, Mac-, Apple® MacOS High Sierra v10.13, Apple® MacOS Majaw v10.14, Apple® MacOS Catalina v10.15. Compatible operating systems Windows Client OS (32/64 bit); Win 1Q, Wins 1, Win 7 Ultimate, Mobile OS-, (0S, Android, Mac-, Apple® MacOS High Sierra v10.13, Apple® MacOS Majaw v10.14, Apple® MacOS Catalina v10.15. Compatible operating systems Windows Client OS (32/64 bit); Win 1Q, Wins 1, Win 7 Ultimate, Mobile OS-, (0S, Android, Mac-, Apple® MacOS High Sierra v10.13, Apple® MacOS Majaw v10.14, Apple® MacOS Catalina v10.15. Windows Client OS (32/64 bit); Win 1Q, Wins 1, Win 7 Ultimate, Mobile OS-, (0S, Android, Mac-, Apple® MacOS High Sierra v10.13, Apple® MacOS Majaw v10.14, Apple® MacOS Catalina v10.15. Windows 2 (6B available hard of User Guide, Search for your (Product Name) - User Guide, Search for the Supported Operating Systems section, UPD PCL6 / PS Pinter Drivers, Supported Operating Systems see www.hp. com/gloud-Special Systems see microsoft.com Mac 2 (6B available hard dive space Internet Connection or USB port Internet Drivoses. For additional OS hardware requirements see microsoft.com Mac 2 (6B available hard dive space Internet Connection or USB port Internet Drivoses. For additional OS hardware requirements see microsoft.com Mac 2 (6B available hard dive space Internet Connection or USB port Internet Drivoses. For additional OS hardware requirements see microsoft.com Mac 2 (6B available hard dive space Internet Connection or USB port Internet Drivoses. For additional OS hardware requirements See microsoft. Sp. VIT.S. (FITTPS), E	Media size	10 x 15 cm, A6, 16K, envelopes (B5, C5 ISO, C6, DL ISO); Custom: 76 x 127 to 216 x 356 mm; Tray 2: A4; RA4; A5; B5 (JIS); B6 (JIS); A6; 16K; 105 x 148 to 216 x 356 mm; Optional Tray 3: A4;
Software solutions are included No software solutions are included in the Box only on http://np.com or http://123.hp.com Warranty One-year, On-site Repair 24-hour /7 day a week phone support Warranty One-year, On-site Repair 24-hour /7 day a week phone support Windows Client OS (32/64 bit)-, Win10, Win8.1, Win7 Ultimate, Mobile OS-, (OS, Android, Mac, Apple* MacOS High Sierra v10.13, Apple* MacOS Majave v10.14, Apple* MacOS Catalina v10.15, Discrete PCLG Printer Driver, For more information on the supported operating systems or house of product name and search for User Guide, Search for your Product Name — Lever Guide, Search for your Product Name and search, Click on User Guide, Search for your Product Name — Lever Guide, Search for your Product Name and search, Click on User Guide, Search for your Product Name and search for User Systems, For more information on the supported operating systems see www.hpne-) Lever Guide, Search for your Product Name and search for User Systems, For more information on the supported operating systems see www.hpne-) Lever Guide, Search for your Product Name and search, Click on User Guide, Search for your Product Name and search Click space Internet connection or USB port Internet browser. For additional OS hardware requirements see microsoft.com, Mac 2 GB available hard drive space Internet connection or USB port Internet browser. For additional OS hardware requirements see microsoft.com, Mac 2 GB available hard drive space Internet connection or USB port Internet browser. For additional OS hardware requirements see microsoft.com, Mac 2 GB available hard drive space Internet connection or USB port Internet Browser. For additional OS hardware requirements see microsoft.com, Mac 2 GB available hard drive space Internet Connection or USB port Internet Browser. For additional OS hardware requirements see apple.com Heart Soft Soft Soft Soft Soft Soft Soft Sof	Printer dimensions (W x D x H)	420 x 390 x 323 mm
What's in the box! #PLaser Ict Enterprise MPF M30f printer, IP Black Onginal Laser Jet Toner Cartridge (~3,000 pages); Getting started Guide; 1 Power cord Marranty One-year, On-site Repair 24-hour, 77 day a week phone support Systems Windows Client OS (32/64 bit)—, Win O, Win B., Win 7 Ultimate, Mobile OS-, iOS, Android, Macr., Apple* MacOS High Sierra v10.13, Apple* MacOS Mojave v10.14, Apple* MacOS Catalina v10.15, Discrete PCLG Printer Driver, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search for LSer Guide, Search for your Product Name)— User Guide, Search for the Supported Operating systems see see www.hp.com/get. Product Name)— User Guide, Search for the Supported Operating systems see www.hp.com/get. Product Name)— User Guide, Search for the Supported Operating systems see www.hp.com/get. Product Name)— User Guide, Search for the Supported Operating systems see www.hp.com/get. Product Name)— User Guide, Search for the Supported Operating systems see www.hp.com/get. Product Name)— User Guide, Search for the Supported Operating systems see www.hp.com/get. Product Name)— User Guide, Search for the Supported Operating Systems see www.hp.com/get. Product Name)— User Guide, Search For Guide, Search For Search	Printer weight	13.01 kg
Systems Windows Client OS (32/64 bit)-, Win10, Win8.1, Win7 Ultimate, Mobile OS-, iOS, Android, Mac-, Apple® MacOS High Sierra v10.13, Apple® MacOS Mojave v10.14, Apple® MacOS Catalina v10.15, Compatible operating systems Windows Client OS (32/64 bit)-, Win10, Win8.1, Win7 Ultimate, Mobile OS-, iOS, Android, Mac-, Apple® MacOS High Sierra v10.13, Apple® MacOS Mojave v10.14, Apple® MacOS Mojave v10.15, Apple® MacOS Mojave v10.14, Apple® MacOS Mo	Software included	No software solutions are included in the Box only on http://hp.com or http://123.hp.com
Windows Client OS (32/64 bit)., Win10, Win8.1, Win7 Ultimate, Mobile OS-, iOS, Android, Mac., Apple® MacOS High Sierra v10.13, Apple® MacOS Mojave v10.14, Apple® MacOS Catalina v10.15, Observate PCL6 Printer Drivers, For more information on the supported operating systems go to http://support.hp.com/Enter your product name and search, Click on User Guide, Search for User Guiden Search for User Guide, Search for User Guide, Search for User Guide, Search for User Guiden Search Comply (Search Search Searc	What's in the box ¹	HP Laser Jet Enterprise MFP M430f printer; HP Black Original Laser Jet Toner Cartridge (~3,000 pages); Getting started Guide; 1 Power cord
Nindows (lient OS 132/64 bit). Win 10, Win8.1, Win7 Ultimate, Mobile OS., OS, Android, Mac., Apple* MacOS High Serra v10.13, Apple* MacOS Catalina v10.15. Sometime for the product name and search for the supported operating systems go to http://support-thp.com. Enter your product name and search for the systems, For more information on the supported operating systems go to http://support-thp.com. Enter your product name and search for the systems, For more information on the supported operating systems see www.horologouth. Windows 2 GB available hard disk space internet connection or USB port Internet browser, For additional OS hardware requirements see applicoment on the supported operating systems see www.horologouth. Windows 2 GB available hard disk space internet connection or USB port Internet browser. For additional OS hardware requirements see applicoment of the structure connection or USB port Internet browser. For additional OS hardware requirements see applicoment of the structure connection or USB port Internet browser. For additional OS hardware requirements see applicoments. Internet connection or USB port Internet browser. For additional OS hardware requirements see applicoments. Internet connection or USB port Internet browser. For additional OS hardware requirements see applicoments. Internet connection or USB port Internet browser. For additional OS hardware requirements see applicoments. Internet connection or USB port Internet browser. For additional OS hardware requirements see applicoments. For additional OS hardware requirements see applicoments see ap	Warranty	One-year, On-site Repair 24-hour / 7 day a week phone support
Discrete PCLG Printer Driver-, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search for the Security of the Supported Operating Systems see to the Supported Operating Systems see to information on the supported operating systems see supple. Search for the Supported Operating Systems see information on the supported operating systems see www.hp.com/go/upd Mindows 2 GB available hard disk space internet connection or USB port Internet worser. For additional OS hardware requirements seem incrosoft.com; Mac 2 GB available hard drive space internet connection or USB port Internet connection or USB port Internet connection or USB port Internet requirements see emple com Identity management. Kerberos authentication. LDAP authentication. 1000 uses PIN codes. Optional HP and 3rd party advanced authentication solutions (e.g., badge readers); Network: PSecrificates,	Systems	
Internet connection or USB port Internet browser. For additional OS hardware requirements see apple.com Identity management. Kerberos authentication, LDAP authentication, 1000 user PIN codes, Optional HP and 3rd party advanced authentication (EAP-PEAP, EAP-TLS), SNMFv3, HTTPS, Certificates, Access Control List, Data: Storage Encryption, Encrypted PDF & Email (uses FIPS) 104 validated cryptographic libraries from Microsoft), SSL/TLS (HTTPS), Encrypted Credentials, Device: HP Sure Start Secure Boot (BIOS integrity Checking with self-heading capability), Intrusion Detection (Constant in-device monitoring for attacks), Whitelesting (loads only known good code), Embedded Trusted Platform Module, HP Connection Inspector, Security lock slot, USB port disablement; Security management: Compatible with HP JetAdvantage Security Manager, Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMS Total Trusted Platform Module, HP Connection Inspector, Security splank defined in Arcsight and Splunk SIEMS Total Mindows Wista B Forns (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts and IPDS Emulation available at Http://www.hp.com/go/laserjetfonts Control panel 4.3° Color Capacitive Touch Control Panel 3.3° Calor Capacitive Touch Control Panel 4.3° Color Capacitive Touch Control Panel 4.3° Color Capacitive Touch Control Panel 4.3° Color Capacitive Touch Control Panel 8.60 Power Requirements: 110-volt input voltage: 110 to 127 VAC (+7-10%), 50 Hz (+7-3 Hz); 220-volt input voltage: 220 to 240 VAC (+7-10%), 50/60Hz (+7-3 Hz) (Not dual voltage, power supply varies by part number with # D ptinon code identifier); Consumption: 525 watts to printing; 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical Electricity Consumption (TEC) 1-1.222 kWh/week (Blue Angel); 0.463 kWh/week (Energy Star 3.0); Power supply type Internal (Built-in) power supply Operating temperature range: 15 to 32.	Compatible operating systems	Discrete PCL6 Printer Driver-, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search, Click on User Guide, Search for your (Product Name) - User Guide, Search for the Supported Operating Systems section, UPD PCL6 / PS Printer Drivers, Supported Operating systems, For more information on the supported operating systems see www.hp.com/go/upd
Identity management Kerberos authentication, LDAP authentication, 1000 user PIN codes, Optional HP and 3rd party advanced authentication solutions (e.g., badge readers); Network: IPsec/firewall with Certificate, Pre-shared Key, Kerberos authentication, Supports Will-10 IPsec configuration Plug-in, 802.1X authentication (EAP-PEAP; EAP-TLS), SMMPv3, HTTPS, Certificates, Access Control List, Data's Storage Encryptopion, Encrypted PP & Email (uses FIPS 140 validated cryptographic libraries from Microsoft), SSL.175. (HTTPS), Encrypted Credentials; Device: HP Sure Start Secure Boot (BIOS Integrity Checking with self-healing capability), Intrusion Detection (Constant in-device monitoring for attacks), Whitelisting (loads only known good code), Embedded Trusted Platform Module, HP Connection Inspector, Security lock slot, USB port disablement; Security management: Compatible with HP JetAdvantage Security Manager, Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMs Fonts and typefaces Internal Trurlype fonts scalable in HP PCL, 92 internal scalable fonts in HP PostScript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono World Type); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPOS Emulation available at Http://www.hp.com/go/laserjetfonts Control panel 13° Color Capacitive Touch Control Panel Display 4.3° diagonal Color TFT-LCD back-lit 480 RGB (H) × 272 (V) Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/66Hz (+/- 3 Hz) (Not dual voltage, power supply varies by part number with # Option code identifier); Consumption: 525 wats (active printing), 10.1 watts (seedy), 1.2 watts (sleep), 0.00 watts (auto-offmanual-on), 0.08 watts (amunal-on), 0.08 watts (auto-offmanual-on), 0.08 watts (auto-offmanual-on), 0.08 watts (auto-offmanual-on), 0.08 watts (auto-offmanual-on),	Minimum system requirements	
Messages processed and accessible in Arcsight and Splunk SIEMS 105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP PostScript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono World Type); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at Http://www.hp.com/go/laserjetfonts Control panel 4.3" Color Capacitive Touch Control Panel Display 4.3" diagonal Color TFT-LCD back-lit 480 R6B (H) x 272 (V) Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60Hz (+/- 3 Hz) (Not dual voltage, power supply varies by part number with # Option code identifier); Consumption 525 watts (active printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical Electricity Consumption (TEC)*1: 1.222 kWh/week (Blue Angel); 0.463 kWh/week (Energy Star 3.0); Power supply type: Internal (Built-in) power supply Operating environment Operating emperature range: 15 to 32.5"C; Recommended operating temperature range: 15 to 27°C Operating humidity range: 10 to 90 sth; Recommended operating humidity range: 30 to 70% RH Eccolabels EPEAT* Silver; CECP; ENERGY STAR® certified* Acoustics Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): Inaudible; Acoustic pressure emissions: 5.4 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): Inaudible EEC 60950-1:2005 +A1:2009 +A2:2013 (international); EN60950-1:2006 +A11:2009 +A1:2010 +A1:22011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010/IEC 62479:2010; IEC 62471:2006 / EN 62471:2008; IEC 62368-1:2014 (EN 62368-1:2014 Laser safety standards 21 CFR 1040-10 and 1040-11 except for deviations pursuant to Laser notice No. 5.0, Dated June 24, 2007; Other safety approvals as required by individu	Security management	Identity management: Kerberos authentication, LDAP authentication, 1000 user PIN codes, Optional HP and 3rd party advanced authentication solutions (e.g., badge readers); Network: IPsec/firewall with Certificate, Pre-shared Key, Kerberos authentication, Supports WIA-10 IPsec configuration Plug-in, 802.1X authentication (EAP-PEAP; EAP-TLS), SMMPV3, HTTPS, Certificates, Access Control List; Data: Storage Encryption, Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft), SSL/TLS (HTTPS), Encrypted Credentials; Device: HP Sure Start Secure Boot (BIOS Integrity Checking with self-healing capability), Intrusion Detection (Constant in-device monitoring for attacks), Whitelisting (loads only known good code), Embedded
Http://www.hp.com/go/laserjetfonts Control panel 4.3° Color Capacitive Touch Control Panel Display 4.3° diagonal Color TFT-LCD back-lit 480 RGB (H) x 272 (V) Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60Hz (+/- 3 Hz) (Not dual voltage, power supply varies by part number with # Option code identifier); Consumption: 525 watts (active printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical Electricity Consumption (TEC) ¹¹ : 1.222 kWh/week (Blue Angel); 0.463 kWh/week (Breergy Star 3.0); Power supply type: Internal (Built-in) power supply Operating environment Operating temperature range: 15 to 32.5°C; Recommended operating temperature range: 15 to 2.7°C Operating humidity range: 10 to 90% RH; Recommended operating humidity range: 30 to 70% RH Ecolabels EPEAT® sliver; CECP; ENERGY STAR® certified ⁴ Mercury-free Acoustics Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): inaudible EC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2011 +A2:2011 +A2:2013 (EU); EN 60825-1:2014/EC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/EC 62479:2010; EIC 62471:2006 / EN 62471:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/EC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/EC 62479:2010; EIC 62471:2006 / EN 62471:2006 +A11:2009 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/EC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/EC 62479:2010; EIC 62471:2006 / EN 62471:2006 +A11:2009 +A12:2011 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/EC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/EC 62479:2010; EIC 62471:2006 / EN 62471:	Fonts and typefaces	Messages processed and accessible in Arcsight and Splunk SIEMs 105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP PostScript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono World Type); 2
Display 4.3" diagonal Color TFT-LCD back-lit 480 RGB (H) x 272 (V) Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60Hz (+/- 3 Hz) (Not dual voltage, power supply varies by part number with # 0ption code identifies; Consumption: 525 watts (active printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical Electricity Consumption (TEC) ¹¹ : 1.222 kWh/week (Blue Angel); 0.463 kWh/week (Energy Star 3.0); Power supply type: Internal (Built-in) power supply Operating temperature range: 15 to 32.5"C; Recommended operating temperature range: 15 to 27"C Operating humidity range: 10 to 90% RH; Recommended operating humidity range: 30 to 70% RH Ecolabels EPEAT® Silver; CECP; ENERGY STAR® certified ⁴ Sustainable impact specifications Mercury-free Acoustics Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): inaudible EC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2011 +A		Http://www.hp.com/go/laserjetfonts
Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60Hz (+/- 3 Hz) (Not dual voltage, power supply varies by part number with # (pition code identifier); Consumption: 525 wasts (active printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical Electricity Consumption (TEC) 11-1.222 kWh/week (Blue rape); 0.463 kWh/week (Energy Star 3.0); Power supply type: Internal (Built-in) power supply Operating temperature range: 15 to 32.5°C; Recommended operating temperature range: 15 to 27°C Operating humidity range: 10 to 90% RH; Recommended operating humidity range: 30 to 70% RH Ecolabels EPEAT® Silver; CECP; ENERGY STAR® certified 4 Sustainable impact specifications Mercury-free Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): Inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions: 55 dB(A) @ 38 ipm; Acoustic pressure emissions: 55 dB(A) @ 38 ipm; Acoustic pressure emissio	Control panel	'
by part number with # Option code identifier): Consumption: \$25 watts (active printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical Electricity Consumption (TEQ) ¹¹ : 1.222 kWh/week (Blue Angel); 0.463 kWh/week (Energy Star 3.0); Power supply type: Internal (Built-in) power supply Operating temperature range: 15 to 32.5°C: Recommended operating temperature range: 15 to 27°C Operating humidity range: 10 to 90% RH; Recommended operating humidity range: 30 to 70% RH EPEAT® Silver; CECP; ENERGY STAR® certified ⁴ Sustainable impact specifications Mercury-free Acoustics Mercury-free Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic	Display	
Operating environment Operating inwildity range: 10 to 90% RH; Recommended operating numidity range: 30 to 70% RH Ecclabels EPEAT® Silver; CECP; ENERGY STAR® certified Sustainable impact specifications Acoustics Acoustics Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acou	Power	by part number with # Option code identifier); Consumption: 525 watts (active printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical
Sustainable impact specifications Acoustics Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): inaudible Safety approvals and requirements EC 60950-1:2005 +A1:2009 +A2:2013 (international); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62369-1:2014 (EV); EN 62369-1:2014/IEC 60825-1:2014 (IC) (EV); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010/IEC 62471:2006; IEC 62368-1:2014; EN 62368-1:2014 Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries. Supported network protocols Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD, Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint; Discovery; EL Bonjour, Web Services Discovery; IP Config: IPv4 (Boott, DHC), Autoli, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/V3, HTTP/HTTPS, Syslog; Security: SNMPv3, SSL	Operating environment	Operating humidity range: 10 to 90% RH; Recommended operating humidity range: 30 to 70% RH
Acoustics Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): Inaudible; Acoustic pressure emissions: 5.4 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): Inaudible Safety approvals and requirements EC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62369-1:2014 (In 62479:2010) (IEC 62479:2010) (IEC 62479:2010) (IEC 62471:2008; IEC 62368-1:2014; EN 62368-1:2014 Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries. Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, IPD, Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint; Discovery; EL Bonjour, Web Services Discovery; IP Config: IPv4 (Boott, DHC), Autoli, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/V3, HTTP/HTTPS, Syslog; Security: SNMPv3, SSL	Ecolabels	
Inaudible IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010/IEC 62479:2010/IEC 62479:2010/IEC 62471:2008; IEC 62368-1:2014; EN 62368-1:2014 Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries. Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD, Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint; Discovery; ELP, Bonjour, Web Services Discovery; IP Config: IPv4 (Boott, DHCP, Autol), Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/V3, HTTP/HTTPS, Syslog; Security: SNMPv3, SSL	Sustainable impact specifications	
Safety approvals and requirements 62479:2010/IEC 62479:2010/ IEC 62471:2006 / EN 62471:2008; IEC 62368-1:2014; EN 62368-1:2014Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UI/cUL Listed and UC Coc (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries. Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD, Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (Boott, DHC), Autole, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/N3, HTTP/HTTPS, Syslog; Security: SNMPv3, SSL	Acoustics	Inaudible
Supported network protocols Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/v3, HTTP/HTTPS, Syslog; Security: SNMPv3, SSL	Safety approvals and	62479:2010/IEC 62479:2010; IEC 62471:2006 / EN 62471:2008; IEC 62368-1:2014; EN 62368-1:2014Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany,
	requirements	pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.

Ordering information

Accessories

Number	Description	
3JN69A	HP Jetdirect 3100w BLE/NFC/Wireless Accessory	
4QL32A	HP Legic Secure USB Reader	
8FP31A	HP Jetdirect LAN Accessory	
8ZN00A	HP HIP2 Card Reader Accessory Kit	
B5L31A	HP Foreign Interface Harness	
D9P29A	HP LaserJet Pro 550-sheet Feeder Tray	
X3D03A	HP Universal USB Proximity Card Reader	
Y7C05A	HP HIP2 Keystroke Reader	

HP Care Packs

Number	Description
U11D7E	HP 3 year Next Business Day Service for LaserJet Enterprise MFP M43x
U11D8E	HP 4 year Next Business Day Service for LaserJet Enterprise MFP M43x
U11D9E	HP 5 year Next Business Day Service for LaserJet Enterprise MFP M43x
U11DBE	HP 3 year 4 hour 9x5 Service for LaserJet Enterprise MFP M43x
U11DCE	HP 4 year 4 hour 9x5 Service for LaserJet Enterprise MFP M43x
U11DDE	HP 5 year 4 hour 9x5 Service for LaserJet Enterprise MFP M43x
U11DME	\mbox{HP} 3 year Parts Exchange Service for Laser Jet Enterprise MFP M43x (Managed Component Only)
U11DNE	HP 4 year Parts Exchange Service for LaserJet Enterprise MFP M43x (Managed Component Only)
U11DQE	HP 5 year Parts Exchange Service for Laser Jet Enterprise MFP M43x (Managed Component Only) $$
U11DRPE	HP 1 year Post Warranty Next Business Day Service for LaserJet Enterprise MFP M43x
U11DSPE	HP 2 year Post Warranty Next Business Day Service for LaserJet Enterprise MFP M43x
U11DTPE	HP 1 year Post Warranty 4 hour 9x5 Service for LaserJet Enterprise MFP M43x
U11DVPE	HP 2 year Post Warranty 4 hour 9x5 Service for LaserJet Enterprise MFP M43x
U11DZPE	HP 1 year Post Wty Parts Exchange Service for LaserJet Enterprise MFP M43x (Managed Component Only)
U11E0PE	HP 2 year Post Wty Parts Exchange Service for LaserJet Enterprise MFP M43x (Managed

Protect your investment with HP Care Pack. Let HP certified engineers resolve your technical issues. For more details on HP Care Pack, go to hp.com/go/cpc















Supplies and Media

Number	Description
4WN07A	HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/Tabloid/11 x 17 in
4WN08A	HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/Letter 8.5 x 11 in
7MV81A	HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/A3/297 x 420 mm
7MV82A	HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/A4/210 x 297 mm
CF276A	HP 76A Black Original LaserJet Toner Cartridge (~3,000 pages)
CF276X	HP 76X High Yield Black Original LaserJet Toner Cartridge (~10,000 pages)

Contact HP via phone: Asia: 65 6253 8500

HP Inc. offices

Australia 13 10 47 hp.com.au China (010) 6564 3888 hp.com.cn Hong Kong (852) 3077 2688 hp.com.hk India (80) 2612 9000 hp.com/in Indonesia (62-21) 579 1088 hp.com/idw Korea (02) 2199 0114 hp.co.kr Malaysia (603) 2332 3333 hp.com.my New Zealand (09) 0800 449 553 hp.con.z Philippines (632) 888 5900 hp.com/ph Singapore (65) 6275 3888 hp.com.sg Taiwan (02) 3789 9900 hp.com/tw Thailand (662) 353 9500 hp.com/th Vietnam (848) 3823 4151 hp.com/vn

Solutions

For more solutions information, please visit hp.com/go/gsc

Footnotes

- ¹ HP's most advanced embedded security features are available on HP Managed and Enterprise devices with HP FutureSmart firmware 4.5 or above. Claim based on HP review of 2019 published features of competitive in-class printers. Only HP offers a combination of security features to automatically detect, stop, and recover from attacks with a self-healing reboot, in alignment with NIST SP 800-193 quidelines for device cyber resiliency. For a list of compatible products, visit
- hp.com/go/PrintersThatProtect. For more information, visit hp.com/go/PrinterSecurityClaims

 Some features enabled by future HP FutureSmart firmware upgrades may not be available on older devices, if for example, physical product characteristics limit the functionality of the new feature.

³ HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin

⁴ Third-party certification based on Common Criteria Information Technology Security Evaluation ISO/IEC 15408 Standard requirements as of May 2019. Certification applicable to HP Managed and Enterprise devices running HP FutureSmart Firmware version 4.5.1 and later. For more information: https://www.commoncriteriaportal.org/files/epfiles/Certification%20Report%20-%20HP%20Intrusion%20Detection.pdf

- Suse of the HP Trusted Platform Module may require a firmware upgrade.

 Wireless performance is dependent on physical environment and distance from access point and may be limited during active VPN connections.
- Dependent upon country setup specifications.
- ⁸ To enable HP Roam, some devices may require firmware to be upgraded and an optional accessory to add Bluetooth® Low Energy (BLE) beaconing capabilities. Subscription may be required. For more information, visit hp.com/go/roam
- 9 Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document

Technical specifications disclaimers

- 1 For vield information on the cartridge included with your printer, see http://www.hp.com/go/tonervield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors.

 ² Declared yields based on ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/toneryield
- 3 Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit: http://www.hp.com/go/learnaboutsupplies 4 EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
- ⁵ To enable HP Roam, some devices may require firmware to be upgraded and an optional accessory to add Bluetooth® Low Energy (BLE) beaconing capabilities. Customer can purchase the HP Jetdirect 3100w BLE/NFC/Wireless accessory or the RadBeacon USB. Subscription may be required. For more information, visit http://www.hp.com/go/roam

 ⁶ Based on standard ITU-T test image #1 at standard resolution. More complicated pages or higher resolution will take longer and use more memory.
- ⁷ Measured using ISO/IEC 24734 Feature Performance Test, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- ⁸ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document First Copy Out from Ready and Simplex Copy Speed measured using ISO/IEC 29183, Duplex Copy Speed measured using ISO/IEC 24735, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims.
- Exact speed varies depending on the system configuration, software application, document complexity, media size, media orientation and media type.

 10 Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device and 230V for Blue Angel.
- 11 Sample Data: Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh).
- 12 Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.

To learn more, visit hp.com

