


TD2430 - 24" 1080P 10-POINT MULTI TOUCH MONITOR WITH HDMI, DP, AND VGA

Key Features

- 24 Inch Full HD (1920x1080p) LED touch monitor with 60Hz refresh rate
- Robust 10-point multi-touch technology feature a robust, pressure-sensing touchscreen
- Freestanding tablet design with muted black finish, stable adjustable stand, and 7H scratch resistant surface
- 50M:1 MEGA Dynamic Contrast Ratio delivers sharp, crisp images
- MacOS users can access touch and gesture controls on touch displays connected to their Apple devices using ViewSonic's vTouch driver. Not available for iPhone and iPad
- The TD2430 supports laptops, PCs, Macs and POS Systems with USB, HDMI, DisplayPort and VGA inputs









MVA PANEL



1920 x 1080 **RESOLUTION**



Product **Description**

Laid flat or angled for customized comfort, this display delivers touchscreen versatility to the max. Offering fantastic flexibility for retail, education, or business settings, the ViewSonic* TD2430 is a 24" (23.6" viewable) Full HD display with 10-point multi-touch functionality. Delivering adjustable positioning, wide-angle viewing, and a durable design, the TD2430 has everything to accommodate your unique needs. Adding even more convenience, cross-compatibility with a wide range of operating systems includes Windows 10, and certain Android and Linux versions.* With a sleek edge-to-edge screen and frameless bezel, this intuitive touchscreen performs like your favorite tablet or smartphone to deliver a highly accurate, ultra-responsive touch experience ideal for interactivity in public environments, kiosk and wayfinding applications, classroom settings, and more. *Supports Windows 7/8/10, Linux 2.6.38 or later, and Android 4.0 or later.

Specifications

UPC	766907846911
Screen Size	24
Viewable Area (in.)	23.6
Display Resolution	1920 x 1080
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	50,000,000:1
Brightness	250 cd/m2
Backlight Life (Hours)	40,000
Response Time (Typical GTG)	25ms
Panel Type	MVA
Colors	16.7M
Viewing Angles	178º horizontal, 178º vertical
Light Source	LED
Panel Surface	7H Scratch Resistant Surface Hardness
Aspect Ratio	16:9
PC Resolution (max)	1920 x 1080
Touch Technology	Projective Capacitive
Touch Points	10-Point Touch
USB Type A	2
USB Type B	1
VGA	1
HDMI 1.4 In	1
DisplayPort	1
Power in	DC 12V / 4.0A
Internal Speakers	2.5W (x2)
Frequency Horizontal	Analog: 24 ~ 82Hz, Digital: 15 ~ 82Hz
Frequency Vertical	Analog: 50 ~ 75Hz, Digital: 24 ~ 75Hz
Analog Sync	Separate Sync / Composite Sync / Sync on Green, TMDS, PCI-E
Eco Mode (Conserve)	19W
Eco Mode (optimized)	22W
Consumption (typical)	25W
Consumption (max)	28W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Physical Controls	1, 2, Up, Down, Power

On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
Tilt (Forward/Back)	20º - 53º, 90º (Flat)
Kensington Lock Slot	1
VESA Compatible	100 x 100 mm
Gross (kg)	7.1
Net Without Stand (kg)	5.5
Net (lbs)	12.2
Gross (lbs)	15.6
Packaging (mm)	643 x 435 x 140
Physical (mm)	573 x 353 x 47
Packaging (in.)	25.3 x 17.1 x 5.5
Physical (in.)	22.6 x 13.9 x 1.9
Regulations	cTUVus, FCC-B w/ ICES003, DOE Energy Star 7.0, DOE EPEAT, TUV-MX-CoC, Mexico Energy, NRCan
Package Contents	LCD Display, AC/DC Adapter, Power Cable, HDMI Cable, USB3.0 Upstream Cable , Audio Cable , Quick Start Guide, ViewSonic Wizard CD-ROM
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907846911







Contact Sales
ViewSonic.com
888.881.8781 email:
salesinfo@viewsonic.com