

POS Terminals

ION TP5





With a sleek, stylish and compact design, the TP5 is perfect for even the most confined POS locations. The TP5 features a TruFlat projected capacitive touchscreen, quad-core CPU, and an optional integrated receipt printer.



Resilient Touch Display

The TP5 features a 14" widescreen LCD with TruFlat projected capacitive (PCAP) multi-touch technology built to take the rigors of heavy everyday use.



Beautiful and Functional

Built on a sturdy aluminum frame, the ION TP5 delivers a durable modern look while maintaining a small footprint, saving valuable counter space.



Integrated Printer (optional)

The integrated printer means no external printer cables creating a clean, cable free environment.



Environmental Resistance

With an IP54 Ingress Protection Rating. The TP5 was designed to withstand harshest of environments.



Cost Effective Performance

Built on Intel's mobile Bay Trail technology, the fanless ION TP5 is powerful and durable enough to handle the most demanding applications.







POS Terminals

ION TP5

| MODEL | ION-TP5E-Z / ION-TP5F-Z |
|----------------|---|
| Processor | Intel Atom Z3735F up to 1.86GHz Quad Core |
| Bezel | TruFlat Bezel |
| Chip Set | Processor Integrated |
| System Memory | 2GB DDR3L |
| Hard Drive | 32GB / 64GB eMMC |
| LCD Display | 14" (356mm) LED LCD |
| Resolution | 1366 x 768 |
| Graphic Memory | Intel Gen7 up to 646MHz |
| Electrical | 90W/19V |
| DODTC | |

| PORTS | | |
|------------------|--------------------------|--|
| USB | 4 x USB Type A (USB 2.0) | |
| Serial | 1 x RJ45 COM1 | |
| LAN | 1 x RJ45 | |
| Cash Drawer Port | 1 x RJ12 | |
| | | |

| Cash Diawer Fort | I A IVIZ |
|--------------------------------|--|
| PHYSICAL | |
| Housing | ABS |
| Weight | 12.13lbs (5.5Kkg) |
| Dimensions (w/base) (WxDxH) | 14.3" x 7.8" x 13.4" (363mm x 197mm x 340mm) |
| Tilt Angle | 0° - 90° |
| Viewing Angle | 80° Horizontal, 145° Vertical |
| Housing Color | Black and Silver |
| Capacitive Touch | 10 Point |

| ENVIRONMENTAL | | |
|-----------------------|--|--|
| Operating Temperature | 32°F - 95°F (0°C - 35°C) | |
| Humidity | 20% - 80% RH non-condensing | |
| Warranty | 3-year warranty with free *2-day Advance Exchange Service | |
| Certifications | FCC Class B, CE, LVD, NOM | |
| Supported OS | Windows 8.1, Windows 10 | |

^{*}Available in USA and Canada

| Interface Details Integrated USB Emulation ESC/POS Command Compatible Print Method Direct Thermal Printing Speed 6.3"/sec (160 mm/sec) Print Resolution 180 DPI x 180 DPI Printing Direction Unidirectional with Friction Feed Sensors Paper End Reliability TPH Life 62.14 miles (100KM) PAPER ION-TPSE-Z Only Type Thermal Paper Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TPSE-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts Cutting Method Full/Partial Cut | DDINITED CDECIFICATION | 1011 7055 7.0 / |
|---|--------------------------|------------------------------------|
| Emulation ESC/POS Command Compatible Print Method Direct Thermal Printing Speed 6.3"/sec (160 mm/sec) Print Resolution 180 DPI x 180 DPI Printing Direction Unidirectional with Friction Feed Sensors Paper End Reliability TPH Life 62.14 miles (100KM) PAPER ION-TP5E-Z Only Type Thermal Paper Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | PRINTER SPECIFICATION | ION-TP5E-Z Only |
| Print Method Direct Thermal Printing Speed 6.3"/sec (160 mm/sec) Print Resolution 180 DPI x 180 DPI Printing Direction Unidirectional with Friction Feed Sensors Paper End Reliability TPH Life 62.14 miles (100KM) PAPER ION-TP5E-Z Only Type Thermal Paper Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Interface Details | Integrated USB |
| Printing Speed 6.3"/sec (160 mm/sec) Print Resolution 180 DPI x 180 DPI Printing Direction Unidirectional with Friction Feed Sensors Paper End Reliability TPH Life 62.14 miles (100KM) PAPER ION-TP5E-Z Only Type Thermal Paper Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Emulation | ESC/POS Command Compatible |
| Print Resolution 180 DPI x 180 DPI Printing Direction Unidirectional with Friction Feed Sensors Paper End Reliability TPH Life 62.14 miles (100KM) PAPER ION-TP5E-Z Only Type Thermal Paper Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Print Method | Direct Thermal |
| Printing Direction Unidirectional with Friction Feed Sensors Paper End Reliability TPH Life 62.14 miles (100KM) PAPER ION-TP5E-Z Only Type Thermal Paper Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Printing Speed | 6.3"/sec (160 mm/sec) |
| Sensors Paper End Reliability TPH Life 62.14 miles (100KM) PAPER ION-TP5E-Z Only Type Thermal Paper Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Print Resolution | 180 DPI x 180 DPI |
| Reliability TPH Life 62.14 miles (100KM) PAPER ION-TP5E-Z Only Type Thermal Paper Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Printing Direction | Unidirectional with Friction Feed |
| PAPER ION-TP5E-Z Only Type Thermal Paper Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Sensors | Paper End |
| Type Thermal Paper Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Reliability | TPH Life 62.14 miles (100KM) |
| Width 3.13" (79.5mm) Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | PAPER | ION-TP5E-Z Only |
| Thickness 0.002" (0.06mm) - 0.0035" (0.09mm) Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Туре | Thermal Paper |
| Roll Diameter Max 3.15" (80mm) Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Width | 3.13" (79.5mm) |
| Roll Core Inner Diameter Minimum 0.314" (8mm) Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Thickness | 0.002" (0.06mm) - 0.0035" (0.09mm) |
| Character Set Extended Graphics, Code Page 1252 Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Roll Diameter | Max 3.15" (80mm) |
| Character/Line (12 x 24) 48 columns Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Roll Core Inner Diameter | Minimum 0.314" (8mm) |
| Barcodes Supported EAN-8, EAN-13, CODE 39, ITF, UPC-A, UPC-E, CODABAR, CODE 93, CODE 128 AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Character Set | Extended Graphics, Code Page 1252 |
| AUTOCUTTER ION-TP5E-Z Only Type Auto-retracting Guillotine Life 1,000,000 Cuts | Character/Line | (12 x 24) 48 columns |
| Type Auto-retracting Guillotine Life 1,000,000 Cuts | Barcodes Supported | |
| Life 1,000,000 Cuts | AUTOCUTTER | ION-TP5E-Z Only |
| | Туре | Auto-retracting Guillotine |
| Cutting Method Full/Partial Cut | Life | 1,000,000 Cuts |
| | Cutting Method | Full/Partial Cut |

| OPTIONAL ACCESSORIES | |
|----------------------|--|
| ION-MR514 | 3-track Magnetic Stripe Reader with USB interface |
| ION-EMV514-UNIPAY1 | Housing for UniPay 1.5 EMV Reader (Not Included) (P/N IDMR-AB83133S Required) |
| ION-RD5-LCM | Integrated 2 x 20 LCM customer display |
| ION-RD5-ZLCD8 | Integrated 8" LCD Customer Display |
| ION-RD5-ZTLCD8 | Integrated 8" LCD Touch Display |
| ION-TP5E-MOUNT | Wall Mount for ION TP5 with Printer |
| ION-TP5F-MOUNT | Wall Mount for Printer-less TP5 |

| WARRANTY EXTENSIONS | |
|---------------------|----------------------------|
| ZWE-TPC | 2-Year Warranty Extension |
| ZOE-TPC3 | 3-Year Overnight Exchange* |
| ZOE-TPC5 | 5-Year Overnight Exchange* |

