



LCD DISPLAY
VP3881


Key Features

- 100% sRGB wide colour gamut coverage
- Hardware colour calibration
- Delta E < 2 colour accuracy
- Pre-calibrated uniformity correction
- 21:9 aspect ratio



Product Description

With a 2300R curved screen and stunning WQHD+ 3840x1600 resolution, the ViewSonic VP3881 delivers the most immersive panoramic viewing experience to date. VP3881 is engineered to deliver incredible detail and unmatched colour accuracy across wide viewing angles, while HDR10 content support displays a dynamic range of vivid colours and rich contrast. The extra screen real estate provided by VP3881's expansive 38" (37.5" viewable) 3-side frameless screen and ultra-wide 21: 9 aspect ratio, along with pre-calibrated IPS colour and integrated speakers make this monitor perfect for video editing and other types of colour-critical content creation. VP3881's sleek, modern design is future-proof with USB 3.1 Type-C, DisplayPort, and HDMI ports, all of which come with HDCP 2.2 content protection for secure 4K content playback and streaming. VP3881 comes equipped with an amazing Delta E < 2 value for precise colour accuracy, integrated colour uniformity for consistent chromaticity across the screen, and a 14-bit 3D look-up table which generates a smooth palette of 4.39 trillion colours. VP3881's built-in hardware calibration functionality is co-developed with X-Rite which allows you to calibrate the monitor over long-term usage.



1. VESA Compatible (Wall Mount 100 x 100 mm)
2. Menu Controls
3. USB 3.1 Type A (x3)
4. USB 3.1 Type B
5. USB 3.1 Type C
6. HDMI (x2)
7. DisplayPort
8. Audio In
9. Audio Out
10. DC In
11. Kensington Lock Slot

Visit Us www.viewsonic.com

DISPLAY

Monitor Size:	38"W (37.5" Viewable)
Panel Technology:	IPS TFT LCD
Resolution:	WQHD+ 3840 x 1600
Display Area:	879.67 mm (H) x 366.53 mm (V)
Aspect Ratio:	21:9
Brightness:	300 cd/m ² (Typ)
Contrast Ratio:	1000:1 (Typ)
Dynamic Contrast Ratio:	20,000,000:1
Viewing Angle:	178 degrees / 178 degrees (Typ)
Refresh Rate:	60Hz
Response Time:	GTG: 5 ms (Typ)
Colours:	1.07 Billion Colours, 10bit (8bit + FRC)

Colour Gamut:	Adobe RGB: 75.67% Coverage / 79.67% Size (Typ) NTSC:76.12% Coverage / 72.71% Size (Typ) sRGB:99.52% Coverage / 107.4% Size (Typ) REC709:99.52% Coverage / 107.4% Size (Typ) SMPTE-C:100% Coverage / 116.06% Size (Typ) EBU:98.04% Coverage / 106.19% Size (Typ) DCI-P3: 79.22% Coverage / 79.22% Size (Typ)
Pixel Size:	0.229 mm (H) x 0.229 mm (V)

INPUT SIGNAL

Frequency:	HDMI/ DisplayPort/ Type-C: Fh = 15 ~ 135KHz ; Fv = 24 ~ 75Hz
Sync:	HDMI: TMDS DisplayPort/ Type-C: Mini-Packet

COMPATIBILITY

PC:	PC Compatibles (3840 x 1600 HDMI/DisplayPort Non-Interlaced)
Mac®:	Power Mac (up to 3840 x1600 HDMI/DisplayPort)

CONNECTOR

Digital:	DisplayPort 1.4 HDR ready x 1 HDMI 2.0 x 2 Type-C x 1
Audio Out:	3.5mm Mini Phone Jack Audio out x 1
Audio In:	3.5mm Mini Phone Jack Audio in x 1

SPEAKERS

5W * 2

USB

Upstream: USB 3.1 Gen 1 Type-C x 1 and Type-B x1
Downstream: USB 3.1 Gen 1 Type-A x 3

POWER

Power:	DC connector x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	66W
Optimize:	57W
Conserve:	48W

MODEL COLOUR

Black

ERGONOMICS

Tilt:	-1.0° ~ 21.0°
Swivel:	120°
Height Adjustment:	0~130 mm

WALL MOUNT

VESA®:	100 mm x 100 mm
--------	-----------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	896 mm (W) x 629 mm (H) x 299 mm (D)
Physical without stand (mm):	896 mm (W) x 398 mm (H) x 103 mm (D)
Packaging (mm):	1046 mm (W) x 490 mm (H) x 375 mm (D)

WEIGHT

Net with stand (kg):	12.69 kg
Net without stand (kg):	7.97 kg
Gross (kg):	19.88 kg

REGULATIONS

cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, NRCAN, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, KC, e-Standby, CCC, China RoHS, China Energy Label

PACKAGE CONTENTS

LCD Display
AC/DC Adapter
Power Cable (1.8M)
DisplayPort Cable (1.8M)
HDMI 2.0 Cable (1.8M)
USB3.1 Gen.1 Type C Cable(1.8M)
USB 3.0 UpStream Cable (Type B to A) (1.8M)
Audio Cable (1.8M)
Quick Start Guide
ViewSonic Wizard CD-ROM

*Actual content may differ from market to market