



4XEM's 35W Dual USB-C Charger

4XEM Part- 4XRLC53835WW



4XEM's compact Dual USB Wall Charger will charge your phone or other USB devices with ease. Quickly plugs into a standard household outlet for fast, efficient charging. Connect the adapter directly to your device via a separate charging cable and you're all set. Compatible with nearly every device that charges via USB. Utilizes a modernized interface featuring USB-C.

Problem it solves: No need to connect your device to a computer for recharging. With the Power Adapter/Wall Charger, you can easily plug into any household outlet for a quick boost! Charge up to 2 devices simultaneously!

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com







Features:

- 2x USB-C ports
- Power Budget: 35W
- Wall mounted charger
- Compatible with any USB charged device
- Compact travel size
- Rounded edges
- Fast Charging

Applications:

- Home
- Office
- Travel
- Meetings
- Classrooms
- Quick Charging





4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com





DATA SHEET

1 Year Warranty Information Warranty

2x USB Type-C Female Connector(s) Charging Port(s)

Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Power Source

Fixed with Non-Retractable Prongs

USB-PD 3.0 Performance **Industry Standards**

CE Certifications **FCC**

White **Physical Characteristics** Colour No Display

None LED Inidicator(s) Power Cable Length N/A

1.33 in [33.7 mm] 1.55 in [39.3 mm] **Product Height** Product Width 1.93 in [49.0 mm] Product Length

2.56 in [65.0 mm] (with power prongs)

2.75 oz [74 g] Weight of Product

35W Power Total Power Budget

35W Max Power Delivery

100-240VAC, 50Hz-60Hz @ 1A 35W: 5/9V 3A, 15V 2.33A, 20V 1.75A Input Voltage

Output Voltage (C1/C2)

35W MAX - 17.5W: 5V 2.4A, 9V 1.94A, 15V 1.16A, 20V 0.87A + 17.5W: 5V 2.4A, 9V 1.94A, 15V 1.16A, 20V 0.87A Output Voltage (C1) + (C2)

Environmental Operating Temperature

Storage Temperature

Humidity

32°F to 104°F [0°C to 40°C] -4°F to 176°F [-20°C to 80°C] 5% to 90% (non-condensing)

Packaging Information Package Type

Package Height Package Width Package Length

Shipping (Package) Weight

Poly-Bag 4.00 in [101.6 mm] 3.00 in [76.2 mm] 1.33 in [33.9 mm] 2.68 oz [76 g]

What's in the Box

Included in Package

1x 35W Dual USB-C Charger

Notes Notes

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep 1-866-999-4936 Ext.104 tschaus@4xem.com



^{*} Product appearance and specifications are subject to change without notice.

^{*} Same day shipping is only available for orders shipping within the United States