

Product data sheet

Specifications



Rack PDU, Basic, 1U, 30A, 208V, (10) C13

AP9571A

Overview

Presentation Reliable rack power distribution designed to increase manageability and efficiency in the data center. The output and input connections are (10) C13. Real-time remote monitoring of connected loads. User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.

Lead time Usually in Stock

Main

Colour Black

product or component type PDU

PDU type Basic

Cord length 12 ft (3.7 m)

Number of cables 1

provided equipment Installation guide
Rack mounting brackets
User manual

Complementary

Input Voltage 200 V
208 V
230 V

Height 1.7 in (4.4 cm)

Width 17.5 in (44.5 cm)

Output Voltage 208 V

Depth 3.03 in (7.7 cm)

net weight 5.62 lb(US) (2.55 kg)

mounting location Front
Rear

Mounting preference No preference

Input Plug Type NEMA L6-30P

mounting mode Rack-mounted

Rack units 1U

Mounting position Horizontal

[In] rated current 24 A

Permissible voltage 200...240 V

Max line current 30 A

| | |
|---------------------------------|------------------|
| Input current limits | 30 A |
| Load capacity | 4992 VA |
| Network frequency | 50/60 Hz |
| Outlet type and quantity | 10 IEC 60320 C13 |

Environment

| | |
|--|--|
| Product certifications | cUL listed PSE UL listed |
| Standards | UL 60950 |
| Ambient air temperature for operation | 23.0000000000...113.0000000000 °F (-5...45 °C) |
| Relative humidity | 5...95 % |
| Operating altitude | 0...15000 ft |
| Ambient air temperature for storage | -13.0000000000...149.0000000000 °F (-25...65 °C) |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |

Packing Units

| | |
|-------------------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.7 in (17.1 cm) |
| Package 1 Width | 6.9 in (17.4 cm) |
| Package 1 Length | 19.02 in (48.3 cm) |
| Package 1 Weight | 8.02 lb(US) (3.64 kg) |

Contractual warranty

| | |
|-----------------|---------------------------|
| Warranty | 2 years repair or replace |
|-----------------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Lead Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)