

Product data sheet

Specifications



APC NetShelter Rack PDU
Advanced Gen 2, Switched,
34.6kW, 3Phase, 43.5kW 400V
63A or 34.6kW 415V 60A, 560P6,
42 Outlet

APDU11450SW

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	9.8 ft (3 m)

Complementary

Input Voltage	415 V 3 phases
Height	71.9 in (1826 mm)
Width	2.2 in (56 mm)
Output Voltage	240 V
Depth	3.0 in (75 mm)
Net weight	27.3 lb(US) (12.4 kg)
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 60 A 3P + N + PE
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Communication port protocol	1000BASE-T 10/100BASE-T
[In] rated current	48 A
Permissible voltage	200...240 V 346...415 V
Input current limits	60 A
Load capacity	34600 VA
Network frequency	50/60 Hz
Outlet type and quantity	21 C13/C15/C19/C21 21C13/C15

Environment

Product certifications	TAA compliance
Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B
IP degree of protection	IP44
Ambient air temperature for operation	23...140 °F (-5...60 °C)
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.000000000...15240.000000000 m)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	83.07 in (211 cm)
Package 1 Width	5.20 in (13.2 cm)
Package 1 Length	10.31 in (26.2 cm)
Package 1 Weight	41.9 lb(US) (19 kg)

Contractual warranty

Warranty	3 years repair or replace
-----------------	---------------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

Use Again

Repack and remanufacture

Take-back

No

Image of product / Alternate images

Alternative



