

# Product datasheet

Specifications



## Power Cord Kit (6 ea), Locking, C19 to C20, 1.8m

AP8716S

### Overview

**Presentation** Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.

**Lead time** Usually in Stock

### Main

<b>Product or component type</b>	Power cord
<b>Input Connection Type</b>	IEC 60320 C20
<b>Cable length</b>	1.8 m
<b>Number of cables</b>	6

### Physical

<b>Colour</b>	Black
<b>Height</b>	30 cm
<b>Width</b>	8 cm
<b>Depth</b>	7 cm
<b>Net weight</b>	2.16 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Not rack-mountable

### Input

<b>Max line current</b>	16 A
<b>Input current limits</b>	16 A

### Output

<b>Max current draw</b>	16 A
<b>Number of power socket outlets</b>	1 IEC 60320 C19
<b>Power cable length</b>	1.8 m

### Conformance

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Product certifications</b>	CCC CSA PSE UL listed VDE
-------------------------------	---------------------------------------

## Environmental

<b>Ambient air temperature for operation</b>	0...75 °C
<b>Relative humidity</b>	20...80 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for storage</b>	-25...75 °C
<b>Storage Relative Humidity</b>	20...80 %
<b>Storage altitude</b>	0.0000000000...15240.0000000000 m

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	30 cm
<b>Package 1 Width</b>	8 cm
<b>Package 1 Length</b>	7 cm
<b>Package 1 Weight</b>	2.16 kg
<b>SCC14</b>	10731304279720

## Logistical informations

<b>Country of origin</b>	CN
--------------------------	----

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back   Transparency   RoHS/REACH

## Resource performance

 Take-Back Program Available

## Well-being performance

 Lead Free

## Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)