



SB1015

FEATURES

- + True-flat, bezel-free, fanless design
- + High performance Intel Quad-Core processor
or i5 dual core processor
- + Durable and sturdy base
- + Easy to change or replace hard disk drive
- + Optional MSR and VFD/LCD customer display

True-flat All-in-One Touch POS Terminal

The Logic Controls SB1015 All-in-One terminal packs great features and value into a sleek and sturdy design. It delivers an economical Point of Sale solution while providing excellent performance and reliability. The highly rugged touch monitor includes a solid base with extra wide hinge for maximum stability. The SB1015 also facilitates options for a quick and professional mounting of integrated magnetic stripe reader and VFD/LCD customer display.



SB1015 specifications

MAINBOARD

| | |
|---------------|---|
| CPU: | Celeron: Intel Celeron J1900 Quad-Core 2.0GHz i5: Intel Core i5 4200U Dual-Core 1.6GHz |
| IO chipset: | Celeron: IFintek F71869 i5: ITE8786E |
| Memory: | DDR3L 1333 SODIMM slot, up to 8GB |
| Ethernet LAN: | Celeron: Realtek RTL8111G PCI Express Gigabit LAN i5: Realtek® RTL8111E Chip PCI Express Gigabit LAN |
| Audio: | ALC887 Audio CODEC, HD Audio CODEC |
| Storage: | SATA 2.5in Hard Disk Drive/SSD, mSATA SSD |

DISPLAY

| | |
|-------------------|--|
| Touch screen: | Projected capacitive touch |
| Touch controller: | USB interface |
| LCD panel: | 15in LED-backlit TFT display, XGA 1024 x 768, 250 nits |

ELECTRICAL

| | |
|-------------------------|-----------------------------------|
| Power supply: | DC 12V 90W external power adapter |
| Input to power adapter: | Input 100 to 240VAC, 50/60Hz |

I/O PORTS

| | |
|---------------|---|
| USB ports: | USB 2.0 x5, USB 3.0 x1 // i5 USB2.0 x4, USB3.0 x2 |
| Serial ports: | RS232 DB9 x3 // i5 RS232 DB9 x2 |
| Ethernet: | Gigabit, RJ45 x1 |
| Video port: | VGA DB15 x1 |
| Audio port: | Line out x1 |

ENVIRONMENTAL

| | |
|------------------------|-----------------------------|
| Operating temperature: | 32°F to 104°F (0°C to 40°C) |
| Relative humidity: | 8% to 80%, non-condensing |

MECHANICAL

| | |
|-------------------------|---|
| Dimensions (W x H x D): | 14.33in x 12.83in x 9.06in (36.4cm x 32.6cm x 23cm) |
| Weight: | 13lbs (5.91Kg) |

