

OmniLink® TM-L90 Plus-i LFC

Intelligent Liner-free Compatible Label Printer



Easy, cost-effective, liner-free label printing for QSRs and food service.

Intelligent — open platform for mobile POS deployments, cloud-based services, online ordering, custom Web applications, peripheral device control and more

Versatile — enables printing from virtually any smartphone or tablet

Compatible — uses Epson-tested, liner-free adhesive labels

Efficient — improves order accuracy and customer satisfaction

Convenient — triple interfaces, including built-in USB and VGA for flexible connectivity

Fast — print speeds of up to 170 mm/sec with 40, 58 and 80 mm print width support options

Cost-effective — enhanced print options reduce paper usage up to 30 percent









OmniLink® TM-L90 Plus-i LFC Intelligent Liner-free Compatible Label Printer

Printer

Print Method Thermal line printing Print Speed 170 mm/sec (thermal receipt); 90 mm/sec (label media)

Print Resolution 203 x 203 dpi

Print Font Font (A/B)

40 mm: 12 x 24, 7 x 17 / 9 x 17, 7 x 17 **58 mm:** 13 x 24, 10 x 17 / 10 x 17, 7 x 17 80 mm: TM-T88 compatible mode 13 x 24 / 10 x 17;

TM-L90 compatible mode 12 x 24 / 9 x 17

Column Capacity 64/48 columns

Character Size 1.13 x 2.13 / 1.5 x 3.0 / 1.0 x 2.0 mm (W x H) Character Set 95 Alphanumeric, 37 International, 128 x 11

Barcode UPC-A, UPC-E, JAN8 (EAN), JAN13 (EAN), ITF, CODE39, CODE93, CODE128, CODABAR, PDF417, MAXICODE, QR Code

Reliability

MTBF: 180.000 hours

Autocutter: 2 million cuts (receipts), 1 million cuts (labels)

Paper Width 40 mm, 58 mm, 80 mm Paper Diameter 4" (102 mm)

Media Thickness 2 mil to 8 mil, depending on media type

General Information

Interface Ethernet (100Base-TX/10Base-T), USB and VGA

Data Buffer 4K or 45 bytes

Power 24 VDC±7%

Power Consumption Approx. 30 W

D.K.D. Function 2 drawers

Color Epson Dark Gray, Epson Cool White

Factory Options PS-180 AC adapter, paper roll spacer, wall-hanging bracket WH-10

Environmental Standards WEEE, RoHS compliant EMI Standards VCCI class A. FCC/ICES-003 Class A. CE marking, Canada EMI, AS/NZS CISPR22 Class A

Safety Standards UL, CSA, TÜV (EN60950) Warranty 1-year limited warranty

Overall Dimensions (W x D x H)

5.5" x 7.9" x 5.8" (140 mm x 148 mm x 203 mm)

Weight Approx. 4.4 lb (2.0 kg)

Intelligent Module and Software

Processor ATMEL

System Memory 256MB Flash Memory 256MB (NAND)

Operating System Embedded Linux Web Server Apache HTTP Server

Internal Battery Life 5 years (Internal calendar and clock) Interfaces USB 2.0 (2x Device, 1x Host), Ethernet (1x RJ45), VGA (1x D-sub15 Fem), memory slot (1x microSD) Software and Utilities ePOS Device, Server Direct Print,

TMNet WebConfig, Easy Setup, ePOS SDK

5.8"

What's in the Box

TM-L90 Plus-i LFC Printer, Thermal roll paper (starter roll for operation check), User guide, Power supply with AC cable

Ordering Information*

Built-in Ethernet, USB and VGA; EDG (Epson Dark Gray)*

C31C412773

Built-in Ethernet, USB, VGA and Freshness C31C412A7601 Label Application; EDG (Epson Dark Gray)*

Epson-tested Media

Iconex Sticky Media,™ 40 mm 9023-1233 Iconex Sticky Media, 58 mm 9023-1823 Iconex Sticky Media, 80 mm 9023-1253 MAXStick® Plus Diamond Adhesive

Formation, 58 mm width

MS214275PLUSD

MAXStick 2Go 4 Stripe Adhesive 80 mm width

MS3183752G04S

*Contact your Epson® representative for additional models. **Includes AC adapter (PS-180-343)

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future eco.epson.com



Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806 185 Renfrew Drive, Markham, Ontario L3R 6G3

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. OmniLink is a registered trademark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency, All other product and brand names are trademarks and/or registered trademarks of their respective companies Epson disclaims any and all rights in these marks. Copyright 2016 Epson America, Inc. Com-SS-Oct-13 CPD-53017 10/16

Contact: