I AM THE NCR REALPOS[™] MULTIFUNCTION PRINTER 7167 Series II Printer

O NCR

编出伪育

TR NCR

1320



NEW TRANSFORMER NCR

信日/高品。

CR. NCR.



Designed to deliver fast receipts and easily manage forms and checks, while helping to reduce your environmental impact.

With intelligent design and operator-friendly features like Lean Receipt and advanced power management, the NCR RealPOS Multifunction Printer can increase your store's productivity and reduce your paper and power usage.

Fast and flexible

Featuring high-speed thermal receipt printing at up to 90 lines per second, this printer helps you to quickly finalize customer transactions. Further, its high-resolution printing supports multiple bar code symbologies, including QR, which enables you to utilize bar-coded receipts to simplify returns and improve customer service.

Reduces your environmental impact and saves money

The NCR Lean Receipt utility provides easy-to-use settings that can help reduce your paper consumption and costs with no application changes required. You can set preferences that automatically adjust a receipt's formatting to reduce white space, top and bottom margins, bar code height and more resulting in significant paper savings. Standby and sleep modes help reduce your total energy costs at the point of sale, resulting in a printer that's reliable and also eco-friendly.

Improves productivity at the checkout

The NCR RealPOS Multifunction Printer provides advanced check-handling features like MICR reading and optional automatic check-flip, which help to reduce costs and improve cashier productivity. The MICR reader enables quick and reliable check validation, while check-flip allows single insertion check handling that minimizes human intervention—and a flat slip table makes endorsing large forms a snap.

Intelligent and intuitive design

NCR human factors engineering studies show that the NCR RealPOS Multifunction Printer is easy and intuitive to operate, contributing to operator productivity and allowing your employees to focus on what's important—your customers.

Key features

- Lean Receipt Utility
- Advanced power management options
- Standby and sleep modes
- Drop-in paper loading with paper low and out sensors
- Two-color printing options

- Flat slip table with impact printing and forms alignment indicator
- Internal memory for macros and graphics
- Cash drawer port (one or two drawers)
- Check MICR reader



Technical specifications

DIMENSIONS

- Height 185.8mm (7.3")
- Height with
- Cover Open 283.7mm (11.2")
- Width 196.4mm (7.7")
- Depth 262mm (10.3")
- Weight
 4.50kg (10.0lbs), Flip Model
 4.25kg (9.4lbs), Non-Flip Model

THERMAL RECEIPT STATION

- Thermal, fixed head, 203 dots per inch
- Print speed: up to 90 lines per second (12" per second, 300mm per second)
- Supports both 80mm and 58mm media rolls
- Single cash drawer connector support one or two drawers
- Two-color printing option
- "Paper low" and "paper out" sensors
- Thermal print head failure detection
- Advanced power management options
- Customizable logos and characters set in RAM
- Auto speed adjustment for smoother printing
- Unicode mode support (UTF-16)
- Removable receipt lid for easy serviceability and maintenance

OPTIONS

• Check flip module – prints both sides of the check

COLUMNS PER LINE AND CHARACTER PITCH (80MM PAPER)

- 44 @ 15.6 CPI (standard)
- 56 @ 20.3 CPI (compressed)
- 22 @ 7.8 CPI (standard double byte)
- 28 @ 10.3 CPI (compressed Kanji double byte)

COLUMNS PER LINE AND CHARACTER PITCH (58MM PAPER)

- 32 @ 15.6 CPI (standard)
- 42 @ 20.3 CPI (compressed)
- 17 @ 8.5 CPI (standard double byte)
- 21 @ 10.2 CPI (compressed Kanji double byte)

PRINT MODES

• Standard, compressed, double high, double width, upside down, rotated, underline, scalable, bold, superscript, italic, subscript, reverse print

SLIP PAPER REQUIREMENTS

• Up to four-ply

LEAN RECEIPT UTILITY

- Reduces paper usage and power consumption
 Seven paper reduction options, including reducing white space, line spacing and margins
 - Seven power reduction options, including standby and sleep modes

Why NCR?

组出创制力的

NCR Corporation (NYSE: NCR) is the global leader in consumer transaction technologies, turning everyday interactions with businesses into exceptional experiences. With its software, hardware, and portfolio of services, NCR enables more than 485 million transactions daily across retail, financial, travel, hospitality, telecom and technology, and small business. NCR solutions run the everyday transactions that make your life easier. NCR is headquartered in Duluth, Georgia with approximately 29,000 employees and does business in 180 countries. NCR is a trademark of NCR Corporation in the United States and other countries.

CHARACTER SETS

NDR

 SBCS Code Page 437(default), 850, 852, 860, 863, 865, 858, 866, 1252, 1256, Katakana, 874, 862, 864 DBCS Code Page 932(default), 936(op), 949(op), 950(op)

BAR CODE GENERATION

 GS1 DataBar™ (Omnidirectional/Truncated/Limited/ Expanded/Stacked), UPC-A, UPC-E, JAN 13 (EAN), JAN 8 (EAN), Code 39, Code 128, Interleaved 2 of 5, Codabar, Code 93, PDF 417, QR Code

POWER REQUIREMENTS

- 24V PoweredUSB™
- Optional external 75-watt power supply
- Optional external 60-watt power supply

LOW POWER CONSUMPTION OPTIONS

- Stand by Mode
- Power-off Mode

ENVIRONMENTAL CONDITIONS

- Operating temperature: 5°C to 45°C (40°F to 112°F)
- Operating humidity: 5%–90%

PRINT DRIVERS

 OPOS (OLE for Retail POS), TAPS, JavaPOS™ for Windows[®] and Linux[®] and USB printer class protocol for Windows

CABINET COLOR OPTIONS

- Black
- Charcoal gray
- Beige

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR RealPOS is either a registered trademark or trademark of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders.

