

## Y Splitter Power Cable, NEMA 5-15P to 2x C13 - 10A, 125V, 18 AWG, 1.5 ft. (0.45 m), Black

MODEL NUMBER: P006-18N-2



Power cord splitter allows 2 devices with C14 inlets to share one AC power input cord and one NEMA 5-15R outlet.

### Features

**Y-Style Power Cord Splitter Connects 2 Devices with C14 Inlets to One AC Outlet** This computer power cord splitter allows two devices with C14 power inlets to share one AC input cord and one NEMA 5-15R outlet. By connecting two devices to one outlet, the power cord splitter frees up space in a PDU or surge protector and helps reduce cable clutter. You can also free up valuable PDU space by connecting bulky power adapters to this splitter, preventing the adapters from blocking adjacent outlets.

**Dual IEC Cable Powers a Wide Variety of Essential Electronics** With this PC power splitter, a single NEMA 5-15R outlet can power two devices, such as computers, monitors, printers, instrument amplifiers and other equipment compatible with a C13 connector. Ideal for areas where AC outlets are limited, such as rack cabinets, this dual IEC power cable is compatible with power and extension cords.

### Highlights

- Connects 2 devices to one AC outlet to save space and reduce cable clutter
- Recommended for powering dual computers, monitors or other compatible peripherals
- Y splitter power cable is ideal replacement for worn-out or missing cable
- NEMA 5-15P plug connects to AC power; C13 plugs connect to devices' C14 inlets

### Applications

- Connect 2 devices like computers, monitors, scanners and printers to one power outlet up to 1.5 ft. away in your home office, work space or dorm room
- Cut cable clutter by powering both monitors in a dual-monitor display mount with a single cord
- Save space in a 0U vertical rack-mount PDU by plugging two rack devices into one outlet

### System Requirements

- Computer or other devices with C14 power connectors

### Package Includes

- P006-18N-2 Y Splitter Power Cable, 1.5 ft., Black

## Specifications

| OVERVIEW                    |                                                    |
|-----------------------------|----------------------------------------------------|
| UPC Code                    | 037332213938                                       |
| Device Compatibility        | Computer; Monitor/HDTV; Printer; Scanner; UPS; PDU |
| Country/Region              | North America                                      |
| INPUT                       |                                                    |
| Maximum Input Amps          | 10                                                 |
| Voltage Compatibility (VAC) | 125                                                |
| CONNECTIONS                 |                                                    |
| Side A - Connector 1        | NEMA 5-15P                                         |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                             |
|--------------------------------------|-----------------------------|
| Side B - Connector 1                 | (2) IEC-320-C13             |
| <b>PHYSICAL</b>                      |                             |
| Plug Color                           | Black                       |
| Cable Jacket Color                   | Black                       |
| Cable Jacket Material                | PVC                         |
| Cable Jacket Rating                  | FT2                         |
| Power Cord Jacket Type               | SJT                         |
| Cable Outer Diameter (OD)            | 7.7mm                       |
| Number of Conductors                 | 3                           |
| Wire Gauge (AWG)                     | 18                          |
| Wire Gauge (OD - mm <sup>2</sup> )   | 0.82                        |
| Cable Length (ft.)                   | 1.5                         |
| Cable Length (m)                     | 0.46                        |
| Shipping Dimensions (hwd / in.)      | 0.50 x 11.50 x 14.00        |
| Shipping Dimensions (hwd / cm)       | 1.27 x 29.21 x 35.56        |
| Shipping Weight (lbs.)               | 0.50                        |
| Shipping Weight (kg)                 | 0.23                        |
| <b>ENVIRONMENTAL</b>                 |                             |
| Operating Temperature Range          | -4° to 140°F (-20° to 60°C) |
| Storage Temperature Range            | -4° to 140°F (-20° to 60°C) |
| Operating Humidity Range             | 20% to 80% RH               |
| Storage Humidity Range               | 20% to 80% RH               |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                             |
| Antibacterial                        | No                          |
| Angled Plug                          | No                          |
| High Voltage                         | No                          |
| Locking Plug                         | No                          |
| Coiled Power Cord                    | No                          |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                             |
| Product Certifications               | cUL Listed; UL Listed       |
| Product Compliance                   | RoHS                        |
| <b>WARRANTY &amp; SUPPORT</b>        |                             |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                        |                           |
|----------------------------------------|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|----------------------------------------|---------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.