


16 10/100/1000Mbps Port Gigabit L2 Managed Switch, 2 Dedicated Gigabit SFP Slots, 36Gbps, Web/CLI, 8-Outlet 120V PDU + Isobar Surge Suppression

MODEL NUMBER: **NSS-G16D2**



Description

The energy-efficient NSS-G16D2 16-Port Gigabit L2 Managed Network Switch does more than complete your home or office LAN. It also features a basic 120V 15A PDU to distribute reliable AC power to critical IT equipment in your wiring closet, server room or equipment rack. Two dedicated mini-GBIC SFP ports are also included for uplinking data to other switches via optical fiber or copper.

This switch features 16 twisted-pair RJ45 Gigabit Ethernet ports that support auto-negotiable 10/100/1000 Mbps and auto MDI/MDIX cross-over detection functions for convenient plug-and-play capability. Easy-to-read LEDs indicate connection and activity status for each port. Built-in management software lets you monitor and control each connected device via secure web-based interface. Each port supports up to 2 Gbps with full duplex.

The rear panel contains eight NEMA 5-15R outlets that supply continuous power to connected devices. Your equipment is protected by 3860 joules of surge suppression, as well as front-panel LEDs that let you monitor line status at a glance. A 12A circuit breaker trips if the current drawn by connected equipment exceeds the PDU's maximum load rating.

The NSS-G16D2 supports IEEE802.3az Energy Efficient Ethernet standards. The heavy-duty metal housing mounts into 1U of an EIA-standard 19-inch rack using the included hardware. The six-foot input cord with NEMA 5-15P plug connects to a protected UPS, generator or mains input AC source.

Features

Enterprise Managed Network Switch

- 16 twisted-pair RJ45 Gigabit Ethernet ports
- Auto-negotiable 10/100/1000 Mbps
- Automatic MDI/MDIX cross-over detection
- 36 Gbps switching capacity (2 Gbps per port with full duplex)
- Easy-to-read LEDs indicate connection and activity status for each port
- Supports 10k jumbo frames

Highlights

- IP-MAC-Port-Binding, ACL, Storm Control
- Port Security, DHCP Snooping, 802.1x, L2
- WEB/CLI management, SNMP, RMON features
- 16 ports and 2 dedicated Mini-GBIC SFP slots
- Enterprise-level, security and layer 2 management
- Cost-effective form factor for small and medium businesses
- Built-in 8-outlet PDU
- 3860 Joule suppression rating, Diagnostic LEDs

Package Includes

- NSS-G16D2 16-Port Gigabit L2 Managed Network Switch
- Mounting hardware
- Owner's manual



- Supports MAC address auto-learning and auto-aging up to 16,000 addresses
- Advanced Enterprise level, L2 management features

Advanced Network Monitoring

- Built-in Ethernet network interface allows full remote access for monitoring, configuration and control and notifications via web browser
- VLAN, trunking and other features improve switch's and network's efficiency and performance

Basic 120V 15A PDU

- 8 NEMA 5-15R rear outlets supply continuous power to connected devices
- 3860 joules of Isobar surge suppression
- Front-panel LEDs indicate protection, fault, and line status
- 40–80 dB EMI/RFI noise reduction

Dual Dedicated Mini-GBIC SFP Ports

- Connect two Mini-GBIC SFP modules for uplinking to other switches via optical fiber or copper
- LEDs indicate interface traffic

Compliant with Energy Efficient Ethernet standards

- Automatically shifts unused ports to low power state without interrupting network connection
- Meets IEEE 802.3ab, 802.3i, 802.3u, 802.3x, 802.3, 802.1q, 802.1d, 802.1w, 802.3ad and 802.3az standards

Dedicated RJ45 Console Port

- Enables command line access to the unit

Mounts Horizontally in 1U of Rack Space

- Compatible with EIA-standard 19 in. racks and rack enclosures
- Fanless metal housing for silent operation
- NEMA 5-15P plug with 6 ft. AC power cord

Specifications

OVERVIEW	
PDU Type	Basic
OUTPUT	
Output Receptacles	(8) 5-15R
Output Circuit Breakers	12A
INPUT	
PDU Input Voltage	100; 120; 127
PDU Plug Type	NEMA 5-15P
Input Cord Length (ft.)	6



Input Cord Length (m)	1.83
Input Phase	Single-Phase
USER INTERFACE, ALERTS & CONTROLS	
Switches	2 included switches enable HARD factory reset and SOFT factory reset options
LED Indicators	Power LED (Green for Power On); Two LEDs per RJ-45 port (Green indicates 10/100Mbps link; Amber indicates 1000Mbps link; LEDs flash to indicate port activity); Two LEDs indicate SFP connection (Green); One LED indicates system status (Green); Set of 3 LEDs indicate surge suppression status (Green: Protection Present / Red: Fault / Green: Line OK)
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	3860
Protection Modes	L-N, L-G, N-G
Clamping Voltage (RMS)	330
EMI / RFI Filtering	40-80dB
PHYSICAL	
Primary Form Factor	Rackmount
Minimum Required Rack Depth (inches)	15.4
Minimum Required Rack Depth (cm)	39.12
Shipping Weight (lbs.)	11.03
Shipping Weight (kg)	5
Unit Dimensions (hwd / in.)	1.71 x 17.32 x 12.4
Unit Dimensions (hwd / cm)	4.34 x 44 x 31.5
Unit Weight (lbs.)	8.49
Unit Weight (kg)	3.85
Color	Black
PDU Form Factor	Horizontal (1U, 2U, etc)
Minimum Required Rack Depth (mm)	391
ENVIRONMENTAL	
Storage Temperature Range	14 to 158 F (-10 to 70 C)
Relative Humidity	5 to 95% (Non-condensing)
Operating Elevation (ft.)	10,000
Operating Temperature	32 to 104 F (0 to 40 C)
Operating Elevation (m)	3,000



CONNECTIONS	
Ports	18
Network Switch Ports	(16) 10/100/1000 (RJ45); (2) Dedicated SFP; (1) Console (RJ45)
CERTIFICATIONS	
Certifications	Compliant standards: IEEE 802.3ab (1000BASE-T GIGABIT ETHERNET), IEEE 802.3i (10BASE-T ETHERNET), IEEE 802.3u (100BASE-T ETHERNET), IEEE 802.3x (FULL DUPLEX/FLOW CONTROL), IEEE 802.3 (NWAY AUTO-NEGOTIATION), 802.1Q (TAGGED VLAN), 802.1D (STP), 802.1w (RSTP), 802.3ad (LACP), 802.3az (ENERGY EFFICIENT ETHERNET)
Approvals	Tested to: UL 60950-1, UL 1449 3rd Edition, CAN/CSA-C22.2 No. 60950-1, FCC Part 15 Class A, REACH, NOM
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>