

VLDT5W

2.8mm fixed lens, white housing



Features

- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30 fps
- IR Range: 65' (depending on scene reflection)
- 3 axis lens mount
- Multi-format HD (TVI, CVI, AHD, CVBS)*
- Signal distance up to 1600 ft.
- True WDR
- Full OSD operation through UTC (up the coax)(TVI)
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- 5 year warranty



Included Junction Box



Camera Specifications

Image Sensor	1/2.8" CMOS
Maximum Resolution	1920 x 1080
Minimum Illumination	Color: 0.001 lux @ F1.2
S/N Ratio	greater than 52dB
Number IR LEDs	24
Field of View (H)	80° - 38°
Compensation	WDR (120dB), BLC, HLC
Electronic Shutter Speed	1/60 sec. - 1/100000 sec.
DNR	Yes
Video Output	TVI / CVI / AHD / CVBS
Image System	PAL / NTSC
Field of View (Horizontal)	115.4°
Field of View (Vertical)	83.4°

Operating & Unit Specifications

Power	12VDC (power supply not included)
Power Consumption	IR off (less than 1W) IR on (less than 3W)
Operating Temperature	-4°F - 104°F
Unit Dimensions	4.5" (W) x 5" (H)
Unit Weight	1.1 lbs.

Optional Accessories



O5VLWM
Dome
Wall Mount



PSW5
12VDC
Power Supply



TVIUTPPT
HD Video
Transceiver
with Pigtail



TVIUTP
HD Video
Transceiver

* Camera defaulted to HD-TVI. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 9/13/18