## Product data sheet

Specifications





APC Smart-UPS, Line Interactive, 1000VA, Tower, 120V, 8x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT1000C

#### **Overview**

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock
Main	
Main Input Voltage	120 V
Other Input Voltage	110 V 125 V
Main Output Voltage	120 V
Other Output Voltage	110 V 125 V
Kw Rating	700 W
Rated power in VA	1000 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	8 NEMA 5-15R
Cable length	6 ft (1.8 m)
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	User Manual USB cable
Range of Product	Smart-UPS

#### Complementary

Software package SmartConnect software for remote power monitoring feature availability varies by terms of use

### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

RBC Quantity	1
Battery life	35 year(s)
Replacement battery	RBC6 □
Battery Charge Power (Watts)	88 W rated

### General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Cloud-enabled monitoring
Redundant	No

## **Physical**

color	Black
Height	8.6 in (21.9 cm)
Width	6.7 in (17.1 cm)
Depth	17.3 in (43.9 cm)
Net Weight	44.3 lb(US) (20.1 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

# Input

Efficiency at full load	75154 V adjustable 82144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

# Output

Harmonic distortion	Less than 5%
Maximum configurable power in VA	1000 VA
Max Configurable Power (Watts)	700 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product Certifications	cULus ENERGY STAR V2.0 (USA)
Equipment protection policy	Lifetime : \$150000

### **Environmental**

Acoustic level	41 dBA
Online Thermal Dissipation	175 Btu/h
Operating altitude	010000 ft
Ambient Air Temperature for Operation	32104 °F (040 °C)
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage altitude	050000 ft (0.000000000015240.0000000000 m)
Relative Humidity	095 %
Storage Relative Humidity	095 %

## **Communications & Management**

Control panel	Multi-function LCD status and control console
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## **Surge Protection and Filtering**

Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304322771
Returnability	No
Country of origin	PH

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.0 in (33 cm)
Package 1 Width	23.2 in (59 cm)
Package 1 Length	13.0 in (33 cm)
Package 1 Weight	49.91 lb(US) (22.64 kg)

### **Contractual warranty**

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



**Green Premium** TM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

### Resource performance

**Energy Efficient Product** 

Take-Back Program Available

#### Well-being performance

Mercury Free

Rohs Exemption Information

Yes

#### **Environmental Certifications**

Energy Star®

ENERGY STAR UPS V2.0 (USA)

#### **Certifications & Standards**

**Reach Regulation REACh Declaration Eu Rohs Directive** Compliant with Exemptions **Environmental Disclosure Product Environmental Profile Circularity Profile** End of Life Information California Proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov