





APC KVM 2G, Digital/IP, 1 Remote/1 Local User, 16 Ports with Virtual Media - FIPS 140-2

KVM1116R

Overview

Lead time	Usually in Stock

Main

24 V DC	
100 V	
120 V	
208 V	
230 V	
240 V	
Switch	
1U	
	100 V 120 V 208 V 230 V 240 V

Physical

Colour	Black
Height	1.7 in (4.3 cm)
Width	16.7 in (42.4 cm)
Depth	7.4 in (18.8 cm)
net weight	5.71 lb(US) (2.59 kg)
mounting location	Front
Mounting preference	No preference
mounting mode	Not rack-mountable

Input

Network frequency 50/60 Hz

Conformance

Product certifications	C-Tick CE EAC TAA compliance UL-AR VCCI class A VDE
Standards	FCC part 15 class A ICES-003 UL 60950-1

Environmental

Ambient air temperature for	32.0000000000122.0000000000 °F (050 °C)
operation	

Operating altitude	010000 ft
Relative humidity	080 %
Ambient air temperature for storage	-4.0000000000140.0000000000 °F (-2060 °C)
Storage altitude	050000 ft (0.000000000015240.0000000000 m)
Storage Relative Humidity	080 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.7 in (14.6 cm)
Package 1 Width	13.0 in (33 cm)
Package 1 Length	24.4 in (61.9 cm)
Package 1 Weight	8.80 lb(US) (3.99 kg)

Contractual warranty

Warranty 2 years repair or replace



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Reach Free Of Svhc	
⊘	Mercury Free	
②	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information