# **GeForce RTX™ 4080 16GB SUPRIM X**







## **SPECIFICATIONS**

Model Name	GeForce RTX™ 4080 16GB SUPRIM X
Graphics Processing Unit	NVIDIA <sup>®</sup> GeForce RTX™ 4080 16GB
Interface	PCI Express® Gen 4
Core Clocks	Extreme Performance: 2640 MHz (MSI Center) Boost: 2625 MHz (GAMING & SILENT Mode)
CUDA® CORES	9728 Units
Memory Speed	22.4 Gbps
Memory	16GB GDDR6X
Memory Bus	256-bit
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI 2.1a)
HDCP Support	Υ
Power consumption	320 W
Power connectors	16-pin x 1
Recommended PSU	850 W (Min.750 W)
Card Dimension (mm)	336 x 142 x 78 mm
Weight (Card / Package)	2364g / 3565g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Υ
<b>Digital Maximum Resolution</b>	7680 x 4320

## **CONNECTIONS**

the U.S. and other countries



## **FEATURES**



### **TRI FROZR 3S**

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



### Vapor Chamber

The GPU and memory modules are covered with a Vapor Chamber which rapidly transfers heat to Core Pipes.



### Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



### **Airflow Control**

Don't sweat it, Airflow Control guides the air to exactly where it needs to be for maximum cooling.



## Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



## **Metal Backplate**

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.