

## ZoomSHOT 4K with OneLINK Bridge System **SKU: 999-69350-300W**



A low-cost point-of-view camera with UHD 4K image quality.

Key Features:

- 30x powered zoom with 70.2° horizontal field of view
- Up to 2160p/30 HD image quality
- HDMI output
- Local 12V power supply for camera included or available with optional OneLINK HDMI or OneLINK Bridge Extension Systems
- RS-232 Control
- Manual Pan/Tilt with EZ Set tensioning system
- Compatible with Kensington lock

The ZoomSHOT 4K is a cost-effective, versatile, high-definition point-of-view camera well-suited for small, medium, and large rooms. It is designed to support a wide range of applications, including houses of worship, pro A/V system integration, live events, IMAG systems, UCC applications, videoconferencing, distance learning classrooms and lecture capture. The camera captures with a full HD 1/2.5" Sony Exmor 8.57 megapixel 2160p image sensor, 30x optical zoom, and 70.2° horizontal field of view. It also features a manual pan/tilt, an EZ Set tensioning system, and a presenter-friendly IR remote control.

The ZoomSHOT 4K OneLINK Bridge System is easy to install and use, and it offers a variety of outputs including simultaneous HDMI, SDI and USB 3.0 outputs. The OneLINK Bridge System also includes audio inputs and echo cancelled outputs usable for in-room conferencing systems.

The ZoomSHOT 4K is a reliable and affordable solution for your video capture needs. Record a lecture, conduct a video conference, or capture live events with outstanding performance and quality. Versatile features, outputs, and ease of use, make this system an excellent choice.

Can also be used as a stand alone camera with no extension system if desired.

**This Package Includes:**

- ZoomSHOT 4K camera (black or white)
- Thin Profile Wall Mount (black or white) with mounting hardware
- Vaddio IR Shot Commander remote with 2x AAA batteries
- OneLINK HDBT EZIM (easy interface module)
- Cables to connect ZoomSHOT 4K to EZIM
- OneLINK Bridge HDBT extension
- 48V power supply for OneLINK Bridge with AC cord set(s)

Total Pixels: 2.14 Megapixel

## Specifications

**Dimensions &  
Measurements**

|                       |                                                      |
|-----------------------|------------------------------------------------------|
| Depth                 | Camera: 5.8 in (14.73 cm)<br>QUSB: 6 in (15.24 cm)   |
| Height                | Camera: 7 in (17.78 cm)<br>QUSB: 1.72 in (4.37 cm)   |
| Max Distance Support  | 150 ft (45.7 m)                                      |
| Operating Temperature | 32° to 104°F (0° to 40°C)                            |
| Product Weight        | Camera: 3.5 lbs (1.59 kg)<br>QUSB: 1.4 lbs (0.64 kg) |
| Shipping Weight       | 1 lbs (0.5 kg)                                       |
| Width                 | Camera: 5.5 in (14 cm)<br>QUSB: 8.38 in (21.27 cm)   |

**Characteristics &  
Features**

|                   |        |
|-------------------|--------|
| 3rd Party Control | RS232  |
| Camera Type       | Fixed  |
| Color             | White  |
| Compatible With   | Vaddio |

|                       |                                                                                                                     |
|-----------------------|---------------------------------------------------------------------------------------------------------------------|
| Control Method        | <ul style="list-style-type: none"> <li>• IR Remote</li> <li>• RS232</li> </ul>                                      |
| Estimated Room Size   | <ul style="list-style-type: none"> <li>• Large Room</li> <li>• Medium Room</li> </ul>                               |
| Field of View         | 70.2 Degrees Wide End                                                                                               |
| Field of View Wide    | Greater than 70                                                                                                     |
| Focus System          | <ul style="list-style-type: none"> <li>• Auto</li> <li>• Manual</li> </ul>                                          |
| Gain                  | <ul style="list-style-type: none"> <li>• Auto</li> <li>• Manual</li> </ul>                                          |
| Image Sensor Type     | 1/2.8 Exmor CMOS                                                                                                    |
| Input Ports           | EZ Power Video                                                                                                      |
| Invertible            | Yes                                                                                                                 |
| Manufacturer          | Vaddio                                                                                                              |
| Max Resolution        | 2160p 30                                                                                                            |
| Minimum Illumination  | 0.3 Lux                                                                                                             |
| OneLINK Compatibility | Yes                                                                                                                 |
| Output Ports          | <ul style="list-style-type: none"> <li>• HDMI 1.4b</li> <li>• RS-232</li> <li>• USB 3.0</li> </ul>                  |
| Pan and Tilt Range    | <ul style="list-style-type: none"> <li>• Tilt 30 degrees to negative 30 degrees</li> <li>• Unlimited Pan</li> </ul> |
| Pan and Tilt Speed    | Manual                                                                                                              |
| Pixels                | 2.14 Megapixel                                                                                                      |
| Power Cord            | US Cord                                                                                                             |
| Power Supply          | <ul style="list-style-type: none"> <li>• 208A</li> <li>• 24VDC</li> </ul>                                           |
| Power Type            | EZ Power                                                                                                            |

|                             |                                                                                                                   |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------|
| Preset Positions            | 16                                                                                                                |
| PTZ Motors                  | No Motors Manual                                                                                                  |
| Quick-Connect Compatibility | QUSB                                                                                                              |
| Signal Type                 | <ul style="list-style-type: none"> <li>• HD YPbPr</li> <li>• HDMI</li> <li>• RS 232</li> <li>• USB 2.0</li> </ul> |
| Solution Type               | Camera with Extension                                                                                             |
| TAA Compliant               | Yes                                                                                                               |
| Tri-Sync Motion             | No                                                                                                                |
| UPC                         | 840077509132                                                                                                      |
| White Balance               | <ul style="list-style-type: none"> <li>• Auto</li> <li>• Manual</li> </ul>                                        |
| Zoom                        | 30x                                                                                                               |

## Certifications & Warranties

|                |                                                                                      |
|----------------|--------------------------------------------------------------------------------------|
| Certifications | <ul style="list-style-type: none"> <li>• CE</li> <li>• FCC</li> <li>• TAA</li> </ul> |
| Warranty       | 3 years                                                                              |

Source: [https://www.legrandav.com/products/cameras/4k\\_fixed\\_camera/zoomshot-4k-onelink-system/999-69350-300w](https://www.legrandav.com/products/cameras/4k_fixed_camera/zoomshot-4k-onelink-system/999-69350-300w)